Comment	Description	Designator	Footprint	LibRef	Quantity
ESP32-C6-MINI-1-H8	8 MB (Quad SPI) , 13.2 16.6 2.4 , 3.0 ~ 3.6 V , 2.4 GHz , 2412 ~ 2484 MHz , 40C ~ 105C	B1	ESP32C6MINI1H8	ESP32-C6-MINI-1-H8	1
TPS22965NTDSGRQ1	5.5V, 4A, 16m Automotive Load Switch With Adjustable Rise Time and Optional Quick Output Discharge	B2	SON50P200X200X80-9N	TPS22965NTDSGRQ1	1
103AT-2	NTC (Negative Temperature Coefficient) Thermistors 10kohm 1%	B3	103AT2	103AT-2	1
MAX17048G+T10	3A 1-Cell/2-Cell Fuel Gauge with ModelGauge	B4	SON50P200X200X80-9N-D	MAX17048G+T10	1
TPS61023DRLT	Switching Voltage Regulators 3-A boost converter with 0.5-V ultra-low input voltage 6-SOT-5X3 -40 to 125	B5	SOTFL50P160X60-6N	TPS61023DRLT	1
GRM188R71C105KE15D	16V 1uF X7R ±10% 0603 Multilayer Ceramic Capacitors MLCC - SMD/SMT ROHS	C1, C8, C13, C14, C20, C21	0603 SMD CERAMIC CAPACITOR	GRM188R71C105KE15D	6
GRM188R71C104KA01D	100nF 16V X7R ±10% 0603 Multilayer Ceramic Capacitors MLCC - SMD/SMT ROHS	C2, C5, C6, C7, C12, C16, C17, C18, C19, C22, C23, C24, C26	0603 SMD CERAMIC CAPACITOR	GRM188R71C104KA01D	13
GRM188R61A106KE69D	10V 10uF X5R ±10% 0603 Multilayer Ceramic Capacitors MLCC - SMD/SMT ROHS	C3, C4, C15, C25	0603 SMD CERAMIC CAPACITOR	GRM188R61A106KE69D	4
GRM188R61A475KE15D	10V 4.7uF X5R ±10% 0603 Multilayer Ceramic Capacitors MLCC - SMD/SMT ROHS	C9, C10, C11	0603 SMD CERAMIC CAPACITOR	GRM188R61A475KE15D	3
GRM187R61A226ME15D	10V 22uF X7R ±10% 0603 Multilayer Ceramic Capacitors MLCC - SMD/SMT ROHS	C27, C28	0603 SMD CERAMIC CAPACITOR	GRM187R61A226ME15D	2
BAT54TW-TP	Small Signal Schottky Diodes	D1	SOT65P222X120-6N	BAT54TW-TP	1
150060RS75000 WL-SMCW_0603_1	0603, Red, Typ. (@20mA): 570nm, 40mcd, 2.0V, 140Â° AlInGaP	D2, D3	WL-SMCW_0603	150060RS75000 WL-SMCW_0603_1	2
150060VS75000 WL-SMCW_0603	0603, Bright Green, Typ.(@20mA): 570nm, 40mcd, 2.0V, 140Â° AlInGaP	D4	WL-SMCW_0603	150060VS75000 WL-SMCW_0603	1
ESDAULC6-3BP6	STMicroelectronics ESDAULC6-3BP6, Triple-Element Bi-Directional ESD Protection Array, 6-Pin SOT-666	D5	SOT50P160X60-6N	ESDAULC6-3BP6	1
USB4930-00-A_REVA	Type C USB 2.0 Connector	J1	GCT_USB4930-00-A_REVA	USB4930-00-A_REVA	1
B2B-PH-K-S	Connector Header Through Hole 2 position 0.079 (2.00mm)	J2	JST_B2B-PH-K-S	B2B-PH-K-S	1
SRN2010BTA-1R0M	Inductores de potencia - SMD Ind,2x1.6x0.9mm,1uH +/-20%,3.1A,shd	L1	SRN2010BTA-1R0M	SRN2010BTA-1R0M	1
BC847BW-7-F	TRANSISTOR	Q1	SOT65P210X110-3N	BC847BW-7-F	1
RC0603FR-0710KL	RES 10K OHM 1% 1/10W 0603	R1, R2, R3, R6, R10, R19, R20	0603 SMD RESISTOR	RC0603FR-0710KL	7
RC0603FR-07100KL	RES 100K OHM 1% 1/10W 0603	R4, R7, R21	0603 SMD RESISTOR	RC0603FR-07100KL	3
RC0603FR-7W470RL	RES 470 OHM 1% 1/10W 0603	R5, R8, R9	0603 SMD RESISTOR	RC0603FR-7W470RL	3
RC0603FR-1022RL	RES 22 OHM 1% 1/10W 0603	R11, R12	0603 SMD RESISTOR	RC0603FR-1022RL	2
RC0603FR-105K11L	RES 5.11K OHM 1% 1/10W 0603	R13, R14	0603 SMD RESISTOR	RC0603FR-105K11L	2
RT0603BRD073K12L	RES 3.12K OHM 1% 1/10W 0603	R15	0603 SMD RESISTOR	RT0603BRD073K12L	1
RC0603FR-074K42L	RES 4.42K OHM 1% 1/10W 0603	R16	0603 SMD RESISTOR	RC0603FR-074K42L	1
RC0603FR-074K7L	RES 4.7K OHM 1% 1/10W 0603	R17, R18	0603 SMD RESISTOR	RC0603FR-074K7L	2
RC0402FR-07732KL	RES 732K OHM 1% 1/16W 0603	R22	0603 SMD RESISTOR	RC0402FR-07732KL	1
Triple Solder Jumper		SJ	Triple Solder Jumper	Triple Solder Jumper	1
BQ24074RGTR	Standalone 1-cell 1.5-A linear battery charger, Power Path, 4.2-V VBAT, 10.5-V OVP and 4.4-V VOUT	U1	QFN50P300X300X100-17N	BQ24074RGTR	1
TLV75733PDRVR	1-A, low-IQ high-accuracy low-dropout (LDO) voltage regulator with enable	U2	VREG_TLV75733PDRVR	TLV75733PDRVR	1
MAX30102EFD+T	Pulse Oximeter and Heart Rate Sensor Digital Output	U3	XDCR_MAX30101EFD+	MAX30102EFD+T	1
RV-3028-C7	Real-Time Clock Module in 1.5 x 3.2 mm package	U4	IC_RV-3028-C7	RV-3028-C7	1
TLV70018DSER	200-mA, Low-IQ, Low-Dropout Regulator for Portable Devices	U5	SON50P150X150X80-6N	TLV70018DSER	1
LSM6DSO32TR	Accelerometer, Gyroscope, Temperature, 6 Axis Sensor IÂ²C, SPI Output	U6	XDCR_LSM6DSO32TR	LSM6DSO32TR	1
EVQ-P7C01P	Black Side Tactile Switch, SPST 50 mA@ 12 V dc 1.7mm	X1, X2, X3, X4	EVQP7C01P	EVQ-P7C01P	4