

Tsie-Report环境安装及部署测试

作者: 罗圣康

日期: 2026-06-12

1、环境安装

根据公司环境下载以下物料

```
docker-29.5.2-linux-x86_64.tgz
docker-compose-linux-x86_64-v5.1.4
mysql-8.0.46-linux-glibc2.17-x86_64.tar.xz
OpenJDK8U-jdk_x64_linux_hotspot_8u492b09.tar.gz
Tsie-Report 软件部署物料-20260525.zip
Tsie-Report 使用手册.pdf
录屏及截图软件.zip
```

(1) Docker 安装及初始化

① 使用以下指令，解压对应压缩包

```
tar -zxvf docker-29.5.2-linux-x86_64.tgz
```

结果如图:

```
[root@localhost qnh1_kh]# tar -zxvf docker-29.5.2-linux-x86_64.tgz
docker/
docker/dockerd
docker/docker-init
docker/ctr
docker/docker-proxy
docker/containerd-shim-runc-v2
docker/docker
docker/containerd
docker/runc
```

② 进入解压后的目录，并执行初始化操作，用于启动docker指令，执行结果如图

```
cd docker
```

```
\cp -f ./ * /usr/bin/
```

#查看文件是否存在/usr/bin, 可不查看

```
for f in *; do [ -e "/usr/bin/$f" ] && ls -l "/usr/bin/$f";  
done
```

```
docker --version #有回显表示安装成功
```

#启动containerd、docker

```
containerd &
```

```
dockerd &
```

```
[root@localhost qnhl_kh]# ls -l  
总用量 1752628  
drwxr-xr-x 2 Appuser Appuser 146 5月 20 22:47 docker  
-rw-r--r-- 1 root root 86920684 6月 12 15:23 docker-29.5.2-linux-x86_64.tgz  
-rw-r--r-- 1 root root 32884231 6月 12 15:23 docker-compose-linux-x86_64-v5.1.4  
-rw-r--r-- 1 root root 103553239 6月 12 15:23 OpenJDK8U-jdk_x64_linux_hotspot_8u492b09.tar.gz  
-rw-r--r-- 1 root root 1563571392 6月 12 15:23 Tsie-Report软件部署物料-20260525.zip  
-rw-r--r-- 1 root root 2269469 6月 12 15:23 Tsie-Report使用手册.pdf  
-rw-r--r-- 1 root root 5480384 6月 12 15:23 录屏及截图软件.zip  
[root@localhost qnhl_kh]# cd docker/  
[root@localhost docker]# ls -l  
总用量 230720  
-rw-r-xr-x 1 Appuser Appuser 43835554 5月 20 22:47 containerd  
-rw-r-xr-x 1 Appuser Appuser 10317986 5月 20 22:47 containerd-shim-runc-v2  
-rw-r-xr-x 1 Appuser Appuser 22589602 5月 20 22:47 ctr  
-rw-r-xr-x 1 Appuser Appuser 42632168 5月 20 22:47 docker  
-rw-r-xr-x 1 Appuser Appuser 95392552 5月 20 22:47 dockerd  
-rw-r-xr-x 1 Appuser Appuser 708456 5月 20 22:47 docker-init  
-rw-r-xr-x 1 Appuser Appuser 2660933 5月 20 22:47 docker-proxy  
-rw-r-xr-x 1 Appuser Appuser 18099392 5月 20 22:47 runc  
[root@localhost docker]# \cp -f * /usr/bin/  
[root@localhost docker]# for f in *; do [ -e "/usr/bin/$f" ] && echo "$f"; done  
containerd  
containerd-shim-runc-v2  
ctr  
docker  
dockerd  
docker-init  
docker-proxy  
runc  
[root@localhost docker]# for f in *; do [ -e "/usr/bin/$f" ] && ls -l "/usr/bin/$f"; done  
-rw-r-xr-x 1 root root 43835554 6月 12 16:29 /usr/bin/containerd  
-rw-r-xr-x 1 root root 10317986 6月 12 16:29 /usr/bin/containerd-shim-runc-v2  
-rw-r-xr-x 1 root root 22589602 6月 12 16:29 /usr/bin/ctr  
-rw-r-xr-x 1 root root 42632168 6月 12 16:29 /usr/bin/docker  
-rw-r-xr-x 1 root root 95392552 6月 12 16:29 /usr/bin/dockerd  
-rw-r-xr-x 1 root root 708456 6月 12 16:29 /usr/bin/docker-init  
-rw-r-xr-x 1 root root 2660933 6月 12 16:29 /usr/bin/docker-proxy  
-rw-r-xr-x 1 root root 18099392 6月 12 16:29 /usr/bin/runc  
[root@localhost docker]# docker --version  
Docker version 29.5.2, build 79eb04c  
[root@localhost docker]#
```

(2) Docker-Compose初始化

① 使用以下指令将程序包初始化, 结果如图所示

```
cp docker-compose-linux-x86_64-v5.1.4 /usr/bin/docker-compose
```

```
chmod +x /usr/bin/docker-compose
```

```
[root@localhost qnhl_kh]# cp docker-compose-linux-x86_64-v5.1.4 /usr/bin/docker-compose
[root@localhost qnhl_kh]# chmod +x /usr/bin/docker-compose
[root@localhost qnhl_kh]# docker-compose --version
Docker Compose version v5.1.4
[root@localhost qnhl_kh]#
```

(3) JDK安装及初始化

- ① 使用以下指令，创建JDK路径及解压JDK，如图所示

```
mkdir -p /usr/local/bin/java
```

```
tar -zxvf OpenJDK8U-jdk_x64_linux_hotspot_8u492b09.tar.gz -C
/usr/local/bin/java/
```

```
[root@localhost qnhl_kh]# mkdir -p /usr/local/bin/java
[root@localhost qnhl_kh]# tar -zxvf OpenJDK8U-jdk_x64_linux_hotspot_8u492b09.tar.gz -C /usr/local/bin/java/
jdk8u492-b09/
jdk8u492-b09/bin/
jdk8u492-b09/bin/rmid
jdk8u492-b09/bin/jarsigner
jdk8u492-b09/bin/jstat
jdk8u492-b09/bin/jjs
jdk8u492-b09/bin/cshsdb
jdk8u492-b09/bin/jps
jdk8u492-b09/bin/hsdb
jdk8u492-b09/bin/jcmd
jdk8u492-b09/bin/javac
jdk8u492-b09/bin/jinfo
jdk8u492-b09/bin/jsadebugd
jdk8u492-b09/bin/iman
```

- ② 使用以下指令，配置java环境变量

```
vi /etc/profile
```

#在profile文件中写入以下内容

```
export JAVA_HOME=/usr/local/bin/java/jdk8u492-b09
```

```
export PATH=$JAVA_HOME/bin:$PATH
```

```
export
```

```
CLASSPATH=.:$JAVA_HOME/lib/dt.jar:$JAVA_HOME/lib/tools.jar
```

```
source /etc/profile
```

```
export JAVA_HOME=/usr/local/bin/java/jdk8u492-b09
export PATH=$JAVA_HOME/bin:$PATH
export CLASSPATH=.:$JAVA_HOME/lib/dt.jar:$JAVA_HOME/lib/tools.jar
```

```
[root@localhost jdk8u492-b09]# vi /etc/profile
[root@localhost jdk8u492-b09]# source /etc/profile
[root@localhost jdk8u492-b09]# vi /etc/profile
[root@localhost jdk8u492-b09]# java -version
openjdk version "1.8.0_492"
OpenJDK Runtime Environment (Temurin)(build 1.8.0_492-b09)
OpenJDK 64-Bit Server VM (Temurin)(build 25.492-b09, mixed mode)
```

(4) MySQL安装及初始化

- ① 使用以下指令把安装包解压到指定目录

```
mkdir -p /usr/local/bin/mysql/

#-z解压.gz, -j解压.bz, -J解压.xz
tar -Jxvf mysql-8.0.46-linux-glibc2.17-x86_64.tar.xz -C
/usr/local/bin/mysql/
```

```
[root@localhost qnhl_kh]# mkdir -p /usr/local/bin/mysql
[root@localhost qnhl_kh]# tar -Jxvf mysql-8.0.46-linux-glibc2.17-x86_64.tar.xz -C /usr/local/bin/mysql/
mysql-8.0.46-linux-glibc2.17-x86_64/bin/
mysql-8.0.46-linux-glibc2.17-x86_64/bin/myisam_ftdump
mysql-8.0.46-linux-glibc2.17-x86_64/bin/myisamchk
mysql-8.0.46-linux-glibc2.17-x86_64/bin/myisamlog
mysql-8.0.46-linux-glibc2.17-x86_64/bin/myisampack
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_config_editor
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_migrate_keyring
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_secure_installation
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_ssl_rsa_setup
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_tzinfo_to_sql
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_upgrade
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqladmin
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlbinlog
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlcheck
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqldump
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlimport
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlpump
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlshow
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqlslap
mysql-8.0.46-linux-glibc2.17-x86_64/lib/
mysql-8.0.46-linux-glibc2.17-x86_64/lib/plugin/
mysql-8.0.46-linux-glibc2.17-x86_64/lib/plugin/authentication_fido_client.so
mysql-8.0.46-linux-glibc2.17-x86_64/lib/plugin/authentication_kerberos_client.so
mysql-8.0.46-linux-glibc2.17-x86_64/lib/plugin/authentication_ldap_sasl_client.so
mysql-8.0.46-linux-glibc2.17-x86_64/lib/plugin/authentication_oci_client.so
mysql-8.0.46-linux-glibc2.17-x86_64/bin/
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysqld-debug
mysql-8.0.46-linux-glibc2.17-x86_64/bin/
mysql-8.0.46-linux-glibc2.17-x86_64/bin/mysql_config
mysql-8.0.46-linux-glibc2.17-x86_64/include/
```

- ②使用以下指令，对 MySQL进行软链接及目录结构构建

```
ln -s /usr/local/bin/mysql/mysql-8.0.46-linux-glibc2.17-x86_64 /usr/local/mysql
```

```
useradd -r -s /sbin/nologin -M mysql
```

```
mkdir -p /usr/local/mysql/{data,logs,tmp}
```

```
chown -R mysql:mysql /usr/local/mysql
```

```
[root@localhost qnhl_kh]# ln -s /usr/local/bin/mysql/mysql-8.0.46-linux-glibc2.17-x86_64 /usr/local/mysql
[root@localhost qnhl_kh]# mkdir -p /usr/local/mysql/{data,logs,tmp}
[root@localhost qnhl_kh]# chown -R mysql:mysql /usr/local/mysql
[root@localhost qnhl_kh]# ls -l /usr/local/mysql/
总用量 268
drwxr-xr-x 2 7161 31415 4096 4月 8 00:56 bin
drwxr-xr-x 2 root root 6 6月 13 11:02 data
drwxr-xr-x 2 7161 31415 38 4月 8 00:56 docs
drwxr-xr-x 3 7161 31415 282 4月 8 00:56 include
drwxr-xr-x 6 7161 31415 201 4月 8 00:56 lib
-rw-r--r-- 1 7161 31415 259907 4月 7 23:27 LICENSE
drwxr-xr-x 2 root root 6 6月 13 11:02 logs
drwxr-xr-x 4 7161 31415 30 4月 8 00:56 man
-rw-r--r-- 1 7161 31415 666 4月 7 23:27 README
drwxr-xr-x 28 7161 31415 4096 4月 8 00:56 share
drwxr-xr-x 2 7161 31415 77 4月 8 00:56 support-files
drwxr-xr-x 2 root root 6 6月 13 11:02 tmp
[root@localhost qnhl_kh]#
```

③ 使用以下指令，对MySQL进行初始化及密码修改

```
vim /etc/my.cnf
```

```
#把以下配置写入my.cnf
```

```
[mysqld]
```

```
port=3306
```

```
user=mysql
```

```
basedir=/usr/local/mysql
```

```
datadir=/usr/local/mysql/data
```

```
socket=/usr/local/mysql/tmp/mysql.sock
```

```
pid-file=/usr/local/mysql/tmp/mysqld.pid
```

```
log-error=/usr/local/mysql/logs/mysqld_error.log
```

```
slow-query-log-file=/usr/local/mysql/logs/slow.log
```

```
max_connections=200
```

```
max_connect_errors=10
```

```
character-set-server=utf8mb4
```

```
collation-server=utf8mb4_bin
```

```
[client]
```

```
socket=/usr/local/mysql/tmp/mysql.sock
```

```
default-character-set=utf8mb4
```

```
[mysqld]
port=3306
user=mysql
basedir=/usr/local/mysql
datadir=/usr/local/mysql/data
socket=/usr/local/mysql/tmp/mysql.sock
pid-file=/usr/local/mysql/tmp/mysqld.pid

log-error=/usr/local/mysql/logs/mysqld_error.log
slow-query-log-file=/usr/local/mysql/logs/slow.log

max_connections=200
max_connect_errors=10

character-set-server=utf8mb4
collation-server=utf8mb4_bin

[client]
default-character-set=utf8mb4
```

#初始化MySQL

```
/usr/local/mysql/bin/mysqld --initialize --user=mysql
```

#查找初始密码

```
grep 'temporary password'
```

```
/usr/local/mysql/logs/mysqld_error.log
```

```
[root@localhost qnhl_kh]# /usr/local/mysql/bin/mysqld --initialize --user=mysql
[root@localhost qnhl_kh]# grep 'temporary password' /usr/local/mysql/logs/mysqld_error.log
2026-06-13T03:32:16.311328Z 6 [Note] [MY-010454] [Server] A temporary password is generated for root@localhost: Yusgr.Qu,6>z
[root@localhost qnhl_kh]#
```

vi /etc/profile

#把环境变量写入profile

```
export PATH=$PATH:/usr/local/mysql/bin:$PATH
```

source /etc/profile

#启动MySQL， 并加入开机自启动

```
cp /usr/local/mysql/support-files/mysql.server /etc/init.d/mysql
```

```
chkconfig --add mysql
chkconfig mysql on
/etc/init.d/mysql start
```

```
unset i
unset -f pathmunge
export JAVA_HOME=/usr/local/bin/java/jdk8u492-b09
export PATH=$JAVA_HOME/bin:$PATH
export CLASSPATH=.:$JAVA_HOME/lib/dt.jar:$JAVA_HOME/lib/tools.jar
export PATH=$PATH:/usr/local/mysql/bin:$PATH
export PATH=$PATH:/usr/local/bin:$PATH
```

```
[root@localhost qnhl_kh]# cp /usr/local/mysql/support-files/mysql.server /etc/init.d/mysql
[root@localhost qnhl_kh]# chkconfig --add mysql
[root@localhost qnhl_kh]# chkconfig mysql on
[root@localhost qnhl_kh]# /etc/init.d/mysql start
Starting MySQL... SUCCESS!
```

`mysql -uroot -p` #密码来自grep 'temporary password'
/usr/local/mysql/logs/mysql_error.log 中获取的

`ALTER USER 'root'@'localhost' IDENTIFIED BY '自己要设定的密码';`

```
[root@localhost qnhl_kh]# mysql -uroot -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 11
Server version: 8.0.46

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> ALTER USER 'root'@'localhost' IDENTIFIED BY '123456';
Query OK, 0 rows affected (0.00 sec)

mysql> exit
Bye
```

(5) 数据库连接常见问题处理

应用启动或运行中遇到以下四种数据库报错时，按对应步骤处理。

报错一：Access denied for user 'root'@'xxx' (using password: YES)

原因：数据库密码错误或不匹配。

① 登录 MySQL

```
mysql -uroot -p
```

② 修改 root 密码

```
ALTER USER 'root'@'localhost' IDENTIFIED BY '123456';
```

如果需从其他主机也使用此密码登录：

```
CREATE USER IF NOT EXISTS 'root'@'%' IDENTIFIED BY '123456';  
ALTER USER 'root'@'%' IDENTIFIED BY '123456';  
GRANT ALL PRIVILEGES ON *.* TO 'root'@'%' WITH GRANT OPTION;  
FLUSH PRIVILEGES;
```

③ 同步修改 bootstrap.yml 中的密码

```
spring:  
  datasource:  
    password: 123456    # 与服务端保持一致
```

报错二：Host is blocked because of many connection errors

原因：连接错误次数超过 `max_connect_errors`（默认 10 次），MySQL 自动封锁该主机。

① 登录 MySQL 并立即解除封锁

```
mysql -uroot -p  
FLUSH HOSTS;
```

② （可选）调大 `max_connect_errors`，防止再次被封锁

编辑 MySQL 配置文件 `/etc/my.cnf`，找到或添加：


```
max_connect_errors=1000
```

保存后重启 MySQL:

```
/etc/init.d/mysql restart
```

报错三: Public Key Retrieval is not allowed

原因: JDBC 连接 URL 缺少 `allowPublicKeyRetrieval=true` 参数 (MySQL 8.x 使用 `caching_sha2_password` 插件时需要)。

① 修改 `bootstrap.yml` 中的 JDBC URL, 添加参数:

```
spring:
  datasource:
    url: jdbc:mysql://192.168.5.128:13306/aj_report?
    characterEncoding=UTF-
    8&serverTimezone=Asia/Shanghai&useSSL=false&allowPublicKeyRetrieval=true
```

关键: 在 URL 末尾加上 `&allowPublicKeyRetrieval=true`

报错四: Data too long for column 'json_str' at row 1

原因: `gaea_report_excel` 表的 `json_str` 字段为 `text` 类型 (最大 64KB), 报表 JSON 串超长。

① 登录 MySQL 后执行:

```
ALTER TABLE gaea_report_excel MODIFY COLUMN `json_str`
mediumtext CHARACTER SET utf8 COLLATE utf8_general_ci NULL
COMMENT '报表json串';
```

② 同步修改初始化 SQL 文件 (第 693 行):

将 `db/v1.0.0__init.sql` 中:

```
`json_str` text ...
```

改为:

```
`json_str` mediumtext ...
```

完成上述所有步骤，则表示所有初始环境均已完成配置。

2、Tsie-Report部署

(1) 部署包解压

```
unzip Tsie-Report软件部署物料-20260525.zip -d /opt/soft_qn/
```

```
[root@localhost qnhl_kh]# unzip Tsie-Report软件部署物料-20260525.zip -d /opt/soft_qn/
Archive:  Tsie-Report软件部署物料-20260525.zip
  creating: /opt/soft_qn/自动报告生成/
  inflating: /opt/soft_qn/自动报告生成/Tsintergy-Report报表工具部署手册-简化版（不带安装链接）.docx
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/._Tsintergy-Report报表工具部署手册.docx
  inflating: /opt/soft_qn/自动报告生成/.DS_Store
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/._.DS_Store
  creating: /opt/soft_qn/自动报告生成/aj-eport/
  inflating: /opt/soft_qn/自动报告生成/aj-eport/.DS_Store
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/._.DS_Store
  creating: /opt/soft_qn/自动报告生成/aj-eport/onlyoffice/
  creating: /opt/soft_qn/自动报告生成/aj-eport/db/
  inflating: /opt/soft_qn/自动报告生成/aj-eport/aj-report-1.7.1.RELEASE-assembly.zip
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/._aj-report-1.7.1.RELEASE-assembly.zip
  inflating: /opt/soft_qn/自动报告生成/aj-eport/onlyoffice/onlyoffice-documentserver_8.1.1.tar
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/onlyoffice/._onlyoffice-documentserver_8.1.1.ta
  inflating: /opt/soft_qn/自动报告生成/aj-eport/onlyoffice/docker-compose.yml
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/onlyoffice/._docker-compose.yml
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.0.0__init.sql
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/db/._V1.0.0__init.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.4.2__update.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.2.0__update.sql
  extracting: /opt/soft_qn/自动报告生成/aj-eport/db/V1.6.0__update.sql
  extracting: /opt/soft_qn/自动报告生成/aj-eport/db/V1.1.0__update.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.5.0__update.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.7.1__add_word_template.sql
  inflating: /opt/soft_qn/__MACOSX/自动报告生成/aj-eport/db/._V1.7.1__add_word_template.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.7.0__update.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.3.0__update.sql
  inflating: /opt/soft_qn/自动报告生成/aj-eport/db/V1.5.1__update.sql
```

(2) 数据库初始化

#进入数据库目录

```
cd /opt/soft_qn/自动报告生成/aj-eport/db/
```

#将所有的sql合并到一个.sql文件

```
cat ./*.sql > all.sql
```

#链接数据库，并执行脚本

```
mysql -uroot -p
```

进入 MySQL 交互界面后，依次执行以下命令：

```
source /opt/soft_qn/自动报告生成/aj-eport/db/all.sql;
```

-- 查看库表建立情况

```
show databases;
```

```
use aj_report;
```

```
show tables;
```

```
[root@localhost aj-eport]# cd db/
[root@localhost db]# ls -l
总用量 116
-rw-r--r-- 1 root root 78984 5月 21 15:25 V1.0.0__init.sql
-rw-r--r-- 1 root root 0 4月 16 09:23 V1.1.0__update.sql
-rw-r--r-- 1 root root 1698 4月 16 09:23 V1.2.0__update.sql
-rw-r--r-- 1 root root 2114 4月 16 09:23 V1.3.0__update.sql
-rw-r--r-- 1 root root 2877 4月 16 09:23 V1.4.2__update.sql
-rw-r--r-- 1 root root 1840 4月 16 09:23 V1.5.0__update.sql
-rw-r--r-- 1 root root 101 4月 16 09:23 V1.5.1__update.sql
-rw-r--r-- 1 root root 0 4月 16 09:23 V1.6.0__update.sql
-rw-r--r-- 1 root root 1925 4月 16 09:23 V1.7.0__update.sql
-rw-r--r-- 1 root root 8780 4月 16 16:03 V1.7.1__add_word_template.sql
[root@localhost db]# cat *.sql > all.sql
[root@localhost db]# mysql -uroot -p
Enter password:
ERROR 1045 (28000): Access denied for user 'root'@'localhost' (using password: YES)
[root@localhost db]# mysql -uroot -p123456
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 145
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> source /opt/soft_qn/自动报告生成/aj-eport/db/all.sql;
Query OK, 0 rows affected (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

Query OK, 1 row affected, 2 warnings (0.01 sec)

Database changed
Query OK, 0 rows affected, 1 warning (0.00 sec)

Query OK, 0 rows affected, 21 warnings (0.01 sec)
```

```
mysql> show databases;
+-----+
| Database |
+-----+
| aj_report |
| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
5 rows in set (0.00 sec)
```

```
mysql> use aj_report
```

```
Database changed
```

```
mysql> show tables;
```

```
+-----+
| Tables_in_aj_report |
+-----+
| access_authority |
| access_role |
| access_role_authority |
| access_user |
| access_user_role |
| flyway_schema_history |
| gaea_dict |
| gaea_dict_item |
| gaea_file |
| gaea_report |
| gaea_report_dashboard |
| gaea_report_dashboard_widget |
| gaea_report_data_set |
| gaea_report_data_set_param |
| gaea_report_data_set_transform |
| gaea_report_data_source |
| gaea_report_excel |
| gaea_report_share |
| gaea_report_word_report |
| gaea_report_word_template |
| gaea_report_word_template_variable |
+-----+
21 rows in set (0.01 sec)
```

(3) 容器包初始化及启动

```
docker load -i onlyoffice-documentserver_8.1.1.tar

docker images

docker-compose -f /opt/soft_qn/自动报告生成/aj-
eport/onlyoffice/docker-compose.yml up -d
```

```
[root@localhost onlyoffice]# docker load -i onlyoffice-documentserver_8.1.1.tar
ERROR[2025-06-13T13:39:48.458024440+08:00] failed to validate image signature error="resolving
signature chain for image sha256:ccb74076a3639b18dd4f75884c144a8d75473293f4e5e861cddf20c065b86aa2: expe
cted image index descriptor, got application/vnd.docker.distribution.manifest.v2+json"
Loaded image: registry.tsintergy.com/tsintergy/onlyoffice/documentserver:8.1.1
[root@localhost onlyoffice]# docker images
```

IMAGE	ID	DISK USAGE	CONTENT SIZE	EXTRA
registry.tsintergy.com/tsintergy/onlyoffice/documentserver:8.1.1	ccb74076a363	8.17GB	4.03GB	

```
[root@localhost onlyoffice]# docker-compose -f /opt/soft_qn/aj-eport/onlyoffice/docker-compose.yml -d up
unknown shorthand flag: 'd' in -d
[root@localhost onlyoffice]# docker-compose -f /opt/soft_qn/aj-eport/onlyoffice/docker-compose.yml up -d
WARN[0000] /opt/soft_qn/aj-eport/onlyoffice/docker-compose.yml: the attribute 'version' is obsolete, it will be ignored, please remove it to avoid potential confusion
[+] up 1/2
  ✓ Network onlyoffice_default Created
[+] up 1/2er onlyoffice-docservice Starting
  ✓ Network onlyoffice_default Created
[+] up 2/2er onlyoffice-docservice Starting
  ✓ Network onlyoffice_default Created
  ✓ Container onlyoffice-docservice Started
[root@localhost onlyoffice]# docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
02e8e41f3eba	registry.tsintergy.com/tsintergy/onlyoffice/documentserver:8.1.1	"/app/ds/run-documen..."	7 seconds ago	Up 5 seconds	443/tcp, 127.0.0.1:8060->80/tcp	onlyoffi

```
[root@localhost onlyoffice]#
```

(3.1) OnlyOffice 容器配置——允许访问私有IP

报错现象：在线预览/编辑文档时失败，OnlyOffice 日志报错：

```
error
downloadFile:url=http://192.168.5.128:9095/word/template/only
office/file/...
DNS lookup 192.168.5.128 is not allowed. Because, It is
private IP address.
```

① 从容器中拷出配置文件到宿主机（仅首次需要）

```
docker cp onlyoffice-
docservice:/etc/onlyoffice/documentserver/default.json
/opt/aj-eport/onlyoffice/default.json
```

② 在宿主机上修改配置，将 allowPrivateIPAddress 改为 true

```
sed -i 's/"allowPrivateIPAddress":
false/"allowPrivateIPAddress": true/' /opt/aj-
eport/onlyoffice/default.json
```

③ 编辑 docker-compose.yml，在 volumes：下添加一行挂载配置，一劳永逸：

```
volumes:
  -
    /opt/onlyoffice/fonts:/usr/share/fonts/truetype/custom:ro
  - /opt/aj-
    eport/onlyoffice/default.json:/etc/onlyoffice/documentserver/
    default.json:ro    # 新增这行
```

④ 重建容器使配置生效

```
cd /opt/aj-eport/onlyoffice
docker-compose down
docker-compose up -d
```

⑤ 验证是否生效

```
docker exec onlyoffice-docservice grep
"allowPrivateIPAddress"
/etc/onlyoffice/documentserver/default.json
# 应输出: "allowPrivateIPAddress": true
```

原理：OnlyOffice 8.x 的 `request-filtering-agent` 默认禁止访问私有 IP（192.168.x.x、10.x.x.x、172.16-31.x.x），导致无法从 Java 后端下载文档。通过 volume 挂载宿主机修改后的配置文件，即使容器重建也能自动生效。

（4）修改配置文件

使用 `vim` 编辑 `bootstrap.yml` 配置文件，根据实际环境修改数据库连接地址、用户名及密码等参数，如图所示：

```
max-file-size: 10MB # 上传附件大小限制/92MB
jackson:
  date-format: yyyy-MM-dd HH:mm:ss
  time-zone: GMT+8
messages:
  basename: i18n/messages
datasource:
  url: jdbc:mysql://192.168.5.128:13306/aj_report?characterEncoding=UTF-8&serverTimezone=Asia/Shanghai&useSSL=false&allowPublicKeyRetrieval=true
  username: root
  password: 123456
  driver-class-name: com.mysql.cj.jdbc.Driver
  type: com.alibaba.druid.pool.DruidDataSource
# 数据库连接池配置
druid:
  initial-size: 50
  min-idle: 50
  max-active: 100
  # 获取连接等待超时的时间
  max-wait: 5000
  # 配置间隔多久才进行一次检测
  time-between-eviction-runs-millis: 60000
```



```

127 | web:
128 |   base-path: /
129 | logging:
130 |   config: classpath:logback.xml
131 |
132 | # 本应用自定义参数
133 | customer:
134 |   # 跳过token验证和权限验证的url清单
135 |   skip-authenticate-urls: /gaeaDict/all, /login, /static, /file/download/, /index.html, /favicon.ico, /reportShare/detailByCode, /v2/api-docs, /reportExcel/e
136 |   file:
137 |     # 导入导出临时文件夹 默认.代表当前目录, 拼接/tmp_zip/目录
138 |     tmpPath: .
139 | user:
140 |   ## 新增用户默认密码
141 |   default:
142 |     password: 123456 改为服务器IP
143 |   onlyoffice:
144 |     server-url: http://192.168.5.128:9095/onlyoffice
145 |     token-secret: my_jwt_secret
146 |     target-url: http://127.0.0.1:8060
147 |

```

(5) 启动后端，及前端验证

#进入安装目录

```

cd /opt/soft_qn/自动报告生成/aj-eport/aj-report-
1.7.1.RELEASE/bin
./start.sh

```

