

Content

- Classic Providers
- Tree-shakable Providers
- Scopes
- Constants as Tokens
- Services and Lazy Loading
- Multi Providers



Classic Providers



Service

```
@Injectable()
export class FlightService {
    [...]
}
```

Classic Providers

```
@NgModule({
    imports: [
        BrowserModule, HttpModule, FormsModule
    declarations: [
        AppComponent, FlightSearchComponent
    ],
    providers: [
        FlightService
    bootstrap: [
        AppComponent
})
export class AppModule {
```

Standalone Components

```
bootstrapApplication(AppComponent, {
   providers: [
     FlightService
  ]
}
```



Injecting Service into Consumer

```
@Component({
    selector: 'flight-search',
    templateUrl: 'flight-search.html'
})
export class FlightSearchComponent {
    from = '';
    to = '';
    flight: Flight[] = [];
    constructor(private flightService: FlightService) { ... }
    flightSearch() { [...] }
    selectFlight(flight) { [...] }
```

Injecting Service into Consumer – NEW in V14

```
@Component({
    selector: 'flight-search',
    templateUrl: 'flight-search.html'
})
export class FlightSearchComponent {
    from = '';
    to = '';
    flight: Flight[] = [];
    flightService = inject(FlightService);
    flightSearch() { [...] }
    selectFlight(flight) { [...] }
```

Abstraction

```
export abstract class FlightService {
    abstract find(from: string, to: string): Observable<Flight[]>;
}
@Injectable()
export class DefaultFlightService implements FlightService {
    find(from: string, to: string): Observable<Flight[]> { ... }
```

"Forward" with useClass

```
@NgModule({
    imports: [
        BrowserModule, HttpModule, FormsModule
    declarations: [
        AppComponent, FlightSearchComponent
    ],
    providers: [
        { provide: FlightService, useClass: DefaultFlightService }
    bootstrap: [
        AppComponent
})
export class AppModule {
```

"Forward" with useClass

```
@NgModule({
    imports: [
        BrowserModule, HttpModule, FormsModule
    declarations: [
        AppComponent, FlightSearchComponent
    providers: [
        { provide: FlightService, useClass: DefaultFlightService }
    bootstrap: [
        AppComponent
export class AppModule {
```

"Forward" with useClass

```
@NgModule({
    imports: [
        BrowserModule, HttpModule, FormsModule
    declarations: [
        AppComponent, FlightSearchComponent
    providers: [
        { provide: FlightService, useClass: DefaultFlightService }
    bootstrap: [
                        Token
                                           Service
        AppComponent
export class AppModule {
```

Tokens

- Interfaces cannot be used as tokens
- However, you can use abstract classes instead

useFactory

```
const DEBUG = !environment.production;
[\ldots]
providers: [{
    provide: FlightService,
    useFactory: (http: HttpClient) => {
        if (DEBUG) {
            return new DummyFlightService();
        } else {
            return new FlightService(http);
}]
```



useFactory

```
const DEBUG = true;
[\ldots]
providers: [{
    provide: FlightService,
    useFactory: (http: HttpClient) => {
        if (DEBUG) {
            return new DummyFlightService();
        } else {
            return new FlightService(http);
     deps: [HttpClient]
}]
```



Types of Providers

useClass

useValue

useFactory

useExisting



Tree-Shakable Provider



Example

```
@Injectable({ providedIn: 'root' })
export class FlightService {
    [...]
}
```


useClass

```
@Injectable({
    providedIn: 'root',
    useClass: DefaultFlightService
})
export abstract class FlightService {
    abstract find(from: string, to: string);
}
```

```
@Injectable()
export class DefaultFlightService implements FlightService {
   find(from: string, to: string) { ... }
}
```



implements vs. extends





useFactory

```
@Injectable({
    providedIn: 'root',
    useFactory: (http: HttpClient) => {
        return new DefaultFlightService(http);
    deps: [HttpClient]
})
export abstract class FlightService {
    abstract find(from: string, to: string): Observable<Flight[]>;
```



DEMO



Scopes



"Locale Service": Own Scope


```
@Component({
    selector: 'flight-search',
    templateUrl: 'app/flight-buchen/flight-buchen.html',
    providers: [{ provide: FlightService, useClass: FlightService}]
})
export class FlightSearchComponent {
    [...]
}
```

Can be used in current component and below!



Scopes

FlightService (global)





DEMO



Multi Providers



Multi

```
export class AppComponent {
    constructor(
       @Inject(FlightService) private flightServices: FlightService[]) {
    }
    [...]
}
```



Multi and Constants

```
export class AppComponent {
    constructor(
       @Inject(FLIGHT_SERVICES) private flightServices: FlightService[]) {
    }
    [...]
}
```



Summary

- forRoot vs. in component
- Classic providers vs. tree-shakable providers
- Factories
- Multi Providers

