



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Components Deep Dive

angular-architects.io

Contents

- Interacting with Content
- Interacting with View
- Working with Handles
- Providers vs. ViewProviders



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Why is this Interesting?

- Reusable Components (Component Libraries)
- Better Understanding for Angular



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Interacting with a Component's **Content**



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Case Study #1: Tabbed Pane

Upcoming Flights Operated Flights Cancelled Flights

Upcoming Flights

1	Hamburg	Berlin	01.02.2025 17:00
2	Hamburg	Frankfurt	01.02.2025 17:30
3	Hamburg	Mallorca	01.02.2025 17:45



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Tabbed Pane

```
<app-tabbed-pane>
  <app-tab title="Upcoming Flights">
    <p>No upcoming flights!</p>
  </app-tab>

  <app-tab title="Operated Flights">
    <p>No operated flights!</p>
  </app-tab>

  <app-tab title="Cancelled Flights">
    <p>No cancelled flights!</p>
  </app-tab>
</app-tabbed-pane>
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

View vs. Content



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

View vs. Content

```
@Component({
  selector: 'tab',
  template: `
    <div *ngIf="visible">
      <h1>{{title}}</h1>
      <div>
        <ng-content></ng-content>
      </div>
    </div>
  `
})
export class TabComponent {
  @Input() title: string;
  visible: boolean = true;
}
```

View

Content

Sample Text ...



Hooks

- 1) `ngOnChanges`
- 2) `ngOnInit`
- 3) `ngDoCheck`
- 4) `ngAfterContentInit`
- 5) `ngAfterContentChecked`
- 6) `ngAfterViewInit`
- 7) `ngAfterViewChecked`
- 8) `ngOnDestroy`



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Hooks

- 1) ngOnChanges
- 2) ngOnInit
- 3) ngDoCheck
- 4) ngAfterContentInit**
- 5) ngAfterContentChecked**
- 6) ngAfterViewInit**
- 7) ngAfterViewChecked**
- 8) ngOnDestroy



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Handles



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Handles

```
<app-tabbed-pane #pane>  
  [...]  
</app-tabbed-pane>
```

Current Page: {{ pane.currentPage }}



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

ViewProviders



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Providers

```
@Component({  
  providers: [NavigatorService]  
})  
export class TabbedPaneComponent {  
  [...]  
}
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Providers

```
@Component({  
  providers: [NavigatorService] // Visible in View and Content  
})  
export class TabbedPaneComponent {  
  [...]  
}
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

View Providers

```
@Component({  
  viewProviders: [NavigatorService] // Visible only in View  
})  
export class TabbedPaneComponent {  
  [...]  
}
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

LAB



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Summary

- Content vs. View
- [Content | View][Child | Children]
- Handles
- Providers vs. ViewProviders



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT