



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Data Binding and OnPush

ANGULARarchitects.io

Contents

- How does data binding work (underneath the covers)?
- Performance-Tuning with OnPush



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Data Binding




ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT


Component Tree in Angular 2+



Rules for Property-Bindings


- Data flows top/down
 - Parent can send data to children
 - Children **cannot** send data to parent
- Dependency graph is a tree
- Angular only needs one "digest"

Property Binding



[<http://victorsavkin.com/post/110170125256/change-detection-in-angular-2>]


Event Bindings (One-Way, Bottom/Up)



Event Bindings (One-Way, Bottom/Up)

- Cheap: No "digest" needed!
- However: Events can change data → Property Binding

Property- and Event-Bindings



View

```
<button [disabled]="!from || !to" (click)="search()">  
  Search  
</button>
```

```
<table>  
  <tr *ngFor="let flight of flights">  
    <td>{{flight.id}}</td>  
    <td>{{flight.date}}</td> ← - - - - - > <td [text-content]="flight.date"></td>  
    <td>{{flight.from}}</td>  
    <td>{{flight.to}}</td>  
    <td><a href="#" (click)="selectFlight(flight)">Select</a></td>  
  </tr>  
</table>
```

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Recap

- Property-Binding: One-Way; Top/Down
- Event-Binding: One-Way; Bottom/Up
- Two-Way-Binding?
- Two-Way = Property-Binding + Event-Binding




Property and Event Bindings

```
<input [ngModel]="from" (ngModelChange)="update($event)">
```



Property and Event Bindings

`<input [ngModel]="from" (ngModelChange)="from = $event">`



Property + *Change*

`<input [(ngModel)]="from">`



New Value



DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Performance Tuning with OnPush



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO




ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

OnPush



Angular just checks when “notified”



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

"Notify" about change?

- Change bound data (@Input)
 - OnPush: Angular just compares the object reference!
 - e. g. `oldFlight === newFlight`
- Raise event within the component
- Notify a bound observable
 - `{{ flights$ | async }}`
- Trigger it manually
 - Don't do this at home ;-)
 - At least: Try to avoid this



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Activate OnPush

```
@Component({  
  [...]  
  changeDetection: ChangeDetectionStrategy.OnPush  
})  
export class FlightCard {  
  [...]  
  @Input() flight;  
}
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

DEMO



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

LAB



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT

Summary

- Event Bindings → Property Bindings
- No cycles allowed!
- OnPush
- Immutables & Observables



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE



SOFTWARE
ARCHITECT