



ANGULAR  
**ARCHITECTS**  
INSIDE KNOWLEDGE

# Services & Dependency Injection

Alex Thalhammer

# Why Services?

Reusable

Example:  
FlightService



# What types of Services?

Infrastructure  
(API/Backend)

Application  
(Functions)

Communication  
bw. Comp.

State  
Management



# Service

```
@Injectable({ providedIn: 'root' })  
export class FlightService {  
  
    [...]  
  
}
```



# Service

global scope

```
@Injectable({ providedIn: 'root' })  
export class FlightService {  
  
    [...]  
  
}
```

**services are singletons  
(in their “scope”)**



# Consumer gets injected service

```
@Component({
  selector: 'app-flight-search',
  templateUrl: 'flight-search.component.html'
})
export class FlightSearchComponent {
  from = '';
  to = '';
  flights: Flight[] = [];

  private readonly flightService = inject(FlightService);

  search(): void { [...] }
  select(flight): void { [...] }
}
```



# Consumer gets injected service in constructor

```
@Component({
  selector: 'app-flight-search',
  templateUrl: 'flight-search.component.html'
})
export class FlightSearchComponent {
  from = '';
  to = '';
  flights: Flight[] = [];

  constructor(private readonly flightService: FlightService) { ... }

  search(): void { [...] }
  select(flight): void { [...] }
}
```

Token

# Token vs. Service

- Token: What the consumer requests  
(e. g. FlightService)
- Service: What the consumer receives  
(e. g. AdvancedFlightService)



# Token

- Almost everything can be a token
- In most cases: default implementation of service
- Abstract (Base)-Class
- Constant
- But no interface



# Factory

```
@Injectable({
  providedIn: 'root',
  useFactory: (http: HttpClient) => {
    return new DefaultFlightService(http);
  },
  deps: [HttpClient]
})
export abstract class FlightService {
  abstract find(from: string, to: string): Observable<Flight[]>;
}
```



# Factory

```
@Injectable({
  providedIn: 'root',
  useFactory: (http: HttpClient) => {
    return new DefaultFlightService(http);
  },
  deps: [HttpClient]
})
export abstract class FlightService {
  abstract find(from: string, to: string): Observable<Flight[]>;
}
```



# Factory

```
@Injectable({
  providedIn: 'root',
  useFactory: (http: HttpClient) => {
    if (environment.production) {
      return new DefaultFlightService(http);
    } else {
      return new DummyFlightService(http);
    }
  },
  deps: [HttpClient]
})
export abstract class FlightService {
  abstract find(from: string, to: string): Observable<Flight[]>;
}
```



# DEMO



ANGULAR  
**ARCHITECTS**  
INSIDE KNOWLEDGE



SOFTWARE  
**ARCHITECT**

# LAB



ANGULAR  
**ARCHITECTS**  
INSIDE KNOWLEDGE



SOFTWARE  
**ARCHITECT**