zee

① 1. add x15, x12, x11
NOP
NOP
ld x13, 4(x15)
ld x12, 0(x2)
NOP
or x13, x15, 13
NOP
NOP
sd x13, 0(x15)

2. No. Because the first one and second one have RAW
four and two have RAW
five and four have RAW

3. code can execute here even don't have hazard detection Unit.
if we do forward. These code are availabe to keep run., Because they don't have RAW (~~three and two~~), that meaning the one of instruction perform memory operation.

② T, NT, T, T, NT.

1. Always - taken.

T, NT, T, T, NT.
T T T T T.

$\frac{3}{5} = 60\% = 0.6$

Always - Not - taken.

T, NT, T, T, NT
NT, NT, NT, NT, NT.

$\frac{2}{5} = 40\% = 0.4$

2. T, NT, T, T, NT.

Begin from NT. → NT

NT in get NT → NT.

T in get NT → NT.

T in get NT → NT.

T, NT, T, T $\frac{1}{4} = 25\% = 0.25$.

NT, NT, NT, NT

3.

1st	2nd	3rd	4.
NT	NT	T	T
NT	T	~~NT~~ T	~~NT~~ T
NT	NT	T	T
NT	T	T	T
T	T	~~NT~~ T	~~NT~~ T

T NT T T NT

T T T T T $\frac{3}{5} = 60\% = 0.6$

③ 0x01, 0x64, 0x2b, 0x02, 0xbe, 0x58, 0xbf
0x0e, 0x1f, 0xb5, 0xbf, 0xba, 0x2e, 0xce

~~Binary tag set offset block~~

~~0x03, 00000011, 0000, 001, 1, 3~~

0x01	00000011	0000	001	1	3	
0x64	01100100	1010	010	0	100	180
0x2b	00101011	0010	101	1	43	
0x02	00000010	0000	001	0	2.	
0xbe	10111110.	1011	111	0	190	
0x58	01011000	0101	100	0	88	
0xbf	10111111	1011	111	1	191	
0x0e	00001110.	0000	111	0	14.	
0x1f	00011111	0001	111	1	31	
0xb5	10110101.	1011	010	1	181	
0xbf	10111111	1011	111	1	191	
0xba	10111010	1011	101	0	186	
0x2e	00101110.	0010	111	0	46	
0xce	11001110.	1100	111	0	206	

~~0x~~ set offset

0x03	00000011	0000	001	1	3	miss	1	0	
0x~~64~~	01100100	1011	010	0	180	miss	2	0	
0x2b	00101011	0010	101	1	43	miss	5	0.	
0x02	00000010	0000	001	0	2	hit	1	0	
0xbe	10111110	1011	111	0	190	miss	7	0	
0x58	01011000	0101	100	0	88	miss	4	0	
0xbf	10111111	1011	111	1	191	hit	7	0.	
0x0e	00001110.	0000	111	0	14.	miss	7	1.	
0x1f	00011111	0001	111	1	31	miss	7	2.	~~set~~ 7 is full
0xb5	10110101	1011	010	1	181	hit	2	0	
0xbf	10111111	1011	101	1	191	hit	7	0.	
0xba	10111010	1011	101	0	186	miss	5	1.	
0x2e	00101110	0010	111	0	46	miss	7	1.	least used=7.1
0xce	11001110	1100	111	0	206	miss	7	2	least used=7.2

(4). 1. { Virtual Address Size 32 bits.
Page size 8KiB.
Page Table Entry Size 4 bytes

8KiB = ?. $\log_2(8 \cdot 2^{10}) = 13$ So the page size = 2^{13}.

number of page = $\frac{\text{Virtual Address Size}}{\text{page size}} = \frac{2^{32}}{2^{13}} = 2^{19}$

Page Table Entry Size = 4 bytes

$2^{19} \cdot 4 = 2097152 = 2048$ KiB = 2MiB.

need running five processes $5 \cdot 2\text{MiB} = 10\text{MiB}$.

2. with up to 256 entries at the 1st level.

$256 = 2^8$ $2^8 \cdot 4 \times 2 = 2048 = 2^{11}$

$\frac{2^8}{2} = 2^7$ $128 \times 2048 = 2^7 \cdot 2^{11} = 2^{18}$

$\begin{cases} 2^{18} \cdot 4 = 2^{18} \cdot 2^2 = 2^{20} = \frac{2^{20}}{2^{10}} = 2^{10}\text{KiB} = \frac{2^{10}}{2^{10}} = 1\text{MiB} \\ 128 \cdot 6 = 768\text{B} = 0.000732\text{MiB} \end{cases}$

Min

$1 + 0.000732 = 1.000732$ MiB

$1.000732 \cdot 5 = 5.003660$ MiB

Max. $256 \times 2048 = 2^8 \cdot 2^{11} = 2^{19}$.

$\begin{cases} 2^{19} \cdot 4 = 2^{19} \cdot 2^2 = 2^{21} = \frac{2^{21}}{2^{10}} = 2^{11}\text{KiB} = \frac{2^{11}}{2^{10}} = 2\text{MiB} \\ 256 \cdot 6 = 1536 = 0.001465\text{MiB} \end{cases}$

$2 + 0.001465 = 2.001465$ MiB

$2.001465 \cdot 5 = 10.007325$ MiB

5. the Minimum is 5.003660 MiB.
Maximum is 10.007325 MiB.