



# User Alert Report

Sites: <http://localhost:8883> <http://localhost:8881> <http://localhost:8882>  
<https://spocs.getpocket.com> <http://localhost:8884>

Generated on Sat, 30 Mar 2024 11:18:14

ZAP Version: 2.14.0

ZAP is supported by the [Crash Override Open Source Fellowship](#)

## Summary of Alerts

Risk Level	Number of Alerts
High	1
Medium	1
Low	2
Informational	1
False Positives:	0

## Alerts

Name	Risk Level	Number of Instances
<a href="#">SQL Injection</a>	High	5
<a href="#">Hidden File Found</a>	Medium	4
<a href="#">Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)</a>	Low	10
<a href="#">X-Content-Type-Options Header Missing</a>	Low	10
<a href="#">User Agent Fuzzer</a>	Informational	12

## Alert Detail

High	SQL Injection
Description	SQL injection may be possible.
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	*/" AND "1"="1" --
Evidence	
Other Info	The page results were successfully manipulated using the boolean conditions [*/" AND "1"="1" -- ] and [*/" AND "1"="2" -- ] The parameter value being modified was NOT stripped from the HTML output for the purposes of the comparison Data was returned for the original parameter. The vulnerability was detected by successfully restricting the data originally returned, by manipulating the parameter
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST

Attack	localhost:8881" AND "1"="1" --
Evidence	
Other Info	The page results were successfully manipulated using the boolean conditions [localhost:8881" AND "1"="1" -- ] and [localhost:8881" AND "1"="2" -- ] The parameter value being modified was NOT stripped from the HTML output for the purposes of the comparison Data was returned for the original parameter. The vulnerability was detected by successfully restricting the data originally returned, by manipulating the parameter
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	1b4da2dc-c2dc-445f-b578-d1be4b9f0232" OR "1"="1" --
Evidence	
Other Info	The page results were successfully manipulated using the boolean conditions [1b4da2dc-c2dc-445f-b578-d1be4b9f0232" AND "1"="1" -- ] and [1b4da2dc-c2dc-445f-b578-d1be4b9f0232" OR "1"="1" -- ] The parameter value being modified was NOT stripped from the HTML output for the purposes of the comparison Data was NOT returned for the original parameter. The vulnerability was detected by successfully retrieving more data than originally returned, by manipulating the parameter
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	http://localhost:8881/login" OR "1"="1" --
Evidence	
Other Info	The page results were successfully manipulated using the boolean conditions [http://localhost:8881/login" AND "1"="1" -- ] and [http://localhost:8881/login" OR "1"="1" -- ] The parameter value being modified was NOT stripped from the HTML output for the purposes of the comparison Data was NOT returned for the original parameter. The vulnerability was detected by successfully retrieving more data than originally returned, by manipulating the parameter
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	PostmanRuntime/7.37.0 AND 1=1 --
Evidence	
Other Info	The page results were successfully manipulated using the boolean conditions [PostmanRuntime/7.37.0 AND 1=1 -- ] and [PostmanRuntime/7.37.0 AND 1=2 -- ] The parameter value being modified was stripped from the HTML output for the purposes of the comparison Data was returned for the original parameter. The vulnerability was detected by successfully restricting the data originally returned, by manipulating the parameter
Instances	5
Solution	<p>Do not trust client side input, even if there is client side validation in place.</p> <p>In general, type check all data on the server side.</p> <p>If the application uses JDBC, use PreparedStatement or CallableStatement, with parameters passed by '?'</p> <p>If the application uses ASP, use ADO Command Objects with strong type checking and parameterized queries.</p> <p>If database Stored Procedures can be used, use them.</p> <p>Do *not* concatenate strings into queries in the stored procedure, or use 'exec', 'exec immediate', or equivalent functionality!</p> <p>Do not create dynamic SQL queries using simple string concatenation.</p> <p>Escape all data received from the client.</p>

	<p>Apply an 'allow list' of allowed characters, or a 'deny list' of disallowed characters in user input.</p> <p>Apply the principle of least privilege by using the least privileged database user possible.</p> <p>In particular, avoid using the 'sa' or 'db-owner' database users. This does not eliminate SQL injection, but minimizes its impact.</p> <p>Grant the minimum database access that is necessary for the application.</p>
Reference	<a href="https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html">https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html</a>
CWE Id	<a href="#">89</a>
WASC Id	19
Plugin Id	<a href="#">40018</a>

Medium	Hidden File Found
Description	A sensitive file was identified as accessible or available. This may leak administrative, configuration, or credential information which can be leveraged by a malicious individual to further attack the system or conduct social engineering efforts.
URL	<a href="http://localhost:8881/.darcs">http://localhost:8881/.darcs</a>
Method	GET
Attack	
Evidence	HTTP/1.1 200 OK
Other Info	
URL	<a href="http://localhost:8881/.bzd">http://localhost:8881/.bzd</a>
Method	GET
Attack	
Evidence	HTTP/1.1 200 OK
Other Info	
URL	<a href="http://localhost:8881/.hg">http://localhost:8881/.hg</a>
Method	GET
Attack	
Evidence	HTTP/1.1 200 OK
Other Info	
URL	<a href="http://localhost:8881/BitKeeper">http://localhost:8881/BitKeeper</a>
Method	GET
Attack	
Evidence	HTTP/1.1 200 OK
Other Info	
Instances	4
Solution	Consider whether or not the component is actually required in production, if it isn't then disable it. If it is then ensure access to it requires appropriate authentication and authorization, or limit exposure to internal systems or specific source IPs, etc.
Reference	<a href="https://blog.hboeck.de/archives/892-Introducing-Snallygaster-a-Tool-to-Scan-for-Secrets-on-Web-Servers.html">https://blog.hboeck.de/archives/892-Introducing-Snallygaster-a-Tool-to-Scan-for-Secrets-on-Web-Servers.html</a>

CWE Id	<a href="#">538</a>
WASC Id	13
Plugin Id	<a href="#">40035</a>

Low	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)
Description	The web/application server is leaking information via one or more "X-Powered-By" HTTP response headers. Access to such information may facilitate attackers identifying other frameworks/components your web application is reliant upon and the vulnerabilities such components may be subject to.
URL	<a href="http://localhost:8881">http://localhost:8881</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/">http://localhost:8881/</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/.darcs">http://localhost:8881/.darcs</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/.bzr">http://localhost:8881/.bzr</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/.hg">http://localhost:8881/.hg</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/BitKeeper">http://localhost:8881/BitKeeper</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	

URL	<a href="http://localhost:8881/favicon.ico">http://localhost:8881/favicon.ico</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/robots.txt">http://localhost:8881/robots.txt</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
URL	<a href="http://localhost:8881/sitemap.xml">http://localhost:8881/sitemap.xml</a>
Method	GET
Attack	
Evidence	X-Powered-By: Express
Other Info	
Instances	10
Solution	Ensure that your web server, application server, load balancer, etc. is configured to suppress "X-Powered-By" headers.
Reference	<a href="https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework">https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework</a> <a href="https://www.troyhunt.com/2012/02/shhh-dont-let-your-response-headers.html">https://www.troyhunt.com/2012/02/shhh-dont-let-your-response-headers.html</a>
CWE Id	<a href="#">200</a>
WASC Id	13
Plugin Id	<a href="#">10037</a>

<b>Low</b>	<b>X-Content-Type-Options Header Missing</b>
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	<a href="http://localhost:8881">http://localhost:8881</a>
Method	GET
Attack	
Evidence	
Other	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages

Info	away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/">http://localhost:8881/</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/.darcs">http://localhost:8881/.darcs</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/.bzzr">http://localhost:8881/.bzzr</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/.hg">http://localhost:8881/.hg</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/BitKeeper">http://localhost:8881/BitKeeper</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/favicon.ico">http://localhost:8881/favicon.ico</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client

	or server error responses.
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/robots.txt">http://localhost:8881/robots.txt</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	<a href="http://localhost:8881/sitemap.xml">http://localhost:8881/sitemap.xml</a>
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Instances	10
Solution	<p>Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages.</p> <p>If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application /web server to not perform MIME-sniffing.</p>
Reference	<a href="https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)">https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)</a> <a href="https://owasp.org/www-community/Security-Headers">https://owasp.org/www-community/Security-Headers</a>
CWE Id	<a href="#">693</a>
WASC Id	15
Plugin Id	<a href="#">10021</a>

Informational	User Agent Fuzzer
Description	Check for differences in response based on fuzzed User Agent (eg. mobile sites, access as a Search Engine Crawler). Compares the response statuscode and the hashcode of the response body with the original response.
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1)
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>

Method	POST
Attack	Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.0)
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (Windows NT 10.0; Trident/7.0; rv:11.0) like Gecko
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/75.0.3739.0 Safari/537.36 Edg/75.0.109.0
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/91.0.4472.124 Safari/537.36
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/91.0
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (compatible; Googlebot/2.1; +http://www.google.com/bot.html)
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST



Attack	Mozilla/5.0 (compatible; Yahoo! Slurp; http://help.yahoo.com/help/us/ysearch/slurp)
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (iPhone; CPU iPhone OS 8_0_2 like Mac OS X) AppleWebKit/600.1.4 (KHTML, like Gecko) Version/8.0 Mobile/12A366 Safari/600.1.4
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	Mozilla/5.0 (iPhone; U; CPU iPhone OS 3_0 like Mac OS X; en-us) AppleWebKit/528.18 (KHTML, like Gecko) Version/4.0 Mobile/7A341 Safari/528.16
Evidence	
Other Info	
URL	<a href="http://localhost:8881/login">http://localhost:8881/login</a>
Method	POST
Attack	msnbot/1.1 (+http://search.msn.com/msnbot.htm)
Evidence	
Other Info	
Instances	12
Solution	
Reference	<a href="https://owasp.org/wstg">https://owasp.org/wstg</a>
CWE Id	
WASC Id	
Plugin Id	<a href="#">10104</a>