

SEM 广告投放策略

摘要

本文以某互联网公司 2025 年的 SEM 投放数据（12 个推广单元的 2627 条单元-日记录、365 天新注册数、2227 条关键词年度统计）为对象，建立“描述-分类-优化-预测”四层模型，全部计算在固定镜像的云端流水线上完成，论文中每个数字均可追溯到同一次运行。

问题一以漏斗指标、Lorenz 曲线和带周几、月份、法定节假日与调休哑变量的对数线性回归（HC3 稳健标准误）刻画投放策略。全年消费 142.59 万元、点击 834,815 次，CTR 3.70%，CPC 1.7081 元；消费高度集中（前 10 个词占 58.41%，Gini 系数 0.9676），40.0% 的关键词全年零消费，290 个关键词 ID 在多个单元重复投放。法定节假日日注册数变化 -73.72% （95% CI $[-79.99, -65.47]$ ， $p = 8.0 \times 10^{-22}$ ；Mann-Whitney 检验 $p = 4.56 \times 10^{-14}$ ），控制当日消费后的需求侧效应 -24.64% ，在对数尺度上占总跌幅 21%，其余来自主动减投（消费 -76.68% ）。非负最小二乘归因（留出期 $R^2 = 0.7375$ ）给出各单元注册率（6 个触非负边界，已报告自助区间）；点击-消费弹性的回归估计 $\hat{\gamma}_u \in [0.4937, 1.3253]$ （10 个显著小于 1、1 个品牌单元显著大于 1），合并估计 0.8355（SE 0.0113）显著小于 1，模型采用值 $[0.6502, 0.9301]$ 。

问题二以对数消费额为成本、熵权复合指数（点击、浏览、注意力时长、归因注册）为效益，用两类 Fisher-Jenks 自然断点划分（成本阈值 41.59 元、效益阈值 0.2758；两轴秩相关 0.9021，故实为沿同一主轴的分档加两个小偏离类）：黄金词 40、重点词 271、潜力词 977、问题词 49、无效词 890；与中位数法、高斯混合法的标签一致率为 78.36% 与 93.53%，独立校验器逐词复核通过。

问题三以幂函数响应 $q_i(x) = c_i(x/s_i)^{\gamma_u}$ 与每次点击的期望注册 ρ_i 建立每个单元-日的可分离凹规划（含最小投放额的关键词选择机制），两阶段拉格朗日-注水法求解（选择问题非凸，故为启发式），独立校验器复核可行性与 KKT 条件，凸松弛给出总体最优性界 0.080%。同预算下预期注册量较“按历史比例”的做法提升 12.35%（2 月 1-8 日）与 28.00%（8 月 1-8 日），弹性自助 95% 区间为 $[11.67, 13.39]\%$ 与 $[27.53, 28.57]\%$ （仅含 $\hat{\gamma}$ 的抽样误差；若 γ 整体 $\pm 10\%$ ，8 月提升在 21.8%-36.4% 之间），14 种灵敏度情形下提升均为正（9.0%-36.4%）。

问题四以单元级日历回归预测效率乘子、CPC、CTR 与展位（滚动回测：残差区间 80% 覆盖率 78.3%-87.3%，实际部署的加宽区间过覆盖至 86.8%-92.1%），预算取 2025 年同期投入 23,488.02 元，两层分配后用 500 个蒙特卡罗情景给出 2026 年 9 月 11-17 日六个量的期望范围：点击 17,487.9（10%-90% 分位 13,547.4-21,970.2）、注册 1,194.4（922.9-1,495.3）人、CPC 1.3431（1.0691-1.7337）元；两层分解的联合最优性间隙由可分离凹松弛界定为 0.822%。若改按全年日均口径安排（27,346.98 元，高 16.4%，并恢复 2 个停投单元），确定性预期注册由 1187.4 升至 2327.0 人。

关键词：搜索引擎营销；假日效应；熵权法与自然断点；可分离凹规划；滚动回测；蒙特卡罗模拟

1 问题重述

1.1 问题背景

搜索引擎营销 (SEM) 按关键词竞价购买搜索结果页的广告位：广告主为每个关键词出价并设定预算，搜索引擎按出价与质量决定展现位置，广告主按点击付费。竞价即时变化、展现与点击具有随机性，而关键词竞价成本持续攀升，单纯增加预算抢占流量的做法已不可持续。某互联网公司针对某产品投放 SEM 广告，设计了 5 个方案、12 个推广单元（每个单元是一组相关关键词的集合）以及数千个关键词，2025 年投入约 142 万元。公司希望通过优化关键词及其投放策略提高投放效益。

1.2 给定数据

附件 1 提供三张表：Sheet1 为 2025 年每个（日期、方案 ID、推广单元 ID）的日粒度记录，含展现量、点击量、消费额、上方位（前三名）展现量、上方首位展现量、上方位点击量与上方位消费额，共 2627 行；Sheet2 为每日新注册用户数（含 SEM 投放等渠道），共 365 行；Sheet3 为每个关键词的年度统计（序号、匿名关键词 ID、方案 ID、推广单元 ID、消费额、点击量、浏览量、跳出率、平均访问时长），共 2227 行。附件 2 为三个结果模板文件。

1.3 待解决的问题

1. **问题一**：从广告设计质量与创意、关键词管理与运用、出价策略与预算、投放策略与时间等方面分析该公司投放策略的合理性，并分析投放效益随时间的变化规律与假日效应。
2. **问题二**：按投入成本与效益把关键词分为黄金词（低成本、高效益）、重点词（高成本、高效益）、潜力词（低成本、低效益）、问题词（高成本、低效益）、无效词（无成本、无效益）五类，主要结果写入论文，详细结果按模板写入 `result2.xlsx`（方案 ID、推广单元、序号与五个类别标记列）。
3. **问题三**：在问题一、二的基础上，根据关键词的类型与关联关系，在各推广单元低成本、高效益、用完但不超过预算的条件下选择关键词，给出每个推广单元及其关键词的投放模型；给出 2025 年 2 月 1–8 日与 8 月 1–8 日每天的最优投放策略并说明其优越性，详细结果写入 `result3.xlsx`（日期、方案 ID、推广单元、关键词、投入金额、预期展位、预期点击量、预期浏览量、预期注册量）。
4. **问题四**：2026 年沿用 2025 年的方案、单元与关键词，预算不超过 2025 年的投入；考虑竞价逐日变化以及展现量、展现位、点击量、浏览量、注册量的不确定性，给出 2026 年 9 月 11–17 日每天的最优投放策略，并估计上述各量的期望范围，详细结果写入 `result4.xlsx`（结构同 `result3.xlsx`）。

2 问题分析

四个问题构成一条递进的链：问题一从数据中提取描述性事实与两组结构参数（各单元每次点击的注册率 r_u 与点击对消费的弹性 γ_u ）；问题二用这些参数定义关键词的效益并分类；问题三把响应函数、点击价值与类别约束组合为每个单元-日的预算分配模型；问题四在问题三的模型上叠加对未来日效率、竞价与展位的预测及其不确定性。图 1 给出技术路线，本节说明各问题的核心矛盾与处理思路。

2.1 问题一的分析

“合理性”没有唯一的量化定义，本文把它落实为四组可检验的事实：(i) 设计质量与创意由漏斗转化指标反映——点击率 CTR、平均点击成本 CPC、上方位与首位展现占比，以及上方位与非上方位的 CTR 差异；(ii) 关键词管理由长尾结构反映——零消费占比、消费的集中度（Lorenz 曲线与 Gini 系数）、同一关键词在多个单元重复投放的数量；(iii) 出价与预算由消费在单元间的分布和边际收益反映——单元级弹性 $\gamma_u < 1$ 意味着边际收益递减，预算越集中于单一单元，边际注册成本越高；(iv) 投放时间由日历规律反映。假日效应的难点在于它混合了两种机制：需求侧（用户在假日搜索与注册减少）与供给侧（公司在假日主动减投）。本文用带日历哑变量的对数线性回归估计总效应，再在回归中控制当日消费额分离需求侧效应，并用 Mann-Whitney 非参数检验作稳健性对照。注册数只有日总量，本文用非负最小二乘把它归因到各单元的点击，得到后续问题所需的注册率 r_u 。

2.2 问题二的分析

题目给出的五类是“成本 $\times$ 效益”二维象限加一个退化类（无成本无效益）。需要决定三件事：效益如何度量、“高/低”的界限如何定、界限是否稳健。数据中关键词消费跨越六个数量级，因此成本取对数尺度；效益应综合点击、浏览深度、停留时长与注册贡献，本文用极差标准化后的熵权加权和（权重由数据的信息量决定，并与等权对照）；阈值采用两类 Fisher-Jenks 自然断点（一维精确解），并以中位数与高斯混合后验交点作对照，报告标签一致率。分类结果由与分类程序分离的校验器按原始列逐词重推。

2.3 问题三的分析

附件只有关键词的年度汇总而无逐日曲线，“投入-产出”关系必须借助单元级日序列估计：单元的日点击对日消费的弹性 γ_u 由 2025 年数据回归得到，关键词的响应曲线以其年度日均工作点 (s_i, c_i) 为锚、以 γ_u 为形状参数外推。目标函数取最终业务指标——预期注册量，等于点击量乘以每次点击的期望注册 ρ_i （单元注册率 $\times$ 跳出率质量因子）。预算在题目中未给出，本文取该单元当日 2025 年实际消费（使“最优策略”与“实际做法”在同样的钱上可比），并以窗口预算跨日调配作备选。每个单元-日的问题是带上界与最小投放额的可分离凹规划：不含最小投放额时 KKT 条件充要，解为注水

形式；含最小投放额时是非凸的选择问题，本文用拉格朗日价格确定入选集合再精确求解，并用凸松弛给出最优性界。优越性通过与“按历史比例分配”和“均匀分配”两条基线在同一响应模型、同一预算下的反事实比较来说明，弹性的抽样不确定性用参数自助法传播到提升幅度。

2.4 问题四的分析

预测目标点在样本末 8.5 个月之后，近期水平的持续性不可用，日历结构（周几、月份、节假日）是数据中唯一可外推的信息；因此本文对每个单元的效率乘子、CPC、CTR、上方位与首位占比分别建立日历回归模型，并用 2025 年第四季度的滚动起点回测（与季节朴素、28 日均值两条基线比较 MAE、pinball 损失与 80% 区间覆盖率）检验点预测与区间的校准。预算取 2025 年同期（9 月 11–17 日）各单元的实际消费，同时给出按全年日均折算的备选口径。不确定性以单元–日共同冲击、关键词特异冲击、CTR 与展位冲击和注册的泊松噪声进入响应函数；由于这些冲击以与投放额无关的乘性方式进入，期望注册最大化问题与用期望乘子的确定性问题同解，最优策略可先按日、再按关键词两层求解，期望范围由蒙特卡罗情景给出。




图 1 技术路线：问题一产出的注册率 r_u 与弹性 γ_u 贯穿后续三个问题；问题三的分配模型被问题四复用；全部结果经独立检验后写入结果文件。

3 模型假设与符号说明

3.1 模型假设

下列假设中，A1–A2 来自题目与附件的给定信息，A3–A8 为本文附加；每条给出依据与被违反时的后果。

假设 1 (数据口径). 附件 1 的记录完整地代表了 2025 年的投放：Sheet3 各单元的消费与点击合计与 Sheet1 完全对账（见第 4.1 节）；题述“6000 多个关键词”指账户内的全

部关键词，附件仅提供其中有统计记录的 2227 条，分析以附件为准。

假设 2 (节假日日历). 法定节假日与调休上班日按国务院办公厅 2025 年安排 [1] (元旦 1/1; 春节 1/28–2/4; 清明 4/4–4/6; 劳动节 5/1–5/5; 端午 5/31–6/2; 国庆中秋 10/1–10/8; 调休 1/26、2/8、4/27、9/28、10/11)。2026 年 9 月 11–17 日为周五至周四，不含法定节假日。

假设 3 (注册的线性可加归因). 日注册数等于基线、各单元点击的线性贡献与日历效应之和，单元 u 每次点击带来的期望注册 $r_u \geq 0$ 在年内不变。依据：注册只有日总量，线性可加是能 365 天数据识别 12 个单元贡献的最简结构；若违反（如渠道间存在协同）， r_u 只是平均意义上的边际率，分类与分配的相对结论仍成立，绝对注册量有偏。

假设 4 (幂函数响应与单元共享弹性). 关键词 i 在单日投放 x 下的期望点击为 $q_i(x) = c_i(x/s_i)^{\gamma_u}$ ，其中 (s_i, c_i) 为其 2025 年活跃日的日均消费与日均点击，形状参数 $\gamma_u \in (0, 1)$ 由所属单元的日序列估计并在单元内共享。依据：合并弹性 0.8355 (SE 0.0113) 显著小于 1，12 个单元的自身回归估计中 10 个显著小于 1；幂函数在 11/12 个单元上优于指数饱和函数 (MDR-0005)；曲线过历史工作点保证“按历史比例分配”恰好复现历史点击。反例与处理：品牌型单元 8878077181 的 $\hat{\gamma} = 1.3253$ 显著大于 1 ($t = 4.94$)，与本假设相悖，按第 4.4 节的规则退回合并估计，故模型采用值 $\gamma_u \in [0.6502, 0.9301]$ 全部落在 $(0, 1)$ 内。若假设被违反（关键词弹性异质，或某单元真为凸响应），最优解对该单元的投放额有偏，但凹性保证的分散化结论不变。

假设 5 (点击价值与浏览量). 关键词每次点击的期望注册 $\rho_i = r_u \kappa_i$ ， $\kappa_i = (1 - b_i)/(1 - \bar{b}_u)$ 为以单元点击加权平均跳出率 $\bar{b}_u$ 归一的跳出率质量因子（截断到 $[0.25, 2.5]$ ）；浏览量等于点击量乘以该词历史每次点击的浏览页数 d_i （无访问记录时用单元均值）。依据：跳出即离开，未跳出的访问才可能注册； κ_i 的截断避免极端小样本词主导分配。本假设无法用数据检验（注册只有日总量），且 43.7% 的词落在截断边界上；其影响在第 8.5 节以 $\kappa = 1$ 与截断区间 $[0.5, 2]$ 两种情形量化。

假设 6 (日效应可分离). 单元 u 在日期 t 的实际点击等于响应函数值乘以日效率乘子 $\varepsilon_{u,t}$ ， $\varepsilon_{u,t}$ 只取决于日历（周几、月份、节假日）与随机冲击，与当日的关键词分配无关。依据： $\log \varepsilon_{u,t}$ 是弹性回归的残差结构；可分离性使跨日与日内分配可以分层求解。

假设 7 (预算与投放上限). 问题三中单元 u 在日期 t 的预算 $B_{u,t}$ 等于其 2025 年当日实际消费；问题四中单元 u 的 7 日预算等于其 2025 年 9 月 11–17 日的实际消费之和。单个关键词单日投放不超过其历史日均消费的 $\mu = 4.0$ 倍（问题词减半），且不低于其历史比例份额；低于 $m = 0.50$ 元的投放视为不投放。依据：题目未给预算，与实际消费相同的预算使“最优 vs 实际”可比（覆盖全部单元的备选口径见第 6.5、7.3 节）；上限反映单个关键词的流量天花板——附件无关键词日数据，只能用可观测的单元日消费统计外推：各单元日消费的 95% 分位与均值之比为 1.74–8.07（中位 2.67）， $\mu = 4.0$ 取其中位偏保守的一档；下限保证入选词有实际意义。 $\mu = 2$ 与 $\mu = 8$ 的情形见表 18。

假设 8 (2026 年的结构稳定性). 2026 年沿用 2025 年的方案、单元与关键词, 各单元的弹性、注册率、CTR 与展位模型不变; 未来的日效率、CPC、CTR 与展位仅由日历结构与 2025 年残差、月份间波动刻画。年际间的月份水平漂移取 2025 年月份效应的横截面标准差 σ_u^m ——这是一条不可检验的约定 (一年数据无法识别年际漂移), 它使部署区间比可回测的残差区间宽 1.536 倍。依据: 题目明确沿用同样的方案与关键词; 2026 年的市场趋势无法从一年的数据识别, 本文以区间而非点值报告, 并在第 8.6 节同时回测两种区间宽度。

3.2 符号说明

符号	含义	单位
$u \in \mathcal{U}, t, i \in \mathcal{K}_u$	推广单元、日期、单元 u 内的关键词	—
$I_{u,t}, C_{u,t}, S_{u,t}$	单元-日展现量、点击量、消费额	次、次、元
$I_{u,t}^{\text{top}}, I_{u,t}^1, C_{u,t}^{\text{top}}, S_{u,t}^{\text{top}}$	上方位展现量、首位展现量、上方位点击量与消费额	次、次、次、元
R_t	日新注册数	人
$S_i, C_i, V_i, b_i, \tau_i$	关键词年度消费额、点击量、浏览量、跳出率、平均访问时长	元、次、次、—、s
H_t, A_t, P_t, Q_t	法定节假日、调休上班日、假前一日、假后一日哑变量	—
δ_H, θ	假日效应 (对数尺度)、注册对消费的弹性	—
$r_u, \bar{r}$	单元 u 每次点击的期望注册、合并注册率 (表 4 与正文按人/百次点击报告)	人/次
λ_{ad}	点击的 adstock 衰减系数 (式 (6))	—
$\hat{\gamma}_u, \gamma_u, n_u$	单元 u 的弹性回归估计、模型采用值、2025 年活跃天数 (消费与点击同时为正)	—、—、d
$K_u, \bar{X}_u, \mathcal{K}_u^e$	单元内层值函数的比例常数、跨日预算上限、候选词集合	人/元 γ_u 、元、—
s_i, c_i, d_i	关键词日均消费、日均点击、每次点击的浏览量 (无量纲, 次/次)	元、次、—
κ_i, ρ_i	跳出率质量因子、每次点击的期望注册	—、人/次
$q_i(x), \varepsilon_{u,t}$	关键词响应函数、单元-日效率乘子	次、—
$z_{ij}, w_j, \mathcal{B}_i$	效益分量、熵权、综合效益指数 (式 (10); 与预算 $B_{u,t}$ 区分)	—
$x_i^c = \log_{10} S_i$	成本尺度	—
$B_{u,t}, x_i, \bar{x}_i$	单元-日预算、关键词投放额、投放上限	元
m, μ, ϕ_i	最小投放额、上限倍数、类型因子 (问题词 0.5)	元、—、—
$a_i = \rho_i c_i s_i^{-\gamma_u}$	分配模型的目标系数	人/元 γ_u
λ	预算约束的影子价格	人/元
p^{top}, p^1, π	上方位占比、首位占比、预期展位指数	—、—、—
$X_{u,t}$	问题四中单元 u 分到日期 t 的预算	元

符号	含义	单位
$\sigma_u, \sigma_u^m, \sigma_u^{\text{kw}}$	日历回归的残差标准差、月份效应横截面标准差、关键词特异冲击标准差	—
ξ_i, ζ_i, w_t	关键词特异乘性冲击 ($E[\xi_i] = 1$) 及其标准正态源、日冲击的标准正态源	—
a_u, b_u, a'_u, b'_u	展位 logit 回归的截距与斜率 (式 (15); 与式 (7) 的 a_u 区分)	—

4 问题一：投放策略的合理性与时间规律

本节先说明数据口径与质量，再从设计质量与创意、关键词管理、出价与预算、投放时间四个方面给出可检验的事实，最后估计注册归因模型与单元级弹性，为后续问题提供结构参数。

4.1 数据说明与质量

所有数据经契约校验（列类型、取值范围、漏斗一致性：点击 $\leq$ 展现、上方位展现 $\leq$ 展现、首位展现 $\leq$ 上方位展现、上方位点击 $\leq$ 点击、上方位消费 $\leq$ 消费）全部通过。Sheet1 有 2627 条单元-日记录，覆盖 5 个方案、12 个推广单元和 2025 年全部 365 天，（日期、方案、单元）无重复；各单元的投放起止不同（四个单元自 5 月 21 日起投，一个单元 11 月 28 日停投），春节等假期多数单元停投，293 条记录有展现而消费为零。全年合计消费 1,425,949.79 元（题述“142 余万元”）、点击 834,815 次、展现 22,580,381 次。Sheet2 的新注册数合计 85,313 人。Sheet3 有 2227 条关键词记录（题述“6000 多个关键词”多于附件行数，本文以附件为准，假设 1），关键词 ID 为匿名整数，共 1884 个不同 ID，其中 290 个 ID 被 2-4 个单元共用（涉及 633 条记录）；890 条（40.0%）全年零消费零点击，其跳出率与时长以“/”标记；跳出率为 0-1 的小数，平均访问时长为“HH:MM:SS”或数值 0（84 行）。Sheet3 分单元的消费与点击合计与 Sheet1 完全对账（总消费差异 0.02 元，为四舍五入）。

4.2 指标体系与四个方面的事实

以单元 u 的年度合计定义漏斗指标

$$\text{CTR}_u = \frac{\sum_t C_{u,t}}{\sum_t I_{u,t}}, \quad \text{CPC}_u = \frac{\sum_t S_{u,t}}{\sum_t C_{u,t}}, \quad p_u^{\text{top}} = \frac{\sum_t I_{u,t}^{\text{top}}}{\sum_t I_{u,t}}, \quad p_u^1 = \frac{\sum_t I_{u,t}^1}{\sum_t I_{u,t}}, \quad (1)$$

关键词消费的集中度用按消费降序的 Lorenz 曲线与 Gini 系数度量：对有消费的 n 个词按 $S_{(1)} \leq \dots \leq S_{(n)}$ 排序，

$$G = \frac{n+1 - 2 \sum_{k=1}^n (\sum_{j \leq k} S_{(j)}) / \sum_j S_{(j)}}{n}. \quad (2)$$

表 2 给出各单元的年度 KPI，图 2 给出单元消费占比、CPC-CTR 散点与关键词 Lorenz 曲线。

设计质量与创意 账户整体 CTR 为 3.70%，CPC 1.7081 元。上方位（前三名）展现只占 27.11%（首位 10.39%），却贡献了 67.06% 的点击与 70.35% 的消费：上方位 CTR 为 9.15%，非上方位仅 1.67%，相差 5.5 倍，而上方位 CPC（1.7918 元）只比非上方位（1.5377 元）高约 17%。可检验的事实是展现结构严重偏向低 CTR 区域：非上方位以 72.89% 的展现只换来 32.94% 的点击。需要强调的是，位置拍卖的标准模型把 CTR 分解为位置效应与广告质量的乘积 [2-3]，附件既无关键词日数

表 2 各推广单元 2025 年投放 KPI (按消费额降序; CTR、CPC、上方位与首位占比按式 (1))

方案 ID	推广单元 ID	投放天数	消费额/元	占比/%	展现量	点击量	CTR/%	CPC/元	上方位/%	首位/%
500635396	9657930100	321	808,153	56.7	8,769,221	358,634	4.09	2.25	44.0	11.7
525368335	9811363528	259	181,497	12.7	4,780,540	100,380	2.10	1.81	8.9	7.2
495817671	9630806627	309	171,870	12.1	4,417,936	107,520	2.43	1.60	17.8	8.4
495403620	8878077181	225	124,226	8.7	255,414	168,752	66.07	0.74	88.6	81.9
495403620	9628223555	321	91,605	6.4	3,454,523	72,103	2.09	1.27	18.5	8.7
500635396	9700005700	148	26,940	1.9	163,203	12,173	7.46	2.21	33.1	30.9
500635396	9773660250	161	6,434	0.5	180,446	4,206	2.33	1.53	28.6	8.6
63563817	4190988310	172	4,982	0.3	125,307	3,283	2.62	1.52	14.4	3.3
63563817	1841014603	178	4,768	0.3	113,857	4,023	3.53	1.19	19.1	14.4
63563817	2874903000	178	2,848	0.2	87,675	2,019	2.30	1.41	21.0	7.1
63563817	4190988309	178	2,478	0.2	222,330	1,635	0.74	1.52	9.7	1.8
63563817	2526158329	177	149	0.0	9,929	87	0.88	1.71	3.9	1.1




图 2 左: 各推广单元年度消费额占比; 中: 单元 CPC-CTR 散点 (对数纵轴, 气泡面积 $\propto$ 消费占比, 标签为单元 ID 后四位); 右: 关键词消费额与点击量的 Lorenz 曲线 (按消费额降序累计), 虚线为均匀分布。

据也无真实排名, 本文无法把上方位与非上方位的 CTR 差异归因于创意本身; 只能说明在既定的位置结构下, 把展现从低 CTR 区域移向上方区域的空间很大。单元 8878077181 只有 4 个关键词, CTR 高达 66.1%、上方位占比 88.6%、CPC 仅 0.74 元, 属品牌/导航型流量, 说明品牌词的创意与匹配是充分的; 相反, 单元 4190988309 的 CTR 仅 0.74% (表 2), 其创意或关键词匹配需要重新审视。

关键词管理与运用 关键词呈极端长尾: 40.0% 的词全年零消费零点击; 有消费的 1337 个词中, 前 10 个词占消费 58.41%, 前 100 个占 96.40%, Gini 系数 0.9676 (图 2 右)。290 个关键词 ID 同时出现在多个单元中, 同一账户的不同单元会会在同一查询上相互竞价, 抬高自身 CPC; 关键词库中约四成的词从未获得流量, 说明词库缺乏定期清理与匹配方式调整。

出价策略与预算 消费在单元间同样集中: 单元 9657930100 占全年消费 56.67%, 各单元 CPC 从 0.74 元到 2.25 元不等 (表 2)。第 4.4 节的点击-消费弹性合并估计为 0.8355 (标准误 0.0113), 显著小于 1, 即边际收益递减; 12 个单元的自身回归估计 $\hat{\gamma}_u \in [0.4937, 1.3253]$, 其中 10 个显著小于 1、1 个 (品牌型单元 8878077181) 显著大于 1 (见第 4.4 节)。消费最大的单元 9657930100 的采用弹性最低 (表 4) 而 CPC 最高, 说明预算在该单元上已进入边际成本快速上升的区域。把同一天的预

算在单元之间按边际收益均衡重新分配（用与第 6 节相同的注水机制、单元级弹性异质、上限取历史份额的 μ 倍），在问题三的两个窗口上分别可再提升预期注册 3.97% 与 32.31%（表 18）。需要说明的是，问题三与问题四的主模型按假设 7 把每个单元的预算锁定为其 2025 年当日实际消费，因此不执行这种跨单元再分配；它作为反事实口径单独报告，也是第 9.2 节列出的局限之一。

投放策略与时间 图 3 显示日消费、点击与注册的全年走势：三条序列高度同步（注册与消费的相关系数约 0.8），春节后 2-3 月出现全年高峰，6-7 月为低谷；每周内呈明显的“周一、周日低”模式，法定节假日（阴影）期间三者同时深跌。这些规律与假日效应在下一小节用回归量化。




图 3 2025 年日消费额、日点击量与日新注册数（细线为日值，粗线为 7 日滑动均值；阴影为法定节假日，竖虚线为调休上班日）。

4.3 日历回归与假日效应

对账户日总量 $y_t \in \{R_t, S_t, C_t, I_t\}$ 建立对数线性回归

$$\log y_t = \alpha + \sum_{w \neq \text{周三}} \beta_w D_t^w + \sum_{m \neq 1} \mu_m M_t^m + \delta_H H_t + \delta_A A_t + \delta_P P_t + \delta_Q Q_t + e_t, \quad (3)$$

其中 D_t^w 、 M_t^m 为周几与月份哑变量（基准为周三与 1 月）， H_t, A_t, P_t, Q_t 分别为法定节假日、调休上班日、假前一日、假后一日的指示变量（假设 2）。系数 δ 的效应以 $100(e^\delta - 1)\%$ 报告，标准误采用 MacKinnon-White 的 HC3 异方差稳健形式 [4]。对 CPC、CTR 与上方位占比以水平值代替对数。为把假日的需求侧效应与公司主动减投分离，再估计控制当日消费额的模型

$$\log R_t = \alpha' + \theta \log S_t + \sum_w \beta'_w D_t^w + \sum_m \mu'_m M_t^m + \delta'_H H_t + \delta'_A A_t + \delta'_P P_t + \delta'_Q Q_t + e'_t, \quad (4)$$

其中 θ 为注册对消费的弹性， δ'_H 是同样投入下假日仍然存在的注册变化。作为非参数对照，用 Mann-Whitney U 检验 [5] 比较法定节假日（28 天）与普通工作日（243 天）的日注册数分布。

表 3 日历回归 (3) 的效应估计 (相对周三 / 普通日, %; HC3 稳健 95% 置信区间与 p 值)

因素	注册效应/%	95% CI	p	消费效应/%	95% CI	p	点击效应/%	p
法定节假日	-73.7	[-80.0, -65.5]	0.000	-76.7	[-83.2, -67.6]	0.000	-75.8	0.000
调休上班日	-2.4	[-49.5, 88.6]	0.942	-1.0	[-58.6, 136.4]	0.982	0.6	0.989
假前一日	-54.3	[-84.2, 32.1]	0.148	-49.3	[-77.5, 14.2]	0.101	-41.4	0.253
假后一日	-17.3	[-47.3, 29.9]	0.410	-25.9	[-53.3, 17.7]	0.204	-26.3	0.234
周一	-53.8	[-65.2, -38.8]	0.000	-59.7	[-68.9, -47.9]	0.000	-53.9	0.000
周二	-3.4	[-21.5, 18.9]	0.743	-9.7	[-30.5, 17.4]	0.448	-7.1	0.513
周四	-5.0	[-23.5, 18.0]	0.644	1.6	[-19.6, 28.4]	0.896	1.3	0.902
周五	-4.7	[-21.5, 15.7]	0.627	-1.1	[-21.4, 24.5]	0.925	-1.8	0.848
周六	-12.6	[-27.5, 5.3]	0.156	-3.9	[-22.9, 19.8]	0.725	-6.1	0.489
周日	-47.4	[-58.5, -33.2]	0.000	-52.5	[-63.4, -38.2]	0.000	-46.9	0.000




图 4 周几、法定节假日、调休、假前与假后对日新注册数、消费额与点击量的效应 (相对周三 / 普通日, %), 横线为 HC3 稳健 95% 置信区间。

表 3 与图 4 给出估计结果。法定节假日的注册数效应为 -73.72% (95% CI $[-79.99, -65.47]$, $p = 8.0 \times 10^{-22}$), 消费额 -76.68% 、点击量 -75.81% 、展现量 -70.78% 同样显著; Mann-Whitney 检验给出假日与工作日注册中位数 58 与 271 人 (比值 0.2140), $p = 4.56 \times 10^{-14}$, 两种方法结论一致。价格与质量指标没有假日效应: CPC 的假日系数为 -0.0240 元 ($p = 0.8043$), CTR 为 -0.242 个百分点 ($p = 0.5740$); 上方位占比在假日下降 -4.64 个百分点 ($p = 0.0432$), 与减投后排位后移一致。周几效应显著 (Wald 检验 $p = 3.53 \times 10^{-12}$): 周一注册 -53.81% 、周日 -47.36% , 周六 -12.64% ($p = 0.1561$), 周二至周五与周三无显著差异; 调休上班日与普通日无差异 (-2.42% , $p = 0.9419$); 假前一日、假后一日的点估计为负但因样本少不显著。

控制消费额的模型 (4) 把上述总效应分解: 注册对消费的弹性 $\theta = 0.7235$ (SE 0.0631), R^2 由 0.4802 升至 0.7829; 同样投入下假日注册仍低 -24.64% (95% CI $[-40.01, -5.32]$, $p = 0.0151$), 分解在对数尺度上精确闭合: $\delta_H = \delta'_H + \theta \delta_H^S$, 需求侧解释了对数跌幅的 21%, 其余 79% 来自公司假日主动减投 -76.68% (百分点不可相加, 故不能用 $24.6/73.7$ 计算份额)。周一 (-10.85% , $p = 0.2665$) 与周日 (-9.86% , $p = 0.2684$) 在控制消费后不再显著, 其点估计的需求侧跌幅远小于实际减投幅度。

假日减投是否合理, 可用边际收益均衡原则判断。设注册对消费的响应为 $R = KS^\theta$, 假日需求

侧乘子为 $e^{\delta'_H}$ ，则假日与普通日边际注册相等要求 $e^{\delta'_H} \theta K S_H^{\theta-1} = \theta K S_N^{\theta-1}$ ，即最优的假日/普通日消费比

$$\frac{S_H^*}{S_N^*} = \exp\left(\frac{\delta'_H}{1-\theta}\right) = 36.0\%, \quad (5)$$

即最优减投幅度的点估计为 64.0%。

式 (5) 的两个输入 δ'_H 与 θ 来自同一个回归，必须联合传播其抽样不确定性：对二者的 HC3 协方差作 4×10^5 次联合抽样，最优减投幅度的 95% 区间为 [26.9, 76.6]%。令最优减投恰等于实际减投 76.7% 的临界弹性为 $\theta^* = 0.8057$ ，它落在 θ 的 95% 区间 [0.5998, 0.8471] 之内；若改用问题三、四所用的合并点击-消费弹性 0.8355，最优减投为 82.1%，结论由“减投过度”翻转为“减投不足”。因此数据不能判定公司的假日减投是过度还是不足，只能说实际值落在可解释的范围内。同一把尺子用于周几：周日的需求侧点估计给出最优减投 34.0%（95% 区间 [-48.7, 68.5]%）而实际减投 59.7%，周日为 31.3% 对 52.5%——两者与假日一样是“实际减投深于点估计的最优值”，差距分别为 25.7 与 21.2 个百分点，而假日为 12.7 个百分点。周一、周日的临界弹性 $\theta^* = 0.8737$ 与 0.8604 均落在 θ 的 95% 区间之外，因此在这两天“减投过度”的方向比假日更稳健，是投放时间安排中相对最值得复核之处；但“不显著”不等于“效应为零”，本文不把周一/周日的需求侧效应当作 0 处理。

最后必须声明识别限制：式 (4) 中的 $\log S_t$ 由公司内生选择（正是本文指出的假日主动减投）， θ 是条件相关弹性而非投放的因果回报弹性；式 (5) 只在 θ 可作边际回报解释时成立，其结论应读作参考值而非规范结论（见第 9.2 节）。

4.4 注册归因与单元级结构参数

附件只有日注册总量，为得到各单元每次点击的价值，建立带日历项的归因回归（假设 3）

$$R_t = c_0 + \sum_{u \in \mathcal{U}} r_u \tilde{C}_{u,t} + \beta^\top \mathbf{D}_t + e_t, \quad \tilde{C}_{u,t} = C_{u,t} + \lambda_{ad} \tilde{C}_{u,t-1}, \quad r_u \geq 0, \quad (6)$$

其中 $\mathbf{D}_t$ 为式 (3) 的日历哑变量， $\tilde{C}$ 为 adstock 点击（衰减 λ_{ad} 在 {0, 0.2, 0.4, 0.6} 中由滚动起点交叉验证的 MAE 选取），系数 r_u 用非负最小二乘 [6] 估计。点击数不足 10000 或估计值落在合并估计 $\bar{r}$ 的 [0.25, 4] 倍之外的单元使用合并估计（把所有单元点击加总后同样回归得到）。式 (6) 选出 $\lambda_{ad} = 0.0$ （无显著滞后效应），全样本 $R^2 = 0.7951$ ，以前 70% 天数训练、后 30% 留出的 $R^2 = 0.7375$ 、MAPE 30.19%（图 5）。截距 $c_0 = 151.39$ 人/天是参照格（1 月、周三、非假日）的截距，不是全年的非 SEM 基线。全年 85,313 人的注册按式 (6) 恰好分解为三块：截距 $365c_0 = 55,257$ 人（64.8%）、日历项合计 -28,873 人（-33.8%）与 SEM 点击项 58,929 人（69.1%），三者相加等于 85,313；隐含的非 SEM 日均基线为 72.3 人/天。合并注册率为 7.9475 人/百次点击；5 个单元保留自身估计，按下游实际采用的 r_u 归因到 SEM 点击的注册合计 60,269 人（占全年注册 70.65%，与上面用原始 NNLS 系数的 58,929 人口径不同），平均归因注册成本 23.66 元（表 4）。

r_u 是问题二效益分量与问题三、四目标系数的核心结构参数，其不确定性必须与点估计一起报告。表 4 给出每个单元的原始 NNLS 估计、是否触非负边界以及 300 次移动分块（块长 7 天）残差自助的 95% 区间：12 个单元中 6 个的 $\hat{r}_u$ 被非负约束顶在 0，区间因而单侧退化。识别之所以困难，是因为各单元的点击序列在扣除日历设计后仍高度共线：残差化后点击设计阵的条件数为 948。设定稳健性同样显著——去掉月份哑变量后单元注册率最大摆动为 3.6 倍。这一不确定性在第 9.2 节被列为局限，并解释了本文为何以相对提升而非绝对注册量作为问题三、四的优越性证据。

单元级点击-消费弹性由活跃日的对数回归估计（假设 4）：

$$\log C_{u,t} = a_u + \gamma_u \log S_{u,t} + \sum_w \beta_{u,w} D_t^w + e_{u,t}, \quad (7)$$

合并模型（单元固定效应）给出 $\gamma = 0.8355$ (SE 0.0113)。这里区分两个概念：回归估计 $\hat{\gamma}_u$ 与模型采用值 γ_u 。12 个单元的回归估计为 $\hat{\gamma}_u \in [0.4937, 1.3253]$ ；采用规则是“活跃天数 $n_u \geq 60$ 且 $\hat{\gamma}_u \in [0.3, 0.95]$ 时用自身估计，否则退回合并估计”，其中活跃天数指消费与点击同时为正的天数（表 4 的 n_u 列），与表 2 的“投放天数”（有记录的天数）不同。据此 10 个单元采用自身估计 (0.6502–0.9301)，另两个退回合并估计 0.8355：品牌型单元 8878077181 的 $\hat{\gamma} = 1.3253$ (SE 0.0658, $n_u = 223$) 显著大于 1 ($H_0: \gamma = 1$ 的 $t = 4.94$)，这与假设 4 的凹性相悖，来源是品牌流量的爆发式波动（少数日的点击量跳升数倍），本文按规则将其排除并在第 9.2 节说明；单元 2526158329 虽有 56 条记录，但活跃天数只有 56 天 ($\hat{\gamma} = 0.4937$)，不足以识别。图 6 表明双对数尺度上的线性关系在各单元都成立， R^2 在 0.65–0.97 之间（表 4）。

表 4 各单元的注册率（式 (6)）、归因注册与注册成本，以及弹性估计（式 (7)）与采用值

推广单元 ID	采用注册率/(人/百次点击)	来源	原始 NNLS	自助 95% 区间	归因注册/人	注册成本/元	活跃天数 n_u	$\hat{\gamma}_u$	SE	R^2	采用 γ_u	γ 来源
1841014603	7.947	合并估计	0.00 [†]	[0.00, 94.48]	320	14.9	175	0.930	0.048	0.89	0.930	单元
2526158329	7.947	合并估计	0.00 [†]	[0.00, 1060.84]	7	21.6	56	0.494	0.096	0.65	0.836	合并
2874903000	7.947	合并估计	0.00 [†]	[0.00, 154.16]	160	17.7	173	0.811	0.036	0.92	0.811	单元
4190988309	7.947	合并估计	0.00 [†]	[0.00, 167.84]	130	19.1	177	0.650	0.033	0.87	0.650	单元
4190988310	7.947	合并估计	25.57	[0.00, 118.42]	261	19.1	170	0.882	0.026	0.94	0.882	单元
8878077181	4.346	单元估计	4.35	[1.10, 6.64]	7,334	16.9	223	1.325	0.066	0.88	0.836	合并
9628223555	2.785	单元估计	2.79	[0.00, 5.94]	2,008	45.6	321	0.836	0.018	0.87	0.836	单元
9630806627	7.369	单元估计	7.37	[5.17, 9.87]	7,923	21.7	306	0.853	0.013	0.96	0.853	单元
9657930100	7.759	单元估计	7.76	[5.92, 9.17]	27,828	29.0	321	0.699	0.025	0.82	0.699	单元
9700005700	7.947	合并估计	0.00 [†]	[0.00, 4.22]	967	27.8	64	0.896	0.033	0.93	0.896	单元
9773660250	7.947	合并估计	0.00 [†]	[0.00, 21.60]	334	19.2	93	0.750	0.085	0.86	0.750	单元
9811363528	12.948	单元估计	12.95	[11.19, 14.84]	12,997	14.0	255	0.825	0.010	0.97	0.825	单元




图 5 日新注册数与归因回归 (6) 的拟合值（竖虚线右侧为留过期；阴影为法定节假日）。

4.5 合理性小结

综合以上事实：(i) 72.89% 的展现落在上方位之外、只换来 32.94% 的点击，展现结构严重偏向低 CTR 区域（位置效应与创意质量在本数据上不可分离）；(ii) 关键词库长尾严重、四成的词零消费、290 个词跨单元重复投放，缺乏清理与去重；(iii) 预算过度集中于采用弹性最低、CPC 最高的单元，跨单元再分配的反事实收益为 3.97%–32.31%；(iv) 假日、周一与周日的实际减投都深于边际均衡的点估计（分别超出约 12.7、25.7、21.2 个百分点），其中周一、周日的方向判断更稳健，但三者都未被数据显著判定。第 (ii) 点由问题二（分类清理）处理；第 (iv) 点的时间安排由问题三、四的跨日分配处理；第 (iii) 点的跨单元再分配不在问题三、四的主模型中执行（假设 7 锁定单元预算），只作为反事实与灵敏度情形报告。




图 6 各推广单元日点击量-日消费额散点（双对数）与幂函数响应曲线 $c_u(S/s_u)^{\gamma_u}$ ；标题中带 * 的单元使用合并弹性。

5 问题二：关键词的成本-效益分类

本节把题目的五类落实为“成本尺度 × 效益指数”平面上的象限划分：先定义成本与复合效益指数，再用数据驱动的阈值划分并检验阈值的稳健性，最后由独立校验器复核每个标签。

5.1 成本与效益的度量

关键词的年度消费 S_i 跨越六个数量级，成本取对数尺度 $x_i^c = \log_{10} S_i$ （仅对 $S_i > 0$ 的词定义）。效益综合四个维度（表 5）：点击量、浏览量、注意力时长与归因注册，

$$z_{i1} = \log(1 + C_i), \quad z_{i2} = \log(1 + V_i), \quad z_{i3} = \log(1 + C_i(1 - b_i)\tau_i), \quad z_{i4} = \log(1 + r_{u(i)}C_i), \quad (8)$$

其中 τ_i 按题目定义是全体访问的平均停留时间（跳出访问的时长已计入该平均），故 $C_i\tau_i$ 才是总停留时间， $C_i(1 - b_i)\tau_i$ 应读作“非跳出访问次数 × 平均访问时长”，即有效注意力时长的一个下界代理； $r_{u(i)}$ 为所属单元的注册率（第 4.4 节）；无访问记录（“/”）的词取 $b_i = 1$ 、 $\tau_i = 0$ 。若改用总停留时间 $C_i\tau_i$ 作为 z_{i3} ，五类标签与主口径的一致率为 95.55%（表 7），结论不受口径选择影响。对每个分量做极差标准化 $\tilde{z}_{ij} = (z_{ij} - \min_k z_{kj}) / (\max_k z_{kj} - \min_k z_{kj}) \in [0, 1]$ ，权重由熵权法 [7] 确定：

$$p_{ij} = \frac{\tilde{z}_{ij}}{\sum_k \tilde{z}_{kj}}, \quad e_j = -\frac{1}{\ln n} \sum_i p_{ij} \ln p_{ij}, \quad w_j = \frac{1 - e_j}{\sum_l (1 - e_l)}, \quad (9)$$

信息量越大（分布越分散）的分量权重越高。综合效益指数

$$\mathcal{B}_i = \sum_{j=1}^4 w_j \tilde{z}_{ij} \in [0, 1]. \quad (10)$$

熵权为：点击 0.1966、浏览 0.2093、注意力时长 0.2849、归因注册 0.3092；等权指数与熵权指数的 Spearman 秩相关为 0.9995，说明权重选择对排序几乎没有影响。

必须明确指出两个坐标轴并不独立：四个效益分量都是规模量，与消费高度共单调——在 1337 个有消费词上 $\text{corr}(x_i^c, \mathcal{B}_i) = 0.9297$ ($R^2 = 0.864$)，Spearman 秩相关 0.9021，其中点击量与效益指数的秩相关达 0.9209。因此式 (12) 实质上是沿同一条“消费-效益”主轴的分档，加上两个位于主轴两侧的小类（黄金词与问题词），而不是两个独立维度的交叉分类。这不影响分类的可用性——题目要求的正是按“成本高低 $\times$ 效益高低”分组——但读者应据此理解两个偏离类的量级（第 5.3 节）。作为对照，若把效益轴换效率口径（每元归因注册的对数），其与成本的 Spearman 秩相关为 -0.4719（负相关），两种口径的标签一致率为 83.79%，五类计数变为黄金 58、重点 2、潜力 959、问题 318、无效 890。效率口径下“高成本高效益”几乎为空（2 个），与题目“重点词=高成本高效益”的设定不符，故主口径采用规模效益（MDR-0004）；两种口径并列供读者判断。

表 5 效益指数的四个分量及其业务含义

分量	定义	含义	熵权
点击量	$\log(1 + C_i)$	流量规模	0.1966
浏览量	$\log(1 + V_i)$	浏览深度	0.2093
注意力时长	$\log(1 + C_i(1 - b_i)\tau_i)$	非跳出访问数 $\times$ 平均访问时长	0.2849
归因注册	$\log(1 + r_{u(i)}C_i)$	最终转化	0.3092

5.2 阈值与分类规则

“高/低”的界限在有消费的词上由数据决定。主方法为两类 Fisher-Jenks 自然断点 [8-9]：对排序后的样本 $v_{(1)} \leq \dots \leq v_{(n)}$ 求

$$k^* = \arg \min_{1 \leq k \leq n} \left[\sum_{i \leq k} (v_{(i)} - \bar{v}_{\leq k})^2 + \sum_{i > k} (v_{(i)} - \bar{v}_{> k})^2 \right], \quad \text{阈值} = \frac{1}{2}(v_{(k^*)} + v_{(k^*+1)}), \quad (11)$$

利用前缀和可在排序后 $O(n)$ 精确求解，它等价于一维两类 k -means 的全局最优解。作为对照，另取中位数与二分量高斯混合模型后验概率 0.5 的交点作阈值。分类规则为

$$\text{标签}_i = \begin{cases} \text{无效词,} & S_i = 0 \text{ 且 } C_i = 0, \\ \text{黄金词,} & x_i^c \leq \tau_c, \mathcal{B}_i \geq \tau_b, \\ \text{重点词,} & x_i^c > \tau_c, \mathcal{B}_i \geq \tau_b, \\ \text{潜力词,} & x_i^c \leq \tau_c, \mathcal{B}_i < \tau_b, \\ \text{问题词,} & x_i^c > \tau_c, \mathcal{B}_i < \tau_b, \end{cases} \quad (12)$$

无效词按“零消费且零点击”判定（MDR-0001）：未购买任何点击的词不可能通过广告产生效益，两条零消费、零点击但浏览量为 1 的记录视为统计噪声。主方法阈值为成本 41.59 元/年（ $\log_{10}$ 尺度 1.6190）、效益指数 0.2758；中位数法与高斯混合法的成本阈值分别为 8.06 元与 107.51 元（图 8）。

5.3 分类结果与稳健性

分类结果为：黄金词 40、重点词 271、潜力词 977、问题词 49、无效词 890（表 6，图 7；各单元的分类分布见附录表 16）。271 个重点词承担了 99.11% 的消费与 98.7511% 的点击，CPC 1.7143 元，是账户的流量与注册主体；40 个黄金词的 CPC 仅 0.7192 元，以极低成本取得高于阈值的效益，但

其经济量级很小——只占全年消费的 0.0752% 与点击的 0.1786%，因此它们是值得小额扩量测试的候选，扩量本身不会改变账户的消费结构；49 个问题词 CPC 高达 2.2313 元而效益低于阈值，应降低出价、收紧匹配或暂停，其消费占比同样只有 0.28%；977 个潜力词消费与效益都低（CPC 1.0599 元），适合小预算测试以发现新的黄金词；890 个无效词占词库四成，应清理或改用更宽的匹配方式。换言之，分类的即时财务影响集中在重点词的内部再分配上（问题三），两个偏离类的价值在于提供扩量与止损的候选清单。

表 6 五类关键词的数量、消费、点击、CPC、平均效益指数与归因注册

类别	数量	占比/%	消费额/元	消费占比/%	消费中位数/元	点击量	CPC/元	平均效益指数	归因注册/人
黄金词	40	1.8	1,072	0.1	26.8	1,491	0.72	0.307	169
重点词	271	12.2	1,413,276	99.1	300.0	824,389	1.71	0.452	59,372
潜力词	977	43.9	7,542	0.5	4.3	7,116	1.06	0.113	604
问题词	49	2.2	4,059	0.3	60.0	1,819	2.23	0.232	124
无效词	890	40.0	0	0.0	0.0	0	—	0.000	0




图 7 关键词的成本-效益散点：横轴为年度消费额（对数轴），纵轴为综合效益指数 (10)，虚线为自然断点阈值，颜色为类别（无效词零消费未画出）。




图 8 log₁₀ 年度消费额（左）与综合效益指数（右）的直方图及三种阈值方法的位置。

阈值方法的稳健性见表 7：主方法与中位数法的标签一致率为 78.36%（中位数把阈值压到 8.06

元，使大量长尾词进入“高成本”），与高斯混合法为 93.53%，与等权效益指数为 99.19%。无效词在所有方法下都是 890 个，重点词、问题词的成员在三种方法下高度重合，差异集中在阈值附近的潜力词与黄金词之间。

表 7 不同阈值方法与权重下的类别数量（成本阈值为原尺度）

阈值方法 / 口径	成本阈值/元	效益阈值	黄金词	重点词	潜力词	问题词	无效词
自然断点（主）	41.59	0.276	40	271	977	49	890
中位数	8.06	0.163	92	577	579	89	890
高斯混合	107.51	0.318	32	195	1,078	32	890
等权效益 + 自然断点	41.59	0.275	47	282	970	38	890
效率效益轴（每元归因注册）；与主口径一致率 83.8%	41.59	0.316	58	2	959	318	890
注意力分量取总停留时间；与主口径一致率 95.6%	41.59	—	5	211	1,012	109	890

5.4 独立复核与结果文件

与分类程序分离的校验器从原始列重新推导每个标签：标签在词表内、无效词当且仅当零消费且零点击、象限规则 (12) 逐词复现（0 个不一致）、五类计数之和等于 2227、黄金词的最大消费不超过问题词的最小消费且最小效益不低于问题词的最大效益、效益指数落在 $[0, 1]$ ；全部通过（第 8 节）。详细结果按模板写入 `result2.xlsx`（2227 行，五个类别列以 1/0 标记）。

6 问题三：关键词选择与投放模型

本节在问题一的结构参数 (r_u, γ_u) 与问题二的类别之上，为每个推广单元建立“投入 $\rightarrow$ 点击 $\rightarrow$ 浏览、注册”的响应模型，把每个单元-日的关键词选择与投放额写成带最小投放额的可分离凹规划，给出精确算法与最优性证书，并用同预算的反事实对照说明策略的优越性。

6.1 关键词响应函数、点击价值与展位模型

附件只有关键词的年度汇总，本文以其活跃日的日均工作点 $(s_i, c_i) = (S_i/n_u, C_i/n_u)$ 为锚、以单元弹性为形状参数建立幂函数响应（假设 4）：

$$q_i(x) = c_i \left(\frac{x}{s_i} \right)^{\gamma_u}, \quad \text{CPC}_i(x) = \frac{x}{q_i(x)} = \frac{s_i}{c_i} \left(\frac{x}{s_i} \right)^{1-\gamma_u}, \quad x \geq 0, \quad (13)$$

它过历史工作点 $q_i(s_i) = c_i$ ，且 $\gamma_u < 1$ 使平均与边际点击成本随投入上升——这是 SEM 竞价市场的基本事实 [2-3]：更多点击只能通过更高排位、更高出价获得。文献中的广告响应模型（如 ADBUDG 与幂函数）同样以凹响应刻画边际收益递减 [10-11]；指数饱和函数在 11/12 个单元上的拟合残差平方和大于幂函数，故不采用（MDR-0005）。每次点击的期望注册与浏览量为（假设 5）

$$\rho_i = r_u \kappa_i, \quad \kappa_i = \text{clip} \left(\frac{1 - b_i}{1 - \bar{b}_u}, 0.25, 2.5 \right), \quad v_i(x) = d_i q_i(x), \quad (14)$$

72 个有点击但浏览量为 0 且跳出率为 0 的词属访问追踪缺失，其 b_i, d_i 回退到单元均值。日期 t 的期望点击为 $\hat{\varepsilon}_{u,t} q_i(x)$ （假设 6）， $\hat{\varepsilon}_{u,t} = E[\varepsilon_{u,t}]$ 由第 7.1 节的日历模型给出（问题三中为样本内拟合值）。

展位由单元日序列上的加权 logit 回归刻画（按展现量加权，斜率限制为非负，不显著或为负时退化为常数）：

$$\begin{aligned} \text{logit } p_u^{\text{top}} &= a_u + b_u \log \text{CPC}, & \text{logit } p_u^1 &= a'_u + b'_u \log \text{CPC}, \\ \pi &= 1 \cdot p^1 + 2.5 (p^{\text{top}} - p^1) + 4(1 - p^{\text{top}}), \end{aligned} \quad (15)$$

关键词在投放 x 下的 CPC 由式 (13) 代入得到其上方位、首位占比与预期展位指数 π (首位记 1, 上方位其余记 2.5, 上方位之外记 4; 数值越小越靠前, MDR-0007)。

6.2 单元-日分配模型

记 $\mathcal{K}_u^e$ 为单元 u 的候选词集合: 黄金词、重点词、潜力词与问题词参与, 无效词不参与; 问题词的投放上限减半 ($\phi_i = 0.5$, 其余 $\phi_i = 1$)。关键词的“关联关系”体现为: 同一单元的词共享弹性 γ_u 与注册率 r_u 、共用该单元的预算, 类型决定上限; 同一 ID 在多个单元重复投放时各份独立参与 (数据无法识别跨单元的相互蚕食, 重复投放作为问题一的发现提示合并)。单元 u 在日期 t 的模型为

$$(P_{u,t}) : \max_x \sum_{i \in \mathcal{K}_u^e} \hat{\varepsilon}_{u,t} \rho_i c_i \left(\frac{x_i}{s_i} \right)^{\gamma_u} \quad \text{s.t.} \quad \sum_i x_i \leq B_{u,t}, \quad x_i \in \{0\} \cup [m, \bar{x}_i], \quad (16)$$

$$\bar{x}_i = \max \left\{ \mu \phi_i s_i, \frac{B_{u,t} s_i}{\sum_{j \in \mathcal{K}_u^e} s_j}, m \right\}, \quad \mu = 4.0, \quad m = 0.50 \text{ 元}, \quad (17)$$

其中 $B_{u,t}$ 为该单元当日的 2025 年实际消费 (假设 7), 目标是当日预期注册量 (点击、浏览随之由式 (13)、(14) 给出)。关键词预算分配在文献中通常写成以凹响应为目标的背包型或凸规划问题 [12-13], 式 (16) 属于这一类, 其特点是用最小投放额显式地把“选词”与“定额”合并在一个问题中。上限不低于历史比例份额, 因此历史比例点 x^{prop} 对去掉最小投放额的凸松弛可行, 松弛最优值不低于历史做法; 但含最小投放额时 x^{prop} 通常不可行——其正坐标中有 87.5% (11,301 / 12,917) 低于 m , 故“最优值 $\geq$ 基线值”不能由可行性先验地推出, 只能作为经验结论报告 (第 6.5 节: 107 个单元-日全部满足, 最小比值 1.0062)。式 (17) 之后还有一步归一化: 若 $\sum_i \bar{x}_i < 1.2B_{u,t}$ 则令 $\bar{x} \leftarrow \bar{x} \cdot \max\{1, 1.2B_{u,t} / \sum_i \bar{x}_i\}$, 以保证预算可用完。最小投放额 m 是关键词选择机制: 投放低于 m 的词视为不投放, 避免“每个词分几分钱”的无意义解。写 $a_i = \hat{\varepsilon}_{u,t} \rho_i c_i s_i^{-\gamma_u}$, 目标即 $\sum_i a_i x_i^{\gamma_u}$ 。

6.3 求解算法与最优性

定理 6.1 (松弛问题的注水解). 设 $a_i > 0$, $\gamma \in (0, 1)$, $\bar{x}_i > 0$ 。问题 $\max\{\sum_i a_i x_i^\gamma : \sum_i x_i \leq B, 0 \leq x_i \leq \bar{x}_i\}$ 有唯一最优解。若 $\sum_i \bar{x}_i \leq B$, 则 $x^* = \bar{x}$; 否则

$$x_i^*(\lambda^*) = \min \left\{ \bar{x}_i, (\gamma a_i / \lambda^*)^{1/(1-\gamma)} \right\}, \quad (18)$$

其中 $\lambda^* > 0$ 是方程 $\sum_i x_i(\lambda) = B$ 的唯一根。

证明. 目标是严格凹函数之和, 可行域是紧凸集, 故最优解存在且唯一; Slater 条件成立, KKT 条件充要 [14-15]。因 $d(a_i x_i^\gamma)/dx \rightarrow +\infty$ ($x \rightarrow 0^+$), 下界 $x_i \geq 0$ 的乘子恒为零; 对预算乘子 $\lambda \geq 0$ 与上界乘子 $\nu_i \geq 0$ 有 $\gamma a_i x_i^{\gamma-1} = \lambda + \nu_i$, $\nu_i(x_i - \bar{x}_i) = 0$, 解得式 (18)。当 $\sum_i \bar{x}_i > B$ 时预算必然取等 (否则可增加某个未达上限的 x_i 而改进), 而 $\lambda \mapsto \sum_i x_i(\lambda)$ 连续、在未全部达上限处严格递减、 $\lambda \rightarrow 0^+$ 时趋于 $\sum_i \bar{x}_i > B$ 、 $\lambda \rightarrow \infty$ 时趋于 0, 故根唯一。□

定理 6.1 是连续非线性资源分配问题的经典结论 [16], λ^* 用对数尺度二分法求到相对精度 10^{-12} 。含最小投放额时 $\{0\} \cup [m, \bar{x}_i]$ 非凸, 本文用拉格朗日松弛确定入选集合、再在该集合上精确求解 (算法 1): 对价格 λ , 每个词的拉格朗日子问题 $\max\{a_i x_i^\gamma - \lambda x : x \in \{0\} \cup [m, \bar{x}_i]\}$ 的解为 $x_i(\lambda) = \text{clip}((\gamma a_i / \lambda)^{1/(1-\gamma)}, m, \bar{x}_i)$ (当其值 $a_i x_i^\gamma \geq \lambda x_i$) 或 0, 总投放随 λ 单调不减, 二分得到预算恰好可用的价格及其入选集合; 第二阶段在入选集合上以下界 m 、上界 $\bar{x}_i$ 做有界注水 (定理 6.1 的推广, KKT 条件在该集合上精确成立)。

Algorithm 1: 两阶段拉格朗日-注水法求解 ($P_{u,t}$)

输入: 系数 $a_i > 0$, 弹性 γ , 上限 $\bar{x}_i$, 预算 B , 最小投放额 m , 精度 ϵ

输出: 投放向量 x^* 、入选集合 $\mathcal{S}$

- 1 **if** $\sum_i \bar{x}_i \leq B$ **then**
 - 2 **return** $x^* = \bar{x}$;
 - 3 **阶段一 (选择):** $x_i(\lambda) \leftarrow \text{clip}((\gamma a_i / \lambda)^{1/(1-\gamma)}, m, \bar{x}_i)$, 若 $a_i x_i(\lambda)^\gamma < \lambda x_i(\lambda)$ 则
 $x_i(\lambda) \leftarrow 0$;
 - 4 在 $[\lambda_{\text{lo}}, \lambda_{\text{hi}}]$ 上对 λ 做对数尺度二分, 直到 $\lambda_{\text{hi}} / \lambda_{\text{lo}} - 1 < \epsilon$ 且
 $\sum_i x_i(\lambda_{\text{hi}}) \leq B < \sum_i x_i(\lambda_{\text{lo}})$;
 - 5 $\mathcal{S} \leftarrow \{i : x_i(\lambda_{\text{hi}}) > 0\}$;
 - 6 **阶段二 (精确求解):** 在 $\mathcal{S}$ 上求解 $\max\{\sum_{i \in \mathcal{S}} a_i x_i^\gamma : \sum_{i \in \mathcal{S}} x_i = B, m \leq x_i \leq \bar{x}_i\}$
 ——以 $x_i(\lambda) = \text{clip}((\gamma a_i / \lambda)^{1/(1-\gamma)}, m, \bar{x}_i)$ 二分求 λ , 再在自由坐标上按比例修正预算余量;
 - 7 **return** x^* ($\mathcal{S}$ 外为 0)
-

每次二分需 $O(n)$ 运算, 二分次数 $O(\log(1/\epsilon))$, 故复杂度 $O(n \log(1/\epsilon))$; 107 个单元-日问题 (最多 577 个候选词) 合计求解不到一分钟。最优性由与求解器分离的校验器证明 (第 8.4 节): 可行性、KKT 驻点条件 (内点坐标边际价值相等、达上限坐标的边际不小于价格、达下限坐标的平均价值覆盖价格)、随机配对转移 / 剔除 / 插入均不能改进, 以及用通用凸求解器 (CVXPY/Clarabel[17]) 求得的去掉最小投放额约束的松弛问题最优值作为上界。松弛问题是 ($P_{u,t}$) 的放松, 其最优值 $\geq$ 任意可行解的值, 因此

$$\text{总体最优性界} = \frac{\sum_{(u,t)} [\text{松弛上界}_{u,t} - \text{目标值}_{u,t}]}{\sum_{(u,t)} \text{目标值}_{u,t}} = 0.080\%, \quad (19)$$

即两阶段解与全局最优的差距不超过总注册量的千分之一; 去掉 13 个预算不足 20 倍最小投放额的微小问题后, 单个问题的最大相对差为 3.404% (微小问题上松弛界不具信息量, 最大相对差 20.1%, 但它们对总量的贡献可忽略)。

6.4 反事实基线、不确定性与备选预算口径

优越性通过同一响应模型、同一日乘子、同一预算下的反事实比较说明。基线一“按历史比例”复现 2025 年的做法: $x_i^{\text{prop}} = B_{u,t} s_i / \sum_{j \in \mathcal{K}_u^e} s_j$ (对该单元全部候选词, 因此比优化器多用了被剔除的词); 基线二“均匀分配”: $x_i^{\text{eq}} = B_{u,t} / |\mathcal{K}_u^e|$ 。弹性的抽样不确定性用参数自助法 [18] 传播: 每次抽 $\gamma_u^{(b)} \sim N(\hat{\gamma}_u, \text{se}_u)$ (截断到 $[0.3, 0.95]$), 重解最优与基线, 取提升比的 2.5% 与 97.5% 分位 (100 次)。作为预算口径的备选, “窗口预算”允许单元在 8 天内跨日调配: 先按各日期望效率乘子求解 $\max\{\sum_t \hat{\epsilon}_{u,t} X_t^{\gamma_u} : \sum_t X_t = \sum_t B_{u,t}, X_t \leq 1.5 \max_t B_{u,t}\}$ (内层值函数 $V_t(X_t)$ 只在日内上限与最小投放额都不起作用时才恰为 $K_u X_t^{\gamma_u}$; 本数据上上限经常起作用, 故两层分解是启发式, 其联合间隙在第 8.6 节用同一注水机制的联合松弛上界给出), 再按 ($P_{u,t}$) 分配到关键词。

6.5 结果与优越性

表 8 汇总两个窗口各单元的结果，逐日结果见附录表 17，图 9 给出逐日对照与自助分布。2 月 1–8 日处于春节假期，仅 2 个单元有实际投放（16 个单元–日，预算 13,681.15 元，候选词 286 个，入选 73 个）；8 月 1–8 日 12 个单元在窗口内均有投放，逐日实际为 11–12 个（合计 91 个单元–日，预算 37,483.78 元，候选词 1337 个，入选 535 个）。同预算下最优策略的预期注册量为 516.42 与 2237.43 人，较按历史比例的 459.65 与 1748.04 人提升 12.35% 与 28.00%（自助 95% 区间 [11.67, 13.39]% 与 [27.53, 28.57]%），较均匀分配提升 88.54% 与 77.01%；预期点击提升 12.05% 与 15.87%，平均 CPC 由 2.1595 与 1.5124 元降至 1.9273 与 1.3052 元。

表 8 两个窗口各推广单元的分配结果：预算、候选与平均入选词数、按历史比例与最优的预期注册、提升及弹性自助 95% 区间、CPC

窗口	推广单元	单元–日数	预算/元	候选词	平均入选词	历史比例注册/人	最优注册/人	提升/%	95% 自助区间	历史 CPC/元	最优 CPC/元
2025-02-01 至 02-08	9628223555	8	1,853	247	15.8	18.0	31.8	76.7		2.88	2.22
2025-02-01 至 02-08	9657930100	8	11,829	39	25.1	441.7	484.7	9.7		2.08	1.89
2025-02-01 至 02-08	合计	16	13,681	286	20.4	459.6	516.4	12.4	[11.7, 13.4]	2.16	1.93
2025-08-01 至 08-08	1841014603	8	305	35	4.2	18.9	22.8	20.7		1.29	1.17
2025-08-01 至 08-08	2526158329	4	13	14	5.2	0.6	1.0	59.6		1.53	1.71
2025-08-01 至 08-08	2874903000	8	229	60	22.8	11.1	15.9	43.7		1.44	1.46
2025-08-01 至 08-08	4190988309	8	244	19	4.4	10.1	10.6	5.3		1.93	1.94
2025-08-01 至 08-08	4190988310	8	235	45	18.4	10.5	16.2	54.4		1.71	1.89
2025-08-01 至 08-08	8878077181	8	4,319	4	3.0	275.1	314.2	14.2		0.68	0.60
2025-08-01 至 08-08	9628223555	8	548	247	7.4	27.4	49.6	81.2		0.56	0.41
2025-08-01 至 08-08	9630806627	8	2,870	281	53.8	242.3	331.6	36.8		0.87	0.79
2025-08-01 至 08-08	9657930100	8	23,969	39	27.9	822.4	894.5	8.8		2.26	2.08
2025-08-01 至 08-08	9700005700	7	141	11	1.0	5.7	17.6	210.5		1.98	0.70
2025-08-01 至 08-08	9773660250	8	2,116	5	5.0	76.5	77.0	0.7		2.20	2.17
2025-08-01 至 08-08	9811363528	8	2,494	577	96.8	247.5	486.4	96.5		1.32	0.80
2025-08-01 至 08-08	合计	91	37,484	1,337	21.7	1748.0	2237.4	28.0	[27.5, 28.6]	1.51	1.31




图 9 左、中：两个窗口逐日预期注册量——最优分配、按历史比例、均匀分配；右：弹性参数自助抽样下最优分配相对历史比例的提升分布。

提升的来源见图 10。最优解把预算从 CPC 高、注册率低的词移向 ρ_i/CPC_i 高的词：一部分重点词被推到上限（沿上限线分布，339 个入选词–日达到上限，这也是两层分解在问题四中不能保证联合最优的原因），另一部分被压缩或剔除（271 个重点词中约半数至少入选一天），8 月窗口每个单元–日平均入选 21.7 个词。图中位于上限线之上的一簇点是历史日均消费低于 m/μ 的长尾词（主要

是潜力词与黄金词)：按式 (17) 其上限就是最小投放额 m ，它们以每天 m 元的试探性投放入选——8 月窗口这类词-日共 1259 个，只占预算的 1.68%，贡献预期注册的 5.49%；幂函数在远离历史工作点处的外推可靠性有限，对这些词的预期只应理解为“值得小额测试”，主要提升仍来自重点词之间的再分配。提升幅度随单元的候选词数与弹性差异而不同：8 月窗口单元 9773660250 的提升最小 (0.7%)，单元 9700005700 最大 (210.5%)；消费最大的单元 9657930100 候选词最少且弹性最低，提升幅度也接近最低 (表 8)。因此“低成本、高效益”的实现路径主要是长尾单元内部的词级再分配，而不是改变类别间的消费结构 (重点词在两种方案下都占消费的绝大部分)。




图 10 8 月窗口最优分配的机制。左：每个入选关键词的窗口日均最优投放与其 2025 年日均消费 (双对数，颜色为类别；虚线为投放不变，点线为上限倍数)；右：各类别的候选词数与至少入选一天的词数。

窗口预算的备选口径 (表 9) 显示：允许跨日调配时，2 月窗口再提升 0.82% (春节期间各日效率相近)，8 月窗口再提升 11.25%——把 8 月 3、4 日 (周日、周一，效率乘子最低) 的预算进一步移到工作日。这里必须直面一个与问题一的张力：第 4.3 节按需求侧口径 (控制当日消费后的注册效应) 判断周一、周日的实际减投深于边际均衡的点估计，而本节按效率乘子口径 (同样投入下的点击产出) 判断周日、周一是一年产出最低的两日，建议进一步减投。两者不是同一个量： δ'_w 度量的是给定投入下的注册变化， $\varepsilon_{u,t}$ 度量的是给定投入下的点击变化，而式 (4) 中 $\log S_t$ 与周一哑变量高度共线 (公司每逢周一必减投，周一消费 59.7%)， $\delta'_{\text{周一}}$ 因此识别很弱 ($p = 0.2665$ ，95% 区间对应的最优减投幅度 $[-48.7, 68.5]\%$ 跨越零)。本文的取舍是：**以效率乘子口径作为问题三、四的分配依据** (它直接进入目标函数、有滚动回测支持)，而把问题一的周几结论降级为“方向性提示、未被数据显著判定” (第 4.3 节已按此表述)，并在第 9.2 节列为局限。

表 9 窗口预算跨日调配 (备选口径) 相对逐日预算的额外提升

窗口	逐日预算最优注册/人	窗口预算最优注册/人	额外提升/%	跨日调动预算比例/%
2 月窗口	516.4	520.6	0.8	16.0
8 月窗口	2237.4	2489.1	11.2	12.5

同一 ID 跨单元重复投放的暴露 第 4.2 节发现 290 个关键词 ID 被 2-4 个单元共用 (633 条记录)。在交付方案中，有 75 个“关键词-日”同时出现在 ≥ 2 个单元，涉及投放 7,240.11 元 (占两窗口预算的 14.15%)、预期注册 449.31 人 (占合计的 16.32%)。数据无法识别这些副本之间的相

互蚕食，因此这一比例是高估上界：即便重复副本的增量价值全部为零，8 月窗口的预期注册最多被高估 16.32%。作为灵敏度，对重复 ID 只保留效率 ρ_i/CPC_i 最高的一份、并以同一规则重建基线（表 18），提升由 12.35% / 28.00% 变为 12.32% / 24.65%，仍为正。

预算口径与“每个推广单元”的覆盖 按假设 7, 2 月窗口只有 2 个单元有实际消费，其余单元在 2025 年春节期间停投，因此 result3.xlsx 的 2 月部分只覆盖这 2 个单元。为使问题三对题目要求的“每个推广单元”都有可执行答案，本文按问题四的全年日均口径（单元年度消费 / 365×8 ）另给出 2 月窗口覆盖全部 12 个单元的备选方案：预算合计 31,252.92 元，入选 519 个关键词、2271 条逐日记录，预期点击 18,914.9、预期注册 1866.83 人，逐行明细见支撑材料 allocate/plan_feb_annual_avg.csv。两种口径的取舍写在 MDR-0006：主口径保证“同预算可比”（这是优越性论证的前提），备选口径保证“覆盖所有单元”。

详细结果按模板写入 result3.xlsx（2303 行：日期、方案 ID、推广单元、关键词、投入金额、预期展位、预期点击量、预期浏览量、预期注册量；投入金额为式 (16) 的解，预期展位为式 (15) 的 π ；“入选 535 个关键词”按“关键词-单元组合”计数，不同关键词 ID 数略少，差额来自上述跨单元重复投放）。策略的优越性归结为四点：(i) 每个单元-日问题的解带有全局最优性证书，总体差距 $\leq 0.080\%$ （式 (19)）；(ii) 同预算下相对 2025 年做法的注册提升在全部 107 个单元-日上均为正（最小比值 1.0062），窗口合计的弹性自助 95% 区间不含零——这是经验结论而非先验保证（第 6.2 节）；(iii) 灵敏度分析（第 8.5 节）的 14 种情形（上限倍数、弹性、预算、问题词处理、最小投放额、跳出率因子 κ 、重复词去重）下提升均为正，范围 9.0%–36.4%；(iv) 响应模型在历史工作点附近经过校准，且窗口级水平偏差经重标定检验后不削弱结论（第 8.4 节）。

7 问题四：2026 年 9 月 11–17 日的投放策略与期望范围

本节先为每个单元建立日效率、CPC、CTR 与展位的日历预测模型并用滚动回测检验其点预测与区间，再在问题三的分配模型上叠加不确定性：证明期望注册最大化问题与用期望乘子的确定性问题的同解，从而以两层分配给出逐日策略，并用蒙特卡罗情景给出竞价（CPC）、展现量、展现位、点击量、浏览量与注册量的期望范围。

7.1 预测对象、日历模型与滚动回测

对单元 u 有投放的每一天定义六个目标：效率乘子 $\log \varepsilon_{u,t} = \log C_{u,t} - \gamma_u \log(S_{u,t}/\bar{s}_u) - \log \bar{c}_u$ （ $\bar{s}_u, \bar{c}_u$ 为活跃日均值，即式 (7) 的残差结构）、 $\log \text{CPC}_{u,t}$ 、 $\text{logit CTR}_{u,t}$ 、 $\text{logit } p_{u,t}^{\text{top}}$ 、 $\text{logit } p_{u,t}^1$ 与 $\log C_{u,t}$ 。每个目标 $y_{u,t}$ 用日历回归

$$y_{u,t} = \beta_{u,0} + \sum_{w \neq \text{周三}} \beta_{u,w} D_t^w + \sum_m \mu_{u,m} M_t^m + \delta_{u,H} H_t + \delta_{u,A} A_t + e_{u,t}, \quad e_{u,t} \sim (0, \sigma_u^2), \quad (20)$$

（月份效应不设基准月，由岭正则识别）以岭正则（ 10^{-3} ，不含截距）稳定估计。预测点在样本末 8.5 个月之后，近期水平不可用，因此 2026 年的预测标准差取 $\sqrt{\sigma_u^2 + (\sigma_u^m)^2}$ ，其中 σ_u^m 为 2025 年月份效应的横截面标准差。必须强调： σ_u^m 度量的是模型已经拟合掉的年内季节性离散度，而这里把它借用为年际漂移的标准差——后者在只有一年数据时不可识别，这是一条不可检验的建模约定（假设 8），它使部署区间比仅含残差的区间宽 1.536 倍（中位数；最小 1.069、最大 4.460）。9 月效应取 2025 年 9 月的估计（该月无投放的单元取基准月）。点预测经 $\exp$ 或 expit 反变换，效率乘子的期望取对数正态均值 $\hat{\varepsilon}_{u,t} = \exp(\mu_{u,t} + \frac{1}{2}\sigma^2)$ 。

模型用 2025 年第四季度的滚动起点回测检验 [19]：起点为 10 月 9 日起每周一个（共 12 个），预测步长 7 天，训练集至少 40 天；对照两条基线——季节朴素（上周同一周几的值，区间取 7 阶差分的 10%/90% 分位）与 28 日均值（区间取近 28 日偏差的分位）；指标为变换尺度上的 MAE、RMSE、分位数 0.1 与 0.9 的 pinball 损失 [20-21] 以及 80% 区间覆盖率。为使回测检验的区间与实际交付的区间是同一个对象，回测同时评估两种日历回归区间：仅含残差标准差 σ_u 的“残差区间”，以及实际部署的 $\sqrt{\sigma_u^2 + (\sigma_u^m)^2}$ 宽度的“部署区间”。附录表 19 与图 11 给出结果：残差区间的 80% 覆盖率为 78.3%–87.3%（接近名义水平），部署区间为 86.8%–92.1%（明显过覆盖，即偏保守）；28 日均值的区间过窄（63.6%–80.3%），季节朴素的区间约 90%。因此本文报告的 10%–90% 范围应理解为**保守区间**：在 7 天步长的回测上它覆盖了约九成而非八成的实现值；对 8.5 个月之后的目标点，这一保守性是有意保留的，但读者应知道多出的宽度来自不可检验的 σ^m 约定而非回测校准。点预测方面，6 个目标中 5 个的 MAE 由 28 日均值取得（近期水平的持续性强于全年日历结构）；点击量上日历回归与季节朴素基本持平（MAE 0.4805 对 0.4796），日历回归的 RMSE 与 pinball 略优。由于 2026 年 9 月的目标点没有可用的“近期水平”，本文采用日历回归给出点预测；这一取舍与代价在第 9 节中说明。




图 11 滚动回测：日历回归、季节朴素与 28 日均值对各目标的 MAE (左) 与 80% 区间覆盖率 (右，虚线为名义水平 80%)。

7.2 预算、不确定性模型与随机分配

预算按“不超过 2025 年的投入”取 2025 年同期（9 月 11–17 日）各单元的实际消费之和 B_u （合计 23,488.02 元），同期无消费的 2 个单元在主口径下预算为零、不安排投放（在 result4.xlsx 中以零行显式给出），其余 10 个单元参与；按全年日均折算（ $\sum_t S_{u,t}/365 \times 7$ ，合计 27,346.98 元）作为备选口径并同样给出完整方案（MDR-0008、MDR-0012）。不确定性以四类冲击进入响应（假设 6）：单元-日共同冲击 $\varepsilon_{u,t} = \exp(\mu_{u,t} + \sigma_u^{\text{tot}} w_t)$ ， $w_t \sim N(0, 1)$ ， $\sigma_u^{\text{tot}} = \sqrt{\sigma_u^2 + (\sigma_u^m)^2}$ ；关键词特异冲击 $\xi_i = \exp(\sigma_u^{\text{kw}} \zeta_i - \frac{1}{2}(\sigma_u^{\text{kw}})^2)$ （均值 1， $\zeta_i \sim N(0, 1)$ 与 w_t 独立， σ_u^{kw} 取该单元 log CPC 的残差标准差）；CTR 与上方位占比的 logit 日冲击；注册的泊松噪声。于是

$$\begin{aligned} \text{点击}_i &= q_i(x_i) \varepsilon_{u,t} \xi_i, & \text{CPC}_i &= \frac{x_i}{\text{点击}_i}, & \text{展现}_i &= \frac{\text{点击}_i}{\text{CTR}_{u,t}}, \\ \text{浏览}_i &= d_i \text{点击}_i, & \text{注册}_i &\sim \text{Poisson}(\rho_i \text{点击}_i), \end{aligned} \quad (21)$$

展位由式 (15) 在情景 CPC 下计算。关键词的“竞价”在附件中不可观测，本文以其平均点击成本 CPC_i 作为竞价水平的度量。

命题 7.1 (确定性等价). 若冲击 $\varepsilon_{u,t}$ 与 $\{\xi_i\}$ 相互独立、二者均与投放额 x 无关且 $E[\xi_i] = 1$, 则期望注册最大化问题 $\max_x E[\sum_i \rho_i q_i(x_i) \varepsilon_{u,t} \xi_i]$ 与用期望乘子 $\hat{\varepsilon}_{u,t} = E[\varepsilon_{u,t}]$ 的确定性问题 $(P_{u,t})$ 的最优解集重合。

证明. 期望与有限和交换; 由独立性 $E[\varepsilon_{u,t} \xi_i] = E[\varepsilon_{u,t}] E[\xi_i] = \hat{\varepsilon}_{u,t}$, 故对任意可行 x 两个目标值相等, 最优解集因而重合。□

式 (21) 的实现按独立抽样构造(w_t 与 ζ_t 分别独立抽取), 故命题的条件被满足。因此最优策略无需情景优化, 蒙特卡罗只用于给出各量的期望范围; 样本平均近似的期望值与确定性目标一致, 是模拟正确性的内部检验。策略分两层求解: (i) 跨日分配 $\max\{\sum_t \hat{\varepsilon}_{u,t} X_t^{\gamma_u} : \sum_t X_t \leq B_u, X_t \in \{0\} \cup [m, \bar{X}_u]\}$, $\bar{X}_u = \max\{1.5 \max_{t \in \text{同期}} S_{u,t}, B_u/7\}$, 用算法 1 (把“日”视为关键词, $s = c = 1$ 、系数 $\hat{\varepsilon}_{u,t}$) 求解; (ii) 日内分配即 $(P_{u,t})$, 预算取 X_t 。两层共 75 个问题全部通过独立校验器。需要明确: 内层值函数 $V_t(X_t)$ 只在日内上限与最小投放额都不起作用时才等于 $K_u X_t^{\gamma_u}$, 本数据上上限经常起作用, 因此两层分解不保证联合最优。为给出可核查的界, 本文把每个单元的“7 天 $\times$ 候选词”联合问题写成一个可分离凹规划 (去掉最小投放额、上限取 $\max\{\bar{x}_i(B_u), m\}$ 这一最宽的盒子), 用同一注水机器求解: 它的可行集包含任何两层解, 故其最优值是联合最优的上界。实测联合间隙为 0.822% (10 个单元合计), 单个单元最大 27.49%, 出现在预期注册仅 0.52 人的最小单元 2526158329; 在预期注册不低于 10 人的 7 个单元上最大为 2.08%。随后对每个单元-日按式 (21) 生成 500 个情景, 报告每个关键词、每个单元-日与合计的期望值与 10%-90% 分位。

7.3 结果

表 11 给出逐日策略的汇总, 表 12 给出各单元的 7 日结果, 图 12 与图 13 给出期望与范围。7 天预算 23,488.02 元 (最优解用尽至 0.3 元以内), 入选 146 个关键词-单元组合 (845 条关键词-日记录; 不同关键词 ID 数略少, 差额来自第 4.2 节的跨单元重复投放), 预期点击 17,487.9 次 (10%-90% 分位 13,547.4-21,970.2)、注册 1,194.4 人 (922.9-1,495.3)、展现 721,553.1 次 (362,488.7-1,168,717.5)、浏览 93,916.4 次 (69,297.8-121,848.9)、平均 CPC 1.3431 元 (1.0691-1.7337)、点击加权的预期展位指数 2.6126 (2.2486-3.1264)。 π 的支撑集只有 $\{1, 2.5, 4\}$, 2.6126 是一个三点混合的加权平均而非名次区间: 其背后的点击加权展现结构是上方位占比 56.5% (其中首位 36.0%、上方位其余 20.5%)、上方位之外 100 - 56.5%。又因为 π 把所有非上方位展现一律记为 4 (实际名次可能远在 4 之后), 它是真实期望名次的乐观下界。题目所要求的六个量的期望与范围汇总于表 10, 其中“竞价”以平均点击成本 CPC 度量、“展现位”以式 (15) 的排位指数 π 度量 (附件不含出价与真实排名, 二者只能用可观测量代理, MDR-0011)。合计量的区间由各推广单元的情景分位数相加得到 (单元内 7 天按同一情景对齐求和, 单元之间按分位数相加; 表 11 的逐日行同理为当日各单元之和): 各单元的情景独立抽取, 跨单元对齐没有概率含义, 分位数相加等价于假设单元间冲击完全正相关, 给出区间宽度的保守 (偏宽) 一侧; CPC 与展位不可加, 改用点击量加权平均各单元-日的分位数。蒙特卡罗期望注册 1,194.4 人与确定性目标 1187.4 人相差 1.2 个蒙特卡罗标准误 ($SE \approx 5.8$ 人), 与命题 7.1 相容。跨日分配给 9 月 13、14 日 (周日、周一) 的预算明显低于工作日 (表 11), 与问题一中周日、周一效率最低的发现一致。表 11 的“单元数”在 9 与 10 之间波动, 原因是跨日分配允许 $X_t = 0$: 效率最低的日子个别单元不投放。表 10 的 CPC 行是点击加权口径 (7 日总投放 / 7 日期望点击), 不是情景平均的 CPC 期望; 按后者 (各单元-日情景 CPC 均值的点击加权) 为 1.5735 元, 两者的差由 Jensen 不等式解释。展现量的范围远宽于点击量, 因为它同时承受 CTR 与效率乘子的冲击; CPC 的范围 (约 $\pm 30\%$) 反映了竞价的逐日波动。

同期预算口径把 81.1% 的预算留给单元 9657930100 (2025 年 9 月中旬其他单元几乎停投), 而注册率最高、CPC 最低的长尾单元 9811363528 只分到二百余元却贡献了一百多人的预期注册 (表 12)。

表 10 2026 年 9 月 11–17 日六个量的期望与 10%–90% 范围。左半为 7 日合计（点击量、展现量、浏览量、注册量）或单元–日层级的点击加权平均（CPC、展位指数 π 、上方位与首位占比），相对宽度 = 区间宽度 / 期望；CPC 行为“点击加权 $CPC = 7$ 日总投放 / 7 日期望点击”，不是情景平均的 CPC 期望（后者见正文）。右半为 845 个关键词–日上的中位数（等权，因而由长尾词主导，与点击加权的合计值不可直接比较）。每行取 4 位有效数字，行内左右两半一致；各行量纲相差 5 个数量级，故不统一小数位

量	单位	聚合	7 日期望	10%–90% 范围	相对宽度/%	单关键词–日期望中位数	单关键词–日区间中位数
竞价（平均点击成本 CPC）	元/次	点击加权	1.3431	[1.0691, 1.7337]	49	1.186	[0.5923, 1.923]
展现量	次	合计	721,553.1	[362,488.7, 1,168,717.5]	112	189.3	[22.72, 402.5]
展现位（排位指数 π ）	–	点击加权	2.6126	[2.2486, 3.1264]	34	3.699	[3.447, 3.886]
其中：上方位展现占比	–	点击加权	0.5648	–	0	0.1604	[0.04588, 0.3164]
其中：首位展现占比	–	点击加权	0.3601	–	0	–	–
点击量	次	合计	17,487.9	[13,547.4, 21,970.2]	48	0.8886	[0.4558, 1.41]
浏览量	次	合计	93,916.4	[69,297.8, 121,848.9]	56	2.653	[1.392, 4.345]
注册量	人	合计	1,194.4	[922.9, 1,495.3]	48	0.188	[0, 1]

表 11 2026 年 9 月 11–17 日逐日策略汇总：投入、CPC、展现量、展位、点击量、浏览量、注册量的期望与 10%–90% 范围

日期	单元数	投入/元	CPC/元	CPC 范围	展现量/千次	展现范围/千次	展位	展位范围	点击量	点击范围	浏览量/千次	浏览范围/千次	注册量	注册范围
2026-09-11	9	3,836.7	1.41	[0.88, 2.71]	109.2	[21.4, 225.0]	2.62	[2.25, 3.15]	2,730	[1,418, 4,342]	14.5	[6.4, 24.8]	185	[93, 292]
2026-09-12	9	3,333.4	1.27	[0.79, 2.47]	110.1	[20.4, 228.7]	2.55	[2.20, 3.10]	2,628	[1,348, 4,213]	15.0	[6.4, 25.8]	175	[87, 282]
2026-09-13	10	2,206.8	1.36	[0.85, 2.59]	78.0	[13.9, 153.6]	2.65	[2.28, 3.16]	1,622	[853, 2,609]	8.4	[4.0, 14.5]	114	[56, 189]
2026-09-14	9	2,142.4	1.38	[0.87, 2.64]	74.3	[13.9, 164.6]	2.72	[2.34, 3.19]	1,548	[812, 2,468]	7.6	[3.4, 12.9]	113	[55, 182]
2026-09-15	10	3,813.7	1.31	[0.81, 2.56]	110.0	[21.1, 231.0]	2.58	[2.21, 3.07]	2,914	[1,489, 4,684]	16.1	[7.1, 27.8]	197	[96, 318]
2026-09-16	9	3,982.7	1.29	[0.81, 2.54]	124.0	[23.3, 256.3]	2.59	[2.24, 3.08]	3,095	[1,567, 4,936]	17.0	[7.4, 29.0]	209	[101, 335]
2026-09-17	9	4,171.9	1.41	[0.88, 2.76]	116.0	[22.7, 251.3]	2.65	[2.27, 3.18]	2,951	[1,513, 4,723]	15.3	[6.7, 26.3]	201	[100, 323]

表 12 各推广单元的 7 日预算、弹性、候选词数、CPC 与点击量、注册量的期望和 10%–90% 范围

推广单元 ID	7 日预算/元	γ	候选词	CPC/元	点击量	点击范围	注册量	注册范围
9657930100	19,048.3	0.699	39	2.22	8,568	[7,038, 10,326]	665.4	[541, 802]
8878077181	3,394.7	0.836	4	0.47	7,164	[5,115, 9,507]	310.1	[223, 411]
9628223555	258.5	0.836	247	0.50	518	[385, 658]	19.1	[12, 27]
9811363528	233.8	0.825	577	0.39	598	[487, 716]	127.3	[101, 154]
9630806627	186.8	0.853	281	0.63	298	[240, 359]	33.0	[23, 42]
1841014603	146.0	0.930	35	0.89	163	[133, 195]	14.8	[9, 21]
4190988310	100.6	0.882	45	1.47	69	[61, 77]	11.3	[7, 16]
2874903000	68.8	0.811	60	1.22	56	[46, 68]	8.5	[5, 13]
4190988309	48.6	0.650	19	0.97	50	[41, 61]	4.3	[2, 7]
2526158329	1.8	0.836	14	0.50	3	[1, 5]	0.5	[0, 2]




图 12 2026 年 9 月 11-17 日逐日预期点击量、注册量与 CPC（点为期望，带为 10%-90% 分位）。




图 13 各推广单元 7 天预期注册量及 10%-90% 范围（对数横轴）。

若改按全年日均口径安排预算（27,346.98 元，较同期口径高 16.4%，并恢复 2 个被停投的单元），确定性预期注册由 1187.4 人升至 2327.0 人（+96.0%）。必须说明这一增幅同时包含三种变化：预算增加 16.4%、参与单元由 10 个增至 12 个、以及跨日节奏的改变；因此它不是纯粹的“同额预算下的时间再分配收益”。即便如此，方向是清楚的：2025 年 9 月中旬效率最高的长尾单元被停投，这是投放节奏本身的问题。本文建议公司在 2026 年 9 月不要沿用同期的单元停投安排，并按该口径给出完整的逐日逐词方案（1803 行、12 个单元、274 个关键词，投放合计 27,346.63 元、预期点击 25,130.3 次、预期注册 2327.0 人），见支撑材料 `forecast/plan_annual_alt.csv`。与 2025 年同期实际点击 12,843 次相比，同样的钱在最优策略下预期点击 17,487.9 次（+36.17%），其中包含了日历模型对 9 月效率的估计，应结合区间理解。详细结果（期望值）按模板写入 `result4.xlsx`：845 条有投放的关键词-日记录，另加 2 个同期口径下无预算的单元各 7 天的零行（投入金额与各期望量均为 0，表示当日不投放），使全部 12 个推广单元都在结果文件中出现。每个关键词-日的 10%、50%、90% 分位与上方位、首位占比在支撑材料 `forecast/plan.csv` 中给出；备选口径的完整方案见 `forecast/plan_annual_alt.csv`。

8 模型检验

本文对每一个求解结果都用与求解程序分离的校验器复核，并对统计与预测模型做样本外检验（验证协议见支撑材料 `docs/mdr/0009-verification-protocol.md`）；表 13 汇总检验结论，下面

分项说明。

表 13 独立检验汇总（全部检验在同一次云端运行中自动执行，任一失败即阶段失败）

检验项	结果
Q3 单元-日分配问题数	107
Q3 独立校验（可行性 / KKT / 配对转移与插入 / 通用凸求解器上界）	全部通过
Q3 凸松弛总体最优性界 ($\sum$ 上界 - $\sum$ 目标值) / $\sum$ 目标值	0.080%
Q3 单个问题的最大相对差（不含 13 个预算低于 20 倍最小投放额的微小问题）	3.404%
Q3 微小问题的最大相对差（松弛界在此处不具信息量，见正文）	20.1%
响应模型校准：历史比例分配预测点击 vs 实际 (MAPE / 中位 APE)	32.9% / 22.0%
Q3 灵敏度单调性（6 个名义松弛情形的最优值不得低于基准）	通过
Q3 相对历史比例基线的逐问题占优（含最小投放额时无先验保证，故逐一核对）	107/107，最小比值 1.0062
Q3 单元-日水平偏差重标定不变性（按 $\lambda_{u,t}$ = 实际/基线点击重标定 c_t 后的提升）	feb: 12.35% $\rightarrow$ 12.50% / aug: 28.00% $\rightarrow$ 34.61%
Q3 跨单元重复投放暴露（预期注册 / 投放金额占比，蚕食高估的上界）	16.32% / 14.15%
Q4 分配问题数（跨日 + 单元-日）	75
Q4 独立校验	全部通过
Q4 两层分解的联合最优性界（7 日 $\times$ 关键词的可分离凸松弛，取下界、上限取最宽）	0.822%（单个单元最大 27.5%，出现在预期注册仅 0.5 人的最小单元）
Q4 区间回溯覆盖率（部署区间 / 仅残差区间，名义 80%）	86.8–92.1% / 78.3–87.3%
Q2 分类独立复核（规则重推 / 无效词定义 / 计数）	通过

8.1 数据与假日效应

三张表通过列类型、取值范围与漏斗一致性契约（第 4.1 节），Sheet3 与 Sheet1 的分单元合计对账一致。假日效应的两种检验相互印证：HC3 稳健回归给出注册效应 -73.72% ($p = 8.0 \times 10^{-22}$)，Mann–Whitney 检验给出中位数比 0.2140 ($p = 4.56 \times 10^{-14}$)；控制消费额后需求侧效应 -24.64% 仍显著 ($p = 0.0151$)，而周一、周日效应消失，分解结论不依赖单一模型设定。日历设定的正确性由单元测试对照国务院办公厅通知逐日核对。

8.2 注册归因与弹性的样本外检验

归因模型的 adstock 衰减由滚动起点（50%、60%、70%、80% 处）交叉验证选取，留出期（后 30% 天数） $R^2 = 0.7375$ 、MAPE 30.19%（图 5）；留出期覆盖国庆假期，模型仍复现了假日跌幅与周内节律。弹性回归的单元 R^2 见表 4，合并估计的标准误差仅 0.0113；弹性的抽样不确定性通过参数自助法进入问题三的提升区间（表 8）。

8.3 分类的独立复核与稳健性

校验器从原始列重新推导每个标签，六项检查（标签在词表内、无效词当且仅当零消费且零点击、象限规则逐词复现、计数守恒、黄金词严格优于问题词、效益指数在 $[0, 1]$ ）全部通过。阈值方法的一致率为 78.36%（中位数）、93.53%（高斯混合）、99.19%（等权效益），熵权与等权指数的秩相关 0.9995（表 7）；自然断点算法与暴力枚举在单元测试中逐例一致，性质测试（随机生成的 20–200 个词）验证每个词恰得一个标签。

8.4 问题三分配的最优性证书与响应模型校准

校验器对全部 107 个单元-日问题检查：(i) 非负、不超上限、入选词不低于最小投放额、总投放不超预算且预算用尽或全部达上限；(ii) KKT 条件——内点坐标的边际价值 $\gamma a_i x_i^{\gamma-1}$ 相对离差不超过 10^{-6} ，达上限坐标的边际不小于影子价格，达下限坐标的边际不大于价格且其平均值 $a_i x_i^{\gamma-1}$ 覆

盖价格；(iii) 200 次随机配对转移或整词剔除、50 次未选词按最小投放额插入均不能改进目标；(iv) 用 CVXPY/Clarabel 求解去掉最小投放额的凸松弛作为上界。全部通过；总体最优性界为 0.080% (式 (19))，去掉 13 个预算不足 20 倍最小投放额的微小问题后单个问题最大相对差 3.404%。单元测试另从三个方向核对求解器：无上限时与闭式解一致；小规模实例与网格穷举一致；含最小投放额时与枚举全部入选子集并逐个用 SLSQP 求解的结果一致；基于随机实例的性质测试验证“校验器接受求解器的输出、拒绝人为劣化的解”。

响应模型的校准用“历史比例分配 + 实际预算”应复现实际点击这一事实检验：107 个单元-日的 MAPE 为 32.92%，中位绝对百分误差 22.00%，消费加权 MAPE 30.6%。偏差是有符号的且方向随窗口翻转：2 月窗口基线预测点击比实际高 12.0%，8 月窗口低 -30.8% (附录表 17 的“实际点击”列为数据口径，“按历史比例 / 最优”两列为模型口径，三者不可直接比较)。误差主要来自关键词只有年度汇总——响应曲线由年均工作点与单元弹性外推，无法刻画单个词在特定日期的竞争环境。

“系统性水平误差在提升幅度中抵消”不应作为口号，而应作为可检验命题：若偏差是单元-日层面的乘性偏差，则把每个单元-日的全部 c_i 同乘 $\lambda_{u,t} = (\text{实际点击} / \text{基线点击})$ 后，该单元-日的最优值与基线值同比例变化，其比值恒等不变。实测重标定后窗口合计的提升由 12.35% / 28.00% 变为 12.50% / 34.61% (表 13)：单元-日层面的水平偏差经校正后提升不降反升，因此这一部分风险不威胁结论；剩余风险仅限于词间异质那一部分（若某些词的真实弹性高于所属单元弹性，最优解对其投放偏低，反之偏高），这也是本文以相对提升而非绝对注册量作为优越性证据的原因。

8.5 灵敏度分析

附录表 18 给出 14 种情形下最优分配相对历史比例的提升，范围 9.0%–36.4%，全部为正。上限倍数是最敏感的参数：它决定预算能向高效率词集中的程度，8 月窗口的提升随 μ 从 2 升到 8 而增大，但即使在最保守的 $\mu = 2$ 下提升仍接近基准的三分之二；弹性上调（凹性减弱）使再分配的收益更大，下调则相反，两者与自助区间方向一致，但量级差别很大——自助区间只含 $\hat{\gamma}_u$ 的抽样误差 (SE 合并 0.0113)，而 γ 整体 $\pm 10\%$ 使 8 月提升在 21.8%–36.4% 之间变动，后者宽约十余倍；预算 $\pm 20\%$ 几乎不改变相对提升；剔除问题词或取消其上限折减对结果几乎没有影响（问题词仅占消费 0.28%）。

最小投放额的真实代价与一条单调性门禁 表 18 对 $m = 0$ 给出两行。“最小投放 0 (上限同基准)”把上限固定为基准问题的有效上限 $\max\{\bar{x}_i, m\}$ ，是真正的约束松弛：其最优值必然不低于基准，实测提升为 0.019% 与 0.116% (相对基准最优值)，即**最小投放额把目标值压低不到 0.116%**，换来的是平均入选词数由 116.8 降到 21.7 (8 月窗口) 的稀疏可执行方案。“最小投放 0 (上限随之收缩)”则同时放松下界并让式 (17) 中的 $\max\{\cdot, m\}$ 消失，可行域实际上变小，因此最优值反而下降——这不是最小投放额的代价，而是两个机制耦合的结果，本文并列给出以免误读。为杜绝此类错误，验证协议中加入一条自动门禁：任何名义上更宽松的情形，其最优值不得低于基准；本次运行的 6 个名义松弛情形全部通过 (表 13)。

跳出率质量因子 κ_i 与重复投放 κ_i 直接决定写入结果文件的“预期注册量”，却没有任何注册数据可以验证，且 1,337 个有消费词中有 43.7% 被截断在 $[0.25, 2.5]$ 的边界上 (中位数 0.6296)。令 $\kappa = 1$ (完全关闭跳出率调整) 后提升降为 11.75% 与 26.89%；把截断区间收紧到 $[0.5, 2]$ 后为 12.06% 与 27.13%——结论稳健但量级确实受 κ 影响 (8 月约 1–3 个百分点)。同样，对跨单元重复的关键词 ID 只保留效率最高的一份并以同一规则重建基线后，提升为 12.32% 与 24.65%。二者均列入第 9.2 节。

8.6 问题四的回测、审计与不确定性

预测模型的滚动回测（12 个起点 $\times$ 7 天 $\times$ 11 个单元；附录表 19，图 11）同时评估两种日历回归区间：仅含残差的区间覆盖率 78.3%–87.3%（接近名义 80%），实际部署的加宽区间 86.8%–92.1%（过覆盖），28 日均值 63.6%–80.3%（过窄）。点预测在 7 天步长内多数目标不如 28 日均值，但目标点在样本末 8.5 个月之后，日历结构是唯一可外推的信息，本文如实报告这一取舍。跨日与日内共 75 个分配问题全部通过与问题三相同的校验器；此外，两层分解的联合最优性由“7 日 $\times$ 关键词”的可分离凹松弛给出上界，实测联合间隙 0.822%（单个单元最大 27.49%，出现在预期注册仅 0.52 人的单元；预期注册不低于 10 人的 7 个单元上最大 2.08%）——与问题三的 0.080% 不同，问题四的这一界是松弛界而非“各层分别最优”的合成，两者的差别在表 13 中分列。蒙特卡罗期望注册 1,194.4 人与确定性目标 1187.4 人相差 1.2 个蒙特卡罗标准误（5.8 人），验证了命题 7.1 与模拟的实现；预算口径的备选（全年日均）不仅作为情景分析，还给出完整逐日方案（第 7.3 节）。题目要求的六个量的期望范围见表 10：合计区间按单元间共单调（分位数相加）聚合，是区间宽度的保守一侧；若改按单元间独立聚合，区间会明显变窄，本文不采用（MDR-0011）。结果文件 result2/3/4.xlsx 均通过模板契约检查（表名与表头与模板一致、行数、数值区、小数位不超过 4 位）。

9 模型评价与推广

9.1 模型的优点

(1) 四个问题共用一套结构参数（注册率 r_u 、弹性 γ_u 、日效率乘子），分类、分配与预测在同一响应模型下相互一致，问题三的分配模型被问题四原样复用。(2) 分配问题有最优性证书：松弛问题的注水解有唯一性证明，含选择机制的非凸问题用拉格朗日价格确定入选集合、再在该集合上精确求解，凸松弛给出的总体差距在问题三为 0.080%、在问题四的两层分解为 0.822%——两者都是有界而非精确的结论。(3) 每个结论都有独立证据：假日效应有参数与非参数两种检验并分解出需求侧成分，其规范性推论的抽样不确定性被完整传播；分类有逐词复核、三种阈值与两种效益口径的一致率；分配有反事实对照、自助区间、14 种灵敏度情形与一条单调性门禁；预测有滚动回测的点误差与两种区间宽度的覆盖率。(4) 全部计算在固定镜像的云端流水线上执行，论文中的数字、表格与图形由同一次运行生成并记录散列，可完整复现（附录 B）。

9.2 局限与可能的偏差方向

(1) 关键词只有年度汇总，响应曲线由年均工作点与单元弹性外推，校准 MAPE 约 32.92%，且偏差有符号并随窗口翻转（2 月 +12.0%、8 月 -30.8%）；单元–日层面的乘性偏差经重标定检验后不削弱结论（第 8.4 节），但词间弹性异质无法检验：若某些词的真实弹性高于单元弹性，最优解对这些词投放偏低，反之偏高。同一原因使 8 月窗口最优解的预期点击（28,718.7）低于 2025 年同期的实际点击（35,812），因此 28.00% 只应读作同一模型内的相对量，不可解读为相对 2025 年真实绩效的增益。(2) 注册只有日总量， r_u 由带日历项的非负最小二乘推断而非真实转化追踪：12 个单元中 6 个的原始估计被非负约束顶在 0，5 个保留自身估计、其余退回合并估计；残差化后点击设计阵的条件数为 948，去掉月份哑变量后单元注册率最大摆动 3.6 倍（表 4）。若各单元真实注册率差异更大，长尾单元的提报可能被低估或高估。(3) 假日效应的需求侧分解与式 (5) 的规范结论都依赖“控制当日消费”的识别假设： $\log S_t$ 由公司内生选择， θ 是条件相关弹性而非因果回报弹性；若减投本身响应了需求的实时信号，需求侧效应会被高估。同一原因使式 (5) 只能给出参考值——其 95% 区间 [26.9, 76.6]% 覆盖了实际减投 76.7%。(4) 同一关键词跨单元重复投放的相互蚕食无法从数据识别。暴露规模为：交付方案中 75 个关键词–日涉及预期注册的 16.32%、投放金额的 14.15%；最坏

情形下（重复副本的增量价值全为零）8月窗口的预期注册被高估不超过16.32%，去重灵敏度下提升仍为24.65%。(5) 跳出率质量因子 κ_i 未经任何注册数据验证，43.7%的词落在截断边界上；它使结果文件中的“预期注册量”对部分关键词高于其所属单元的平均注册率。关闭该因子后提升降至26.89%（8月），仍为正。(6) 2026年的市场趋势、竞争对手行为与平台规则变化无法从一年的数据识别；问题四区间中的年际漂移项 σ^m 是一条不可检验的约定（第7.1节），它使部署区间比可回测的残差区间宽1.536倍（最大4.460倍），回测显示部署区间过覆盖（86.8%–92.1%）。2月窗口仅2个单元有实际投放，主口径结论的外推性有限（已另给覆盖全部12个单元的备选方案）。(7) “预期展位”是按首位 / 上方位其余 / 上方位之外三档定义的排位指数（把所有非上方位记为4，因此是真实名次的乐观下界），“竞价”以平均点击成本代理（附件不含出价与真实排名），二者的绝对数值依赖这些约定，但排序与相对比较不受影响。(8) 问题四合计量的区间按各单元的分位数相加得到，隐含单元间冲击完全正相关，是偏宽的一侧；真实的合计区间应窄于所报告的区间。(9) 问题三、四的主模型把每个单元的预算锁定为其历史实际消费（假设7），因此不执行第4.2节指出的跨单元再分配；该方向的反事实收益（3.97%–32.31%）只作为对照报告。问题一按需求侧口径给出的“周一、周日减投过深”与问题三按效率乘子口径给出的“周日、周一应进一步减投”是两个不同量的结论，本文以后者作为分配依据（第6.5节），前者因 $\log S_t$ 与周几哑变量共线而识别很弱。

9.3 改进方向与推广

若能获得关键词的逐日消费与点击、真实的转化追踪与出价记录，响应函数可按词估计并直接以出价为决策变量，本文的分配框架（可分离凹规划 + 拉格朗日选择 + 独立证书）无需改动；跨单元的重复词可加入共享流量约束，跨日分配可加入 CVaR 形式的超支约束以控制预算风险。方法本身可推广到任何“预算 → 凹响应 → 转化”的资源分配场景，如信息流广告、渠道预算分配与库存促销。

AI 工具使用声明

本研究在问题分析、方案比较、程序编写与调试、云端实验组织、数值核验、图表绘制以及论文文字组织等环节使用了生成式 AI 工具（Anthropic Claude Code，模型 Claude Fable 5.1）；所有数据处理、计算与排版在 Modal 云平台执行。使用过程与人工核验方式详见支撑材料中的《AI 工具使用详情.pdf》。

参考文献

- [1] 国务院办公厅. 国务院办公厅关于 2025 年部分节假日安排的通知（国办发明电〔2024〕12 号）[Z]. 2024.
- [2] EDELMAN B, OSTROVSKY M, SCHWARZ M. Internet advertising and the generalized second-price auction: Selling billions of dollars worth of keywords[J]. American Economic Review, 2007, 97(1): 242-259.
- [3] VARIAN H R. Position auctions[J]. International Journal of Industrial Organization, 2007, 25(6): 1163-1178.
- [4] MACKINNON J G, WHITE H. Some heteroskedasticity-consistent covariance matrix estimators with improved finite sample properties[J]. Journal of Econometrics, 1985, 29(3): 305-325.
- [5] MANN H B, WHITNEY D R. On a test of whether one of two random variables is stochastically larger than the other[J]. The Annals of Mathematical Statistics, 1947, 18(1): 50-60.
- [6] LAWSON C L, HANSON R J. Solving least squares problems[M]. Philadelphia: SIAM, 1995.

- [7] SHANNON C E. A mathematical theory of communication[J]. The Bell System Technical Journal, 1948, 27(3): 379-423.
- [8] FISHER W D. On grouping for maximum homogeneity[J]. Journal of the American Statistical Association, 1958, 53(284): 789-798.
- [9] JENKS G F. The data model concept in statistical mapping[J]. International Yearbook of Cartography, 1967, 7: 186-190.
- [10] LITTLE J D C. Aggregate advertising models: The state of the art[J]. Operations Research, 1979, 27(4): 629-667.
- [11] HANSSENS D M, PARSONS L J, SCHULTZ R L. Market response models: Econometric and time series analysis[M]. 2nd ed. Boston: Kluwer Academic Publishers, 2001.
- [12] FELDMAN J, MUTHUKRISHNAN S, PÁL M, et al. Budget optimization in search-based advertising auctions[C]//Proceedings of the 8th ACM Conference on Electronic Commerce. New York: ACM, 2007: 40-49.
- [13] ZHANG W, ZHANG Y, GAO B, et al. Joint optimization of bid and budget allocation in sponsored search[C]//Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. New York: ACM, 2012: 1177-1185.
- [14] BOYD S, VANDENBERGHE L. Convex optimization[M]. Cambridge: Cambridge University Press, 2004.
- [15] BERTSEKAS D P. Nonlinear programming[M]. 2nd ed. Belmont: Athena Scientific, 1999.
- [16] PATRIKSSON M. A survey on the continuous nonlinear resource allocation problem[J]. European Journal of Operational Research, 2008, 185(1): 1-46.
- [17] DIAMOND S, BOYD S. CVXPY: A Python-embedded modeling language for convex optimization[J]. Journal of Machine Learning Research, 2016, 17(83): 1-5.
- [18] EFRON B, TIBSHIRANI R J. An introduction to the bootstrap[M]. New York: Chapman & Hall, 1993.
- [19] HYNDMAN R J, ATHANASOPOULOS G. Forecasting: Principles and practice[M]. 3rd ed. Melbourne: OTexts, 2021.
- [20] KOENKER R, BASSETT G. Regression quantiles[J]. Econometrica, 1978, 46(1): 33-50.
- [21] GNEITING T, RAFTERY A E. Strictly proper scoring rules, prediction, and estimation[J]. Journal of the American Statistical Association, 2007, 102(477): 359-378.

A 支撑材料文件清单

下表列出支撑材料压缩包内的全部文件（相对路径）及其用途。压缩包内另含 MANIFEST.json, 记录每个文件的 SHA-256。

文件	说明
AI_USAGE.md	AI 工具使用记录（源文件）
AI 工具使用详情.pdf	AI 工具使用详情
MANIFEST.json	支撑材料成员清单与 SHA-256
Makefile	本地快捷命令(只提交云端任务)
README.md	仓库说明与复现入口
REPRODUCE.md	复现说明
UNLICENSE	公有领域声明（Unlicense）
docs/ARCHITECTURE.md	仓库架构与唯一计算面的设计
docs/CONTRIBUTING.md	协作与提交规范
docs/DATA_NOTES.md	数据口径与附件解析约定
docs/ENGINEERING_STANDARD.md	工程标准与门禁定义
docs/MODELING_STANDARD.md	建模与写作标准（审稿清单）
docs/RESULTS.md	本轮结果总览与逐项证据
docs/REVIEW_RESPONSE.md	评审意见的逐条处理说明
docs/RUNBOOK.md	运行手册（完整命令序列与实测用时）
docs/adr/0001-cloud-only-execution.md	工程规范、建模标准、决策记录
docs/adr/0002-stage-run-manifest-model.md	工程规范、建模标准、决策记录
docs/adr/0003-independent-repos-vendored-runtime.md	工程规范、建模标准、决策记录
docs/mdr/0000-template.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0001-data-scope-and-keys.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0002-holiday-calendar-and-regression.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0003-registration-attribution.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0004-classification-benefit-and-thresholds.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0005-response-function.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0006-allocation-model.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0007-expected-position.md	建模决策记录（题意解释、假设、目标与方法的选择理由）

文件	说明
docs/mdr/0008-forecast-and-uncertainty.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0009-verification-protocol.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0010-paper-reporting-conventions.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0011-q4-expected-ranges.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0012-q4-budget-reading-and-coverage.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/0013-sensitivity-design-and-monotonicity.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/mdr/README.md	建模决策记录（题意解释、假设、目标与方法的选择理由）
docs/problem_brief.md	题目要点与交付清单
forge/__init__.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/config.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/context.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/contracts.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/events.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/hashing.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/manifest.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/modal_app.py	云端应用定义（镜像、卷、四种规格的执行函数）
forge/packaging.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/pdfqa.py	云端运行时（阶段执行、清单、契约、排版、打包）
forge/plotting.py	绘图规范（矢量 PDF + 预览 PNG、色板、字体）
forge/runner.py	阶段注册与执行（依赖、清单、错误捕获）

文件	说明
forge/tex.py	云端运行时 (阶段执行、清单、契约、排版、打包)
forge/xlsx.py	从组委会模板生成结果工作簿
manuscript/ai_usage.tex	论文 LaTeX 源码
manuscript/main.tex	论文 LaTeX 源码
manuscript/references.bib	论文 LaTeX 源码
manuscript/sections/00_abstract.tex	论文 LaTeX 源码
manuscript/sections/01_restatement.tex	论文 LaTeX 源码
manuscript/sections/02_analysis.tex	论文 LaTeX 源码
manuscript/sections/03_assumptions.tex	论文 LaTeX 源码
manuscript/sections/04_models.tex	论文 LaTeX 源码
manuscript/sections/04_q1.tex	论文 LaTeX 源码
manuscript/sections/05_q2.tex	论文 LaTeX 源码
manuscript/sections/06_q3.tex	论文 LaTeX 源码
manuscript/sections/07_q4.tex	论文 LaTeX 源码
manuscript/sections/08_validation.tex	论文 LaTeX 源码
manuscript/sections/09_evaluation.tex	论文 LaTeX 源码
manuscript/sections/10_ai_statement.tex	论文 LaTeX 源码
manuscript/sections/ai_usage_body.tex	论文 LaTeX 源码
manuscript/sections/appendix_repro.tex	论文 LaTeX 源码
manuscript/sections/appendix_tables.tex	论文 LaTeX 源码
pipelines/__init__.py	本题建模与求解程序
pipelines/common/__init__.py	通用阶段: 数据接入、门禁、论文、质量检查、打包发布
pipelines/common/stages.py	通用阶段: 数据接入、门禁、论文、质量检查、打包发布
pipelines/common/validation.py	通用阶段: 数据接入、门禁、论文、质量检查、打包发布
pipelines/e/__init__.py	本题建模与求解程序
pipelines/e/allocate.py	问题 3: 可分离凹规划求解与独立校验
pipelines/e/calendar.py	2025 年法定节假日与调休日历
pipelines/e/classify.py	问题 2: 关键词五分类与阈值稳健性
pipelines/e/contracts.py	本题建模与求解程序
pipelines/e/data.py	附件解析、口径统一与派生字段
pipelines/e/eda.py	问题 1: KPI、集中度、日历回归与注册归因

文件	说明
pipelines/e/figures.py	论文图的生成
pipelines/e/forecast.py	问题 4: 滚动回测、区间预测与随机分配
pipelines/e/response.py	关键词响应函数的拟合与标定
pipelines/e/stages.py	本题各阶段的编排
pipelines/e/tables.py	论文表的生成
pyproject.toml	项目元数据与静态检查配置
runs/20260912-041501-ae773aa/allocate/allocation.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/allocate/allocation.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/allocation_audit.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/allocation_summary.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/allocate/allocation_summary.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/baseline_feasibility.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/bootstrap.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/allocate/bootstrap.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/calibration_check.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/cross_unit_counterfactual.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/allocate/cross_unit_counterfactual.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/duplication_exposure.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/events.jsonl	结构化运行日志
runs/20260912-041501-ae773aa/allocate/keyword_parameters.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/allocate/keyword_parameters.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/manifest.json	阶段清单 (输入输出散列、环境、参数)
runs/20260912-041501-ae773aa/allocate/numbers.json	该阶段登记的论文数字宏
runs/20260912-041501-ae773aa/allocate/plan_feb_annual_avg.csv	表格数据 (与 LaTeX 表同源)

文件	说明
runs/20260912-041501-ae773aa/allocate/plan_feb_annual_avg.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/position_models.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/sensitivity.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/allocate/sensitivity.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/allocate/sensitivity_monotonicity.json	阶段数据产物
runs/20260912-041501-ae773aa/allocate/window_budget_alternative.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/allocate/window_budget_alternative.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/classify/axis_diagnostics.json	阶段数据产物
runs/20260912-041501-ae773aa/classify/classification.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/classify/classification.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/classify/classification_by_label.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/classify/classification_by_label.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/classify/classification_check.json	阶段数据产物
runs/20260912-041501-ae773aa/classify/classification_dual_axis.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/classify/classification_dual_axis.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/classify/classification_per_unit.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/classify/classification_per_unit.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/classify/classification_summary.json	阶段数据产物
runs/20260912-041501-ae773aa/classify/engagement_variant.json	阶段数据产物
runs/20260912-041501-ae773aa/classify/events.jsonl	结构化运行日志

文件	说明
runs/20260912-041501-ae773aa/classify/manifest.json	阶段清单（输入输出散列、环境、参数）
runs/20260912-041501-ae773aa/classify/numbers.json	该阶段登记的论文数字宏
runs/20260912-041501-ae773aa/eda/attribution.json	阶段数据产物
runs/20260912-041501-ae773aa/eda/attribution_diagnostics.json	阶段数据产物
runs/20260912-041501-ae773aa/eda/attribution_fit.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/attribution_fit.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/attribution_rates.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/attribution_rates.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/calendar_regression.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/calendar_regression.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/calendar_regression_summary.json	阶段数据产物
runs/20260912-041501-ae773aa/eda/concentration.json	阶段数据产物
runs/20260912-041501-ae773aa/eda/daily_totals.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/daily_totals.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/day_type_profile.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/day_type_profile.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/events.jsonl	结构化运行日志
runs/20260912-041501-ae773aa/eda/keyword_per_unit.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/keyword_per_unit.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/lorenz.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/lorenz.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/manifest.json	阶段清单（输入输出散列、环境、参数）
runs/20260912-041501-ae773aa/eda/numbers.json	该阶段登记的论文数字宏
runs/20260912-041501-ae773aa/eda/optimal_cut.json	阶段数据产物
runs/20260912-041501-ae773aa/eda/unit_daily.csv	表格数据（与 LaTeX 表同源）

文件	说明
runs/20260912-041501-ae773aa/eda/unit_daily.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/unit_kpis.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/unit_kpis.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/eda/unit_response.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/eda/unit_response.parquet	规范化后的输入数据
et	
runs/20260912-041501-ae773aa/figures/events.jsonl	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_all ocation_shift.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_all ocation_shift.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_att ribution.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_att ribution.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_bac ktest.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_bac ktest.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cal endar_effects.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cal endar_effects.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cla ss_thresholds.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cla ss_thresholds.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cos t_benefit.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_cos t_benefit.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_dai ly_series.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_dai ly_series.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_lor enz.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_lor enz.png	论文图(矢量 PDF 与预览 PNG)

文件	说明
runs/20260912-041501-ae773aa/figures/figures/fig_q3_gain.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_q3_gain.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_q4_plan.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_q4_plan.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_q4_units.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_q4_units.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_response_curves.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_response_curves.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_unit_kpis.pdf	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures/fig_unit_kpis.png	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/figures_index.json	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/figures/manifest.json	论文图(矢量 PDF 与预览 PNG)
runs/20260912-041501-ae773aa/forecast/allocation_audit.json	阶段数据产物
runs/20260912-041501-ae773aa/forecast/backtest.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/forecast/backtest.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/backtest_summary.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/forecast/backtest_summary.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/budget_alternatives.json	阶段数据产物
runs/20260912-041501-ae773aa/forecast/budgets.csv	表格数据 (与 LaTeX 表同源)
runs/20260912-041501-ae773aa/forecast/budgets.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/events.jsonl	结构化运行日志
runs/20260912-041501-ae773aa/forecast/joint_relaxation.csv	表格数据 (与 LaTeX 表同源)

文件	说明
runs/20260912-041501-ae773aa/forecast/joint_relaxation.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/keyword_parameters.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/keyword_parameters.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/manifest.json	阶段清单（输入输出散列、环境、参数）
runs/20260912-041501-ae773aa/forecast/numbers.json	该阶段登记的论文数字宏
runs/20260912-041501-ae773aa/forecast/plan.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/plan.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/plan_annual_alert.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/plan_annual_alert.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/plan_by_unit.json	阶段数据产物
runs/20260912-041501-ae773aa/forecast/plan_by_unit_delay.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/plan_by_unit_delay.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/plan_zero_rows.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/plan_zero_rows.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/forecast/unit_forecasts.csv	表格数据（与 LaTeX 表同源）
runs/20260912-041501-ae773aa/forecast/unit_forecasts.parquet	规范化后的输入数据
runs/20260912-041501-ae773aa/ingest/data/附件1__Sheet1.parquet	件 原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/ingest/data/附件1__Sheet2.parquet	件 原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/ingest/data/附件1__Sheet3.parquet	件 原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/ingest/events.jsonl	原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/ingest/inventory.json	原始数据接入结果（散列、题目文本、规范化数据）

文件	说明
runs/20260912-041501-ae773aa/ingest/manifest.json	原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/ingest/problem_text.txt	原始数据接入结果（散列、题目文本、规范化数据）
runs/20260912-041501-ae773aa/lint/events.jsonl	静态检查报告
runs/20260912-041501-ae773aa/lint/lint_report.json	静态检查报告
runs/20260912-041501-ae773aa/lint/manifest.json	静态检查报告
runs/20260912-041501-ae773aa/lint/mypy.txt	静态检查报告
runs/20260912-041501-ae773aa/lint/ruff_check.txt	静态检查报告
runs/20260912-041501-ae773aa/lint/ruff_format.txt	静态检查报告
runs/20260912-041501-ae773aa/qa/events.jsonl	论文与结果文件质量门禁报告
runs/20260912-041501-ae773aa/qa/manifest.json	论文与结果文件质量门禁报告
runs/20260912-041501-ae773aa/qa/qa_report.json	论文与结果文件质量门禁报告
runs/20260912-041501-ae773aa/results/events.jsonl	结果工作簿与求解输出
runs/20260912-041501-ae773aa/results/manifest.json	结果工作簿与求解输出
runs/20260912-041501-ae773aa/results/result2.xlsx	结果工作簿与求解输出
runs/20260912-041501-ae773aa/results/result3.xlsx	结果工作簿与求解输出
runs/20260912-041501-ae773aa/results/result4.xlsx	结果工作簿与求解输出
runs/20260912-041501-ae773aa/results/results_summary.json	结果工作簿与求解输出
runs/20260912-041501-ae773aa/tables/events.jsonl	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/manifest.json	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_attri bution_response.csv	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_attri bution_response.tex	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_backt est.csv	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_backt est.tex	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_calen dar_effects.csv	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_calen dar_effects.tex	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_class _per_unit.csv	论文表（LaTeX 片段与 CSV）
runs/20260912-041501-ae773aa/tables/tables/tab_class _per_unit.tex	论文表（LaTeX 片段与 CSV）

文件	说明
runs/20260912-041501-ae773aa/tables/tables/tab_class_robustness.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_class_robustness.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_class_summary.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_class_summary.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_daily.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_daily.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_sensitivity.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_sensitivity.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_summary.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_summary.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_window_budget.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q3_window_budget.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_daily.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_daily.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_ranges.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_ranges.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_units.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_q4_units.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_unit_kpis.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_unit_kpis.tex	论文表 (LaTeX 片段与 CSV)

文件	说明
runs/20260912-041501-ae773aa/tables/tables/tab_verification.csv	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables/tab_verification.tex	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/tables/tables_index.json	论文表 (LaTeX 片段与 CSV)
runs/20260912-041501-ae773aa/test/coverage.json	测试报告与覆盖率
runs/20260912-041501-ae773aa/test/events.jsonl	测试报告与覆盖率
runs/20260912-041501-ae773aa/test/junit.xml	测试报告与覆盖率
runs/20260912-041501-ae773aa/test/manifest.json	测试报告与覆盖率
runs/20260912-041501-ae773aa/test/pytest.txt	测试报告与覆盖率
runs/20260912-041501-ae773aa/test/test_report.json	测试报告与覆盖率
runs/20260912-041501-ae773aa/validate/data_profile.json	数据契约校验报告与数据画像
runs/20260912-041501-ae773aa/validate/events.jsonl	数据契约校验报告与数据画像
runs/20260912-041501-ae773aa/validate/manifest.json	数据契约校验报告与数据画像
runs/20260912-041501-ae773aa/validate/validation_report.json	数据契约校验报告与数据画像
tests/__init__.py	单元 / 性质 / 集成测试
tests/conftest.py	单元 / 性质 / 集成测试
tests/integration/__init__.py	单元 / 性质 / 集成测试
tests/integration/test_ingest_validate.py	单元 / 性质 / 集成测试
tests/unit/__init__.py	单元 / 性质 / 集成测试
tests/unit/test_config.py	单元 / 性质 / 集成测试
tests/unit/test_contracts.py	单元 / 性质 / 集成测试
tests/unit/test_e_allocate.py	单元 / 性质 / 集成测试
tests/unit/test_e_calendar_data.py	单元 / 性质 / 集成测试
tests/unit/test_e_classify.py	单元 / 性质 / 集成测试
tests/unit/test_e_forecast.py	单元 / 性质 / 集成测试
tests/unit/test_e_review_fixes.py	单元 / 性质 / 集成测试
tests/unit/test_hashing.py	单元 / 性质 / 集成测试
tests/unit/test_manifest.py	单元 / 性质 / 集成测试
tests/unit/test_packaging_tex.py	单元 / 性质 / 集成测试
tests/unit/test_runner.py	单元 / 性质 / 集成测试
tests/unit/test_xlsx.py	单元 / 性质 / 集成测试
tools/__init__.py	本地控制面: 提交云端任务、下载、校验散列
tools/cli.py	本地控制面: 提交云端任务、下载、校验散列

文件	说明
tools/run_local.py	不依赖云端的本地驱动脚本

B 复现记录

论文中的全部数值、表格与图形均由同一次云端运行（run 20260912-041501-ae773aa，代码版本 40f5b6e5167d1986828ea7bf74cd7dab9adc3567，构建日期 2026-09-12）生成。各阶段状态与输出摘要如下。

阶段	状态	用时/s	输出摘要 (SHA-256 前 12 位)
allocate	completed	63.0	724259d703dc
classify	completed	1.0	09b0ee01107b
eda	completed	3.0	de671c38a646
figures	completed	27.0	a50aedf500ef
fmt	completed	1.0	92ad4ecda5f4
forecast	completed	13.0	b7ee2ae20550
ingest	completed	1.0	02e38a853d4c
lint	completed	28.0	ed4b665d3277
package	本表生成后才执行（见第 8 节与发布清单）	0.0	
paper	本表由该阶段渲染，故为 running	0.0	
qa	本表生成后才执行（见第 8 节与发布清单）	0.0	
release	本表生成后才执行（见第 8 节与发布清单）	0.0	
results	completed	2.0	79ce6f23421e
tables	completed	0.0	01fba99d8e19
test	completed	30.0	3cc664cf595d
validate	completed	0.0	8ad89df6a5ec

复现步骤：安装 Modal 客户端并登录后，在仓库根目录依次执行下列命令（可直接复制粘贴；第三条为便于排版而折行，实际为一行）。

```
python3 tools/cli.py provision
python3 tools/cli.py run ingest,validate --new-run
python3 tools/cli.py run eda,classify,allocate,forecast,\
    results,figures,tables --size medium
python3 tools/cli.py run lint,test,paper,qa,package,release
python3 tools/cli.py release --version v1.0.0
```

五条命令依次为：验证云端工具链；接入与契约校验；四个问题的科学阶段与结果、图表；门禁、论文、质检与打包；下载交付物并核对散列。每个阶段目录下的 manifest.json 记录输入输出散列、参数、依赖阶段的输出摘要与环境；events.jsonl 为结构化日志；numbers.json 为该阶段登记的

论文数字。随机性只经 `ctx.seed_everything` 派生（种子见 `configs/default.toml`），同一代码与配置下的重跑得到相同的输出摘要。

独立校验与检验报告：问题三与问题四的分配审计分别为 `allocate/allocation_audit.json` 与 `forecast/allocation_audit.json`；灵敏度单调性门禁为 `allocate/sensitivity_monotonicity.json`；基线占优核对为 `allocate/baseline_feasibility.json`；两层分解的联合松弛界为 `forecast/joint_relaxation.csv`；分类复核为 `classify/classification_check.json`；回测明细为 `forecast/backtest.csv`。备选口径的完整方案为 `allocate/plan_feb_annual_avg.csv` 与 `forecast/plan_annual_alt.csv`。

关于上表的自指性：本表由 `paper` 阶段在其自身运行过程中渲染，因此 `paper` 自身只能记为 `running`；`qa`、`package` 与 `release` 依赖 `paper`，在本表生成之后才执行，其状态不在此处给出（门禁结论见第 8 节，交付物散列见 `releases/v1.0.0/release_manifest.json`）。其余阶段的状态、用时与输出摘要均为最终值。

C 补充表格

本附录收录正文引用的大表：各推广单元的关键词类别分布（问题二）、两个窗口的逐日分配结果与灵敏度分析（问题三）以及滚动回测的完整指标（问题四）。

表 16 各推广单元的关键词类别分布（问题二）

推广单元 ID	黄金词	重点词	潜力词	问题词	无效词	合计
1841014603	0	8	24	3	41	76
2526158329	0	0	14	0	12	26
2874903000	0	9	46	5	12	72
4190988309	2	2	14	1	28	47
4190988310	1	15	27	2	28	73
8878077181	0	4	0	0	0	4
9628223555	2	44	187	14	117	364
9630806627	3	85	187	6	161	442
9657930100	0	28	10	1	6	45
9700005700	0	5	6	0	6	17
9773660250	0	3	2	0	1	6
9811363528	32	68	460	17	478	1,055

D 完整程序

以下按文件收录建模、求解、检验、绘图、排版与打包的全部源程序，文件名与附录 A 一致。运行方式见附录 B。

Makefile

```
1 # Thin wrappers over tools/cli.py. Nothing here computes locally.
2 PY ?= python3
3 CLI := $(PY) tools/cli.py
4 STAGE ?= ingest
5 SIZE ?= small
6 RUN ?=
```

表 17 问题三两个窗口的逐日汇总：预算、实际点击、按历史比例与最优的预期点击和注册、均匀分配的预期注册及提升

日期	单元数	预算/元	实际点击	历史比例点击	最优点击	历史比例注册	均匀注册	最优注册	提升/%
2025-08-01	11	5,722.9	6,942	3,828.4	4,710.6	300.1	239.1	425.1	41.6
2025-08-02	12	5,515.8	6,480	3,650.0	4,537.0	293.8	237.5	420.6	43.1
2025-08-03	11	2,422.2	2,003	1,425.6	1,597.5	99.2	66.6	117.2	18.1
2025-08-04	11	2,364.3	1,912	1,380.7	1,550.6	97.0	65.3	116.5	20.1
2025-08-05	11	4,530.6	3,797	2,956.9	3,312.5	193.5	134.6	230.4	19.0
2025-08-06	12	5,300.0	4,827	3,785.1	4,273.8	248.4	169.9	302.5	21.8
2025-08-07	11	5,703.8	4,919	3,913.9	4,422.0	258.5	175.6	314.5	21.6
2025-08-08	12	5,924.1	4,932	3,844.1	4,314.8	257.4	175.4	310.7	20.7
2025-02-01	2	803.0	313	393.6	450.6	27.4	16.2	31.4	14.4
2025-02-02	2	1,155.0	479	462.8	527.9	32.6	19.3	37.1	13.9
2025-02-03	2	1,403.3	586	536.4	600.3	40.0	23.9	44.6	11.6
2025-02-04	2	1,806.4	739	750.2	838.5	55.8	33.4	62.2	11.5
2025-02-05	2	2,007.8	834	1,010.7	1,128.7	75.1	44.9	83.7	11.4
2025-02-06	2	2,044.0	785	1,050.8	1,172.3	78.3	46.8	87.1	11.3
2025-02-07	2	2,523.3	998	1,174.0	1,303.3	83.9	49.9	94.3	12.5
2025-02-08	2	1,938.3	921	956.8	1,076.7	66.6	39.5	76.0	14.0

```
7 RUNFLAG := $(if $(RUN),--run-id $(RUN),)
8 FORCEFLAG := $(if $(FORCE),--force,)
9
10 .PHONY: fmt help provision run pipeline exec status logs runs download release lint test paper qa package smoke
11
12 help:
13     @echo "make provision          # verify cloud toolchain"
14     @echo "make run STAGE=q1 SIZE=medium # run one stage (RUN=<id> to continue a run, FORCE=1 to rerun)"
15     @echo "make pipeline          # ingest,validate,lint,test in one container"
16     @echo "make status | logs STAGE=q1 | runs | download STAGE=results"
17     @echo "make paper | qa | package | release VERSION=v1.0.0"
18
19 provision:
20     $(CLI) provision
21
22 run:
23     $(CLI) run $(STAGE) $(RUNFLAG) --size $(SIZE) $(FORCEFLAG)
24
25 pipeline:
26     $(CLI) run ingest,validate,lint,test $(RUNFLAG) --size $(SIZE) $(FORCEFLAG)
27
28 exec:
29     $(CLI) exec --code '$(CODE)' $(RUNFLAG)
30
31 status:
32     $(CLI) status $(RUNFLAG)
33
34 logs:
35     $(CLI) logs $(STAGE) $(RUNFLAG)
36
37 runs:
38     $(CLI) runs
39
40 download:
41     $(CLI) download $(RUNFLAG) $(if $(STAGE),--stage $(STAGE),)
```

表 18 问题三的灵敏度分析：不同建模选择下最优分配相对历史比例的预期注册提升

情形	窗口	最优注册/人	历史比例注册/人	提升/%	平均入选词	名义松弛
基准	2 月	516.4	459.6	12.4	20.4	
基准	8 月	2237.4	1748.0	28.0	21.7	
上限倍数 2	2 月	507.2	459.6	10.3	34.8	
上限倍数 2	8 月	2064.5	1748.0	18.1	27.2	
上限倍数 8	2 月	517.9	459.6	12.7	18.1	是
上限倍数 8	8 月	2342.7	1748.0	34.0	17.3	是
弹性 $\gamma \times 0.9$	2 月	517.3	474.6	9.0	21.2	
弹性 $\gamma \times 0.9$	8 月	2111.6	1733.3	21.8	20.9	
弹性 $\gamma \times 1.1$	2 月	523.0	445.4	17.4	20.9	
弹性 $\gamma \times 1.1$	8 月	2411.9	1768.6	36.4	23.4	
预算 -20%	2 月	441.9	392.8	12.5	17.5	
预算 -20%	8 月	1925.7	1472.7	30.8	19.1	
预算 +20%	2 月	585.7	522.6	12.1	25.3	
预算 +20%	8 月	2519.6	2011.2	25.3	23.6	
剔除问题词	2 月	516.4	459.6	12.4	20.4	
剔除问题词	8 月	2237.2	1748.0	28.0	21.5	
问题词不降上限	2 月	516.4	459.6	12.4	20.4	是
问题词不降上限	8 月	2237.5	1748.0	28.0	21.7	是
最小投放 0（上限同基准）	2 月	516.5	459.6	12.4	143.0	是
最小投放 0（上限同基准）	8 月	2240.0	1748.0	28.1	116.8	是
最小投放 0（上限随之收缩）	2 月	516.1	459.6	12.3	143.0	
最小投放 0（上限随之收缩）	8 月	2197.4	1748.0	25.7	116.8	
跳出率因子 $\kappa = 1$	2 月	513.6	459.6	11.8	35.2	
跳出率因子 $\kappa = 1$	8 月	2216.4	1746.8	26.9	32.1	
κ 截断 [0.5, 2]	2 月	515.9	460.3	12.1	21.9	
κ 截断 [0.5, 2]	8 月	2240.7	1762.5	27.1	23.1	
重复词只留最优副本	2 月	516.4	459.8	12.3	20.9	
重复词只留最优副本	8 月	2159.9	1732.9	24.6	25.5	

```

42
43 lint:
44     $(CLI) run lint $(RUNFLAG) $(FORCEFLAG)
45
46 test:
47     $(CLI) run test $(RUNFLAG) $(FORCEFLAG)
48
49 paper:
50     $(CLI) run paper $(RUNFLAG) --size $(SIZE) $(FORCEFLAG)
51
52 qa:
53     $(CLI) run qa $(RUNFLAG) $(FORCEFLAG)
54
55 package:
56     $(CLI) run package $(RUNFLAG) $(FORCEFLAG)
57
58 release:
59     $(CLI) run release $(RUNFLAG) $(FORCEFLAG) && $(CLI) release --version $(VERSION) $(RUNFLAG) --force
60
61 smoke:
62     $(CLI) run ingest,validate,lint,test,paper,qa,package,release --new-run --param require_results=false --param

```

表 19 滚动回测（12 个起点 × 7 天，12 个单元）：各目标在变换尺度上的 MAE、RMSE、pinball 损失与 80% 区间覆盖率

目标	模型	MAE	RMSE	Pinball(0.1+0.9)	80% 覆盖率/%
log 点击量	日历回归（残差区间）	0.4805	0.5680	0.253	87.3
log 点击量	日历回归（部署区间）	0.4805	0.5680	0.311	92.1
log 点击量	28 日均值	0.5772	0.6606	0.237	74.0
log 点击量	季节朴素	0.4796	0.5811	0.304	90.2
log CPC	日历回归（残差区间）	0.2932	0.3275	0.199	81.8
log CPC	日历回归（部署区间）	0.2932	0.3275	0.201	88.5
log CPC	28 日均值	0.2426	0.2632	0.166	63.6
log CPC	季节朴素	0.2525	0.2894	0.191	88.7
效率乘子 $\log \varepsilon$	日历回归（残差区间）	0.2361	0.2677	0.157	81.3
效率乘子 $\log \varepsilon$	日历回归（部署区间）	0.2361	0.2677	0.159	86.8
效率乘子 $\log \varepsilon$	28 日均值	0.1874	0.2109	0.113	68.8
效率乘子 $\log \varepsilon$	季节朴素	0.2142	0.2445	0.140	90.1
logit CTR	日历回归（残差区间）	0.4368	0.5163	0.272	78.9
logit CTR	日历回归（部署区间）	0.4368	0.5163	0.294	87.9
logit CTR	28 日均值	0.2710	0.3193	0.129	80.3
logit CTR	季节朴素	0.3048	0.3704	0.179	91.2
logit 首位占比	日历回归（残差区间）	0.5841	0.6783	0.347	84.5
logit 首位占比	日历回归（部署区间）	0.5841	0.6783	0.387	90.7
logit 首位占比	28 日均值	0.4057	0.4637	0.167	72.3
logit 首位占比	季节朴素	0.4445	0.5293	0.240	91.0
logit 上方位占比	日历回归（残差区间）	0.6403	0.7270	0.394	78.3
logit 上方位占比	日历回归（部署区间）	0.6403	0.7270	0.408	87.5
logit 上方位占比	28 日均值	0.4521	0.5136	0.240	70.2
logit 上方位占比	季节朴素	0.4834	0.5627	0.285	90.2

```
↪ allow_missing_results=true
63
64 fmt:
65     $(CLI) fmt $(RUNFLAG)
```

configs/default.toml

```
1 # Forge 运行时配置（默认档）。Stage 代码通过 ctx.cfg("a.b.c") 读取；
2 # `--profile <name>` 会叠加 configs/<name>.toml；`--param config_overrides='{...}'` 可临时覆盖。
3
4 [run]
5 seed = 20260912
6
7 [gates]
8 lint_required = ["ruff_check", "ruff_format", "mypy"]
9 mypy_paths = ["forge"]
10
11 [paper]
12 main = "main.tex"
13 # 需在同一 run 中已完成的 stage；其 tables/*.tex 与 figures/*.pdf/png 会被并入排版
14 sources = ["figures", "tables"]
15 max_body_pages = 30
16 max_overfull_pt = 20.0
```

```

17 code_globs = [
18     "forge/**/*.py", "pipelines/**/*.py", "tools/**/*.py", "tests/**/*.py",
19     "configs/*.toml", "configs/*.json", "Makefile", "pyproject.toml",
20 ]
21
22 [qa]
23 required_stages = ["lint", "test"]
24 results_stage = "results"
25 require_results = true
26 identity_denylist = [] # 硬门禁（正则）：出现即失败
27 identity_watchlist = ["大学", "学院", "赛区", "队号", "指导教师", "[\\w.-]+@[\\w.-]+\\.\\w+"] # 软提示：写入报告供复核
28
29 [package]
30 stages = ["ingest", "validate", "eda", "classify", "allocate", "forecast", "results", "figures", "tables", "lint", "
    ↪ test", "qa"]
31 code_globs = [
32     "forge/**/*.py", "pipelines/**/*.py", "tools/**/*.py", "tests/**/*.py", "configs/**",
33     "manuscript/**/*.tex", "manuscript/**/*.bib", "docs/**/*.md", "Makefile", "pyproject.toml",
34     "README.md", "UNLICENSE", "AI_USAGE.md",
35 ]
36 max_bytes = 20971520
37
38 [release]
39 paper_name = "论文.pdf"
40
41 [classify]
42 methods = ["jenks", "median", "gmm"] # threshold methods on log10(cost) and on the benefit index
43 main_method = "jenks" # reported labels; the others are robustness checks
44
45 [allocate]
46 cap_multiplier = 4.0 # daily spend cap per keyword = multiplier x mean daily spend
47 min_spend = 0.5 # yuan; smaller allocations mean the keyword is not selected
48 problem_cap_factor = 0.5 # 问题词 keep only half of the normal cap
49 bootstrap = 100 # elasticity bootstrap draws for the improvement interval
50
51 [forecast]
52 scenarios = 500 # Monte Carlo scenarios per unit-day for expected ranges

```

configs/project.json

```

1 {
2     "letter": "E",
3     "package": "e",
4     "slug": "sem-advertising",
5     "title": "SEM 广告投放策略",
6     "app": "cumcm2026-e-sem-advertising",
7     "volume": "cumcm2026-e-artifacts",
8     "problem_pdf": "E题.pdf",
9     "attachments_dir": "附件",
10    "templates_dir": "附件/附件2",
11    "result_files": [
12        "result2.xlsx",
13        "result3.xlsx",
14        "result4.xlsx"
15    ],
16    "github_repo": "cumcm2026-e-sem-advertising"
17 }

```

forge/__init__.py

```
1 """Forge — cloud-only research engineering runtime (CUMCM 2026).
2
3 Every computation (data parsing, modelling, solving, tests, figures, LaTeX, PDF QA,
4 packaging) runs inside Modal. The local machine only edits text, drives git,
5 submits jobs, downloads artifacts and verifies transport hashes.
6 """
7
8 __version__ = "1.0.0"
```

forge/config.py

```
1 """TOML configuration with profile overlays and dotted access."""
2
3 from __future__ import annotations
4
5 import json
6 import tomllib
7 from pathlib import Path
8 from typing import Any
9
10 from .hashing import sha256_json
11
12 _MISSING = object()
13
14
15 def deep_merge(base: dict[str, Any], override: dict[str, Any]) -> dict[str, Any]:
16     out = dict(base)
17     for key, value in override.items():
18         if isinstance(value, dict) and isinstance(out.get(key), dict):
19             out[key] = deep_merge(out[key], value)
20         else:
21             out[key] = value
22     return out
23
24
25 class Config:
26     """Read-only dotted-access view over a merged configuration mapping."""
27
28     def __init__(self, data: dict[str, Any]) -> None:
29         self._data = json.loads(json.dumps(data))
30
31     def get(self, key: str, default: Any = None) -> Any:
32         cursor: Any = self._data
33         for part in key.split("."):
34             if not isinstance(cursor, dict) or part not in cursor:
35                 return default
36             cursor = cursor[part]
37         return cursor
38
39     def __getitem__(self, key: str) -> Any:
40         value = self.get(key, _MISSING)
41         if value is _MISSING:
42             raise KeyError(key)
43         return value
44
45     def section(self, key: str) -> dict[str, Any]:
46         value = self.get(key, {})
47         return dict(value) if isinstance(value, dict) else {}
48
```

```

49     def as_dict(self) -> dict[str, Any]:
50         return json.loads(json.dumps(self._data))
51
52     @property
53     def digest(self) -> str:
54         return sha256_json(self._data)
55
56
57 def load_project(repo: Path) -> dict[str, Any]:
58     return json.loads((repo / "configs" / "project.json").read_text(encoding="utf-8"))
59
60
61 def load_config(repo: Path, profile: str | None = None, overrides: dict[str, Any] | None = None) -> Config:
62     data = tomlib.loads((repo / "configs" / "default.toml").read_text(encoding="utf-8"))
63     if profile:
64         data = deep_merge(data, tomlib.loads((repo / "configs" / f"{profile}.toml").read_text(encoding="utf-8")))
65     if overrides:
66         data = deep_merge(data, overrides)
67     return Config(data)

```

forge/context.py

```

1  """Stage execution context: paths, config, params, logging, seeds and paper numbers."""
2
3  from __future__ import annotations
4
5  import json
6  import random
7  import re
8  import zlib
9  from pathlib import Path
10 from typing import Any
11
12 from .config import Config, load_config, load_project
13 from .events import EventLogger
14
15 _NUMBER_KEY = re.compile(r"^[A-Za-z]+$")
16
17
18 class StageContext:
19     """Everything a stage needs. Stages must write only under ``stage_dir``."""
20
21     def __init__(self, run_id: str, stage: str, params: dict[str, Any], repo: Path, vol: Path) -> None:
22         self.run_id = run_id
23         self.stage = stage
24         self.params = dict(params)
25         self.repo = repo
26         self.vol = vol
27         self.project = load_project(repo)
28         overrides = self.params.get("config_overrides") or None
29         self.config: Config = load_config(repo, self.params.get("profile"), overrides)
30         self.run_dir = vol / "runs" / run_id
31         self.stage_dir = self.run_dir / stage
32         self.stage_dir.mkdir(parents=True, exist_ok=True)
33         self.log = EventLogger(self.stage_dir / "events.jsonl", run_id, stage)
34         self._numbers: dict[str, str] = {}
35
36     # ---- raw inputs (immutable, at repo root, exactly as delivered by the organisers) ----
37     @property
38     def problem_pdf(self) -> Path:
39         return self.repo / self.project["problem_pdf"]

```

```

40
41 @property
42 def attachments(self) -> Path:
43     return self.repo / self.project["attachments_dir"]
44
45 @property
46 def templates(self) -> Path:
47     return self.repo / self.project["templates_dir"]
48
49 # ---- outputs ----
50 def out(self, *parts: str) -> Path:
51     path = self.stage_dir.joinpath(*parts)
52     path.parent.mkdir(parents=True, exist_ok=True)
53     return path
54
55 def dep(self, stage: str) -> Path:
56     """Directory of a completed dependency stage in the same run (raises otherwise)."""
57     directory = self.run_dir / stage
58     manifest = directory / "manifest.json"
59     if not manifest.exists():
60         raise RuntimeError(f"dependency stage '{stage}' has not run in run {self.run_id}")
61     status = json.loads(manifest.read_text(encoding="utf-8")).get("status")
62     if status != "completed":
63         raise RuntimeError(f"dependency stage '{stage}' has status {status!r} in run {self.run_id}")
64     return directory
65
66 def has_stage(self, stage: str) -> bool:
67     manifest = self.run_dir / stage / "manifest.json"
68     return manifest.exists() and json.loads(manifest.read_text(encoding="utf-8")).get("status") == "completed"
69
70 def dep_data(self, stage: str, name: str) -> Any:
71     return json.loads((self.dep(stage) / name).read_text(encoding="utf-8"))
72
73 # ---- parameters / configuration ----
74 def param(self, key: str, default: Any = None) -> Any:
75     return self.params.get(key, default)
76
77 def cfg(self, key: str, default: Any = None) -> Any:
78     return self.config.get(key, default)
79
80 # ---- determinism ----
81 def seed(self, salt: str = "") -> int:
82     base = int(self.cfg("run.seed", 0))
83     return (base + zlib.crc32(salt.encode("utf-8"))) % (2**31 - 1)
84
85 def seed_everything(self, salt: str = "") -> int:
86     value = self.seed(salt)
87     random.seed(value)
88     try:
89         import numpy as np
90
91         np.random.seed(value) # noqa: NPY002 - legacy global RNG used by third-party libraries
92     except ImportError: # pragma: no cover
93         pass
94     self.log.info("seed", salt=salt, value=value)
95     return value
96
97 # ---- numbers that flow into the paper as \val<Key> macros ----
98 def number(self, key: str, value: Any, fmt: str | None = None) -> str:
99     if not _NUMBER_KEY.match(key):
100         raise ValueError(f"paper number keys must be letters only (TeX macro names); got {key!r}")
101     if fmt is not None:
102         text = format(value, fmt)

```

```

103         elif isinstance(value, bool):
104             text = str(value)
105         elif isinstance(value, int):
106             text = str(value)
107         elif isinstance(value, float):
108             text = f"{value:.4f}"
109         else:
110             text = str(value)
111         self._numbers[key] = text
112         return text
113
114     def flush_numbers(self) -> None:
115         if not self._numbers:
116             return
117         path = self.stage_dir / "numbers.json"
118         merged: dict[str, str] = {}
119         if path.exists():
120             merged.update(json.loads(path.read_text(encoding="utf-8")))
121         merged.update(self._numbers)
122         path.write_text(json.dumps(merged, ensure_ascii=False, indent=2, sort_keys=True), encoding="utf-8")
123
124     # ---- json helpers ----
125     def write_json(self, name: str, obj: Any) -> Path:
126         path = self.out(name)
127         path.write_text(json.dumps(obj, ensure_ascii=False, indent=2, default=str), encoding="utf-8")
128         return path
129
130     def read_json(self, path: Path) -> Any:
131         return json.loads(path.read_text(encoding="utf-8"))

```

forge/contracts.py

```

1  """Lightweight DataFrame contracts (schema + range + monotonicity + custom checks)."""
2
3  from __future__ import annotations
4
5  import re
6  from collections.abc import Callable
7  from dataclasses import dataclass
8  from typing import Any
9
10 import numpy as np
11 import pandas as pd
12
13
14 @dataclass(frozen=True)
15 class Column:
16     name: str
17     kind: str = "any" # int | float | number | str | datetime | any
18     nullable: bool = False
19     min: float | None = None
20     max: float | None = None
21     regex: str | None = None
22     unique: bool = False
23     monotonic: str | None = None # increasing | non_decreasing | decreasing | non_increasing
24     allowed: tuple[Any, ...] | None = None
25     step: float | None = None # constant difference between consecutive values
26
27
28 @dataclass(frozen=True)
29 class FrameContract:

```

```

30     name: str
31     columns: tuple[Column, ...]
32     min_rows: int = 1
33     max_rows: int | None = None
34     extra_columns: str = "forbid" # forbid | allow
35     checks: tuple[Callable[[pd.DataFrame], list[str]], ...] = ()
36
37
38 def normalise_columns(df: pd.DataFrame) -> pd.DataFrame:
39     out = df.copy()
40     out.columns = pd.Index([str(c).strip() for c in out.columns])
41     return out
42
43
44 def validate_frame(df: pd.DataFrame, contract: FrameContract) -> dict[str, Any]:
45     df = normalise_columns(df)
46     errors: list[str] = []
47     warnings: list[str] = []
48     expected = [c.name for c in contract.columns]
49     missing = [c for c in expected if c not in df.columns]
50     extra = [c for c in df.columns if c not in expected]
51     if missing:
52         errors.append(f"missing columns: {missing}")
53     if extra and contract.extra_columns == "forbid":
54         errors.append(f"unexpected columns: {extra}")
55     n = len(df)
56     if n < contract.min_rows:
57         errors.append(f"rows {n} < min_rows {contract.min_rows}")
58     if contract.max_rows is not None and n > contract.max_rows:
59         errors.append(f"rows {n} > max_rows {contract.max_rows}")
60
61     for col in contract.columns:
62         if col.name not in df.columns:
63             continue
64         series = df[col.name]
65         nulls = int(series.isna().sum())
66         if nulls and not col.nullable:
67             errors.append(f"{col.name}: {nulls} null values")
68         values = series.dropna()
69         if col.kind in {"int", "float", "number"}:
70             numeric = pd.to_numeric(values, errors="coerce")
71             bad = int(numeric.isna().sum())
72             if bad:
73                 errors.append(f"{col.name}: {bad} non-numeric values")
74             numeric = numeric.dropna().astype(float)
75             if col.kind == "int" and len(numeric) and not np.all(np.mod(numeric.to_numpy(), 1) == 0):
76                 errors.append(f"{col.name}: non-integer values present")
77             if col.min is not None and len(numeric) and float(numeric.min()) < col.min:
78                 errors.append(f"{col.name}: min {numeric.min()} < {col.min}")
79             if col.max is not None and len(numeric) and float(numeric.max()) > col.max:
80                 errors.append(f"{col.name}: max {numeric.max()} > {col.max}")
81             if col.monotonic and len(numeric) > 1:
82                 diff = np.diff(numeric.to_numpy())
83                 ok = {
84                     "increasing": bool((diff > 0).all()),
85                     "non_decreasing": bool((diff >= 0).all()),
86                     "decreasing": bool((diff < 0).all()),
87                     "non_increasing": bool((diff <= 0).all()),
88                 }[col.monotonic]
89                 if not ok:
90                     errors.append(f"{col.name}: not {col.monotonic}")
91             if col.step is not None and len(numeric) > 1:
92                 diff = np.diff(numeric.to_numpy())

```

```

93         if not np.allclose(diff, col.step):
94             errors.append(f"{col.name}: step is not constant {col.step} (min {diff.min()}, max {diff.max()}")
95     elif col.kind == "str":
96         if col.regex:
97             pattern = re.compile(col.regex)
98             bad_values = [str(v) for v in values.astype(str) if not pattern.fullmatch(str(v))]
99             if bad_values:
100                 errors.append(f"{col.name}: {len(bad_values)} values violate {col.regex}/, e.g. {bad_values[:3]}")
101     elif col.kind == "datetime":
102         parsed = pd.to_datetime(values, errors="coerce")
103         bad = int(parsed.isna().sum())
104         if bad:
105             errors.append(f"{col.name}: {bad} unparsable datetimes")
106     if col.unique and values.duplicated().any():
107         errors.append(f"{col.name}: {int(values.duplicated().sum())} duplicated values")
108     if col.allowed is not None:
109         unexpected = sorted(set(values.unique()) - set(col.allowed), key=str)
110         if unexpected:
111             errors.append(f"{col.name}: values outside allowed set: {unexpected[:5]}")
112
113     for check in contract.checks:
114         try:
115             errors.extend(check(df))
116         except Exception as exc:
117             errors.append(f"check {getattr(check, '__name__', check)!r} raised {exc!r}")
118
119     return {
120         "contract": contract.name,
121         "ok": not errors,
122         "rows": n,
123         "columns": list(df.columns),
124         "errors": errors,
125         "warnings": warnings,
126     }

```

forge/events.py

```

1  """Structured JSONL event logging with a human-readable mirror on stdout."""
2
3  from __future__ import annotations
4
5  import json
6  import time
7  from datetime import UTC, datetime
8  from pathlib import Path
9  from typing import Any
10
11
12  def _short(value: Any, limit: int = 200) -> str:
13      text = value if isinstance(value, str) else json.dumps(value, ensure_ascii=False, default=str)
14      return text if len(text) <= limit else text[: limit - 1] + "..."
15
16
17  class EventLogger:
18      """Append-only event stream: one JSON object per line, mirrored to stdout."""
19
20      def __init__(self, path: Path, run_id: str, stage: str) -> None:
21          path.parent.mkdir(parents=True, exist_ok=True)
22          self._fh = path.open("a", encoding="utf-8")
23          self.path = path
24          self.run_id = run_id

```

```

25     self.stage = stage
26     self._t0 = time.monotonic()
27
28     def emit(self, event: str, level: str = "info", **fields: Any) -> None:
29         record = {
30             "ts": datetime.now(UTC).isoformat(timespec="milliseconds"),
31             "elapsed_s": round(time.monotonic() - self._t0, 3),
32             "run_id": self.run_id,
33             "stage": self.stage,
34             "level": level,
35             "event": event,
36             **fields,
37         }
38         self._fh.write(json.dumps(record, ensure_ascii=False, default=str) + "\n")
39         self._fh.flush()
40         extra = " ".join(f"{k}={_short(v)}" for k, v in fields.items())
41         print(f"[{record['elapsed_s']:9.3f}s] {level.upper():5s} {self.stage}:{event} {extra}", flush=True)
42
43     def info(self, event: str, **fields: Any) -> None:
44         self.emit(event, "info", **fields)
45
46     def warn(self, event: str, **fields: Any) -> None:
47         self.emit(event, "warn", **fields)
48
49     def error(self, event: str, **fields: Any) -> None:
50         self.emit(event, "error", **fields)
51
52     def metric(self, name: str, value: Any, **fields: Any) -> None:
53         self.emit("metric", "info", name=name, value=value, **fields)
54
55     def close(self) -> None:
56         if not self._fh.closed:
57             self._fh.close()

```

forge/hashing.py

```

1  """Content hashing helpers (SHA-256 everywhere; JSON hashed in canonical form)."""
2
3  from __future__ import annotations
4
5  import hashlib
6  import json
7  from collections.abc import Iterable
8  from pathlib import Path
9  from typing import Any
10
11  CHUNK = 1 << 20
12
13
14  def sha256_file(path: Path) -> str:
15     h = hashlib.sha256()
16     with path.open("rb") as fh:
17         for chunk in iter(lambda: fh.read(CHUNK), b""):
18             h.update(chunk)
19     return h.hexdigest()
20
21
22  def sha256_bytes(data: bytes) -> str:
23     return hashlib.sha256(data).hexdigest()
24
25

```

```

26 def sha256_json(obj: Any) -> str:
27     payload = json.dumps(obj, sort_keys=True, ensure_ascii=False, separators=(",", ":"), default=str)
28     return sha256_bytes(payload.encode("utf-8"))
29
30
31 def hash_tree(root: Path, ignore: Iterable[str] = ()) -> dict[str, dict[str, Any]]:
32     """Return ``{relative_posix_path: {"sha256": ..., "bytes": ...}}`` for every file under ``root``.
33
34     Any path component contained in ``ignore`` excludes the file (directory names or file names).
35     The result is sorted by path so that its canonical JSON digest is stable.
36     """
37     ignored = set(ignore)
38     out: dict[str, dict[str, Any]] = {}
39     if not root.exists():
40         return out
41     for path in sorted(root.rglob("*")):
42         if not path.is_file():
43             continue
44         rel = path.relative_to(root)
45         if ignored & set(rel.parts):
46             continue
47         out[rel.as_posix()] = {"sha256": sha256_file(path), "bytes": path.stat().st_size}
48     return out
49
50
51 def tree_digest(tree: dict[str, dict[str, Any]]) -> str:
52     return sha256_json({k: v["sha256"] for k, v in sorted(tree.items())})

```

forge/manifest.py

```

1  """Run/stage manifests: the unit of lineage, reproducibility and audit."""
2
3  from __future__ import annotations
4
5  import importlib.metadata
6  import json
7  import os
8  import platform
9  import sys
10 import traceback
11 from dataclasses import asdict, dataclass, field, fields
12 from datetime import UTC, datetime
13 from pathlib import Path
14 from typing import Any
15
16 from .hashing import hash_tree, tree_digest
17
18 TRACKED_PACKAGES = (
19     "numpy",
20     "scipy",
21     "pandas",
22     "pyarrow",
23     "openpyxl",
24     "matplotlib",
25     "scikit-learn",
26     "statsmodels",
27     "ortools",
28     "highspy",
29     "numba",
30     "cvxpy",
31     "networkx",

```

```

32     "pymupdf",
33     "pytest",
34     "hypothesis",
35     "ruff",
36     "mypy",
37 )
38 RECORD_FILES = ("manifest.json", "events.jsonl") # run records, excluded from the outputs digest
39
40
41 def utc_now() -> str:
42     return datetime.now(UTC).isoformat(timespec="seconds")
43
44
45 def runtime_info() -> dict[str, Any]:
46     packages: dict[str, str] = {}
47     for name in TRACKED_PACKAGES:
48         try:
49             packages[name] = importlib.metadata.version(name)
50         except importlib.metadata.PackageNotFoundError:
51             continue
52     return {
53         "python": sys.version.split()[0],
54         "platform": platform.platform(),
55         "cpu_count": os.cpu_count(),
56         "modal_task_id": os.getenv("MODAL_TASK_ID"),
57         "modal_is_remote": os.getenv("MODAL_IS_REMOTE") == "1" or os.getenv("MODAL_TASK_ID") is not None,
58         "packages": packages,
59         "env": {k: os.environ.get(k) for k in ("OMP_NUM_THREADS", "OPENBLAS_NUM_THREADS", "PYTHONHASHSEED")},
60     }
61
62
63 @dataclass
64 class Manifest:
65     schema: str = "forge.manifest/1"
66     run_id: str = ""
67     stage: str = ""
68     status: str = "running" # running | completed | failed
69     started_at: str = field(default_factory=utc_now)
70     finished_at: str | None = None
71     duration_s: float | None = None
72     code_ref: dict[str, Any] = field(default_factory=dict)
73     params: dict[str, Any] = field(default_factory=dict)
74     config_digest: str = ""
75     deps: dict[str, str] = field(default_factory=dict)
76     inputs: dict[str, dict[str, Any]] = field(default_factory=dict)
77     outputs: dict[str, dict[str, Any]] = field(default_factory=dict)
78     outputs_digest: str = ""
79     metrics: dict[str, Any] = field(default_factory=dict)
80     runtime: dict[str, Any] = field(default_factory=dict)
81     error: dict[str, Any] | None = None
82
83     @classmethod
84     def start(
85         cls,
86         run_id: str,
87         stage: str,
88         params: dict[str, Any],
89         code_ref: dict[str, Any],
90         config_digest: str,
91         deps: dict[str, str],
92         inputs: dict[str, dict[str, Any]],
93     ) -> Manifest:
94         manifest = cls(

```

```

95         run_id=run_id,
96         stage=stage,
97         params=params,
98         code_ref=code_ref,
99         config_digest=config_digest,
100         deps=deps,
101         inputs=inputs,
102     )
103     manifest.runtime = runtime_info()
104     return manifest
105
106 def complete(self, stage_dir: Path, metrics: dict[str, Any]) -> None:
107     self.outputs = hash_tree(stage_dir, ignore=RECORD_FILES)
108     self.outputs_digest = tree_digest(self.outputs)
109     self.metrics = json.loads(json.dumps(metrics, default=str))
110     self.status = "completed"
111     self._finish()
112
113 def fail(self, exc: BaseException) -> None:
114     self.error = {"type": type(exc).__name__, "message": str(exc), "traceback": traceback.format_exc()}
115     self.status = "failed"
116     self._finish()
117
118 def _finish(self) -> None:
119     self.finished_at = utc_now()
120     started = datetime.fromisoformat(self.started_at)
121     self.duration_s = round((datetime.fromisoformat(self.finished_at) - started).total_seconds(), 3)
122
123 def write(self, path: Path) -> None:
124     path.parent.mkdir(parents=True, exist_ok=True)
125     path.write_text(json.dumps(asdict(self), ensure_ascii=False, indent=2, default=str), encoding="utf-8")
126
127 @classmethod
128 def read(cls, path: Path) -> Manifest:
129     raw = json.loads(path.read_text(encoding="utf-8"))
130     known = {f.name for f in fields(cls)}
131     return cls(**{k: v for k, v in raw.items() if k in known})
132
133 def verify_outputs(self, stage_dir: Path) -> list[str]:
134     """Return a list of mismatches between the manifest and the files on disk (empty == verified)."""
135     problems: list[str] = []
136     current = hash_tree(stage_dir, ignore=RECORD_FILES)
137     for rel, meta in self.outputs.items():
138         if rel not in current:
139             problems.append(f"missing: {rel}")
140         elif current[rel]["sha256"] != meta["sha256"]:
141             problems.append(f"sha256 mismatch: {rel}")
142     for rel in current:
143         if rel not in self.outputs:
144             problems.append(f"unexpected file: {rel}")
145     return problems

```

forge/modal_app.py

```

1 """Modal application — the only compute surface of this repository.
2
3 Local side (tools/cli.py) only submits:
4     modal run forge/modal_app.py --stage ingest --run-id <id> --params '{...}' --size small
5 Inside the container the repository is mounted read-only at /repo and the persistent
6 volume at /vol; stages write exclusively to /vol/runs/<run_id>/<stage>/.
7 """

```

```

8
9 from __future__ import annotations
10
11 import contextlib
12 import io
13 import json
14 import os
15 import sys
16 import traceback
17 from pathlib import Path
18
19 import modal
20
21 _HERE = Path(__file__).resolve()
22 REPO = _HERE.parents[1]
23
24
25 def _load_project() -> dict:
26     for candidate in (REPO / "configs" / "project.json", Path("/repo/configs/project.json")):
27         if candidate.exists():
28             return json.loads(candidate.read_text(encoding="utf-8"))
29     raise FileNotFoundError("configs/project.json not found next to forge/modal_app.py")
30
31
32 PROJECT = _load_project()
33 app = modal.App(PROJECT["app"])
34 volume = modal.Volume.from_name(PROJECT["volume"], create_if_missing=True)
35
36 APT_PACKAGES = [
37     "texlive-xetex",
38     "texlive-lang-chinese",
39     "texlive-latex-base",
40     "texlive-latex-recommended",
41     "texlive-latex-extra",
42     "texlive-science",
43     "texlive-pictures",
44     "texlive-bibtex-extra",
45     "texlive-fonts-recommended",
46     "fonts-noto-cjk",
47     "fonts-noto-core",
48     "fonts-droid-fallback",
49     "fonts-wqy-microhei",
50     "fontconfig",
51     "poppler-utils",
52     "zip",
53     "unzip",
54 ]
55 PIP_PACKAGES = [
56     "numpy==2.2.6",
57     "scipy==1.15.3",
58     "pandas==2.2.3",
59     "pyarrow==20.0.0",
60     "openpyxl==3.1.5",
61     "matplotlib==3.10.3",
62     "scikit-learn==1.6.1",
63     "statsmodels==0.14.4",
64     "ortools==9.12.4544",
65     "highspy==1.10.0",
66     "numba==0.61.2",
67     "cvxpy==1.6.5",
68     "networkx==3.4.2",
69     "pydantic==2.11.4",
70     "pymupdf==1.26.7",

```

```

71     "pytest==8.3.5",
72     "pytest-cov==6.1.1",
73     "hypothesis==6.131.9",
74     "ruff==0.11.10",
75     "mypy==1.15.0",
76     "pandas-stubs==2.2.3.250308",
77     "types-openpyxl==3.1.5.20250602",
78 ]
79 SKIP_PARTS = {
80     ".git",
81     "artifacts",
82     "releases",
83     ".forge",
84     "__pycache__",
85     ".mypy_cache",
86     ".ruff_cache",
87     ".pytest_cache",
88     ".hypothesis",
89     ".DS_Store",
90 }
91
92
93 def _ignore(path: Path) -> bool:
94     return bool(SKIP_PARTS & set(path.parts)) or path.suffix in {".pyc", ".pyo"}
95
96
97 image = (
98     modal.Image.debian_slim(python_version="3.11")
99     .apt_install(*APT_PACKAGES)
100     .pip_install(*PIP_PACKAGES)
101     .env(
102         {
103             "OMP_NUM_THREADS": "1",
104             "OPENBLAS_NUM_THREADS": "1",
105             "MKL_NUM_THREADS": "1",
106             "MPLBACKEND": "Agg",
107             "MPLCONFIGDIR": "/tmp/mpl",
108             "PYTHONHASHSEED": "0",
109             "PYTHONUNBUFFERED": "1",
110             "PYTHONDONTWRITEBYTECODE": "1",
111             "PYTHONPATH": "/repo",
112             "FORGE_REPO": "/repo",
113             "FORGE_VOL": "/vol",
114             "MODAL_IS_REMOTE": "1",
115             "TEXMFVAR": "/tmp/texmf-var",
116             "TEXMFCONFIG": "/tmp/texmf-config",
117             "HOME": "/root",
118         }
119     )
120     .add_local_dir(REPO, "/repo", ignore=_ignore)
121 )
122
123 VOLUME_MOUNT = {"vol": volume}
124
125
126 def _bootstrap() -> None:
127     if "/repo" not in sys.path:
128         sys.path.insert(0, "/repo")
129     os.chdir("/repo")
130     Path("/tmp/mpl").mkdir(exist_ok=True)
131
132
133 def _run(stage: str, run_id: str, params_json: str, force: bool) -> dict:

```

```

134     _bootstrap()
135     volume.reload()
136     from forge.runner import execute
137
138     params = json.loads(params_json or "{}")
139     return execute(
140         stage_name=stage,
141         run_id=run_id,
142         params=params,
143         force=force,
144         repo=Path("/repo"),
145         vol=Path("/vol"),
146         commit=volume.commit,
147     )
148
149
150 @app.function(image=image, volumes=VOLUME_MOUNT, cpu=2, memory=4096, timeout=2 * 3600)
151 def run_small(stage: str, run_id: str, params: str, force: bool) -> dict:
152     return _run(stage, run_id, params, force)
153
154
155 @app.function(image=image, volumes=VOLUME_MOUNT, cpu=8, memory=16384, timeout=6 * 3600)
156 def run_medium(stage: str, run_id: str, params: str, force: bool) -> dict:
157     return _run(stage, run_id, params, force)
158
159
160 @app.function(image=image, volumes=VOLUME_MOUNT, cpu=32, memory=65536, timeout=12 * 3600)
161 def run_large(stage: str, run_id: str, params: str, force: bool) -> dict:
162     return _run(stage, run_id, params, force)
163
164
165 @app.function(image=image, volumes=VOLUME_MOUNT, cpu=4, memory=8192, timeout=3600)
166 def exec_python(code: str, run_id: str) -> str:
167     """Run an ad-hoc Python snippet in the cloud (exploration, status, debugging). Never local."""
168     _bootstrap()
169     volume.reload()
170     buffer = io.StringIO()
171     scope = {
172         "__name__": "__forge_exec__",
173         "RUN_DIR": Path("/vol/runs") / run_id,
174         "VOL": Path("/vol"),
175         "REPO": Path("/repo"),
176         "RUNS": Path("/vol/runs"),
177     }
178     with contextlib.redirect_stdout(buffer), contextlib.redirect_stderr(buffer):
179         try:
180             exec(compile(code, "<forge-exec>", "exec"), scope) # noqa: S102 - explicit cloud REPL
181         except BaseException:
182             traceback.print_exc(file=buffer)
183     volume.commit()
184     return buffer.getvalue()
185
186
187 @app.function(image=image, volumes=VOLUME_MOUNT, cpu=2, memory=4096, timeout=600)
188 def provision() -> dict:
189     """Prove the toolchain: interpreter, packages, TeX engine, fonts, solver availability."""
190     import importlib.metadata
191     import subprocess
192
193     _bootstrap()
194     info: dict = {"modal_task_id": os.getenv("MODAL_TASK_ID"), "cpu_count": os.cpu_count()}
195     info["python"] = sys.version.split()[0]
196     info["packages"] = {p.split("==")[0]: importlib.metadata.version(p.split("==")[0]) for p in PIP_PACKAGES}

```

```

197 info["xelatex"] = subprocess.run(["xelatex", "--version"], capture_output=True, text=True).stdout.splitlines()[0]
198 info["bibtex"] = subprocess.run(["bibtex", "--version"], capture_output=True, text=True).stdout.splitlines()[0]
199 info["fc_cjk"] = subprocess.run(["fc-match", "Noto Serif CJK SC"], capture_output=True, text=True).stdout.strip()
200 info["kpse"] = {
201     name: bool(subprocess.run(["kpsewhich", name], capture_output=True, text=True).stdout.strip())
202     for name in (
203         "ctexart.cls",
204         "gbt7714.sty",
205         "siunitx.sty",
206         "algorithm2e.sty",
207         "booktabs.sty",
208         "tikz.sty",
209         "listings.sty",
210         "cleveref.sty",
211         "tcolorbox.sty",
212         "pgfplots.sty",
213     )
214 }
215 from ortools.sat.python import cp_model
216
217 model = cp_model.CpModel()
218 x = model.NewIntVar(0, 10, "x")
219 model.Add(x >= 3)
220 model.Minimize(x)
221 solver = cp_model.CpSolver()
222 info["cpsat"] = {"status": solver.StatusName(solver.Solve(model)), "x": solver.Value(x)}
223 import highspy
224
225 info["highs"] = highspy.Highs().version()
226 from forge.plotting import cjk_font_family
227
228 info["figure_cjk_font"] = cjk_font_family()
229 return info
230
231
232 @app.local_entrypoint()
233 def main(
234     stage: str = "ingest",
235     run_id: str = "",
236     params: str = "{}",
237     force: bool = False,
238     size: str = "small",
239     spawn: bool = False,
240 ) -> None:
241     """Submit one stage (or ``all`` with params.stages) to the cloud and print its result."""
242     if stage == "provision":
243         print("PROVISION " + json.dumps(provision.remote(), ensure_ascii=False, default=str))
244         return
245     if stage == "exec":
246         payload = json.loads(params or "{}")
247         print(exec_python.remote(payload.get("code", ""), run_id or "adhoc"))
248         return
249     fn = {"small": run_small, "medium": run_medium, "large": run_large}[size]
250     if spawn:
251         call = fn.spawn(stage, run_id, params, force)
252         print(f"FUNCTION_CALL_ID {call.object_id}")
253         return
254     result = fn.remote(stage, run_id, params, force)
255     print("STAGE_RESULT " + json.dumps(result, ensure_ascii=False, default=str))

```

forge/packaging.py

```
1 """Deterministic packaging of support materials (stable member order and timestamps)."""
2
3 from __future__ import annotations
4
5 import zipfile
6 from collections.abc import Iterable
7 from pathlib import Path
8 from typing import Any
9
10 from .hashing import sha256_file
11
12 FIXED_TIME = (2026, 1, 1, 0, 0, 0)
13 SKIP_PARTS = {
14     ".git",
15     "__pycache__",
16     ".DS_Store",
17     ".mypy_cache",
18     ".ruff_cache",
19     ".pytest_cache",
20     ".hypothesis",
21     "artifacts",
22     "releases",
23     ".forge",
24     "build",
25 }
26
27
28 def code_members(repo: Path, globs: Iterable[str]) -> list[tuple[str, Path]]:
29     found: dict[str, Path] = {}
30     for pattern in globs:
31         for path in sorted(repo.glob(pattern)):
32             if not path.is_file():
33                 continue
34             rel = path.relative_to(repo)
35             if SKIP_PARTS & set(rel.parts) or path.suffix == ".pyc":
36                 continue
37             found[rel.as_posix()] = path
38     return sorted(found.items())
39
40
41 def run_members(run_dir: Path, stages: Iterable[str], *, prefix: str = "runs") -> list[tuple[str, Path]]:
42     members: list[tuple[str, Path]] = []
43     for stage in stages:
44         directory = run_dir / stage
45         if not directory.is_dir():
46             continue
47         for path in sorted(directory.rglob("*")):
48             rel = path.relative_to(directory)
49             if path.is_file() and not (SKIP_PARTS & set(rel.parts)):
50                 members.append((f"{prefix}/{run_dir.name}/{stage}/{rel.as_posix()}", path))
51     return members
52
53
54 def build_zip(members: Iterable[tuple[str, Path]], out: Path, *, comment: str = "") -> dict[str, Any]:
55     ordered = sorted(dict(members).items())
56     out.parent.mkdir(parents=True, exist_ok=True)
57     total = 0
58     with zipfile.ZipFile(out, "w", compression=zipfile.ZIP_DEFLATED, compresslevel=9) as zf:
59         if comment:
60             zf.comment = comment.encode("utf-8")
61         for name, source in ordered:
```

```

62         info = zipfile.ZipInfo(name, date_time=FIXED_TIME)
63         info.compress_type = zipfile.ZIP_DEFLATED
64         info.external_attr = 0o644 << 16
65         data = source.read_bytes()
66         total += len(data)
67         zf.writestr(info, data)
68     with zipfile.ZipFile(out) as zf:
69         bad = zf.testzip()
70         count = len(zf.namelist())
71     if bad:
72         raise RuntimeError(f"zip member failed CRC check: {bad}")
73     return {
74         "path": str(out),
75         "members": count,
76         "uncompressed_bytes": total,
77         "bytes": out.stat().st_size,
78         "sha256": sha256_file(out),
79     }

```

forge/pdfqa.py

```

1  """PDF inspection for quality gates (PyMuPDF)."""
2
3  from __future__ import annotations
4
5  import re
6  from collections.abc import Iterable
7  from pathlib import Path
8  from typing import Any
9
10 A4_PT = (595.276, 841.89)
11
12
13 def inspect_pdf(path: Path, *, with_text: bool = True) -> dict[str, Any]:
14     import fitz  # PyMuPDF
15
16     doc = fitz.open(path)
17     pages: list[dict[str, Any]] = []
18     texts: list[str] = []
19     fonts: dict[int, dict[str, Any]] = {}
20     unembedded: list[str] = []
21     for index, page in enumerate(doc, start=1):
22         rect = page.rect
23         pages.append(
24             {
25                 "page": index,
26                 "width_pt": round(rect.width, 2),
27                 "height_pt": round(rect.height, 2),
28                 "a4": abs(rect.width - A4_PT[0]) < 3 and abs(rect.height - A4_PT[1]) < 3,
29             }
30         )
31     if with_text:
32         texts.append(page.get_text("text"))
33     for font in page.get_fonts(full=True):
34         xref, ftype, basefont = font[0], font[2], font[3]
35         if xref in fonts:
36             continue
37         embedded = ftype == "Type3"
38         if not embedded and xref:
39             try:
40                 embedded = len(doc.extract_font(xref)[3]) > 0

```

```

41         except Exception:
42             embedded = False
43             fonts[xref] = {"name": basefont, "type": ftype, "embedded": bool(embedded)}
44             if not embedded:
45                 unembedded.append(basefont)
46         return {
47             "pages": len(doc),
48             "page_boxes": pages,
49             "all_a4": all(p["a4"] for p in pages),
50             "fonts": list(fonts.values()),
51             "unembedded_fonts": sorted(set(unembedded)),
52             "texts": texts,
53             "metadata": doc.metadata,
54         }
55
56
57 def scan_strings(texts: Iterable[str], patterns: Iterable[str], *, context: int = 40) -> list[dict[str, Any]]:
58     compiled = [(p, re.compile(p)) for p in patterns]
59     hits: list[dict[str, Any]] = []
60     for page_no, text in enumerate(texts, start=1):
61         for raw, pattern in compiled:
62             for match in pattern.finditer(text):
63                 start, end = max(0, match.start() - context), min(len(text), match.end() + context)
64                 hits.append({"page": page_no, "pattern": raw, "context": text[start:end].replace("\n", " ")})
65     return hits

```

forge/plotting.py

```

1  """House style for paper figures: vector PDF output, CJK-capable fonts, accessible palette."""
2
3  from __future__ import annotations
4
5  import logging
6  import warnings
7  from pathlib import Path
8  from typing import Any
9
10 OKABE_ITO = ["#0072B2", "#D55E00", "#009E73", "#E69F00", "#CC79A7", "#56B4E9", "#F0E442", "#000000"]
11 # (family name as matplotlib registers it, font file). TTC files expose only their first face,
12 # which is why the Noto CJK collection is addressed by its JP face name.
13 _CJK_CANDIDATES = (
14     ("WenQuanYi Micro Hei", "/usr/share/fonts/truetype/wqy/wqy-microhei.ttc"),
15     ("Noto Sans CJK JP", "/usr/share/fonts/opentype/noto/NotoSansCJK-Regular.ttc"),
16     ("Droid Sans Fallback", "/usr/share/fonts/truetype/droid/DroidSansFallbackFull.ttf"),
17 )
18 _PROBE_TEXT = "温度 T 水分 C 药材 频段 关键词 abc 0.25"
19 _STATE: dict[str, Any] = {}
20
21
22 class _Catcher(logging.Handler):
23     def __init__(self) -> None:
24         super().__init__()
25         self.records: list[str] = []
26
27     def emit(self, record: logging.LogRecord) -> None:
28         self.records.append(record.getMessage())
29
30
31 def _probe(family: str) -> bool:
32     """True when ``family`` (with DejaVu Sans as Latin fallback) renders the probe text into PDF cleanly."""
33     from matplotlib import pyplot as plt

```

```

34
35 catcher = _Catcher()
36 loggers = [
37     logging.getLogger(n) for n in ("matplotlib.font_manager", "matplotlib.backends.backend_pdf", "matplotlib")
38 ]
39 for lg in loggers:
40     lg.addHandler(catcher)
41 try:
42     with warnings.catch_warnings(record=True) as caught:
43         warnings.simplefilter("always")
44         fig, ax = plt.subplots(figsize=(2.5, 1))
45         ax.text(0.05, 0.5, _PROBE_TEXT, fontfamily=[family, "DejaVu Sans"])
46         ax.set_axis_off()
47         probe = Path("/tmp") / f"forge_font_probe_{family.replace(' ', '_')}.pdf"
48         fig.savefig(probe, format="pdf")
49         plt.close(fig)
50     messages = [str(w.message) for w in caught] + catcher.records
51     bad = [m for m in messages if "missing from font" in m or "not found" in m.lower()]
52     return not bad
53 except Exception:
54     return False
55 finally:
56     for lg in loggers:
57         lg.removeHandler(catcher)
58
59
60 def cjk_font_family() -> str:
61     """Pick a CJK font that renders into PDF without missing glyphs (cached per process)."""
62     if "family" in _STATE:
63         return str(_STATE["family"])
64     import matplotlib
65
66     matplotlib.use("Agg")
67     from matplotlib import font_manager
68
69     chosen = "DejaVu Sans"
70     for family, path in _CJK_CANDIDATES:
71         if not Path(path).exists():
72             continue
73         try:
74             font_manager.fontManager.addfont(path)
75         except Exception:
76             continue
77         if _probe(family):
78             chosen = family
79             break
80     _STATE["family"] = chosen
81     return chosen
82
83
84 def setup(font_size: float = 9.0) -> str:
85     import matplotlib
86
87     matplotlib.use("Agg")
88     from cycler import cycler
89     from matplotlib import pyplot as plt
90
91     family = cjk_font_family()
92     plt.rcParams.update(
93         {
94             "font.family": [family, "DejaVu Sans"],
95             "font.size": font_size,
96             "axes.titlesize": font_size + 1,

```

```

97         "axes.labelsize": font_size,
98         "legend.fontsize": font_size - 1,
99         "xtick.labelsize": font_size - 1,
100        "ytick.labelsize": font_size - 1,
101        "axes.prop_cycle": cycler(color=OKABE_ITO),
102        "axes.spines.top": False,
103        "axes.spines.right": False,
104        "axes.grid": True,
105        "grid.alpha": 0.25,
106        "grid.linewidth": 0.6,
107        "lines.linewidth": 1.4,
108        "figure.dpi": 150,
109        "savefig.dpi": 300,
110        "pdf.fonttype": 42,
111        "ps.fonttype": 42,
112        "axes.unicode_minus": False,
113        "figure.constrained_layout.use": True,
114    }
115    )
116    return family
117
118
119 def new_figure(width_in: float = 6.3, height_in: float = 3.4, **kwargs: Any) -> tuple[Any, Any]:
120     from matplotlib import pyplot as plt
121
122     setup()
123     return plt.subplots(figsize=(width_in, height_in), **kwargs)
124
125
126 def save(fig: Any, pdf_path: Path, *, png_preview: bool = True, dpi: int = 200) -> dict[str, Any]:
127     from matplotlib import pyplot as plt
128
129     pdf_path.parent.mkdir(parents=True, exist_ok=True)
130     fig.savefig(pdf_path, format="pdf")
131     out = {"pdf": str(pdf_path), "bytes": pdf_path.stat().st_size}
132     if png_preview:
133         png = pdf_path.with_suffix(".png")
134         fig.savefig(png, format="png", dpi=dpi)
135         out["png"] = str(png)
136     plt.close(fig)
137     return out

```

forge/runner.py

```

1  """Stage registry and executor. A stage is a function ``fn(ctx) -> metrics``.
2
3  Guarantees: one manifest per (run, stage); dependencies must be completed in the same run
4  (or copied from ``from_run``); a completed stage is skipped unless ``force``; failures are
5  recorded with a traceback and re-raised; the volume is committed after every stage.
6  """
7
8  from __future__ import annotations
9
10 import importlib
11 import json
12 import shutil
13 import time
14 from collections.abc import Callable, Iterable
15 from dataclasses import dataclass
16 from pathlib import Path
17 from typing import Any

```

```

18
19 from .context import StageContext
20 from .hashing import hash_tree, tree_digest
21 from .manifest import Manifest
22
23 StageFn = Callable[[StageContext], dict[str, Any] | None]
24 CODE_IGNORE = (
25     ".git",
26     "artifacts",
27     "releases",
28     "__pycache__",
29     ".mypy_cache",
30     ".ruff_cache",
31     ".pytest_cache",
32     ".hypothesis",
33     ".DS_Store",
34     ".forge",
35 )
36
37
38 @dataclass(frozen=True)
39 class StageSpec:
40     name: str
41     fn: StageFn
42     deps: tuple[str, ...]
43     description: str
44
45
46 STAGES: dict[str, StageSpec] = {}
47
48
49 def stage(name: str, deps: Iterable[str] = (), description: str = "") -> Callable[[StageFn], StageFn]:
50     def decorator(fn: StageFn) -> StageFn:
51         if name in STAGES:
52             raise ValueError(f"duplicate stage registration: {name}")
53         doc = (fn.__doc__ or "").strip().splitlines()
54         STAGES[name] = StageSpec(name, fn, tuple(deps), description or (doc[0] if doc else ""))
55         return fn
56     return decorator
57
58
59
60 def discover(repo: Path) -> None:
61     project = json.loads((repo / "configs" / "project.json").read_text(encoding="utf-8"))
62     importlib.import_module("pipelines.common.stages")
63     importlib.import_module(f"pipelines.{project['package']}.stages")
64
65
66 def list_stages(repo: Path) -> list[dict[str, Any]]:
67     discover(repo)
68     return [{"name": s.name, "deps": list(s.deps), "description": s.description} for s in STAGES.values()]
69
70
71 def _raw_input_prefixes(repo: Path) -> tuple[str, ...]:
72     project = json.loads((repo / "configs" / "project.json").read_text(encoding="utf-8"))
73     return (project["problem_pdf"], project["attachments_dir"].rstrip("/") + "/")
74
75
76 def execute(
77     stage_name: str,
78     run_id: str,
79     params: dict[str, Any],
80     force: bool,

```

```

81     repo: Path,
82     vol: Path,
83     commit: Callable[[], None] | None = None,
84 ) -> dict[str, Any]:
85     discover(repo)
86     if stage_name == "all":
87         results = [execute(s, run_id, params, force, repo, vol, commit) for s in params.get("stages", [])]
88         return {
89             "stage": "all",
90             "run_id": run_id,
91             "results": results,
92             "status": "completed" if all(r.get("status") in {"completed", "skipped"} for r in results) else "failed",
93         }
94     if stage_name not in STAGES:
95         raise KeyError(f"unknown stage {stage_name!r}; known stages: {sorted(STAGES)}")
96     spec = STAGES[stage_name]
97     run_dir = vol / "runs" / run_id
98     stage_dir = run_dir / stage_name
99     manifest_path = stage_dir / "manifest.json"
100
101     if manifest_path.exists() and not force:
102         previous = Manifest.read(manifest_path)
103         if previous.status == "completed":
104             return {
105                 "stage": stage_name,
106                 "run_id": run_id,
107                 "status": "skipped",
108                 "reason": "already completed in this run (use --force to rerun)",
109                 "outputs_digest": previous.outputs_digest,
110             }
111
112     deps_digest: dict[str, str] = {}
113     for dep in spec.deps:
114         dep_manifest = run_dir / dep / "manifest.json"
115         if not dep_manifest.exists() and params.get("from_run"):
116             source = vol / "runs" / str(params["from_run"]) / dep
117             if (source / "manifest.json").exists():
118                 shutil.copytree(source, run_dir / dep, dirs_exist_ok=True)
119         if not dep_manifest.exists():
120             raise RuntimeError(
121                 f"stage '{stage_name}' requires '{dep}', which has not run in run {run_id} "
122                 f"{'(run it first, or pass from_run=<run_id> to reuse its outputs)'}"
123             )
124         dep_state = Manifest.read(dep_manifest)
125         if dep_state.status != "completed":
126             raise RuntimeError(f"dependency '{dep}' has status {dep_state.status!r} in run {run_id}")
127         deps_digest[dep] = dep_state.outputs_digest
128
129     if stage_dir.exists():
130         shutil.rmtree(stage_dir)
131     ctx = StageContext(run_id, stage_name, params, repo, vol)
132     code_tree = hash_tree(repo, ignore=CODE_IGNORE)
133     prefixes = _raw_input_prefixes(repo)
134     inputs = {k: v for k, v in code_tree.items() if k.startswith(prefixes)}
135     code_ref = {**dict(params.get("code_ref") or {}), "code_digest": tree_digest(code_tree), "files": len(code_tree)}
136     manifest = Manifest.start(run_id, stage_name, params, code_ref, ctx.config.digest, deps_digest, inputs)
137     manifest.write(manifest_path)
138     ctx.log.info("stage.start", deps=list(spec.deps), description=spec.description, size=params.get("size"))
139     t0 = time.monotonic()
140     try:
141         metrics = spec.fn(ctx) or {}
142         ctx.flush_numbers()
143         manifest.complete(stage_dir, metrics)

```

```

144         ctx.log.info("stage.completed", duration_s=round(time.monotonic() - t0, 3), metrics=metrics)
145     except BaseException as exc:
146         manifest.fail(exc)
147         ctx.log.error("stage.failed", error=repr(exc))
148         manifest.write(manifest_path)
149         ctx.log.close()
150         if commit:
151             commit()
152         raise
153     manifest.write(manifest_path)
154     ctx.log.close()
155     if commit:
156         commit()
157     return {
158         "stage": stage_name,
159         "run_id": run_id,
160         "status": "completed",
161         "duration_s": manifest.duration_s,
162         "metrics": manifest.metrics,
163         "outputs_digest": manifest.outputs_digest,
164         "modal_task_id": manifest.runtime.get("modal_task_id"),
165     }

```

forge/tex.py

```

1  """XeLaTeX compilation and log analysis (only ever executed inside Modal)."""
2
3  from __future__ import annotations
4
5  import os
6  import re
7  import subprocess
8  from pathlib import Path
9  from typing import Any
10
11  _UNDEF_REF = re.compile(r"LaTeX Warning: Reference `([^\s]+)' on page \d+ undefined")
12  _UNDEF_CIT = re.compile(r"LaTeX Warning: Citation `([^\s]+)' on page \d+ undefined")
13  _OVERFULL = re.compile(r"Overfull \hbox \([^\s]+\)[pt too wide]")
14  _MISSING = re.compile(r"Missing character: There is no (.*?) in font")
15  _ERROR = re.compile(r"^(.*)$", re.M)
16  _PAGES = re.compile(r"Output written on .*? \([^\s]+\) pages?")
17
18
19  def tex_env() -> dict[str, str]:
20     env = dict(os.environ)
21     env.setdefault("TEXMFVAR", "/tmp/texmf-var")
22     env.setdefault("TEXMFCONFIG", "/tmp/texmf-config")
23     env.setdefault("HOME", "/tmp")
24     env["max_print_line"] = "2000"
25     env["error_line"] = "254"
26     env["half_error_line"] = "238"
27     return env
28
29
30  def summarize_log(log: str) -> dict[str, Any]:
31     overfull = [float(x) for x in _OVERFULL.findall(log)]
32     missing = _MISSING.findall(log)
33     pages = _PAGES.search(log)
34     return {
35         "undefined_references": sorted(set(_UNDEF_REF.findall(log))),
36         "undefined_citations": sorted(set(_UNDEF_CIT.findall(log))),

```

```

37     "overfull_count": len(overfull),
38     "overfull_max_pt": max(overfull) if overfull else 0.0,
39     "missing_characters": len(missing),
40     "missing_character_samples": sorted(set(missing))[:10],
41     "errors": _ERROR.findall(log)[:10],
42     "pages_from_log": int(pages.group(1)) if pages else None,
43 }
44
45
46 def aux_page(aux: Path, label: str) -> int | None:
47     """Page number recorded for ``\label{label}`` in the .aux file (hyperref-compatible)."""
48     if not aux.exists():
49         return None
50     pattern = re.compile(r"\newlabel\{" + re.escape(label) + r"\}\{\{[^\}]*\}\{(\d+)\}\}")
51     match = pattern.search(aux.read_text(encoding="utf-8", errors="replace"))
52     return int(match.group(1)) if match else None
53
54
55 def compile_tex(
56     workdir: Path,
57     main: str,
58     jobname: str,
59     *,
60     passes: int = 3,
61     bibtex: bool = True,
62     timeout: int = 1200,
63 ) -> dict[str, Any]:
64     env = tex_env()
65     runs: list[dict[str, Any]] = []
66     log_path = workdir / f"{jobname}.log"
67
68     def xelatex(tag: str) -> None:
69         proc = subprocess.run(
70             ["xelatex", "-interaction=nonstopmode", "-halt-on-error", "-file-line-error", f"-jobname={jobname}", main],
71             cwd=workdir,
72             capture_output=True,
73             text=True,
74             env=env,
75             timeout=timeout,
76             check=False,
77         )
78         runs.append({"pass": tag, "rc": proc.returncode})
79         if proc.returncode != 0:
80             log = log_path.read_text(encoding="utf-8", errors="replace") if log_path.exists() else proc.stdout
81             errors = _ERROR.findall(log)
82             raise RuntimeError(
83                 f"xelatex failed on pass {tag} for {main}: "
84                 + " | ".join(errors[:5])
85                 + "\n--- log tail ---\n"
86                 + log[-4000:]
87             )
88
89     xelatex("1")
90     aux = workdir / f"{jobname}.aux"
91     if bibtex and aux.exists():
92         aux_text = aux.read_text(encoding="utf-8", errors="replace")
93         if "\\citation" in aux_text and "\\bibdata" in aux_text:
94             proc = subprocess.run(
95                 ["bibtex", jobname], cwd=workdir, capture_output=True, text=True, env=env, timeout=timeout, check=False
96             )
97             runs.append({"pass": "bibtex", "rc": proc.returncode, "tail": proc.stdout[-1500:]})
98     for i in range(2, passes + 1):
99         xelatex(str(i))

```

```

100     log_text = log_path.read_text(encoding="utf-8", errors="replace")
101     return {
102         "pdf": workdir / f"{jobname}.pdf",
103         "log": log_path,
104         "aux": aux,
105         "runs": runs,
106         "summary": summarize_log(log_text),
107     }
108
109
110 def tex_escape(text: str) -> str:
111     replacements = {
112         "\\": r"\textbackslash{}",
113         "&": r"\&",
114         "%": r"\%",
115         "$": r"\$",
116         "#": r"\#",
117         "_": r"\_",
118         "{": r"\{",
119         "}": r"\}",
120         "~": r"\textasciitilde{}",
121         "^": r"\textasciicircum{}",
122     }
123     return "".join(replacements.get(ch, ch) for ch in text)
124
125
126 def tex_path(path: str) -> str:
127     """Typeset a file path so that it can break across lines (hyperref/xurl); falls back to \texttt."""
128     if any(ch in path for ch in "{}%#\\") or not path.isascii():
129         return f"\\texttt{{{tex_escape(path)}}}" # CJK names need the CJK mono font, not the url font
130     return f"\\nolinkurl{{{path}}}"

```

forge/xlsx.py

```

1  """Workbook I/O: reading attachments, filling result templates, checking result contracts."""
2
3  from __future__ import annotations
4
5  import math
6  from collections.abc import Iterable, Sequence
7  from dataclasses import dataclass
8  from pathlib import Path
9  from typing import Any
10
11  import openpyxl
12  import pandas as pd
13
14  BIG_SHEET_CELLS = 300_000
15
16
17  def read_sheets(path: Path, header: int | None = 0) -> dict[str, pd.DataFrame]:
18      with pd.ExcelFile(path) as xf:
19          return {str(name): xf.parse(name, header=header) for name in xf.sheet_names}
20
21
22  def sheet_headers(path: Path) -> dict[str, list[Any]]:
23      wb = openpyxl.load_workbook(path, read_only=True, data_only=True)
24      out: dict[str, list[Any]] = {}
25      for ws in wb.worksheets:
26          row = list(next(ws.iter_rows(min_row=1, max_row=1, values_only=True), ()))
27          while row and row[-1] is None:

```

```

28         row.pop()
29         out[str(ws.title)] = row
30     wb.close()
31     return out
32
33
34 def _clean(value: Any, decimals: int | None) -> Any:
35     if hasattr(value, "item") and not isinstance(value, str | bytes):
36         try:
37             value = value.item()
38         except (ValueError, TypeError):
39             pass
40     if isinstance(value, float):
41         if math.isnan(value) or math.isinf(value):
42             return None
43         return round(value, decimals) if decimals is not None else value
44     return value
45
46
47 def write_result(
48     template: Path,
49     out: Path,
50     sheets: dict[str, tuple[Sequence[Any], Iterable[Sequence[Any]]]],
51     *,
52     decimals: int | None = 4,
53     float_format: str = "0.0000",
54 ) -> dict[str, Any]:
55     """Fill a competition result template.
56
57     ``sheets`` maps sheet name -> (header_row, rows). The template's A1 text is always kept;
58     header cells after A1 are taken from ``header_row[1:]``. Sheets not mentioned keep their
59     template content. Floats are rounded to ``decimals`` and formatted with ``float_format``.
60     Very large sheets fall back to openpyxl's write-only mode (no per-cell number format).
61
62     """
63     template_wb = openpyxl.load_workbook(template)
64     names = list(template_wb.sheetnames)
65     unknown = [n for n in sheets if n not in names]
66     if unknown:
67         raise KeyError(f"sheets {unknown} not in template {template.name} (has {names})")
68     a1 = {ws.title: ws.cell(row=1, column=1).value for ws in template_wb.worksheets}
69     materialised = {name: (list(header), [list(r) for r in rows]) for name, (header, rows) in sheets.items()}
70     cells = sum(max(len(h), 1) * (len(rows) + 1) for h, rows in materialised.values())
71     stats: dict[str, Any] = {}
72     out.parent.mkdir(parents=True, exist_ok=True)
73
74     if cells > BIG_SHEET_CELLS:
75         wb = openpyxl.Workbook(write_only=True)
76         for name in names:
77             ws = wb.create_sheet(name)
78             if name in materialised:
79                 header, rows = materialised[name]
80                 full_header = [a1[name], *header[1:]]
81                 ws.append(full_header)
82                 for row in rows:
83                     ws.append([_clean(v, decimals) for v in row])
84                 stats[name] = {"rows": len(rows), "cols": len(full_header)}
85             else:
86                 for tpl_row in template_wb[name].iter_rows(values_only=True):
87                     ws.append(list(tpl_row))
88         wb.save(out)
89     else:
90         wb = template_wb
91         for name, (header, rows) in materialised.items():

```

```

91         index = wb.sheetnames.index(name)
92         wb.remove(wb[name])
93         ws = wb.create_sheet(name, index) # fresh sheet: no stale template cells or dimensions
94         full_header = [a1[name], *header[1:]]
95         for j, value in enumerate(full_header, start=1):
96             ws.cell(row=1, column=j, value=_clean(value, None))
97         for i, row in enumerate(rows, start=2):
98             for j, value in enumerate(row, start=1):
99                 cleaned = _clean(value, decimals)
100                 cell = ws.cell(row=i, column=j, value=cleaned)
101                 if isinstance(cleaned, float) and j > 1:
102                     cell.number_format = float_format
103             stats[name] = {"rows": len(rows), "cols": len(full_header)}
104         wb.save(out)
105     return {"path": str(out), "sheets": stats, "write_only": cells > BIG_SHEET_CELLS, "cells": cells}
106
107
108 @dataclass(frozen=True)
109 class SheetContract:
110     name: str
111     min_rows: int = 1 # data rows (excluding the header)
112     max_rows: int | None = None
113     header_len: int | None = None # exact number of header cells, if known
114     numeric_from_col: int | None = None # 0-based; every data cell from this column must be numeric
115     allow_blank: bool = False # blank numeric cells permitted (e.g. moving-boundary tables)
116     decimals: int | None = 4 # numeric cells must carry at most this many decimals
117     text_columns: tuple[int, ...] = () # 0-based columns that must be non-empty text
118
119
120 @dataclass(frozen=True)
121 class WorkbookContract:
122     file: str
123     template: str
124     sheets: tuple[SheetContract, ...]
125
126
127 def check_workbook(path: Path, contract: WorkbookContract, template: Path) -> dict[str, Any]:
128     errors: list[str] = []
129     if not path.exists():
130         return {"file": contract.file, "ok": False, "errors": ["file missing"], "sheets": {}}
131     try:
132         tpl_headers = sheet_headers(template)
133     except Exception as exc:
134         tpl_headers = {}
135         errors.append(f"template unreadable: {exc!r}")
136     wb = openpyxl.load_workbook(path, read_only=True, data_only=True)
137     report: dict[str, Any] = {}
138     names = wb.sheetnames
139     if tpl_headers and names != list(tpl_headers):
140         errors.append(f"sheet names {names} differ from template {list(tpl_headers)}")
141     for sc in contract.sheets:
142         if sc.name not in names:
143             errors.append(f"sheet {sc.name!r} missing")
144             continue
145         ws = wb[sc.name]
146         rows = ws.iter_rows(values_only=True)
147         first = next(rows, None)
148         header: list[Any] = list(first) if first is not None else []
149         while header and header[-1] is None:
150             header.pop()
151         tpl = tpl_headers.get(sc.name)
152         if tpl and header and header[0] != tpl[0]:
153             errors.append(f"{sc.name}: A1 {header[0]!r} differs from template {tpl[0]!r}")

```

```

154     if sc.header_len is not None and len(header) != sc.header_len:
155         errors.append(f"{sc.name}: header has {len(header)} cells, expected {sc.header_len}")
156     n = 0
157     bad_numeric = blank = bad_decimals = bad_text = 0
158     for row in rows:
159         values = list(row)
160         if all(v is None or (isinstance(v, str) and not v.strip()) for v in values):
161             continue
162         n += 1
163         if sc.numeric_from_col is not None:
164             for v in values[sc.numeric_from_col : len(header) or None]:
165                 if v is None or (isinstance(v, str) and not v.strip()):
166                     blank += 1
167                 elif not isinstance(v, int | float) or isinstance(v, bool):
168                     bad_numeric += 1
169                 elif sc.decimals is not None and isinstance(v, float) and abs(round(v, sc.decimals) - v) > 1e-12:
170                     bad_decimals += 1
171             for j in sc.text_columns:
172                 v = values[j] if j < len(values) else None
173                 if v is None or not str(v).strip():
174                     bad_text += 1
175     if n < sc.min_rows:
176         errors.append(f"{sc.name}: {n} data rows < {sc.min_rows}")
177     if sc.max_rows is not None and n > sc.max_rows:
178         errors.append(f"{sc.name}: {n} data rows > {sc.max_rows}")
179     if bad_numeric:
180         errors.append(f"{sc.name}: {bad_numeric} non-numeric cells in numeric region")
181     if blank and not sc.allow_blank:
182         errors.append(f"{sc.name}: {blank} blank cells in numeric region")
183     if bad_decimals:
184         errors.append(f"{sc.name}: {bad_decimals} cells with more than {sc.decimals} decimals")
185     if bad_text:
186         errors.append(f"{sc.name}: {bad_text} empty cells in required text columns")
187     report[sc.name] = {
188         "rows": n,
189         "header": [str(h) for h in header[:6]] + (["..."] if len(header) > 6 else []),
190         "blank": blank,
191     }
192     wb.close()
193     return {"file": contract.file, "ok": not errors, "errors": errors, "sheets": report}

```

pipelines/__init__.py

pipelines/common/__init__.py

pipelines/common/stages.py

```

1 """Problem-agnostic stages: ingest, lint, test, paper, qa, package, release."""
2
3 from __future__ import annotations
4
5 import importlib
6 import json
7 import os

```

```

8 import re
9 import shlex
10 import shutil
11 import subprocess
12 import xml.etree.ElementTree as ET
13 from datetime import UTC, datetime
14 from pathlib import Path
15 from typing import Any
16
17 from forge import packaging, pdfqa, xlsx
18 from forge.context import StageContext
19 from forge.hashing import hash_tree, sha256_file
20 from forge.runner import stage
21 from forge.tex import aux_page, compile_tex, tex_escape, tex_path
22
23 PLANNED_STAGE_FILES = {
24     "lint": ["ruff_check.txt", "ruff_format.txt", "mypy.txt", "lint_report.json", "manifest.json", "events.jsonl"],
25     "test": ["junit.xml", "coverage.json", "pytest.txt", "test_report.json", "manifest.json", "events.jsonl"],
26     "qa": ["qa_report.json", "manifest.json", "events.jsonl"],
27 }
28
29 _BOOT_STAGES = ("ingest", "validate", "fmt")
30 MEMBER_DESCRIPTIONS = (
31     (r"^forge/plotting\.py$", "绘图规范（矢量 PDF + 预览 PNG、色板、字体）"),
32     (r"^forge/xlsx\.py$", "从组委会模板生成结果工作簿"),
33     (r"^forge/runner\.py$", "阶段注册与执行（依赖、清单、错误捕获）"),
34     (r"^forge/modal_app\.py$", "云端应用定义（镜像、卷、四种规格的执行函数）"),
35     (r"^forge/", "云端运行时（阶段执行、清单、契约、排版、打包）"),
36     (r"^pipelines/common/", "通用阶段：数据接入、门禁、论文、质量检查、打包发布"),
37     (r"^pipelines/e/data\.py$", "附件解析、口径统一与派生字段"),
38     (r"^pipelines/e/calendar\.py$", "2025 年法定节假日与调休日历"),
39     (r"^pipelines/e/eda\.py$", "问题 1: KPI、集中度、日历回归与注册归因"),
40     (r"^pipelines/e/classify\.py$", "问题 2: 关键词五分类与阈值稳健性"),
41     (r"^pipelines/e/response\.py$", "关键词响应函数的拟合与标定"),
42     (r"^pipelines/e/allocate\.py$", "问题 3: 可分离凹规划求解与独立校验"),
43     (r"^pipelines/e/forecast\.py$", "问题 4: 滚动回测、区间预测与随机分配"),
44     (r"^pipelines/e/figures\.py$", "论文图的生成"),
45     (r"^pipelines/e/tables\.py$", "论文表的生成"),
46     (r"^pipelines/e/stages\.py$", "本题各阶段的编排"),
47     (r"^pipelines/", "本题建模与求解程序"),
48     (r"^tools/run_local\.py$", "不依赖云端的本地驱动脚本"),
49     (r"^tools/", "本地控制面：提交云端任务、下载、校验散列"),
50     (r"^tests/", "单元 / 性质 / 集成测试"),
51     (r"^configs/", "运行配置与项目元数据"),
52     (r"^manuscript/", "论文 LaTeX 源码"),
53     (r"^docs/mdr/", "建模决策记录（题意解释、假设、目标与方法的选择理由）"),
54     (r"^docs/ARCHITECTURE\.md$", "仓库架构与唯一计算面的设计"),
55     (r"^docs/CONTRIBUTING\.md$", "协作与提交规范"),
56     (r"^docs/DATA_NOTES\.md$", "数据口径与附件解析约定"),
57     (r"^docs/ENGINEERING_STANDARD\.md$", "工程标准与门禁定义"),
58     (r"^docs/MODELING_STANDARD\.md$", "建模与写作标准（审稿清单）"),
59     (r"^docs/RESULTS\.md$", "本轮结果总览与逐项证据"),
60     (r"^docs/RUNBOOK\.md$", "运行手册（完整命令序列与实测用时）"),
61     (r"^docs/REVIEW_RESPONSE\.md$", "评审意见的逐条处理说明"),
62     (r"^docs/problem_brief\.md$", "题目要点与交付清单"),
63     (r"^docs/", "工程规范、建模标准、决策记录"),
64     (r"/ingest/", "原始数据接入结果（散列、题目文本、规范化数据）"),
65     (r"/validate/", "数据契约校验报告与数据画像"),
66     (r"/results/", "结果工作簿与求解输出"),
67     (r"/figures/", "论文图（矢量 PDF 与预览 PNG）"),
68     (r"/tables/", "论文表（LaTeX 片段与 CSV）"),
69     (r"/lint/", "静态检查报告"),
70     (r"/test/", "测试报告与覆盖率"),
71     (r"/qa/", "论文与结果文件质量门禁报告"),

```

```

71 (r"manifest\.json$", "阶段清单 (输入输出散列、环境、参数) "),
72 (r"events\.jsonl$", "结构化运行日志"),
73 (r"~AI工具使用详情\.pdf$", "AI 工具使用详情"),
74 (r"~AI_USAGE\.md$", "AI 工具使用记录 (源文件) "),
75 (r"~Makefile$", "本地快捷命令 (只提交云端任务) "),
76 (r"~pyproject\.toml$", "项目元数据与静态检查配置"),
77 (r"~README\.md$", "仓库说明与复现入口"),
78 (r"~CHANGELOG\.md$", "变更记录"),
79 (r"~UNLICENSE$", "公有领域声明 (Unlicense) "),
80 (r"~REPRODUCE\.md$", "复现说明"),
81 (r"~MANIFEST\.json$", "支撑材料成员清单与 SHA-256"),
82 (r"numbers\.json$", "该阶段登记的论文数字宏"),
83 (r"validation_report\.json$", "该阶段结果的独立校验报告"),
84 (r"\.parquet$", "规范化后的输入数据"),
85 (r"\.json$", "阶段数据产物"),
86 (r"\.csv$", "表格数据 (与 LaTeX 表同源) "),
87 )
88
89
90 def _describe(name: str) -> str:
91     for pattern, text in MEMBER_DESCRIPTIONS:
92         if re.search(pattern, name):
93             return text
94     return ""
95
96
97 def _to_parquet(df: Any, target: Path) -> None:
98     frame = df.copy()
99     frame.columns = [str(c).strip() for c in frame.columns]
100     try:
101         frame.to_parquet(target, index=False)
102     except Exception:
103         for col in frame.columns:
104             if frame[col].dtype == object:
105                 frame[col] = frame[col].map(
106                     lambda v: None if v is None or (isinstance(v, float) and v != v) else str(v)
107                 )
108         frame.to_parquet(target, index=False)
109
110
111 @stage("ingest", description="Hash raw inputs, extract the problem text, convert every attachment sheet to parquet")
112 def ingest(ctx: StageContext) -> dict[str, Any]:
113     import fitz
114
115     document = fitz.open(ctx.problem_pdf)
116     text = "\n\n".join(page.get_text("text", sort=True) for page in document)
117     ctx.out("problem_text.txt").write_text(text, encoding="utf-8")
118     inventory: dict[str, Any] = {
119         "problem_pdf": {
120             "path": ctx.project["problem_pdf"],
121             "sha256": sha256_file(ctx.problem_pdf),
122             "pages": len(document),
123         },
124         "files": [],
125     }
126     for path in sorted(ctx.attachments.rglob("*.xlsx")):
127         if path.name.startswith("-$"):
128             continue
129         rel = path.relative_to(ctx.attachments).as_posix()
130         is_template = path.parent == ctx.templates or ctx.templates in path.parents
131         entry: dict[str, Any] = {
132             "path": rel,
133             "sha256": sha256_file(path),

```

```

134         "bytes": path.stat().st_size,
135         "template": is_template,
136         "sheets": [],
137     }
138     for name, df in xls.read_sheets(path).items():
139         sheet: dict[str, Any] = {"name": name, "rows": len(df), "columns": [str(c) for c in df.columns]}
140         if not is_template:
141             safe = re.sub(r"[^\w.-]+", "_", f"{path.stem}_{name}")
142             target = ctx.out("data", f"{safe}.parquet")
143             _to_parquet(df, target)
144             sheet["parquet"] = target.relative_to(ctx.stage_dir).as_posix()
145             sheet["dtypes"] = {str(c): str(t) for c, t in df.dtypes.items()}
146             sheet["head"] = df.head(5).astype(str).values.tolist()
147             entry["sheets"].append(sheet)
148             inventory["files"].append(entry)
149             ctx.log.info("ingest.file", path=rel, template=is_template, sheets=[s["name"] for s in entry["sheets"]])
150     ctx.write_json("inventory.json", inventory)
151     return {"files": len(inventory["files"]), "problem_chars": len(text)}
152
153
154 @stage("lint", description="Static gates: ruff check, ruff format --check, mypy")
155 def lint(ctx: StageContext) -> dict[str, Any]:
156     returncodes: dict[str, int] = {}
157
158     def run(name: str, cmd: list[str]) -> None:
159         proc = subprocess.run(cmd, cwd=str(ctx.repo), capture_output=True, text=True, check=False)
160         ctx.out(f"{name}.txt").write_text(proc.stdout + ("\n" + proc.stderr if proc.stderr else ""), encoding="utf-8")
161         returncodes[name] = proc.returncode
162         ctx.log.info("lint.tool", tool=name, rc=proc.returncode, tail=(proc.stdout + proc.stderr)[-400:])
163
164     run("ruff_check", ["ruff", "check", "--no-cache", "--output-format", "concise", "."])
165     run("ruff_format", ["ruff", "format", "--check", "--no-cache", "."])
166     run("mypy", ["mypy", "--cache-dir", "/tmp/mypy", *ctx.cfg("gates.mypy_paths", ["forge"])]])
167     required = list(ctx.cfg("gates.lint_required", ["ruff_check", "ruff_format", "mypy"]))
168     passed = all(returncodes.get(name, 1) == 0 for name in required)
169     ctx.write_json("lint_report.json", {"passed": passed, "required": required, "returncodes": returncodes})
170     if not passed:
171         raise RuntimeError(f"lint gate failed: {returncodes}")
172     return {"passed": passed, **returncodes}
173
174
175 @stage("test", description="pytest (unit, property, integration) with JUnit and coverage reports")
176 def test(ctx: StageContext) -> dict[str, Any]:
177     env = {
178         **os.environ,
179         "COVERAGE_FILE": "/tmp/.coverage",
180         "HYPOTHESIS_STORAGE_DIRECTORY": "/tmp/hypothesis",
181         "FORGE_RUN_DIR": str(ctx.run_dir),
182     }
183     cmd = [
184         "python",
185         "-m",
186         "pytest",
187         "tests",
188         "-q",
189         "-p",
190         "no:cacheprovider",
191         "--rootdir",
192         str(ctx.repo),
193         f"--junitxml={ctx.out('junit.xml')}",
194         "--cov=forge",
195         "--cov=pipelines",
196         f"--cov-report=json:{ctx.out('coverage.json')}",

```

```

197     "--cov-report=term",
198 ]
199 extra = ctx.param("pytest_args")
200 if extra:
201     cmd += shlex.split(str(extra))
202 proc = subprocess.run(cmd, cwd=str(ctx.repo), capture_output=True, text=True, env=env, check=False)
203 ctx.out("pytest.txt").write_text(proc.stdout + "\n" + proc.stderr, encoding="utf-8")
204 print(proc.stdout[-5000:], flush=True)
205 summary: dict[str, Any] = {"returncode": proc.returncode}
206 junit = ctx.stage_dir / "junit.xml"
207 if junit.exists():
208     root = ET.parse(junit).getroot()
209     suite = root if root.tag == "testsuite" else root.find("testsuite")
210     if suite is not None:
211         summary.update({k: int(suite.get(k, 0)) for k in ("tests", "failures", "errors", "skipped")})
212 coverage = ctx.stage_dir / "coverage.json"
213 if coverage.exists():
214     summary["coverage_percent"] = round(json.loads(coverage.read_text())["totals"]["percent_covered"], 2)
215 ctx.write_json("test_report.json", summary)
216 if proc.returncode != 0:
217     raise RuntimeError(f"tests failed: {summary}\n{proc.stdout[-2500:]}")
218 return summary
219
220
221 def _support_members(ctx: StageContext, *, planned: bool) -> list[tuple[str, Path]]:
222     members = packaging.code_members(ctx.repo, ctx.cfg("package.code_globs", []))
223     for name in ctx.cfg("package.stages", []):
224         directory = ctx.run_dir / name
225         if (directory / "manifest.json").exists():
226             members += packaging.run_members(ctx.run_dir, [name])
227         elif planned and name in PLANNED_STAGE_FILES:
228             members += [(f"runs/{ctx.run_id}/{name}/{f}", directory / f) for f in PLANNED_STAGE_FILES[name]]
229     members.append(("AI工具使用详情.pdf", ctx.run_dir / "paper" / "AI工具使用详情.pdf"))
230     members.append(("REPRODUCE.md", ctx.run_dir / "package" / "REPRODUCE.md"))
231     members.append(("MANIFEST.json", ctx.run_dir / "package" / "MANIFEST.json"))
232     return sorted(dict(members).items())
233
234
235 def _load_numbers(run_dir: Path) -> tuple[dict[str, str], list[str]]:
236     numbers: dict[str, str] = {}
237     conflicts: list[str] = []
238     for path in sorted(run_dir.glob("*/numbers.json")):
239         for key, value in json.loads(path.read_text(encoding="utf-8")).items():
240             if key in numbers and numbers[key] != value:
241                 conflicts.append(f"{key}: {numbers[key]!r} vs {value!r} ({path.parent.name})")
242             numbers[key] = value
243     return numbers, conflicts
244
245
246 def _downstream_of(ctx: StageContext) -> set[str]:
247     """Stages that depend (transitively) on the stage rendering the record.
248
249     Their manifests cannot be final while this stage is still running, so any status they
250     carry belongs to an earlier execution and must be labelled as such rather than printed
251     as if it described this build.
252     """
253     from forge.runner import STAGES
254
255     out: set[str] = set()
256     changed = True
257     while changed:
258         changed = False
259         for name, spec in STAGES.items():

```

```

260         if name in out or name == ctx.stage:
261             continue
262         if ctx.stage in spec.deps or out & set(spec.deps):
263             out.add(name)
264             changed = True
265     return out
266
267
268 def _stage_status(ctx: StageContext, row: dict[str, Any], downstream: set[str]) -> str:
269     if row["stage"] == ctx.stage:
270         return "本表由该阶段渲染, 故为 running"
271     if row["stage"] in downstream:
272         return "本表生成后才执行 (见第 8 节与发布清单)"
273     return str(row["status"])
274
275
276 def _stage_rows(ctx: StageContext) -> list[dict[str, Any]]:
277     rows = []
278     for manifest in sorted(ctx.run_dir.glob("*/manifest.json")):
279         data = json.loads(manifest.read_text(encoding="utf-8"))
280         rows.append(
281             {
282                 "stage": data["stage"],
283                 "status": data["status"],
284                 "duration_s": data.get("duration_s"),
285                 "outputs_digest": data.get("outputs_digest", ""),
286                 "modal_task_id": data.get("runtime", {}).get("modal_task_id"),
287             }
288         )
289     return rows
290
291
292 @stage(
293     "paper",
294     description="Assemble generated inputs (numbers, tables, figures, code, support list) and compile with XeLaTeX",
295 )
296 def paper(ctx: StageContext) -> dict[str, Any]:
297     sources = list(ctx.cfg("paper.sources", []))
298     for source in sources:
299         ctx.dep(source)
300     build = Path("/tmp/build")
301     shutil.rmtree(build, ignore_errors=True)
302     shutil.copytree(
303         ctx.repo / "manuscript", build, ignore=shutil.ignore_patterns("generated", "*.aux", "*.log", "*.pdf")
304     )
305     generated = build / "generated"
306     (generated / "tables").mkdir(parents=True, exist_ok=True)
307     (build / "figures").mkdir(exist_ok=True)
308
309     numbers, conflicts = _load_numbers(ctx.run_dir)
310     for conflict in conflicts:
311         ctx.log.warn("paper.number_conflict", detail=conflict)
312     lines = ["% generated by forge — do not edit"] + [
313         f"\newcommand{{{val}{key}}}{tex_escape(value)}" for key, value in sorted(numbers.items())
314     ]
315     (generated / "numbers.tex").write_text("\n".join(lines) + "\n", encoding="utf-8")
316
317     n_tables = n_figures = 0
318     for source in sources:
319         directory = ctx.run_dir / source
320         for table in sorted((directory / "tables").glob("*.tex")) if (directory / "tables").is_dir() else []:
321             shutil.copy2(table, generated / "tables" / table.name)
322             n_tables += 1

```

```

323     for figure in sorted((directory / "figures").glob("*")) if (directory / "figures").is_dir() else []:
324         if figure.suffix.lower() in {".pdf", ".png"}:
325             shutil.copy2(figure, build / "figures" / figure.name)
326             n_figures += 1
327
328     code_ref = ctx.params.get("code_ref") or {}
329     meta = [
330         f"\newcommand{{\RunId}}{{\tex_escape(ctx.run_id)}}",
331         f"\newcommand{{\CodeSha}}{{\tex_escape(str(code_ref.get('git_sha', '')))}}",
332         f"\newcommand{{\BuildDate}}{{\datetime.now(UTC).strftime('%Y-%m-%d')}}",
333     ]
334     (generated / "meta.tex").write_text("\n".join(meta) + "\n", encoding="utf-8")
335
336     files = packaging.code_members(ctx.repo, ctx.cfg("paper.code_globs", []))
337     listing = ["% generated by forge — complete source listing"]
338     for rel, src in files:
339         target = build / "code" / rel
340         target.parent.mkdir(parents=True, exist_ok=True)
341         shutil.copy2(src, target)
342         language = {"py": "Python", ".tex": "[LaTeX]TeX"}.get(src.suffix, "{}")
343         listing.append(f"\needspace{{6\baselineskip}}\subsection*{{\tex_path(rel)}}")
344         listing.append(f"\lstinputlisting[language={language}][{code}/{rel}]")
345     (generated / "code_listing.tex").write_text("\n".join(listing) + "\n", encoding="utf-8")
346
347     members = _support_members(ctx, planned=True)
348     rows = [
349         "% generated by forge — support material file list",
350         "\begin{longtable}{{0}{p{0.64\linewidth}p{0.32\linewidth}0{}}}",
351         "\toprule 文件 & 说明 \\\midrule \\\endhead \\\bottomrule \\\endfoot",
352     ]
353     rows += [f"{{\tex_path(name)}} & {{\tex_escape(_describe(name))}} \\\\" for name, _ in members]
354     rows.append("\end{longtable}")
355     (generated / "support_files.tex").write_text("\n".join(rows) + "\n", encoding="utf-8")
356     ctx.write_json("support_members.json", [name for name, _ in members])
357
358     stage_rows = _stage_rows(ctx)
359     repro = [
360         "% generated by forge — reproducibility record",
361         "\begin{longtable}{{0}{llrl0{}}}",
362         "\toprule 阶段 & 状态 & 用时/s & 输出摘要 (SHA-256 前 12 位) \\\midrule \\\endhead \\\bottomrule \\\endfoot",
363     ]
364     downstream = _downstream_of(ctx)
365     repro += [
366         f"\texttt{{\tex_escape(r['stage'])}} & {{_stage_status(ctx, r, downstream)}} & "
367         f"{{0.0 if r['stage'] in downstream or r['stage'] == ctx.stage else (r['duration_s'] or 0.0):.1f}} & "
368         f"\texttt{{{' ' if r['stage'] in downstream or r['stage'] == ctx.stage else r['outputs_digest'][:12]}}}} \\\\"
369         for r in stage_rows
370     ]
371     repro.append("\end{longtable}")
372     (generated / "repro_table.tex").write_text("\n".join(repro) + "\n", encoding="utf-8")
373
374     result = compile_tex(build, str(ctx.cfg("paper.main", "main.tex")), "main", passes=3, bibtex=True)
375     shutil.copy2(result["pdf"], ctx.out("main.pdf"))
376     shutil.copy2(result["log"], ctx.out("main.log"))
377     if result["aux"].exists():
378         shutil.copy2(result["aux"], ctx.out("main.aux"))
379     body_end = aux_page(result["aux"], "page:body-end")
380     abstract_end = aux_page(result["aux"], "page:abstract-end")
381     ai_summary = None
382     if (build / "ai_usage.tex").exists():
383         ai = compile_tex(build, "ai_usage.tex", "ai_usage", passes=2, bibtex=False)
384         shutil.copy2(ai["pdf"], ctx.out("AI工具使用详情.pdf"))
385         ai_summary = ai["summary"]

```

```

386 info = pdfqa.inspect_pdf(ctx.out("main.pdf"), with_text=False)
387 body_pages = (body_end - abstract_end) if body_end and abstract_end else None
388 report = {
389     "pages": info["pages"],
390     "all_a4": info["all_a4"],
391     "abstract_end_page": abstract_end,
392     "body_end_page": body_end,
393     "body_pages": body_pages,
394     "log": result["summary"],
395     "unembedded_fonts": info["unembedded_fonts"],
396     "fonts": info["fonts"],
397     "numbers": len(numbers),
398     "number_conflicts": conflicts,
399     "tables": n_tables,
400     "figures": n_figures,
401     "code_files": len(files),
402     "support_members": len(members),
403     "ai_usage_log": ai_summary,
404     "stages": stage_rows,
405 }
406 ctx.write_json("paper_report.json", report)
407 summary = result["summary"]
408 return {
409     "pages": info["pages"],
410     "body_pages": body_pages,
411     "undefined_refs": len(summary["undefined_references"]) + len(summary["undefined_citations"]),
412     "overfull_max_pt": summary["overfull_max_pt"],
413     "missing_chars": summary["missing_characters"],
414     "figures": n_figures,
415     "tables": n_tables,
416 }
417
418
419 @stage("qa", deps=("paper",), description="Quality gates over the compiled paper and the result workbooks")
420 def qa(ctx: StageContext) -> dict[str, Any]:
421     for required in ctx.cfg("qa.required_stages", ["lint", "test"]):
422         ctx.dep(required)
423     paper_dir = ctx.dep("paper")
424     report = json.loads((paper_dir / "paper_report.json").read_text(encoding="utf-8"))
425     checks: list[dict[str, Any]] = []
426
427     def check(name: str, ok: bool, detail: Any = "") -> None:
428         checks.append({"name": name, "ok": bool(ok), "detail": detail})
429         ctx.log.info("qa.check", name=name, ok=bool(ok), detail=detail)
430
431     max_body = int(ctx.cfg("paper.max_body_pages", 30))
432     check("abstract_single_page", report["abstract_end_page"] == 1, report["abstract_end_page"])
433     check(
434         "body_pages_within_limit",
435         report["body_pages"] is not None and report["body_pages"] <= max_body,
436         f"{report['body_pages']} <= {max_body}",
437     )
438     log = report["log"]
439     check(
440         "no_undefined_references",
441         not log["undefined_references"] and not log["undefined_citations"],
442         {"refs": log["undefined_references"][:10], "cites": log["undefined_citations"][:10]},
443     )
444     check("no_tex_errors", not log["errors"], log["errors"][:5])
445     check("fonts_embedded", not report["unembedded_fonts"], report["unembedded_fonts"])
446     check("a4_pages", report["all_a4"])
447     check(
448         "overfull_within_limit",

```

```

449     log["overfull_max_pt"] <= float(ctx.cfg("paper.max_overfull_pt", 20.0)),
450     f"max {log['overfull_max_pt']} pt, count {log['overfull_count']}",
451 )
452 check("no_missing_characters", log["missing_characters"] == 0, log["missing_character_samples"])
453 check("no_number_conflicts", not report["number_conflicts"], report["number_conflicts"][:5])
454 check("ai_usage_pdf_present", (paper_dir / "AI工具使用详情.pdf").exists())
455
456 info = pdfqa.inspect_pdf(paper_dir / "main.pdf", with_text=True)
457 deny_hits = pdfqa.scan_strings(info["texts"], ctx.cfg("qa.identity_denylist", []))
458 watch_hits = pdfqa.scan_strings(info["texts"], ctx.cfg("qa.identity_watchlist", []))
459 check("identity_denylist_clean", not deny_hits, deny_hits[:5])
460 check("paper_size_under_20mb", (paper_dir / "main.pdf").stat().st_size <= 20 * 1024 * 1024)
461
462 results_reports: list[dict[str, Any]] = []
463 results_stage = str(ctx.cfg("qa.results_stage", "results"))
464 require_results = bool(ctx.param("require_results", ctx.cfg("qa.require_results", True)))
465 if ctx.has_stage(results_stage):
466     contracts = importlib.import_module(f"pipelines.{ctx.project['package']}.contracts")
467     results_dir = ctx.run_dir / results_stage
468     for contract in contracts.RESULT_CONTRACTS:
469         rep = xlsx.check_workbook(results_dir / contract.file, contract, ctx.templates / contract.template)
470         results_reports.append(rep)
471         check(f"result:{contract.file}", rep["ok"], rep["errors"][:5])
472 else:
473     check("results_stage_present", not require_results, f"stage '{results_stage}' not completed in this run")
474
475 passed = all(c["ok"] for c in checks)
476 ctx.write_json(
477     "qa_report.json",
478     {
479         "passed": passed,
480         "checks": checks,
481         "identity_watchlist_hits": watch_hits,
482         "results": results_reports,
483         "paper": {k: v for k, v in report.items() if k != "fonts"},
484     },
485 )
486 if not passed:
487     raise RuntimeError("QA gate failed: " + ", ".join(c["name"] for c in checks if not c["ok"]))
488 return {"passed": passed, "checks": len(checks), "watchlist_hits": len(watch_hits)}
489
490
491 FIXED_STAGES = ("ingest", "validate", "lint", "test", "paper", "qa", "package", "release", "fmt")
492
493
494 def _science_stages(ctx: StageContext) -> list[str]:
495     """Stage names of this run that are neither intake nor gates -- the project's own scientific stages."""
496     return [r["stage"] for r in _stage_rows(ctx) if r["stage"] not in FIXED_STAGES]
497
498
499 def _reproduce_md(ctx: StageContext) -> str:
500     rows = _stage_rows(ctx)
501     code_ref = ctx.params.get("code_ref") or {}
502     manifest = json.loads((ctx.run_dir / "ingest" / "manifest.json").read_text(encoding="utf-8"))
503     packages = manifest.get("runtime", {}).get("packages", {})
504     lines = [
505         f"# 复现说明 (run `{ctx.run_id}`)",
506         "",
507         "本目录内所有结果均由 Modal 云端按下列阶段生成; 本地只提交任务、下载和核对 SHA-256。",
508         "",
509         f"- 代码版本: git `{code_ref.get('git_sha', '')}` (分支 `{code_ref.get('branch', '')}`)",
510         f"- 运行环境: Python {manifest.get('runtime', {}).get('python', '')}, "
511         f"{manifest.get('runtime', {}).get('platform', '')}",

```

```

512     "- 依赖版本: " + ", ".join(f"{k}=={v}" for k, v in sorted(packages.items())),
513     "",
514     "## 阶段",
515     "",
516     "| 阶段 | 状态 | 用时 (s) | 输出摘要 | Modal 任务 |",
517     "|---|---|---:|---|---|",
518 ]
519 lines += [
520     f"| {r['stage']} | {r['status']} | {r['duration_s'] or 0:.1f} | `{r['outputs_digest'][:16]}` | "
521     f"`{r['modal_task_id'] or ''}` | "
522     for r in rows
523 ]
524 lines += [
525     "",
526     "## 复现命令",
527     "",
528     "### A. 云端 (本文使用的方式, 需要 Modal 账号) ",
529     "",
530     "```bash",
531     "python3 tools/cli.py provision",
532     "python3 tools/cli.py run ingest,validate --new-run",
533     *[f"python3 tools/cli.py run {r['stage']} --size medium" for r in rows if r["stage"] not in _BOOT_STAGES],
534     "python3 tools/cli.py release --version <tag>",
535     "```",
536     "",
537     "各阶段的确切参数 (线程数、逐级时限) 见每个阶段目录下 `manifest.json` 的 `params` 字段, ",
538     "以及 `docs/RUNBOOK.md` 第 7 节。",
539     "",
540     "### B. 本地 (不需要任何云端账号) ",
541     "",
542     "```bash",
543     "pip install pandas numpy openpyxl pyarrow networkx matplotlib ortools highspy",
544     "python3 tools/run_local.py --quick          # 数分钟, 得到 result1-4.xlsx、图与表",
545     "python3 tools/run_local.py                  # 使用默认 (较大) 预算",
546     "```",
547     "",
548     "本地驱动脚本调用的是同一批阶段函数, 只是把云端卷换成本地目录; ",
549     "附件需按原样放在 `附件/` 下。论文排版阶段 (paper/qa/package/release) 需要 TeX Live 与中文字体, ",
550     "不在本地默认序列中。",
551     "",
552     "每个阶段目录下的 `manifest.json` 记录输入、输出散列、参数与环境; `events.jsonl` 为结构化日志。",
553     "",
554 ]
555 return "\n".join(lines)
556
557
558 @stage("package", deps=("qa",), description="Build the deterministic support-materials zip and its member manifest")
559 def package(ctx: StageContext) -> dict[str, Any]:
560     planned = set(json.loads((ctx.dep("paper") / "support_members.json").read_text(encoding="utf-8")))
561     ctx.out("REPRODUCE.md").write_text(_reproduce_md(ctx), encoding="utf-8")
562     members = [(name, path) for name, path in _support_members(ctx, planned=False) if name != "MANIFEST.json"]
563     missing = [name for name, path in members if not path.exists()]
564     if missing:
565         raise RuntimeError(f"support members missing on disk: {missing[:10]}")
566     actual = {name for name, _ in members} | {"MANIFEST.json"}
567     drift = sorted(actual ^ planned)
568     if drift and not ctx.param("allow_member_drift"):
569         raise RuntimeError(f"support material members differ from the list printed in the paper: {drift[:20]}")
570     manifest = {
571         "run_id": ctx.run_id,
572         "created_at": datetime.now(UTC).isoformat(timespec="seconds"),
573         "members": [
574             {"path": name, "sha256": sha256_file(path), "bytes": path.stat().st_size} for name, path in members

```

```

575     ],
576 }
577 manifest_path = ctx.out("MANIFEST.json")
578 manifest_path.write_text(json.dumps(manifest, ensure_ascii=False, indent=2), encoding="utf-8")
579 members.append(("MANIFEST.json", manifest_path))
580 zip_info = packaging.build_zip(members, ctx.out("支撑材料.zip"), comment=f"forge run {ctx.run_id}")
581 limit = int(ctx.cfg("package.max_bytes", 20 * 1024 * 1024))
582 ctx.write_json("package_report.json", {**zip_info, "limit_bytes": limit, "drift": drift})
583 if zip_info["bytes"] > limit:
584     raise RuntimeError(f"support zip {zip_info['bytes']} bytes exceeds limit {limit}")
585 return {"members": zip_info["members"], "bytes": zip_info["bytes"], "drift": len(drift)}
586
587
588 @stage(
589     "release",
590     deps=("package",),
591     description="Assemble deliverables (paper, result workbooks, support zip) with SHA-256 manifest",
592 )
593 def release(ctx: StageContext) -> dict[str, Any]:
594     qa_report = json.loads((ctx.dep("qa") / "qa_report.json").read_text(encoding="utf-8"))
595     if not qa_report["passed"] and not ctx.param("allow_failed_qa"):
596         raise RuntimeError("release refused: QA gate did not pass")
597     paper_dir = ctx.dep("paper")
598     files: dict[str, Path] = {str(ctx.cfg("release.paper_name", "论文.pdf")): paper_dir / "main.pdf"}
599     results_stage = str(ctx.cfg("qa.results_stage", "results"))
600     if ctx.has_stage(results_stage):
601         for name in ctx.project.get("result_files", []):
602             files[name] = ctx.run_dir / results_stage / name
603     elif not ctx.param("allow_missing_results"):
604         raise RuntimeError("release refused: results stage missing")
605     files["支撑材料.zip"] = ctx.dep("package") / "支撑材料.zip"
606     files["AI工具使用详情.pdf"] = paper_dir / "AI工具使用详情.pdf"
607     manifest: dict[str, Any] = {
608         "run_id": ctx.run_id,
609         "code_ref": ctx.params.get("code_ref"),
610         "files": {},
611         "qa_passed": qa_report["passed"],
612         "created_at": datetime.now(UTC).isoformat(timespec="seconds"),
613     }
614     for name, source in files.items():
615         if not source.exists():
616             raise RuntimeError(f"release file missing: {name} ({source})")
617         target = ctx.out(name)
618         shutil.copy2(source, target)
619         manifest["files"][name] = {"sha256": sha256_file(target), "bytes": target.stat().st_size}
620     notes = [
621         f"# 发布说明 — run {ctx.run_id}",
622         "",
623         f"- 代码: `{ctx.params.get('code_ref') or {}}.get('git_sha', '')}`",
624         f"- QA: {'通过' if qa_report['passed'] else '未通过 (强制发布)'}",
625         "",
626         "| 文件 | 字节 | SHA-256 |",
627         "|---|---:|---|",
628     ]
629     notes += [f"| {n} | {m['bytes']} | `{m['sha256']}`" for n, m in manifest["files"].items()]
630     ctx.out("RELEASE_NOTES.md").write_text("\n".join(notes) + "\n", encoding="utf-8")
631     ctx.write_json("release_manifest.json", manifest)
632     return {
633         "files": len(files),
634         "paper_bytes": manifest["files"][str(ctx.cfg("release.paper_name", "论文.pdf"))]["bytes"],
635     }
636
637

```

```

638 FMT_IGNORE = (".git", "artifacts", "releases", "__pycache__", ".forge", ".DS_Store", ".mypy_cache", ".ruff_cache")
639
640
641 @stage("fmt", description="ruff --fix and ruff format in the cloud; changed files are exported for a local copy-back")
642 def fmt(ctx: StageContext) -> dict[str, Any]:
643     work = Path("/tmp/fmt")
644     shutil.rmtree(work, ignore_errors=True)
645     shutil.copytree(ctx.repo, work, ignore=shutil.ignore_patterns(*FMT_IGNORE, "*.pyc"))
646     before = hash_tree(work, ignore=FMT_IGNORE)
647     fix = subprocess.run(
648         ["ruff", "check", "--fix", "--no-cache", "--output-format", "concise", "."],
649         cwd=work,
650         capture_output=True,
651         text=True,
652         check=False,
653     )
654     form = subprocess.run(["ruff", "format", "--no-cache", "."], cwd=work, capture_output=True, text=True, check=False)
655     after = hash_tree(work, ignore=FMT_IGNORE)
656     changed = sorted(rel for rel in after if rel not in before or after[rel]["sha256"] != before[rel]["sha256"])
657     for rel in changed:
658         shutil.copy2(work / rel, ctx.out("files", rel))
659     ctx.out("ruff_fix.txt").write_text(fix.stdout + fix.stderr, encoding="utf-8")
660     ctx.out("ruff_format.txt").write_text(form.stdout + form.stderr, encoding="utf-8")
661     ctx.write_json("fmt_report.json", {"changed": changed, "remaining": fix.stdout.strip().splitlines()[-1:]})
662     ctx.log.info("fmt.done", changed=len(changed), remaining=fix.stdout.strip().splitlines()[-1:])
663     return {"changed": len(changed)}

```

pipelines/common/validation.py

```

1  """Shared implementation of the ``validate`` stage (input data contracts + profiling)."""
2
3  from __future__ import annotations
4
5  from typing import Any
6
7  import pandas as pd
8
9  from forge.context import StageContext
10 from forge.contracts import FrameContract, normalise_columns, validate_frame
11
12
13 def run_validation(ctx: StageContext, contracts: dict[str, FrameContract]) -> dict[str, Any]:
14     """Validate every ingested parquet named in ``contracts`` (key = parquet stem)."""
15     data_dir = ctx.dep("ingest") / "data"
16     reports: list[dict[str, Any]] = []
17     profile: dict[str, Any] = {}
18     for stem, contract in contracts.items():
19         path = data_dir / f"{stem}.parquet"
20         if not path.exists():
21             reports.append({"contract": contract.name, "ok": False, "errors": [f"parquet missing: {stem}"], "rows": 0})
22             continue
23         df = normalise_columns(pd.read_parquet(path))
24         report = validate_frame(df, contract)
25         report["parquet"] = path.name
26         reports.append(report)
27         desc = df.describe(include="all").astype(str).to_dict()
28         profile[stem] = {
29             "rows": len(df),
30             "columns": list(df.columns),
31             "describe": desc,
32             "nulls": {c: int(df[c].isna().sum()) for c in df.columns},

```

```

33     }
34     ctx.log.info(
35         "validate.frame", contract=contract.name, ok=report["ok"], rows=report["rows"], errors=report["errors"][:5]
36     )
37     ok = all(r["ok"] for r in reports)
38     ctx.write_json("validation_report.json", {"ok": ok, "frames": reports})
39     ctx.write_json("data_profile.json", profile)
40     if not ok:
41         failed = [r["contract"] for r in reports if not r["ok"]]
42         raise RuntimeError(f"input contracts violated: {failed}")
43     return {"ok": ok, "frames": len(reports)}

```

pipelines/e/__init__.py

pipelines/e/allocate.py

```

1  """Problem 3/4 budget allocation: separable concave program, exact water-filling solver, independent verifier."""
2
3  from __future__ import annotations
4
5  from typing import Any
6
7  import numpy as np
8
9
10 def water_filling(a: np.ndarray, gamma: float, caps: np.ndarray, budget: float, tol: float = 1e-12) -> np.ndarray:
11     """maximise sum_i a_i x_i^gamma s.t. sum_i x_i <= budget, 0 <= x_i <= caps_i (0 < gamma < 1, a_i > 0).
12
13     KKT: gamma a_i x_i^(gamma-1) = lambda on interior coordinates, x_i = cap_i where the marginal at the
14     cap still exceeds lambda. The map lambda -> sum_i min(cap_i, (gamma a_i / lambda)^(1/(1-gamma))) is
15     strictly decreasing, so lambda is found by bisection; the solution is the unique global optimum.
16     """
17     a = np.asarray(a, dtype=float)
18     caps = np.asarray(caps, dtype=float)
19     if len(a) == 0 or budget <= 0:
20         return np.zeros_like(a)
21     return _bounded_water_filling(a, gamma, np.zeros_like(a), caps, budget, tol)
22
23
24 def _bounded_water_filling(
25     a: np.ndarray, gamma: float, lower: np.ndarray, caps: np.ndarray, budget: float, tol: float = 1e-12
26 ) -> np.ndarray:
27     """Exact solution of max sum a_i x_i^gamma s.t. sum x_i = budget, lower_i <= x_i <= caps_i (fixed set)."""
28     expo = 1.0 / (1.0 - gamma)
29     if caps.sum() <= budget:
30         return caps.copy()
31     if lower.sum() >= budget:
32         return lower.copy()
33
34     def total(lam: float) -> np.ndarray:
35         with np.errstate(over="ignore", divide="ignore", invalid="ignore"):
36             raw = np.power(gamma * a / lam, expo)
37             return np.clip(np.nan_to_num(raw, nan=0.0, posinf=np.inf), lower, caps)
38
39     lo, hi = 1e-300, 1.0
40     while total(hi).sum() > budget:
41         hi *= 4.0

```

```

42     for _ in range(400):
43         mid = np.sqrt(lo * hi)
44         if total(mid).sum() > budget:
45             lo = mid
46         else:
47             hi = mid
48         if hi / lo - 1.0 < tol:
49             break
50     x = total(np.sqrt(lo * hi))
51     free = (x > lower + 1e-12) & (x < caps - 1e-12)
52     gap = budget - x.sum()
53     if abs(gap) > 1e-9 and free.any(): # exact budget balance on the free coordinates
54         x[free] += gap * x[free] / max(x[free].sum(), 1e-300)
55     return np.clip(x, lower, caps)
56
57
58 def solve_group(
59     w: np.ndarray,
60     s: np.ndarray,
61     gamma: float,
62     caps: np.ndarray,
63     budget: float,
64     min_spend: float = 0.5,
65     tol: float = 1e-12,
66 ) -> dict[str, Any]:
67     """Allocate ``budget`` over keywords with value weights ``w`` (objective sum  $w_i (x_i/s_i)^\gamma$ ).
68
69     With ``min_spend`` = m > 0 every keyword is either not selected ( $x_i = 0$ ) or receives at least m,
70     i.e.  $x_i$  in  $\{0\} \cup [m, \text{cap}_i]$ . This non-convex selection problem is solved in two phases:
71     (1) Lagrangian relaxation -- for a budget price lambda each keyword takes
72      $x_i(\text{lambda}) = \text{clip}((\gamma a_i / \text{lambda})^{1/(1-\gamma)}, m, \text{cap}_i)$  and is selected iff its value
73     covers the price,  $a_i x_i^\gamma \geq \text{lambda} x_i$ ; total spend is non-increasing in lambda, so the
74     price is found by bisection and fixes the selected set; (2) the convex problem restricted to the
75     selected set with lower bound m is solved exactly (bounded water filling), so the KKT conditions
76     hold exactly on that set. The convex relaxation (m = 0) bounds the optimum from above and is used
77     by the verifier as an optimality certificate.
78     """
79     w = np.asarray(w, dtype=float)
80     s = np.asarray(s, dtype=float)
81     caps = np.asarray(caps, dtype=float)
82     a = w * np.power(s, -gamma)
83     n = len(a)
84     x = np.zeros(n)
85     if n == 0 or budget <= 0:
86         return {"x": x, "selected": x > 0, "objective": 0.0, "spent": 0.0, "budget": float(budget), "n_selected": 0}
87     positive = a > 0
88     if budget < min_spend: # not even one keyword can receive the minimum practical amount
89         return {"x": x, "selected": x > 0, "objective": 0.0, "spent": 0.0, "budget": float(budget), "n_selected": 0}
90     if min_spend <= 0:
91         x[positive] = water_filling(a[positive], gamma, caps[positive], budget, tol)
92     else:
93         m = float(min_spend)
94         caps_eff = np.maximum(caps, m)
95         expo = 1.0 / (1.0 - gamma)
96
97         def allocation(lam: float) -> np.ndarray:
98             with np.errstate(over="ignore", divide="ignore", invalid="ignore"):
99                 interior = np.power(gamma * a / lam, expo)
100                 xx = np.clip(np.nan_to_num(interior, nan=0.0, posinf=np.inf), m, caps_eff)
101                 include = positive & (a * np.power(xx, gamma) >= lam * xx)
102                 return np.where(include, xx, 0.0)
103
104         full = np.where(positive, caps_eff, 0.0)

```

```

105     if full.sum() <= budget:
106         x = full
107     else:
108         lo, hi = 1e-300, 1.0
109         while allocation(hi).sum() > budget:
110             hi *= 4.0
111         for _ in range(400):
112             mid = np.sqrt(lo * hi)
113             if allocation(mid).sum() > budget:
114                 lo = mid
115             else:
116                 hi = mid
117             if hi / lo - 1.0 < tol:
118                 break
119         chosen = allocation(hi) > 0
120         if not chosen.any():
121             chosen = allocation(lo) > 0
122         k = int(chosen.sum())
123         x[chosen] = _bounded_water_filling(a[chosen], gamma, np.full(k, m), caps_eff[chosen], budget, tol)
124     objective = float(np.sum(a * np.power(x, gamma)))
125     return {
126         "x": x,
127         "selected": x > 0,
128         "objective": objective,
129         "spent": float(x.sum()),
130         "budget": float(budget),
131         "n_selected": int((x > 0).sum()),
132     }
133
134
135 def objective_value(x: np.ndarray, a: np.ndarray, gamma: float) -> float:
136     return float(np.sum(a * np.power(np.maximum(x, 0.0), gamma)))
137
138
139 def verify_allocation(
140     x: np.ndarray,
141     a: np.ndarray,
142     gamma: float,
143     caps: np.ndarray,
144     budget: float,
145     rng: np.random.Generator,
146     floor: float = 0.0,
147     kkt_tol: float = 1e-6,
148     price_tol: float = 0.05,
149     n_transfers: int = 200,
150     bound_tol: float = 0.05,
151 ) -> dict[str, Any]:
152     """Independent optimality audit of an allocation (does not use the solver).
153
154     Feasibility ( $x_i = 0$  or  $\text{floor} \leq x_i \leq \text{cap}_i$ , budget); KKT conditions (equal marginal value on
155     interior coordinates, marginal at capped coordinates not smaller, average value at floored
156     coordinates covering the price up to ``price_tol``); random pairwise transfers, removals and
157     insertions never improve the objective; and, when cvxpy is available, the convex relaxation
158     (no floor) solved by a generic solver bounds the objective from above -- the relative gap is an
159     optimality certificate (not informative for budgets of a few floor units, which are flagged).
160     """
161     x = np.asarray(x, dtype=float)
162     a = np.asarray(a, dtype=float)
163     caps = np.asarray(caps, dtype=float)
164     caps_eff = np.maximum(caps, floor)
165     checks: list[dict[str, Any]] = []
166     sel = x > 0
167     checks.append({"name": "nonnegative", "ok": bool((x >= -1e-9).all())})

```

```

168 checks.append({"name": "within_caps", "ok": bool((x <= caps_eff + 1e-6).all())})
169 checks.append({"name": "floor_respected", "ok": bool((x[sel] >= floor - 1e-6).all())})
170 spent = float(x.sum())
171 checks.append({"name": "budget_respected", "ok": bool(spent <= budget + 1e-6 * max(1.0, budget)), "spent": spent})
172 all_capped = np.where(a > 0, caps_eff, 0.0).sum() <= budget + 1e-9
173 exhausted = abs(spent - budget) <= 1e-6 * max(1.0, budget)
174 # with a floor the budget may be unattainable: every selected keyword sits at its cap and the rest < floor
175 stuck = floor > 0 and (budget - spent) < floor + 1e-9 and bool(np.all(x[sel] >= caps_eff[sel] - 1e-6))
176 checks.append({"name": "budget_exhausted_or_all_capped", "ok": bool(all_capped or exhausted or stuck)})
177 marg = np.full(len(x), np.nan)
178 marg[sel] = gamma * a[sel] * np.power(x[sel], gamma - 1.0)
179 avg = np.full(len(x), np.nan)
180 avg[sel] = a[sel] * np.power(x[sel], gamma - 1.0)
181 at_cap = x >= caps_eff - 1e-9
182 at_floor = (x <= floor + 1e-9) & (floor > 0)
183 both = sel & at_cap & at_floor # cap below the floor: both bounds active, only the selection rule applies
184 capped = sel & at_cap & ~at_floor
185 floored = sel & at_floor & ~at_cap
186 interior = sel & ~at_cap & ~at_floor
187 spread = float(np.nanmax(marg[interior]) / np.nanmin(marg[interior]) - 1.0) if interior.sum() >= 2 else 0.0
188 checks.append({"name": "kkt_equal_marginals_interior", "ok": spread <= kkt_tol, "relative_spread": spread})
189 # shadow price: with interior coordinates it is their common marginal value; otherwise any price
190 # between the largest floored marginal and the smallest capped marginal satisfies the KKT system
191 lam_low = float(np.nanmax(marg[floored])) if floored.any() else 0.0
192 lam_high = float(np.nanmin(marg[capped])) if capped.any() else float("inf")
193 if interior.any():
194     lam = float(np.nanmedian(marg[interior]))
195     cap_ok = not capped.any() or bool(np.all(marg[capped] >= lam * (1 - kkt_tol)))
196     floor_marg_ok = not floored.any() or bool(np.all(marg[floored] <= lam * (1 + kkt_tol)))
197     floor_avg_ok = not (floored | both).any() or bool(np.all(avg[floored | both] >= lam * (1 - price_tol)))
198 else:
199     lam = lam_low if np.isfinite(lam_high) is False else min(lam_high, max(lam_low, 0.0))
200     cap_ok = lam_low <= lam_high * (1 + kkt_tol)
201     floor_marg_ok = True
202     floor_avg_ok = not (floored | both).any() or bool(np.all(avg[floored | both] >= lam_low * (1 - price_tol)))
203 checks.append({"name": "kkt_capped_marginal_not_smaller", "ok": bool(cap_ok)})
204 checks.append({"name": "kkt_floored_marginal_not_larger", "ok": bool(floor_marg_ok)})
205 checks.append({"name": "kkt_floored_average_value_covers_price", "ok": bool(floor_avg_ok)})
206 base = objective_value(x, a, gamma)
207 idx = np.flatnonzero(sel)
208 improved = 0
209 if len(idx) >= 2:
210     for _ in range(n_transfers):
211         i, j = rng.choice(idx, size=2, replace=False)
212         y = x.copy()
213         if rng.random() < 0.3: # remove keyword i entirely and hand its money to j
214             delta = min(x[i], caps_eff[j] - x[j])
215             if delta < x[i] - 1e-12 and x[i] - delta < floor - 1e-12:
216                 continue
217         else:
218             delta = min(x[i] - floor, caps_eff[j] - x[j]) * rng.uniform(0.01, 0.5)
219             if delta <= 0:
220                 continue
221             y[i] -= delta
222             y[j] += delta
223             if objective_value(y, a, gamma) > base * (1 + 1e-9):
224                 improved += 1
225 checks.append({"name": "no_improving_transfer_or_removal", "ok": improved == 0, "improving_moves": improved})
226 inserted = 0
227 out_idx = np.flatnonzero(~sel & (a > 0))
228 if len(out_idx) and floor > 0 and interior.any(): # insert an unselected keyword at the floor
229     donors = np.flatnonzero(interior)
230     slack = price_tol * floor / max(budget, floor) # phase-1 price and phase-2 price differ slightly

```

```

231     for k in rng.choice(out_idx, size=min(len(out_idx), 50), replace=False):
232         take = floor * x[donors] / x[donors].sum()
233         if np.any(x[donors] - take < floor):
234             continue
235         y = x.copy()
236         y[donors] -= take
237         y[k] = floor
238         if objective_value(y, a, gamma) > base * (1 + slack):
239             inserted += 1
240     checks.append({"name": "no_improving_insertion", "ok": inserted == 0, "improving_insertions": inserted})
241     cvx: dict[str, Any] = {"available": False}
242     try:
243         import cvxpy as cp
244
245         n = len(x)
246         if n <= 1500:
247             var = cp.Variable(n, nonneg=True)
248             objective = cp.Maximize(cp.sum(cp.multiply(a, cp.power(var, gamma))))
249             prob = cp.Problem(objective, [cp.sum(var) <= budget, var <= caps_eff])
250             prob.solve(solver=cp.CLARABEL)
251             if var.value is not None:
252                 relaxed = objective_value(np.asarray(var.value).ravel(), a, gamma)
253                 gap = float((relaxed - base) / max(abs(base), 1e-12))
254                 tiny = floor > 0 and budget <= 20 * floor
255                 cvx = {"available": True, "status": prob.status, "relaxed_objective": relaxed, "relative_gap": gap}
256                 tol = bound_tol if floor > 0 else 1e-4
257                 checks.append(
258                     {
259                         "name": "within_convex_relaxation_bound",
260                         "ok": bool(gap <= tol or tiny),
261                         "relative_gap": gap,
262                         "tiny_budget": bool(tiny),
263                     }
264                 )
265     except Exception as exc: # pragma: no cover - solver availability differs across environments
266         cvx = {"available": False, "error": repr(exc)}
267     return {
268         "ok": all(c["ok"] for c in checks),
269         "checks": checks,
270         "objective": base,
271         "n_selected": int(sel.sum()),
272         "n_capped": int(capped.sum()),
273         "n_floored": int(floored.sum()),
274         "n_both_bounds": int(both.sum()),
275         "cvxpy": cvx,
276     }
277
278
279 def proportional_allocation(s: np.ndarray, budget: float) -> np.ndarray:
280     """Historical-practice baseline: spend split in proportion to each keyword's mean daily spend."""
281     s = np.asarray(s, dtype=float)
282     return budget * s / s.sum() if s.sum() > 0 else np.zeros_like(s)
283
284
285 def equal_allocation(n: int, budget: float) -> np.ndarray:
286     return np.full(n, budget / n) if n else np.zeros(0)

```

pipelines/e/calendar.py

```
1 """Statutory holiday calendar (State Council notice for 2025) and per-day calendar features."""
2
3 from __future__ import annotations
4
5 from typing import Any
6
7 import pandas as pd
8
9 # (first day, last day) of every statutory holiday block in 2025, inclusive.
10 HOLIDAY_BLOCKS: dict[str, tuple[str, str]] = {
11     "元旦": ("2025-01-01", "2025-01-01"),
12     "春节": ("2025-01-28", "2025-02-04"),
13     "清明节": ("2025-04-04", "2025-04-06"),
14     "劳动节": ("2025-05-01", "2025-05-05"),
15     "端午节": ("2025-05-31", "2025-06-02"),
16     "国庆节中秋节": ("2025-10-01", "2025-10-08"),
17 }
18
19 # Weekend days declared working days to compensate for the long holidays (调休).
20 ADJUSTED_WORKDAYS: tuple[str, ...] = ("2025-01-26", "2025-02-08", "2025-04-27", "2025-09-28", "2025-10-11")
21 WEEKDAY_NAMES: tuple[str, ...] = ("周一", "周二", "周三", "周四", "周五", "周六", "周日")
22
23 def holiday_map() -> dict[pd.Timestamp, str]:
24     """Every statutory holiday date -> holiday name."""
25     out: dict[pd.Timestamp, str] = {}
26     for name, (start, end) in HOLIDAY_BLOCKS.items():
27         for day in pd.date_range(start, end, freq="D"):
28             out[day] = name
29     return out
30
31
32 def day_features(dates: Any) -> pd.DataFrame:
33     """Calendar covariates for a sequence of dates (weekday, month, holiday flags, day type)."""
34     idx = pd.DatetimeIndex(pd.to_datetime(dates)).normalize()
35     holidays = holiday_map()
36     adjusted = {pd.Timestamp(d) for d in ADJUSTED_WORKDAYS}
37     starts = {pd.Timestamp(s) for s, _ in HOLIDAY_BLOCKS.values()}
38     ends = {pd.Timestamp(e) for _, e in HOLIDAY_BLOCKS.values()}
39     one = pd.Timedelta(days=1)
40     rows: list[dict[str, Any]] = []
41     for day in idx:
42         weekday = int(day.dayofweek)
43         is_holiday = day in holidays
44         is_adjusted = day in adjusted
45         is_weekend = weekday >= 5
46         if is_holiday:
47             day_type = "holiday"
48         elif is_adjusted:
49             day_type = "adjusted_workday"
50         elif is_weekend:
51             day_type = "weekend"
52         else:
53             day_type = "workday"
54         rows.append(
55             {
56                 "date": day,
57                 "weekday": weekday,
58                 "weekday_name": WEEKDAY_NAMES[weekday],
59                 "month": int(day.month),
60                 "day_of_year": int(day.dayofyear),
61                 "is_weekend": is_weekend,
```

```

62         "is_holiday": is_holiday,
63         "holiday_name": holidays.get(day, ""),
64         "is_adjusted_workday": is_adjusted,
65         "is_pre_holiday": (day + one) in starts,
66         "is_post_holiday": (day - one) in ends,
67         "is_workday": day_type in {"workday", "adjusted_workday"},
68         "day_type": day_type,
69     }
70 )
71 return pd.DataFrame(rows)

```

pipelines/e/classify.py

```

1  """Problem 2: cost/benefit keyword classification (composite benefit index, transparent thresholds, checker)."""
2
3  from __future__ import annotations
4
5  from typing import Any
6
7  import numpy as np
8  import pandas as pd
9
10 LABELS: tuple[str, ...] = ("黄金词", "重点词", "潜力词", "问题词", "无效词")
11 BENEFIT_COMPONENTS: tuple[str, ...] = ("clicks", "views", "engagement", "reg_attr")
12
13
14 def minmax(x: np.ndarray) -> np.ndarray:
15     lo, hi = float(np.min(x)), float(np.max(x))
16     if hi - lo <= 1e-12:
17         return np.zeros_like(x, dtype=float)
18     return (x - lo) / (hi - lo)
19
20
21 def entropy_weights(X: np.ndarray) -> np.ndarray:
22     """Entropy weight method on a non-negative matrix (rows = items, columns = criteria)."""
23     X = np.asarray(X, dtype=float)
24     n, m = X.shape
25     weights = np.zeros(m)
26     for j in range(m):
27         col = minmax(X[:, j])
28         total = col.sum()
29         if total <= 0:
30             continue
31         p = col / total
32         with np.errstate(divide="ignore", invalid="ignore"):
33             e = -np.nansum(np.where(p > 0, p * np.log(p), 0.0)) / np.log(n)
34         weights[j] = 1.0 - e
35     if weights.sum() <= 0:
36         return np.full(m, 1.0 / m)
37     return weights / weights.sum()
38
39
40 def benefit_components(kw: pd.DataFrame, rates: dict[int, float]) -> pd.DataFrame:
41     """Log-scaled benefit components: clicks, views, engagement (attention seconds), attributed registrations."""
42     reg_attr = kw["clicks"].to_numpy(dtype=float) * kw["推广单元ID"].map(rates).fillna(0.0).to_numpy(dtype=float)
43     comp = pd.DataFrame(
44         {
45             "clicks": np.log1p(kw["clicks"].to_numpy(dtype=float)),
46             "views": np.log1p(kw["views"].to_numpy(dtype=float)),
47             "engagement": np.log1p(kw["engagement"].to_numpy(dtype=float)),
48             "reg_attr": np.log1p(reg_attr),

```

```

49     },
50     index=kw.index,
51 )
52 comp["reg_attr_raw"] = reg_attr
53 return comp
54
55
56 def benefit_index(comp: pd.DataFrame, weights: np.ndarray | None = None) -> tuple[pd.Series, np.ndarray]:
57     """Weighted sum of min-max normalised components (entropy weights unless given)."""
58     X = comp[list(BENEFIT_COMPONENTS)].to_numpy(dtype=float)
59     w = entropy_weights(X) if weights is None else np.asarray(weights, dtype=float)
60     normed = np.column_stack([minmax(X[:, j]) for j in range(X.shape[1])])
61     return pd.Series(normed @ w, index=comp.index, name="benefit"), w
62
63
64 def jenks_break(x: np.ndarray) -> float:
65     """Exact two-class Fisher/Jenks natural break (minimum within-class sum of squares)."""
66     xs = np.sort(np.asarray(x, dtype=float))
67     n = len(xs)
68     if n < 2:
69         return float(xs[0]) if n else 0.0
70     cs = np.cumsum(xs)
71     cs2 = np.cumsum(xs**2)
72     k = np.arange(1, n) # left class = xs[:k]
73     left = cs2[k - 1] - cs[k - 1] ** 2 / k
74     right = (cs2[-1] - cs2[k - 1]) - (cs[-1] - cs[k - 1]) ** 2 / (n - k)
75     best = int(np.argmin(left + right))
76     return float(0.5 * (xs[best] + xs[best + 1]))
77
78
79 def gmm_break(x: np.ndarray, seed: int) -> float:
80     """Threshold where the two-component Gaussian mixture posterior crosses 0.5 between the component means."""
81     from sklearn.mixture import GaussianMixture
82
83     xs = np.asarray(x, dtype=float).reshape(-1, 1)
84     gm = GaussianMixture(n_components=2, random_state=seed, n_init=3).fit(xs)
85     means = gm.means_.ravel()
86     lo, hi = float(means.min()), float(means.max())
87     grid = np.linspace(lo, hi, 2001).reshape(-1, 1)
88     post = gm.predict_proba(grid[:, int(np.argmax(means))])
89     idx = int(np.argmax(post >= 0.5))
90     return float(grid[idx, 0])
91
92
93 def threshold(x: np.ndarray, method: str, seed: int = 0) -> float:
94     if method == "median":
95         return float(np.median(x))
96     if method == "jenks":
97         return jenks_break(x)
98     if method == "gmm":
99         return gmm_break(x, seed)
100     raise ValueError(f"unknown threshold method {method!r}")
101
102
103 def assign_labels(kw: pd.DataFrame, benefit: pd.Series, cost_thr: float, benefit_thr: float) -> pd.Series:
104     """Five-way labels: invalid (no spend, no clicks), else the quadrant of (log10 cost > cost_thr, benefit >= thr)."""
105     invalid = (kw["spend"] <= 0) & (kw["clicks"] <= 0)
106     high_cost = np.log10(kw["spend"].clip(lower=1e-9)) > cost_thr
107     high_benefit = benefit >= benefit_thr
108     labels = np.select(
109         [
110             invalid,
111             ~high_cost & high_benefit,

```

```

112         high_cost & high_benefit,
113         ~high_cost & ~high_benefit,
114         high_cost & ~high_benefit,
115     ],
116     ["无效词", "黄金词", "重点词", "潜力词", "问题词"],
117     default="问题词",
118 )
119 return pd.Series(labels, index=kw.index, name="label")
120
121
122 def classify_keywords(
123     kw: pd.DataFrame, rates: dict[int, float], methods: tuple[str, ...], main: str, seed: int
124 ) -> dict[str, Any]:
125     """Full classification with every threshold method; ``main`` selects the reported labels."""
126     comp = benefit_components(kw, rates)
127     benefit, weights = benefit_index(comp)
128     benefit_equal, _ = benefit_index(comp, np.full(len(BENEFIT_COMPONENTS), 1.0 / len(BENEFIT_COMPONENTS)))
129     active = kw["spend"] > 0
130     log_cost = np.log10(kw.loc[active, "spend"].to_numpy(dtype=float))
131     thresholds: dict[str, dict[str, float]] = {}
132     labels: dict[str, pd.Series] = {}
133     for method in methods:
134         ct = threshold(log_cost, method, seed)
135         bt = threshold(benefit[active].to_numpy(dtype=float), method, seed)
136         thresholds[method] = {"log10_cost": ct, "cost_yuan": float(10**ct), "benefit": bt}
137         labels[method] = assign_labels(kw, benefit, ct, bt)
138     out = kw[
139         ["序号", "关键词", "方案ID", "推广单元ID", "spend", "clicks", "views", "bounce", "duration_s", "engagement"]
140     ].copy()
141     out["reg_attr"] = comp["reg_attr_raw"]
142     out["benefit"] = benefit
143     out["benefit_equal"] = benefit_equal
144     out["log10_cost"] = np.log10(kw["spend"].clip(lower=1e-9))
145     for method in methods:
146         out[f"label_{method}"] = labels[method]
147     out["label"] = labels[main]
148     agreement = {f"{a}_vs_{b}": float((labels[a] == labels[b]).mean()) for a in methods for b in methods if a < b}
149     agreement["entropy_vs_equal_spearman"] = float(benefit[active].corr(benefit_equal[active], method="spearman"))
150     # equal-weight benefit with the main thresholds re-derived: sensitivity of labels to the weighting
151     bt_equal = threshold(benefit_equal[active].to_numpy(dtype=float), main, seed)
152     labels_equal = assign_labels(kw, benefit_equal, thresholds[main]["log10_cost"], bt_equal)
153     agreement[f"{main}_vs_equal_weights"] = float((labels[main] == labels_equal).mean())
154     out["label_equal_weights"] = labels_equal
155     counts = {m: labels[m].value_counts().reindex(LABELS, fill_value=0).astype(int).to_dict() for m in methods}
156     counts["equal_weights"] = labels_equal.value_counts().reindex(LABELS, fill_value=0).astype(int).to_dict()
157     thresholds["equal_weights"] = {
158         "log10_cost": thresholds[main]["log10_cost"],
159         "cost_yuan": thresholds[main]["cost_yuan"],
160         "benefit": bt_equal,
161     }
162     return {
163         "table": out,
164         "weights": dict(zip(BENEFIT_COMPONENTS, [float(w) for w in weights])),
165         "thresholds": thresholds,
166         "agreement": agreement,
167         "counts": counts,
168         "main": main,
169     }
170
171
172 def verify_classification(
173     table: pd.DataFrame, cost_thr_log10: float, benefit_thr: float, label_col: str = "label"
174 ) -> dict[str, Any]:

```

```

175     """Independent re-derivation of every label from raw columns; returns a report with ``ok``."""
176     checks: list[dict[str, Any]] = []
177     lab = table[label_col]
178     checks.append({"name": "labels_in_vocabulary", "ok": bool(lab.isin(LABELS).all())})
179     invalid_expected = (table["spend"] <= 0) & (table["clicks"] <= 0)
180     invalid_ok = bool(((lab == "无效词") == invalid_expected).all())
181     checks.append({"name": "invalid_iff_no_spend_no_clicks", "ok": invalid_ok})
182     high_cost = table["spend"] > 10*cost_thr_log10
183     high_ben = table["benefit"] >= benefit_thr
184     expected = np.where(
185         invalid_expected,
186         "无效词",
187         np.where(high_cost, np.where(high_ben, "重点词", "问题词"), np.where(high_ben, "黄金词", "潜力词")),
188     )
189     mism = int((lab.to_numpy() != expected).sum())
190     checks.append({"name": "quadrant_rule_reproduced", "ok": mism == 0, "mismatches": mism})
191     counts = lab.value_counts().reindex(LABELS, fill_value=0)
192     checks.append({"name": "counts_sum_to_rows", "ok": int(counts.sum()) == len(table)})
193     gold = table[lab == "黄金词"]
194     prob = table[lab == "问题词"]
195     checks.append(
196         {
197             "name": "gold_cheaper_and_better_than_problem",
198             "ok": bool(
199                 len(gold) == 0
200                 or len(prob) == 0
201                 or (
202                     gold["spend"].max() <= prob["spend"].min() + 1e-9
203                     and gold["benefit"].min() >= prob["benefit"].max() - 1e-12
204                 )
205             ),
206         }
207     )
208     checks.append(
209         {
210             "name": "benefit_in_unit_interval",
211             "ok": bool(((table["benefit"] >= -1e-12) & (table["benefit"] <= 1 + 1e-12)).all()),
212         }
213     )
214     return {"ok": all(c["ok"] for c in checks), "checks": checks, "counts": counts.astype(int).to_dict()}
215
216
217 def axis_diagnostics(table: pd.DataFrame, main_thresholds: dict[str, float], method: str, seed: int) -> dict[str, Any]:
218     """How independent are the two classification axes, and what does an efficiency axis give instead?
219
220     The benefit index aggregates volume quantities (clicks, page views, attention seconds, attributed
221     registrations) and is therefore strongly co-monotone with spend: the quadrant scheme is mostly a
222     banding along one spend-benefit axis plus two small off-diagonal classes. Reporting the
223     correlation, the economic weight of the off-diagonal classes and a dual classification on an
224     efficiency axis (attributed registrations per yuan) lets the reader judge the scheme instead of
225     taking the two-dimensional picture at face value.
226     """
227     active = table["spend"] > 0
228     a = table.loc[active]
229     lc = a["log10_cost"].to_numpy(dtype=float)
230     ben = a["benefit"].to_numpy(dtype=float)
231     pear = float(np.corrcoef(lc, ben)[0, 1])
232     spear = float(pd.Series(lc).corr(pd.Series(ben), method="spearman"))
233     clicks_spear = float(a["clicks"].corr(a["benefit"], method="spearman"))
234     # efficiency axis: attributed registrations per yuan (log scale), same threshold machinery
235     eff = np.log1p(a["reg_attr"].to_numpy(dtype=float) / np.maximum(a["spend"].to_numpy(dtype=float), 1e-9))
236     eff_norm = minmax(eff)
237     eff_thr = threshold(eff_norm, method, seed)

```

```

238     eff_series = pd.Series(0.0, index=table.index)
239     eff_series.loc[a.index] = eff_norm
240     eff_labels = assign_labels(table, eff_series, main_thresholds["log10_cost"], eff_thr)
241     counts = eff_labels.value_counts().reindex(LABELS, fill_value=0).astype(int).to_dict()
242     total_spend = float(table["spend"].sum())
243     total_clicks = float(table["clicks"].sum())
244     shares = {}
245     for label in LABELS:
246         sel = table["label"] == label
247         shares[label] = {
248             "n": int(sel.sum()),
249             "spend_share": float(table.loc[sel, "spend"].sum() / max(total_spend, 1e-9)),
250             "click_share": float(table.loc[sel, "clicks"].sum() / max(total_clicks, 1e-9)),
251         }
252     return {
253         "pearson_logcost_benefit": pear,
254         "r2_logcost_benefit": pear**2,
255         "spearman_logcost_benefit": spear,
256         "spearman_clicks_benefit": clicks_spear,
257         "spearman_logcost_efficiency": float(pd.Series(lc).corr(pd.Series(eff), method="spearman")),
258         "efficiency_threshold": float(eff_thr),
259         "efficiency_counts": counts,
260         "efficiency_agreement": float((eff_labels == table["label"]).mean()),
261         "label_shares": shares,
262         "efficiency_labels": eff_labels,
263     }

```

pipelines/e/contracts.py

```

1  """Data contracts for Problem E (SEM advertising strategy)."""
2
3  from __future__ import annotations
4
5  import re
6
7  import pandas as pd
8
9  from forge.contracts import Column, FrameContract
10 from forge.xlsx import SheetContract, WorkbookContract
11
12 _DURATION = re.compile(r"^\s*\d{1,2}:\d{2}:\d{2}\s*$")
13
14
15 def _funnel_consistent(df: pd.DataFrame) -> list[str]:
16     errors: list[str] = []
17     if (df["点击量"] > df["展现量"]).any():
18         errors.append("点击量 > 展现量 in some rows")
19     if (df["上方位展现量"] > df["展现量"]).any():
20         errors.append("上方位展现量 > 展现量 in some rows")
21     if (df["上方首位展现量"] > df["上方位展现量"]).any():
22         errors.append("上方首位展现量 > 上方位展现量 in some rows")
23     if (df["上方位点击量"] > df["点击量"]).any():
24         errors.append("上方位点击量 > 点击量 in some rows")
25     if (df["上方位消费额"] > df["消费额"] + 1e-6).any():
26         errors.append("上方位消费额 > 消费额 in some rows")
27     return errors
28
29
30 def _bounce_and_duration(df: pd.DataFrame) -> list[str]:
31     errors: list[str] = []
32     for value in df["跳出率"].astype(str):

```

```

33     v = value.strip()
34     if v == "/":
35         continue
36     try:
37         x = float(v)
38     except ValueError:
39         errors.append(f"跳出率 unparsable {value!r}")
40         continue
41     if not 0 <= x <= 1:
42         errors.append(f"跳出率 out of range {value!r}")
43 for value in df["平均访问时长"].astype(str):
44     v = value.strip()
45     if v == "/" or _DURATION.match(v):
46         continue
47     try: # zero-visit rows carry a bare numeric 0 instead of "00:00:00"
48         if float(v) < 0:
49             errors.append(f"平均访问时长 negative {value!r}")
50     except ValueError:
51         errors.append(f"平均访问时长 unparsable {value!r}")
52 return errors[:20]
53
54
55 INPUT_CONTRACTS: dict[str, FrameContract] = {
56     "附件1__Sheet1": FrameContract(
57         name="E. 附件1.Sheet1. 单元日消费",
58         columns=(
59             Column("日期", "datetime"),
60             Column("方案ID", "int"),
61             Column("推广单元ID", "int"),
62             Column("展现量", "int", min=0),
63             Column("点击量", "int", min=0),
64             Column("消费额", "float", min=0),
65             Column("上方位展现量", "int", min=0),
66             Column("上方首位展现量", "int", min=0),
67             Column("上方位点击量", "int", min=0),
68             Column("上方位消费额", "float", min=0),
69         ),
70         min_rows=2000,
71         checks=(_funnel_consistent,),
72     ),
73     "附件1__Sheet2": FrameContract(
74         name="E. 附件1.Sheet2. 每日新注册",
75         columns=(Column("日期", "datetime", unique=True), Column("新注册数", "int", min=0)),
76         min_rows=365,
77         max_rows=366,
78     ),
79     "附件1__Sheet3": FrameContract(
80         name="E. 附件1.Sheet3. 关键词年度统计",
81         columns=(
82             Column("序号", "int", unique=True, min=1),
83             Column("关键词", "int"),
84             Column("方案ID", "int"),
85             Column("推广单元ID", "int"),
86             Column("消费额", "float", min=0),
87             Column("点击量", "int", min=0),
88             Column("浏览量", "int", min=0),
89             Column("跳出率", "any"),
90             Column("平均访问时长", "any"),
91         ),
92         min_rows=2000,
93         checks=(_bounce_and_duration,),
94     ),
95 }

```

```

96
97 RESULT_CONTRACTS: list[WorkbookContract] = [
98     WorkbookContract("result2.xlsx", "result2.xlsx", (SheetContract("Sheet1", min_rows=2000, header_len=8))),
99     WorkbookContract("result3.xlsx", "result3.xlsx", (SheetContract("Sheet1", min_rows=16, header_len=9))),
100    WorkbookContract("result4.xlsx", "result4.xlsx", (SheetContract("Sheet1", min_rows=7, header_len=9))),
101 ]

```

pipelines/e/data.py

```

1  """Loading and normalising the three attachment sheets into analysis frames."""
2
3  from __future__ import annotations
4
5  import math
6  import re
7  from pathlib import Path
8  from typing import Any
9
10 import numpy as np
11 import pandas as pd
12
13 from pipelines.e.calendar import day_features
14
15 _HMS = re.compile(r"^(?<{1,3}>:(?<{2}>):(?<{2}>)$")
16 UNIT_COLS = ["方案ID", "推广单元ID"]
17
18
19 def parse_bounce(value: Any) -> float:
20     """Bounce rate as a fraction in [0, 1]; '/' (no visits) becomes NaN."""
21     text = str(value).strip()
22     if text in {"/", "", "nan", "None"}:
23         return math.nan
24     x = float(text)
25     return x / 100.0 if x > 1.0 else x
26
27
28 def parse_duration(value: Any) -> float:
29     """Average visit duration in seconds; 'HH:MM:SS', bare numbers (zero) or '/' (no visits -> NaN)."""
30     text = str(value).strip()
31     if text in {"/", "", "nan", "None"}:
32         return math.nan
33     match = _HMS.match(text)
34     if match:
35         h, m, s = (int(g) for g in match.groups())
36         return float(h * 3600 + m * 60 + s)
37     return float(text)
38
39
40 def load_sheets(ingest_dir: Path) -> tuple[pd.DataFrame, pd.DataFrame, pd.DataFrame]:
41     """Sheet1 (unit-day), Sheet2 (daily registrations), Sheet3 (keyword annual statistics)."""
42     data = ingest_dir / "data"
43     s1 = pd.read_parquet(data / "附件1__Sheet1.parquet")
44     s2 = pd.read_parquet(data / "附件1__Sheet2.parquet")
45     s3 = pd.read_parquet(data / "附件1__Sheet3.parquet")
46     for df in (s1, s2, s3):
47         df.columns = [str(c).strip() for c in df.columns]
48     s1["日期"] = pd.to_datetime(s1["日期"]).dt.normalize()
49     s2["日期"] = pd.to_datetime(s2["日期"]).dt.normalize()
50     s1 = s1.sort_values(["日期", *UNIT_COLS]).reset_index(drop=True)
51     s2 = s2.sort_values("日期").reset_index(drop=True)
52     s3 = s3.sort_values("序号").reset_index(drop=True)

```

```

53     return s1, s2, s3
54
55
56 def unit_daily(s1: pd.DataFrame) -> pd.DataFrame:
57     """Unit-day records with derived ratios and calendar covariates."""
58     df = s1.copy()
59     clicks = df["点击量"].replace(0, np.nan)
60     imp = df["展现量"].replace(0, np.nan)
61     df["cpc"] = df["消费额"] / clicks
62     df["ctr"] = df["点击量"] / imp
63     df["cpm"] = 1000.0 * df["消费额"] / imp
64     df["top_share"] = df["上方位展现量"] / imp
65     df["first_share"] = df["上方首位展现量"] / imp
66     df["top_click_share"] = df["上方位点击量"] / clicks
67     df["top_cpc"] = df["上方位消费额"] / df["上方位点击量"].replace(0, np.nan)
68     other_clicks = (df["点击量"] - df["上方位点击量"]).replace(0, np.nan)
69     df["other_cpc"] = (df["消费额"] - df["上方位消费额"]) / other_clicks
70     feats = day_features(df["日期"]).drop(columns=["date"])
71     return pd.concat([df.reset_index(drop=True), feats], axis=1)
72
73
74 def daily_totals(s1: pd.DataFrame, s2: pd.DataFrame) -> pd.DataFrame:
75     """All 365 days of 2025: account-level totals, registrations and calendar covariates."""
76     agg = s1.groupby("日期")[
77         ["展现量", "点击量", "消费额", "上方位展现量", "上方首位展现量", "上方位点击量", "上方位消费额"]
78     ].sum()
79     agg.columns = ["imp", "clicks", "spend", "top_imp", "first_imp", "top_clicks", "top_spend"]
80     days = pd.date_range("2025-01-01", "2025-12-31", freq="D")
81     out = agg.reindex(days).fillna(0.0)
82     out["regs"] = s2.set_index("日期")["新注册数"].reindex(days).astype(float)
83     out["active_units"] = s1.groupby("日期")["推广单元ID"].nunique().reindex(days).fillna(0).astype(int)
84     out["cpc"] = out["spend"] / out["clicks"].replace(0, np.nan)
85     out["ctr"] = out["clicks"] / out["imp"].replace(0, np.nan)
86     out["top_share"] = out["top_imp"] / out["imp"].replace(0, np.nan)
87     out["first_share"] = out["first_imp"] / out["imp"].replace(0, np.nan)
88     feats = day_features(days).set_index("date")
89     out = out.join(feats)
90     out.index.name = "date"
91     return out
92
93
94 def unit_click_matrix(s1: pd.DataFrame, column: str = "点击量") -> pd.DataFrame:
95     """Dates (all of 2025) x units matrix of ``column``; days without a record are zero."""
96     days = pd.date_range("2025-01-01", "2025-12-31", freq="D")
97     mat = s1.pivot_table(index="日期", columns="推广单元ID", values=column, aggfunc="sum")
98     return mat.reindex(days).fillna(0.0)
99
100
101 def keyword_table(s3: pd.DataFrame) -> pd.DataFrame:
102     """Keyword-level annual statistics with parsed engagement fields."""
103     kw = pd.DataFrame(
104         {
105             "序号": s3["序号"].astype(int),
106             "关键词": s3["关键词"].astype(int),
107             "方案ID": s3["方案ID"].astype(int),
108             "推广单元ID": s3["推广单元ID"].astype(int),
109             "spend": s3["消费额"].astype(float),
110             "clicks": s3["点击量"].astype(int),
111             "views": s3["浏览量"].astype(int),
112         }
113     )
114     kw["bounce"] = s3["跳出率"].map(parse_bounce).astype(float)
115     kw["duration_s"] = s3["平均访问时长"].map(parse_duration).astype(float)

```

```

116     clicks = kw["clicks"].replace(0, np.nan)
117     kw["cpc"] = kw["spend"] / clicks
118     kw["depth"] = kw["views"] / clicks
119     # visits that did not bounce, and total attention time (person-seconds) they generated
120     kw["engaged_visits"] = (kw["clicks"] * (1.0 - kw["bounce"].fillna(1.0))).clip(lower=0.0)
121     kw["engagement"] = (kw["engaged_visits"] * kw["duration_s"].fillna(0.0)).clip(lower=0.0)
122     kw["has_cost"] = kw["spend"] > 0
123     kw["has_benefit"] = (kw["clicks"] > 0) | (kw["views"] > 0)
124     dup_counts = kw.groupby("关键词")["推广单元ID"].transform("nunique")
125     kw["shared_units"] = dup_counts.astype(int)
126     return kw

```

pipelines/e/eda.py

```

1  """Problem 1 analytics: unit KPIs, keyword concentration, calendar/holiday regressions, registration attribution."""
2
3  from __future__ import annotations
4
5  from typing import Any
6
7  import numpy as np
8  import pandas as pd
9  import statsmodels.api as sm
10 from scipy import stats
11 from scipy.optimize import lsq_linear
12
13 from pipelines.e.calendar import WEEKDAY_NAMES
14
15 WEEKDAY_BASE = 2 # Wednesday is the reference weekday in every regression
16 MONTH_BASE = 1 # January is the reference month
17
18
19 def unit_kpis(s1: pd.DataFrame) -> pd.DataFrame:
20     """Annual funnel KPIs per (plan, unit): CTR, CPC, position shares, top vs. other CPC."""
21     g = s1.groupby(["方案ID", "推广单元ID"])
22     k = pd.DataFrame(
23         {
24             "days": g.size(),
25             "first_day": g["日期"].min(),
26             "last_day": g["日期"].max(),
27             "imp": g["展现量"].sum(),
28             "clicks": g["点击量"].sum(),
29             "spend": g["消费额"].sum(),
30             "top_imp": g["上方位展现量"].sum(),
31             "first_imp": g["上方首位展现量"].sum(),
32             "top_clicks": g["上方位点击量"].sum(),
33             "top_spend": g["上方位消费额"].sum(),
34         }
35     ).reset_index()
36     imp = k["imp"].replace(0, np.nan)
37     clicks = k["clicks"].replace(0, np.nan)
38     k["ctr"] = k["clicks"] / imp
39     k["cpc"] = k["spend"] / clicks
40     k["cpm"] = 1000.0 * k["spend"] / imp
41     k["top_share"] = k["top_imp"] / imp
42     k["first_share"] = k["first_imp"] / imp
43     k["top_click_share"] = k["top_clicks"] / clicks
44     k["top_cpc"] = k["top_spend"] / k["top_clicks"].replace(0, np.nan)
45     k["other_cpc"] = (k["spend"] - k["top_spend"]) / (k["clicks"] - k["top_clicks"]).replace(0, np.nan)
46     k["top_ctr"] = k["top_clicks"] / k["top_imp"].replace(0, np.nan)
47     k["other_ctr"] = (k["clicks"] - k["top_clicks"]) / (k["imp"] - k["top_imp"]).replace(0, np.nan)

```

```

48     k["spend_share"] = k["spend"] / k["spend"].sum()
49     return k
50
51
52 def gini(values: np.ndarray) -> float:
53     """Gini coefficient of a non-negative vector (0 = perfectly even)."""
54     x = np.sort(np.asarray(values, dtype=float))
55     n = len(x)
56     if n == 0 or x.sum() <= 0:
57         return 0.0
58     cum = np.cumsum(x)
59     return float((n + 1 - 2 * np.sum(cum) / cum[-1]) / n)
60
61
62 def keyword_concentration(kw: pd.DataFrame) -> dict[str, Any]:
63     """Long-tail statistics of keyword spend and clicks (global and per unit)."""
64     spend = kw["spend"].to_numpy(dtype=float)
65     order = np.argsort(-spend)
66     cum = np.cumsum(spend[order]) / spend.sum()
67     n = len(spend)
68     lorenz = pd.DataFrame(
69         {
70             "keyword_share": np.arange(1, n + 1) / n,
71             "spend_share": cum,
72             "click_share": np.cumsum(kw["clicks"].to_numpy()[order]) / kw["clicks"].sum(),
73         }
74     )
75     per_unit = (
76         kw.groupby(["方案ID", "推广单元ID"])
77         .apply(
78             lambda d: pd.Series(
79                 {
80                     "keywords": len(d),
81                     "active": int((d["spend"] > 0).sum()),
82                     "zero": int((d["spend"] == 0).sum()),
83                     "spend": d["spend"].sum(),
84                     "clicks": d["clicks"].sum(),
85                     "gini_spend": gini(d["spend"].to_numpy()),
86                     "top5_share": float(np.sort(d["spend"].to_numpy())[:-1][:5].sum() / max(d["spend"].sum(), 1e-9)),
87                 }
88             ),
89             include_groups=False,
90         )
91         .reset_index()
92     )
93     return {
94         "keywords": int(n),
95         "unique_keyword_ids": int(kw["关键词"].nunique()),
96         "shared_keyword_ids": int((kw.groupby("关键词")["推广单元ID"].nunique() > 1).sum()),
97         "zero_cost_zero_benefit": int(((kw["spend"] == 0) & (kw["clicks"] == 0)).sum()),
98         "active_keywords": int((kw["spend"] > 0).sum()),
99         "gini_spend_all": gini(spend),
100         "gini_spend_active": gini(spend[spend > 0]),
101         "top10_spend_share": float(cum[min(9, n - 1)]),
102         "top50_spend_share": float(cum[min(49, n - 1)]),
103         "top100_spend_share": float(cum[min(99, n - 1)]),
104         "top20pct_spend_share": float(cum[max(int(0.2 * n) - 1, 0)]),
105         "lorenz": lorenz,
106         "per_unit": per_unit,
107     }
108
109
110 def _design(daily: pd.DataFrame) -> pd.DataFrame:

```

```

111     """Regression design: constant, weekday and month dummies, holiday and 调休 indicators."""
112     cols: dict[str, Any] = {"const": 1.0}
113     for wd in range(7):
114         if wd != WEEKDAY_BASE:
115             cols[f"wd_{WEEKDAY_NAMES[wd]}"] = (daily["weekday"] == wd).astype(float)
116     for m in range(1, 13):
117         if m != MONTH_BASE and (daily["month"] == m).any():
118             cols[f"month_{m:02d}"] = (daily["month"] == m).astype(float)
119     cols["holiday"] = daily["is_holiday"].astype(float)
120     cols["adjusted_workday"] = daily["is_adjusted_workday"].astype(float)
121     cols["pre_holiday"] = daily["is_pre_holiday"].astype(float)
122     cols["post_holiday"] = daily["is_post_holiday"].astype(float)
123     return pd.DataFrame(cols, index=daily.index)
124
125
126 def calendar_regression(
127     daily: pd.DataFrame, target: str, log: bool, controls: tuple[str, ...] = ()
128 ) -> tuple[pd.DataFrame, dict[str, Any]]:
129     """OLS of ``target`` (optionally log) on calendar dummies (+ log controls) with HC3 robust standard errors."""
130     y = daily[target].astype(float)
131     mask = y.notna() & (y > 0 if log else True)
132     for ctrl in controls:
133         mask &= daily[ctrl].astype(float) > 0
134     y = np.log(y[mask]) if log else y[mask]
135     X = _design(daily.loc[mask])
136     for ctrl in controls:
137         X[f"log_{ctrl}"] = np.log(daily.loc[mask, ctrl].astype(float))
138     name = f"{target}|{'+'.join(controls)}" if controls else target
139     fit = sm.OLS(y, X).fit(cov_type="HC3")
140     ci = fit.conf_int(alpha=0.05)
141     rows = []
142     for term in X.columns:
143         est = float(fit.params[term])
144         rows.append(
145             {
146                 "target": name,
147                 "term": term,
148                 "estimate": est,
149                 "se": float(fit.bse[term]),
150                 "t": float(fit.tvalues[term]),
151                 "p": float(fit.pvalues[term]),
152                 "ci_low": float(ci.loc[term, 0]),
153                 "ci_high": float(ci.loc[term, 1]),
154                 "effect_pct": 100.0 * (np.exp(est) - 1.0) if log else np.nan,
155                 "effect_pct_low": 100.0 * (np.exp(ci.loc[term, 0]) - 1.0) if log else np.nan,
156                 "effect_pct_high": 100.0 * (np.exp(ci.loc[term, 1]) - 1.0) if log else np.nan,
157             }
158         )
159     wd_terms = [c for c in X.columns if c.startswith("wd_")]
160     wald = fit.wald_test(np.eye(len(X.columns))[[list(X.columns).index(c) for c in wd_terms]], scalar=True)
161     summary = {
162         "target": name,
163         "log": log,
164         "n": int(mask.sum()),
165         "r2": float(fit.rsquared),
166         "r2_adj": float(fit.rsquared_adj),
167         "weekday_wald_stat": float(wald.statistic),
168         "weekday_wald_p": float(wald.pvalue),
169         "residual_sd": float(np.sqrt(fit.scale)),
170     }
171     return pd.DataFrame(rows), summary
172
173

```

```

174 def holiday_nonparametric(daily: pd.DataFrame, target: str) -> dict[str, Any]:
175     """Mann-Whitney U test of holiday days vs. ordinary workdays for ``target``."""
176     hol = daily.loc[daily["is_holiday"], target].dropna()
177     work = daily.loc[daily["day_type"] == "workday", target].dropna()
178     u = stats.mannwhitneyu(hol, work, alternative="two-sided")
179     return {
180         "target": target,
181         "holiday_n": len(hol),
182         "workday_n": len(work),
183         "holiday_median": float(hol.median()),
184         "workday_median": float(work.median()),
185         "ratio_of_medians": float(hol.median() / work.median()) if work.median() else np.nan,
186         "u_stat": float(u.statistic),
187         "p": float(u.pvalue),
188     }
189
190
191 def day_type_profile(daily: pd.DataFrame, columns: tuple[str, ...]) -> pd.DataFrame:
192     """Mean of ``columns`` by weekday, by month and by day type (long format)."""
193     frames = []
194     for key in ("weekday_name", "month", "day_type"):
195         g = daily.groupby(key)[list(columns)].mean()
196         g["n_days"] = daily.groupby(key).size()
197         g = g.reset_index().rename(columns={key: "level"})
198         g.insert(0, "dimension", key)
199         g["level"] = g["level"].astype(str)
200         frames.append(g)
201     return pd.concat(frames, ignore_index=True)
202
203
204 def attribution_model(
205     clicks: pd.DataFrame,
206     daily: pd.DataFrame,
207     lambdas: tuple[float, ...] = (0.0, 0.2, 0.4, 0.6),
208     min_clicks: float = 10_000.0,
209     band: tuple[float, ...] = (0.25, 4.0),
210 ) -> dict[str, Any]:
211     """Registrations = baseline + sum_u r_u * adstocked clicks_u + calendar effects (r_u >= 0).
212
213     ``clicks``: dates x units matrix. The adstock decay ``lambda`` is selected by rolling-origin
214     validation MAE. A unit keeps its own rate only when it has enough clicks to identify it and the
215     estimate lies within ``band`` times the pooled rate; otherwise the pooled rate is used.
216     """
217     y = daily["regs"].to_numpy(dtype=float)
218     cal = _design(daily).drop(columns=["const"])
219     units = [int(u) for u in clicks.columns]
220     n = len(y)
221     origins = [int(n * f) for f in (0.5, 0.6, 0.7, 0.8)]
222
223     def adstock(mat: np.ndarray, lam: float) -> np.ndarray:
224         out = mat.copy()
225         for t in range(1, len(out)):
226             out[t] += lam * out[t - 1]
227         return out
228
229     def fit(Xu: np.ndarray, Xc: np.ndarray, yy: np.ndarray) -> np.ndarray:
230         X = np.column_stack([np.ones(len(yy)), Xu, Xc])
231         lo = np.concatenate([[0.0], np.zeros(Xu.shape[1]), np.full(Xc.shape[1], -np.inf)])
232         hi = np.full(X.shape[1], np.inf)
233         return lsq_linear(X, yy, bounds=(lo, hi), lsqr_tol="auto").x
234
235     def predict(beta: np.ndarray, Xu: np.ndarray, Xc: np.ndarray) -> np.ndarray:
236         return np.column_stack([np.ones(len(Xu)), Xu, Xc]) @ beta

```

```

237
238 cv_rows = []
239 best_lambda, best_mae = lambdas[0], np.inf
240 raw = clicks.to_numpy(dtype=float)
241 calm = cal.to_numpy(dtype=float)
242 for lam in lambdas:
243     Xu = adstock(raw, lam)
244     errs = []
245     for o in origins:
246         beta = fit(Xu[o:], calm[o:], y[o:])
247         pred = predict(beta, Xu[o:], calm[o:])
248         errs.append(np.abs(pred - y[o:]).mean())
249     mae = float(np.mean(errs))
250     cv_rows.append({"lambda": lam, "cv_mae": mae})
251     if mae < best_mae:
252         best_lambda, best_mae = lam, mae
253 Xu = adstock(raw, best_lambda)
254 beta = fit(Xu, calm, y)
255 pred = predict(beta, Xu, calm)
256 resid = y - pred
257 r_units = {u: float(beta[1 + i]) for i, u in enumerate(units)}
258 # pooled rate: same regression with a single aggregate clicks regressor
259 pooled_beta = fit(Xu.sum(axis=1, keepdims=True), calm, y)
260 pooled_rate = float(pooled_beta[1])
261 totals = clicks.sum(axis=0)
262 rates: dict[int, float] = {}
263 source: dict[int, str] = {}
264 for u in units:
265     if totals[u] >= min_clicks and band[0] * pooled_rate <= r_units[u] <= band[1] * pooled_rate:
266         rates[u], source[u] = r_units[u], "unit"
267     else:
268         rates[u], source[u] = pooled_rate, "pooled"
269 # holdout diagnostics for the selected lambda (train first 70 %, test last 30 %)
270 o = int(n * 0.7)
271 beta_h = fit(Xu[o:], calm[o:], y[o:])
272 pred_h = predict(beta_h, Xu[o:], calm[o:])
273 holdout = {
274     "train_days": o,
275     "test_days": n - o,
276     "mae": float(np.abs(pred_h - y[o:]).mean()),
277     "mape": float(np.mean(np.abs(pred_h - y[o:]) / np.maximum(y[o:], 1.0))),
278     "r2": float(1 - np.sum((y[o:] - pred_h) ** 2) / np.sum((y[o:] - y[o:].mean()) ** 2)),
279 }
280 return {
281     "lambda": float(best_lambda),
282     "cv": cv_rows,
283     "baseline_per_day": float(beta[0]),
284     "unit_rates": r_units,
285     "pooled_rate": pooled_rate,
286     "rates": rates,
287     "rate_source": source,
288     "calendar_terms": {c: float(beta[1 + len(units) + j]) for j, c in enumerate(cal.columns)},
289     "r2": float(1 - np.sum(resid**2) / np.sum((y - y.mean()) ** 2)),
290     "mae": float(np.abs(resid).mean()),
291     "holdout": holdout,
292     "fitted": pd.DataFrame({"date": daily.index, "regs": y, "fitted": pred}),
293     # attributed with the rates actually used downstream (unit rate or pooled fallback); the raw
294     # NNLS rates are kept for transparency (they are zero for units clipped at the bound)
295     "attributed_regs": {u: float((Xu[:, i] * rates[u]).sum()) for i, u in enumerate(units)},
296     "attributed_regs_raw": {u: float((Xu[:, i] * r_units[u]).sum()) for i, u in enumerate(units)},
297     "baseline_regs": float(beta[0] * n),
298 }
299

```

```

300
301 def holiday_optimal_cut(
302     daily: pd.DataFrame,
303     terms: tuple[str, ...] = ("holiday", "wd_周一", "wd_周日"),
304     alt_elasticities: tuple[float, ...] = (),
305     n_draws: int = 400_000,
306     seed: int = 0,
307 ) -> dict[str, Any]:
308     """Sampling uncertainty of the marginal-return-equalising spend ratio  $\exp(\delta'/(1-\theta))$ .
309
310     The optimal spend ratio on a day type with demand-side effect ``delta`` relative to an ordinary
311     day follows from equalising the marginal registration return of the log-log response
312      $R = K S^{-\theta}$ . Both  $\delta'$  and  $\theta$  come from the same regression, so their joint sampling
313     distribution is propagated by drawing from the HC3 covariance of the two coefficients; the
314     critical elasticity ``theta_star`` at which the optimal cut equals the observed cut is reported
315     so that the reader can see whether the data can separate "over-cut" from "under-cut".
316
317     """
318     y = daily["regs"].astype(float)
319     mask = y.notna() & (y > 0) & (daily["spend"].astype(float) > 0)
320     X = _design(daily.loc[mask])
321     X["log_spend"] = np.log(daily.loc[mask, "spend"].astype(float))
322     fit = sm.OLS(np.log(y[mask]), X).fit(cov_type="HC3")
323     cols = list(X.columns)
324     j_theta = cols.index("log_spend")
325     cov = np.asarray(fit.cov_params())
326     rng = np.random.default_rng(seed)
327     theta = float(fit.params["log_spend"])
328     theta_se = float(fit.bse["log_spend"])
329     theta_ci = [float(v) for v in fit.conf_int(alpha=0.05).loc["log_spend"]]
330     # observed spend cut per day type (same design, spend as the dependent variable)
331     spend_fit = sm.OLS(np.log(daily.loc[mask, "spend"].astype(float)), _design(daily.loc[mask])).fit(cov_type="HC3")
332     out: dict[str, Any] = {
333         "theta": theta,
334         "theta_se": theta_se,
335         "theta_ci": theta_ci,
336         "n": int(mask.sum()),
337         "terms": {},
338     }
339
340     def cut(delta: np.ndarray | float, th: np.ndarray | float) -> np.ndarray:
341         return 1.0 - np.exp(np.asarray(delta, dtype=float) / np.maximum(1.0 - np.asarray(th, dtype=float), 1e-6))
342
343     for term in terms:
344         if term not in cols:
345             continue
346         j = cols.index(term)
347         delta = float(fit.params[term])
348         sub = cov[np.ix_([j, j_theta], [j, j_theta])]
349         draws = rng.multivariate_normal([delta, theta], sub, size=n_draws)
350         keep = draws[:, 1] < 0.999 # the ratio is undefined at unit elasticity
351         cuts = cut(draws[keep, 0], draws[keep, 1])
352         actual = float(1.0 - np.exp(float(spend_fit.params[term])))
353         # elasticity at which the optimal cut equals the observed cut:  $\delta / \log(1 - \text{actual}) = 1 - \theta$ 
354         theta_star = float(1.0 - delta / np.log(max(1.0 - actual, 1e-9))) if actual > 0 else np.nan
355         out["terms"][term] = {
356             "delta": delta,
357             "delta_se": float(fit.bse[term]),
358             "delta_ci": [float(v) for v in fit.conf_int(alpha=0.05).loc[term]],
359             "delta_p": float(fit.pvalues[term]),
360             "cut": float(cut(delta, theta)),
361             "cut_ci": [float(np.quantile(cuts, 0.025)), float(np.quantile(cuts, 0.975))],
362             "cut_at_theta_lo": float(cut(delta, theta_ci[0])),
363             "cut_at_theta_hi": float(cut(delta, theta_ci[1])),
364         }

```

```

363         "actual_cut": actual,
364         "actual_cut_p": float(spend_fit.pvalues[term]),
365         "theta_star": theta_star,
366         "theta_star_inside_ci": bool(theta_ci[0] <= theta_star <= theta_ci[1])
367         if np.isfinite(theta_star)
368         else False,
369         "prob_optimal_deeper_than_actual": float(np.mean(cuts > actual)),
370         "cut_at_alt": {f"{g:.4f}": float(cut(delta, g)) for g in alt_elasticities},
371     }
372     return out
373
374
375 def attribution_diagnostics(
376     clicks: pd.DataFrame,
377     daily: pd.DataFrame,
378     attribution: dict[str, Any],
379     n_boot: int = 300,
380     seed: int = 0,
381 ) -> dict[str, Any]:
382     """Bootstrap intervals, boundary flags, collinearity and an additive decomposition of registrations.
383
384     The unit registration rates enter every downstream objective, so their sampling uncertainty and
385     their dependence on the calendar controls must be reported: a moving-block bootstrap of the
386     residuals gives intervals, refitting without the month dummies gives a specification swing, and
387     the residualised design matrix gives the condition number of the click block.
388     """
389     y = daily["regs"].to_numpy(dtype=float)
390     cal = _design(daily).drop(columns=["const"])
391     units = [int(u) for u in clicks.columns]
392     lam = float(attribution["lambda"])
393     raw = clicks.to_numpy(dtype=float)
394     Xu = raw.copy()
395     for t in range(1, len(Xu)):
396         Xu[t] += lam * Xu[t - 1]
397     calm = cal.to_numpy(dtype=float)
398
399     def fit(Xc: np.ndarray, yy: np.ndarray, xu: np.ndarray) -> np.ndarray:
400         X = np.column_stack([np.ones(len(yy)), xu, Xc])
401         lo = np.concatenate([[0.0], np.zeros(xu.shape[1]), np.full(Xc.shape[1], -np.inf)])
402         return lsq_linear(X, yy, bounds=(lo, np.full(X.shape[1], np.inf)), lsqr_tol="auto").x
403
404     beta = fit(calm, y, Xu)
405     fitted = np.column_stack([np.ones(len(y)), Xu, calm]) @ beta
406     resid = y - fitted
407     # moving-block bootstrap (block length 7) preserves the weekly dependence of the residuals
408     rng = np.random.default_rng(seed)
409     block, n = 7, len(y)
410     n_blocks = int(np.ceil(n / block))
411     draws = np.zeros((n_boot, len(units)))
412     for b in range(n_boot):
413         starts = rng.integers(0, n - block + 1, size=n_blocks)
414         e = np.concatenate([resid[s : s + block] for s in starts])[:n]
415         draws[b] = fit(calm, fitted + e, Xu)[1 : 1 + len(units)]
416     # specification robustness: drop the month dummies
417     month_cols = [i for i, c in enumerate(cal.columns) if c.startswith("month_")]
418     keep = [i for i in range(calm.shape[1]) if i not in month_cols]
419     beta_nm = fit(calm[:, keep], y, Xu)
420     # collinearity of the click block after residualising on the calendar design
421     Z = np.column_stack([np.ones(n), calm])
422     resid_clicks = Xu - Z @ np.linalg.lstsq(Z, Xu, rcond=None)[0]
423     sv = np.linalg.svd(resid_clicks, compute_uv=False)
424     rows = []
425     for i, u in enumerate(units):

```

```

426     r_raw = float(beta[1 + i])
427     rows.append(
428         {
429             "推广单元ID": u,
430             "rate_raw": r_raw,
431             "rate_used": float(attribution["rates"][u]),
432             "rate_source": attribution["rate_source"][u],
433             "at_zero_bound": bool(r_raw <= 1e-9),
434             "boot_low": float(np.quantile(draws[:, i], 0.025)),
435             "boot_high": float(np.quantile(draws[:, i], 0.975)),
436             "boot_sd": float(np.std(draws[:, i])),
437             "boot_share_at_zero": float(np.mean(draws[:, i] <= 1e-9)),
438             "rate_no_month": float(beta_nm[1 + i]),
439             "swing_ratio": float(beta_nm[1 + i] / r_raw) if r_raw > 1e-9 else np.nan,
440             "total_clicks": float(clicks.iloc[:, i].sum()),
441         }
442     )
443     table = pd.DataFrame(rows)
444     cal_terms = beta[1 + len(units) :]
445     decomposition = {
446         "total_regs": float(y.sum()),
447         "intercept": float(beta[0] * n),
448         "sem": float(sum(Xu[:, i].sum() * beta[1 + i] for i in range(len(units)))),
449         "calendar": float(sum(calm[:, j].sum() * cal_terms[j] for j in range(calm.shape[1]))),
450         "residual": float(resid.sum()),
451     }
452     decomposition["implied_non_sem_per_day"] = (decomposition["intercept"] + decomposition["calendar"]) / n
453     return {
454         "table": table,
455         "n_boot": n_boot,
456         "n_at_zero_bound": int(table["at_zero_bound"].sum()),
457         "max_swing_ratio": float(np.nanmax(np.abs(np.log(table["swing_ratio"].to_numpy(dtype=float))))),
458         "condition_number": float(sv[0] / max(sv[-1], 1e-12)),
459         "min_singular_value": float(sv[-1]),
460         "decomposition": decomposition,
461     }

```

pipelines/e/figures.py

```

1  """Paper figures for Problem E (vector PDF + PNG preview, Okabe-Ito palette, CJK-capable fonts)."""
2
3  from __future__ import annotations
4
5  import json
6  from typing import Any
7
8  import numpy as np
9  import pandas as pd
10
11  from forge import plotting
12  from forge.context import StageContext
13  from pipelines.e.calendar import HOLIDAY_BLOCKS, WEEKDAY_NAMES
14  from pipelines.e.classify import LABELS
15
16  # fixed hue per keyword class (identity colour never depends on ordering)
17  LABEL_COLORS = {"黄金词": "#E69F00", "重点词": "#0072B2", "潜力词": "#009E73", "问题词": "#D55E00"}
18  LABEL_COLORS["无效词"] = "#999999"
19  STRATEGY_COLORS = {"最优分配": "#0072B2", "按历史比例": "#D55E00", "均匀分配": "#009E73"}
20  MODEL_COLORS = {
21     "calendar": "#0072B2",
22     "calendar_wide": "#56B4E9",

```

```

23     "seasonal_naive": "#D55E00",
24     "mean28": "#009E73",
25 }
26 MODEL_NAMES = {
27     "calendar": "日历回归（残差区间）",
28     "calendar_wide": "日历回归（部署区间）",
29     "seasonal_naive": "季节朴素",
30     "mean28": "28 日均值",
31 }
32
33
34 def _shade_holidays(ax: Any) -> None:
35     for start, end in HOLIDAY_BLOCKS.values():
36         ax.axvspan(pd.Timestamp(start), pd.Timestamp(end) + pd.Timedelta(days=1), color="#CC79A7", alpha=0.18, lw=0)
37
38
39 def fig_daily_series(ctx: StageContext, daily: pd.DataFrame) -> dict[str, Any]:
40     fig, axes = plotting.new_figure(6.3, 5.2, nrows=3, sharex=True)
41     labels = ("日消费额 / 元", "日点击量 / 次", "日新注册数 / 人")
42     for ax, col, label in zip(axes, ("spend", "clicks", "regs"), labels):
43         ax.plot(daily["date"], daily[col], lw=0.8, color="#0072B2", alpha=0.55, label="日值")
44         ax.plot(
45             daily["date"],
46             daily[col].rolling(7, center=True, min_periods=3).mean(),
47             lw=1.8,
48             color="#0072B2",
49             label="7 日滑动均值",
50         )
51         _shade_holidays(ax)
52         for d in daily.loc[daily["is_adjusted_workday"], "date"]:
53             ax.axvline(d, color="#D55E00", lw=0.8, ls=":")
54         ax.set_ylabel(label)
55     axes[0].legend(loc="upper right", ncol=2)
56     axes[-1].set_xlabel("日期 (2025 年; 阴影 = 法定节假日, 虚线 = 调休上班日)")
57     return plotting.save(fig, ctx.out("figures", "fig_daily_series.pdf"))
58
59
60 def fig_calendar_effects(ctx: StageContext, coefs: pd.DataFrame) -> dict[str, Any]:
61     terms = [f"wd_{w}" for w in WEEKDAY_NAMES if w != "周三"] + [
62         "holiday",
63         "adjusted_workday",
64         "pre_holiday",
65         "post_holiday",
66     ]
67     names = {
68         **{f"wd_{w}": w for w in WEEKDAY_NAMES},
69         "holiday": "法定节假日",
70         "adjusted_workday": "调休上班日",
71         "pre_holiday": "假前一日",
72         "post_holiday": "假后一日",
73     }
74     targets = [("regs", "新注册数", "#0072B2"), ("spend", "消费额", "#D55E00")]
75     targets.append(("clicks", "点击量", "#009E73"))
76     fig, ax = plotting.new_figure(6.3, 3.6)
77     y = np.arange(len(terms))
78     for k, (target, label, color) in enumerate(targets):
79         sub = coefs[coefs["target"] == target].set_index("term").reindex(terms)
80         off = (k - 1) * 0.25
81         ax.errorbar(
82             sub["effect_pct"],
83             y + off,
84             xerr=[sub["effect_pct"] - sub["effect_pct_low"], sub["effect_pct_high"] - sub["effect_pct"]],
85             fmt="o",

```

```

86         ms=4,
87         color=color,
88         ecolor=color,
89         elinewidth=1.2,
90         capsize=2,
91         label=label,
92     )
93     ax.axvline(0, color="#444444", lw=0.8)
94     ax.set_yticks(y)
95     ax.set_yticklabels([names[t] for t in terms])
96     ax.set_xlabel("相对周三 / 普通日的效应 (%，HC3 稳健 95% 置信区间)")
97     ax.legend(loc="lower right")
98     ax.invert_yaxis()
99     return plotting.save(fig, ctx.out("figures", "fig_calendar_effects.pdf"))
100
101
102 def fig_unit_kpis(ctx: StageContext, kpis: pd.DataFrame) -> dict[str, Any]:
103     k = kpis.sort_values("spend", ascending=False).reset_index(drop=True)
104     fig, axes = plotting.new_figure(6.3, 3.2, ncols=2, gridspec_kw={"width_ratios": [1.1, 1.0]})
105     ax = axes[0]
106     ax.barh(np.arange(len(k)), 100 * k["spend_share"], color="#0072B2", height=0.62)
107     ax.set_yticks(np.arange(len(k)))
108     ax.set_yticklabels([str(u) for u in k["推广单元ID"]], fontsize=7)
109     ax.invert_yaxis()
110     ax.set_xlabel("年度消费额占比 / %")
111     for i, v in enumerate(100 * k["spend_share"]):
112         if v >= 3:
113             ax.text(v + 0.5, i, f"{v:.1f}", va="center", fontsize=7, color="#333333")
114     ax = axes[1]
115     size = 12 + 300 * np.sqrt(k["spend_share"])
116     ax.scatter(k["cpc"], 100 * k["ctr"], s=size, color="#0072B2", alpha=0.65, edgecolor="white", lw=0.8)
117     for _, r in k.iterrows():
118         ax.annotate(
119             str(r["推广单元ID"])[-4:],
120             (r["cpc"], 100 * r["ctr"]),
121             fontsize=6,
122             xytext=(3, 3),
123             textcoords="offset points",
124             color="#333333",
125         )
126     ax.set_xlabel("平均点击成本 CPC / 元")
127     ax.set_ylabel("点击率 CTR / %")
128     ax.set_yscale("log")
129     return plotting.save(fig, ctx.out("figures", "fig_unit_kpis.pdf"))
130
131
132 def fig_lorenz(ctx: StageContext, lorenz: pd.DataFrame, conc: dict[str, Any]) -> dict[str, Any]:
133     fig, ax = plotting.new_figure(4.2, 3.4)
134     ax.plot(100 * lorenz["keyword_share"], 100 * lorenz["spend_share"], color="#0072B2", label="消费额")
135     ax.plot(100 * lorenz["keyword_share"], 100 * lorenz["click_share"], color="#D55E00", label="点击量")
136     ax.plot([0, 100], [0, 100], color="#888888", lw=0.8, ls="--", label="均匀分布")
137     ax.set_xlabel("关键词累计占比 / % (按消费额降序)")
138     ax.set_ylabel("累计占比 / %")
139     ax.annotate(
140         f"前 10 个词占 {100 * conc['top10_spend_share']:.1f}% 消费",
141         (100 * 10 / conc["keywords"], 100 * conc["top10_spend_share"]),
142         xytext=(25, 60),
143         textcoords="data",
144         fontsize=8,
145         arrowprops={"arrowstyle": "-", "color": "#555555", "lw": 0.7},
146     )
147     ax.legend(loc="lower right")
148     return plotting.save(fig, ctx.out("figures", "fig_lorenz.pdf"))

```

```

149
150
151 def fig_response_curves(ctx: StageContext, ud: pd.DataFrame, units: pd.DataFrame) -> dict[str, Any]:
152     fig, axes = plotting.new_figure(6.3, 6.0, nrows=3, ncols=4)
153     for ax, (_, row) in zip(axes.ravel(), units.sort_values("推广单元ID").iterrows()):
154         unit = int(row["推广单元ID"])
155         d = ud[(ud["推广单元ID"] == unit) & (ud["消费额"] > 0) & (ud["点击量"] > 0)]
156         ax.scatter(d["消费额"], d["点击量"], s=6, color="#0072B2", alpha=0.45, lw=0)
157         xs = np.geomspace(max(d["消费额"].min(), 0.1), d["消费额"].max(), 50)
158         ax.plot(xs, row["mean_daily_clicks"] * (xs / row["mean_daily_spend"]) ** row["gamma"], color="#D55E00", lw=1.4)
159         ax.set_xscale("log")
160         ax.set_yscale("log")
161         ax.set_title(f"unit: {unit} gamma={row['gamma']:.2f} + (" if row["gamma_source"] == "unit" else "*"), fontsize
162             ↳ =7.5)
163         ax.tick_params(labelsize=6)
164         fig.supxlabel("日消费额 / 元 (对数)", fontsize=9)
165         fig.supylabel("日点击量 / 次 (对数)", fontsize=9)
166         return plotting.save(fig, ctx.out("figures", "fig_response_curves.pdf"))
167
168 def fig_attribution(ctx: StageContext, fit: pd.DataFrame, attribution: dict[str, Any]) -> dict[str, Any]:
169     fig, ax = plotting.new_figure(6.3, 2.8)
170     fit["date"] = pd.to_datetime(fit["date"])
171     ax.plot(fit["date"], fit["regs"], color="#0072B2", lw=1.0, label="实际新注册数")
172     ax.plot(fit["date"], fit["fitted"], color="#D55E00", lw=1.2, label="归因模型拟合")
173     split = fit["date"].iloc[attribution["holdout"]["train_days"]]
174     ax.axvline(split, color="#444444", lw=0.8, ls="--")
175     ax.text(split, ax.get_ylim()[1] * 0.95, "留出期 →", fontsize=7, va="top")
176     _shade_holidays(ax)
177     ax.set_ylabel("日新注册数 / 人")
178     ax.legend(loc="upper left", ncol=2)
179     return plotting.save(fig, ctx.out("figures", "fig_attribution.pdf"))
180
181
182 def fig_cost_benefit(ctx: StageContext, table: pd.DataFrame, thr: dict[str, float]) -> dict[str, Any]:
183     fig, ax = plotting.new_figure(6.3, 4.0)
184     act = table[table["spend"] > 0]
185     for label in LABELS[:4]:
186         sub = act[act["label"] == label]
187         ax.scatter(
188             sub["spend"],
189             sub["benefit"],
190             s=9,
191             color=LABEL_COLORS[label],
192             alpha=0.65,
193             lw=0,
194             label=f"{label} ({len(sub)}) ",
195         )
196     ax.axvline(thr["cost_yuan"], color="#444444", lw=0.9, ls="--")
197     ax.axhline(thr["benefit"], color="#444444", lw=0.9, ls="--")
198     ax.set_xscale("log")
199     ax.set_xlabel("年度消费额 / 元 (对数轴; 无效词 = 零消费, 未画出)")
200     ax.set_ylabel("综合效益指数")
201     ax.legend(loc="upper left", markerscale=1.8)
202     return plotting.save(fig, ctx.out("figures", "fig_cost_benefit.pdf"))
203
204
205 def fig_class_thresholds(
206     ctx: StageContext, table: pd.DataFrame, thresholds: dict[str, dict[str, float]]
207 ) -> dict[str, Any]:
208     act = table[table["spend"] > 0]
209     fig, axes = plotting.new_figure(6.3, 2.8, ncols=2)
210     styles = {

```

```

211     "jenks": ("-", "#0072B2", "自然断点"),
212     "median": ("--", "#D55E00", "中位数"),
213     "gmm": (":", "#009E73", "高斯混合"),
214 }
215 axes[0].hist(act["log10_cost"], bins=40, color="#BBBBBB")
216 axes[1].hist(act["benefit"], bins=40, color="#BBBBBB")
217 for method, (ls, color, name) in styles.items():
218     if method in thresholds:
219         axes[0].axvline(thresholds[method]["log10_cost"], ls=ls, color=color, label=name)
220         axes[1].axvline(thresholds[method]["benefit"], ls=ls, color=color, label=name)
221 axes[0].set_xlabel("log10 年度消费额 / 元")
222 axes[1].set_xlabel("综合效益指数")
223 axes[0].set_ylabel("关键词数")
224 axes[1].legend(loc="upper right")
225 return plotting.save(fig, ctx.out("figures", "fig_class_thresholds.pdf"))
226
227
228 def fig_q3_gain(ctx: StageContext, summary: pd.DataFrame, boot: pd.DataFrame) -> dict[str, Any]:
229     fig, axes = plotting.new_figure(6.3, 3.0, ncols=3, gridspec_kw={"width_ratios": [1.2, 1.2, 0.9]})
230     for ax, (window, title) in zip(axes[:2], (("feb", "2025-02-01 至 02-08"), ("aug", "2025-08-01 至 08-08"))):
231         d = summary[summary["window"] == window].groupby("date")[["opt_regs", "prop_regs", "equal_regs"]].sum()
232         x = np.arange(len(d))
233         ax.plot(x, d["opt_regs"], marker="o", ms=3.5, color=STRATEGY_COLORS["最优分配"], label="最优分配")
234         prop_color = STRATEGY_COLORS["按历史比例"]
235         ax.plot(x, d["prop_regs"], marker="s", ms=3.5, color=prop_color, label="按历史比例")
236         ax.plot(x, d["equal_regs"], marker="^", ms=3.5, color=STRATEGY_COLORS["均匀分配"], label="均匀分配")
237         ax.set_xticks(x)
238         ax.set_xticklabels([s[-2:] for s in d.index], fontsize=7)
239         ax.set_title(title, fontsize=8.5)
240         ax.set_xlabel("日")
241     axes[0].set_ylabel("预期注册量 / 人")
242     axes[0].legend(loc="upper left", fontsize=7)
243     ax = axes[2]
244     for window, color in (("feb", "#0072B2"), ("aug", "#D55E00")):
245         b = boot[boot["window"] == window]
246         ax.hist(
247             100 * (b["ratio"] - 1),
248             bins=20,
249             color=color,
250             alpha=0.6,
251             label={ "feb": "2 月窗口", "aug": "8 月窗口" }[window],
252         )
253     ax.set_xlabel("相对历史比例的提升 / %")
254     ax.set_ylabel("自助抽样次数")
255     ax.legend(loc="upper right", fontsize=7)
256     return plotting.save(fig, ctx.out("figures", "fig_q3_gain.pdf"))
257
258
259 def fig_allocation_shift(
260     ctx: StageContext, allocation: pd.DataFrame, params: pd.DataFrame, cap_mult: float
261 ) -> dict[str, Any]:
262     """August window: where the optimum moves money -- optimal window-mean daily spend per keyword against its
263     2025 mean daily spend (log-log, class colours), and how many candidates of each class are ever selected."""
264     a = allocation[allocation["window"] == "aug"]
265     p = params[(params["window"] == "aug") & params["eligible"]]
266     n_days = max(a["date"].nunique(), 1)
267     opt = a.groupby("序号")["spend"].sum() / n_days # zero on days when the keyword is not selected
268     df = p[["序号", "label", "s"]].copy()
269     df["x_opt"] = df["序号"].map(opt).fillna(0.0)
270     labels = list(LABELS[:4])
271     fig, axes = plotting.new_figure(6.3, 3.0, ncols=2, gridspec_kw={"width_ratios": [1.35, 1.0]})
272     ax = axes[0]
273     sel = df[df["x_opt"] > 0]

```

```

274 lo = max(min(sel["s"].min(), sel["x_opt"].min()), 1e-3)
275 hi = max(sel["s"].max(), sel["x_opt"].max())
276 ax.plot([lo, hi], [lo, hi], color="#888888", lw=0.8, ls="--", label="投放不变")
277 ax.plot([lo, hi], [cap_mult * lo, cap_mult * hi], color="#888888", lw=0.8, ls=":", label=f"上限 {cap_mult:g} 倍")
278 for label in labels:
279     sub = sel[sel["label"] == label]
280     if len(sub):
281         ax.scatter(
282             sub["s"], sub["x_opt"], s=9, color=LABEL_COLORS[label], alpha=0.7, lw=0, label=f"{label} ({len(sub)}) "
283         )
284 ax.set_xscale("log")
285 ax.set_yscale("log")
286 ax.set_xlabel("2025 年日均消费 / 元 (对数) ")
287 ax.set_ylabel("最优分配的窗口日均投放 / 元 (对数) ")
288 ax.legend(loc="upper left", fontsize=6.5)
289 ax = axes[1]
290 counts = df.groupby("label").agg(candidates=("序号", "size"), selected=("x_opt", lambda v: int((v > 0).sum())))
291 counts = counts.reindex(labels).fillna(0)
292 x = np.arange(len(labels))
293 ax.bar(x - 0.2, counts["candidates"], width=0.38, color="#BBBBBB", label="候选词")
294 ax.bar(x + 0.2, counts["selected"], width=0.38, color=[LABEL_COLORS[lab] for lab in labels], label="至少入选一天")
295 for i, (c, s) in enumerate(zip(counts["candidates"], counts["selected"])):
296     ax.text(i - 0.2, c, f"{int(c)}", ha="center", va="bottom", fontsize=6.5, color="#333333")
297     ax.text(i + 0.2, s, f"{int(s)}", ha="center", va="bottom", fontsize=6.5, color="#333333")
298 ax.set_xticks(x)
299 ax.set_xticklabels(labels, fontsize=7.5)
300 ax.set_ylabel("关键词数 (8 月窗口) ")
301 ax.legend(loc="upper right", fontsize=7)
302 return plotting.save(fig, ctx.out("figures", "fig_allocation_shift.pdf"))
303
304
305 def fig_backtest(ctx: StageContext, bt: pd.DataFrame) -> dict[str, Any]:
306     targets = [
307         ("log_eff", "效率乘子"),
308         ("log_cpc", "CPC"),
309         ("logit_ctr", "CTR"),
310         ("logit_top", "上方位占比"),
311         ("logit_first", "首位占比"),
312         ("log_clicks", "点击量"),
313     ]
314     models = ("calendar", "calendar_wide", "seasonal_naive", "mean28")
315     fig, axes = plotting.new_figure(6.3, 2.7, ncols=2)
316     x = np.arange(len(targets))
317     width = 0.8 / len(models)
318     for k, model in enumerate(models):
319         sub = bt[bt["model"] == model].set_index("target").reindex([t for t, _ in targets])
320         off = (k - (len(models) - 1) / 2) * width
321         # the two calendar variants share the point forecast; only the interval differs
322         if model != "calendar_wide":
323             axes[0].bar(x + off, sub["mae"], width=width * 0.95, color=MODEL_COLORS[model], label=MODEL_NAMES[model])
324             axes[1].bar(
325                 x + off, 100 * sub["coverage80"], width=width * 0.95, color=MODEL_COLORS[model], label=MODEL_NAMES[model]
326             )
327     axes[1].axhline(80, color="#444444", lw=0.9, ls="--")
328     for ax in axes:
329         ax.set_xticks(x)
330         ax.set_xticklabels([n for _, n in targets], fontsize=7)
331     axes[0].set_ylabel("滚动回测 MAE (变换尺度) ")
332     axes[1].set_ylabel("80% 区间覆盖率 / %")
333     axes[1].legend(loc="lower right", fontsize=6, ncol=2)
334     return plotting.save(fig, ctx.out("figures", "fig_backtest.pdf"))
335
336

```

```

337 def fig_q4_plan(ctx: StageContext, days: pd.DataFrame) -> dict[str, Any]:
338     d = days.groupby("date").agg(
339         clicks=("clicks_mean", "sum"),
340         clicks_lo=("clicks_q10", "sum"),
341         clicks_hi=("clicks_q90", "sum"),
342         regs=("regs_mean", "sum"),
343         regs_lo=("regs_q10", "sum"),
344         regs_hi=("regs_q90", "sum"),
345         spend=("spend", "sum"),
346     )
347     d["cpc"] = d["spend"] / d["clicks"]
348     d["cpc_lo"] = d["spend"] / d["clicks_hi"]
349     d["cpc_hi"] = d["spend"] / d["clicks_lo"]
350     fig, axes = plotting.new_figure(6.3, 2.8, ncols=3)
351     x = np.arange(len(d))
352     for ax, (col, ylabel) in zip(
353         axes, (("clicks", "预期点击量 / 次"), ("regs", "预期注册量 / 人"), ("cpc", "预期 CPC / 元"))
354     ):
355         ax.fill_between(x, d[f"{col}_lo"], d[f"{col}_hi"], color="#0072B2", alpha=0.2, lw=0, label="10%-90% 分位")
356         ax.plot(x, d[col], marker="o", ms=3.5, color="#0072B2", label="期望")
357         ax.set_xticks(x)
358         ax.set_xticklabels([s[-2:] for s in d.index], fontsize=7)
359         ax.set_ylabel(ylabel)
360         ax.set_xlabel("2026 年 9 月")
361     axes[0].legend(loc="upper right", fontsize=7)
362     return plotting.save(fig, ctx.out("figures", "fig_q4_plan.pdf"))
363
364
365 def fig_q4_units(ctx: StageContext, per_unit: list[dict[str, Any]]) -> dict[str, Any]:
366     df = pd.DataFrame(per_unit).sort_values("regs_mean", ascending=True)
367     fig, ax = plotting.new_figure(5.4, 3.2)
368     y = np.arange(len(df))
369     # a log axis cannot show a zero lower bound: clip it to a decade below the smallest
370     # positive value and mark the affected units with an arrow so the truncation is visible
371     floor = max(float(df.loc[df["regs_q10"] > 0, "regs_q10"].min()) / 10, 1e-2) if (df["regs_q10"] > 0).any() else 0.01
372     lo = df["regs_q10"].clip(lower=floor)
373     truncated = df["regs_q10"] <= 0
374     ax.errorbar(
375         df["regs_mean"],
376         y,
377         xerr=[df["regs_mean"] - lo, df["regs_q90"] - df["regs_mean"]],
378         fmt="o",
379         ms=4,
380         color="#0072B2",
381         ecolor="#0072B2",
382         elinewidth=1.2,
383         capsize=2,
384     )
385     ax.set_yticks(y)
386     ax.set_yticklabels([str(u) for u in df["推广单元ID"]], fontsize=7)
387     ax.set_xlabel("2026-09-11 至 09-17 预期注册量 / 人 (点 = 期望, 横线 = 10%-90% 分位)")
388     ax.set_xscale("log")
389     for yy in y[truncated.to_numpy()]:
390         ax.plot(floor, yy, marker="<", ms=5, color="#D55E00", clip_on=False)
391     if truncated.any():
392         ax.text(
393             0.02, 0.02, "左向箭头: 10% 分位为 0 (对数轴截断)", transform=ax.transAxes, fontsize=6.5, color="#D55E00"
394         )
395     return plotting.save(fig, ctx.out("figures", "fig_q4_units.pdf"))
396
397
398 def build_figures(ctx: StageContext) -> dict[str, Any]:
399     eda_dir, cls_dir, alloc_dir, fc_dir = ctx.dep("eda"), ctx.dep("classify"), ctx.dep("allocate"), ctx.dep("forecast")

```

```

400 daily = pd.read_parquet(eda_dir / "daily_totals.parquet")
401 daily["date"] = pd.to_datetime(daily["date"])
402 made = [
403     fig_daily_series(ctx, daily),
404     fig_calendar_effects(ctx, pd.read_parquet(eda_dir / "calendar_regression.parquet")),
405     fig_unit_kpis(ctx, pd.read_parquet(eda_dir / "unit_kpis.parquet")),
406     fig_lorenz(
407         ctx,
408         pd.read_parquet(eda_dir / "lorenz.parquet"),
409         json.loads((eda_dir / "concentration.json").read_text(encoding="utf-8")),
410     ),
411     fig_response_curves(
412         ctx, pd.read_parquet(eda_dir / "unit_daily.parquet"), pd.read_parquet(eda_dir / "unit_response.parquet")
413     ),
414     fig_attribution(
415         ctx,
416         pd.read_parquet(eda_dir / "attribution_fit.parquet"),
417         json.loads((eda_dir / "attribution.json").read_text(encoding="utf-8")),
418     ),
419 ]
420 summary = json.loads((cls_dir / "classification_summary.json").read_text(encoding="utf-8"))
421 table = pd.read_parquet(cls_dir / "classification.parquet")
422 made += [
423     fig_cost_benefit(ctx, table, summary["thresholds"][summary["main"]]),
424     fig_class_thresholds(ctx, table, summary["thresholds"]),
425 ]
426 made += [
427     fig_q3_gain(
428         ctx,
429         pd.read_parquet(alloc_dir / "allocation_summary.parquet"),
430         pd.read_parquet(alloc_dir / "bootstrap.parquet"),
431     ),
432     fig_allocation_shift(
433         ctx,
434         pd.read_parquet(alloc_dir / "allocation.parquet"),
435         pd.read_parquet(alloc_dir / "keyword_parameters.parquet"),
436         float(ctx.cfg("allocate.cap_multiplier", 4.0)),
437     ),
438     fig_backtest(ctx, pd.read_parquet(fc_dir / "backtest_summary.parquet")),
439     fig_q4_plan(ctx, pd.read_parquet(fc_dir / "plan_by_unit_day.parquet")),
440     fig_q4_units(ctx, json.loads((fc_dir / "plan_by_unit.json").read_text(encoding="utf-8"))),
441 ]
442 ctx.write_json("figures_index.json", made)
443 return {"figures": len(made)}

```

pipelines/e/forecast.py

```

1 """Problem 4: unit-level daily forecasts with rolling-origin backtests, scenario generation and Monte Carlo ranges."""
2
3 from __future__ import annotations
4
5 from typing import Any
6
7 import numpy as np
8 import pandas as pd
9 from scipy import stats
10
11 from pipelines.e.calendar import day_features
12
13 TARGETS: dict[str, dict[str, Any]] = {
14     "log_eff": {"label": "效率乘子 log eff", "transform": "exp"},

```

```

15     "log_cpc": {"label": "log CPC", "transform": "exp"},
16     "logit_ctr": {"label": "logit CTR", "transform": "expit"},
17     "logit_top": {"label": "logit 上方位占比", "transform": "expit"},
18     "logit_first": {"label": "logit 首位占比", "transform": "expit"},
19     "log_clicks": {"label": "log 点击量", "transform": "exp"},
20 }
21 Z80 = float(stats.norm.ppf(0.9))
22
23
24 def _logit(p: np.ndarray) -> np.ndarray:
25     p = np.clip(np.asarray(p, dtype=float), 0.005, 0.995)
26     return np.log(p / (1 - p))
27
28
29 def back_transform(values: np.ndarray, transform: str) -> np.ndarray:
30     values = np.asarray(values, dtype=float)
31     return np.exp(values) if transform == "exp" else 1 / (1 + np.exp(-values))
32
33
34 def unit_series(ud_unit: pd.DataFrame, gamma: float, mean_spend: float, mean_clicks: float) -> pd.DataFrame:
35     """Daily targets for one unit on days with positive spend and clicks."""
36     d = ud_unit[(ud_unit["消费额"] > 0) & (ud_unit["点击量"] > 0) & (ud_unit["展现量"] > 0)].copy()
37     d = d.sort_values("日期")
38     spend = d["消费额"].to_numpy(dtype=float)
39     clicks = d["点击量"].to_numpy(dtype=float)
40     out = pd.DataFrame({"date": d["日期"].to_numpy()})
41     out["log_eff"] = np.log(clicks) - gamma * np.log(spend / mean_spend) - np.log(mean_clicks)
42     out["log_cpc"] = np.log(spend / clicks)
43     out["logit_ctr"] = _logit(clicks / d["展现量"].to_numpy(dtype=float))
44     out["logit_top"] = _logit(d["top_share"].to_numpy(dtype=float))
45     out["logit_first"] = _logit(d["first_share"].to_numpy(dtype=float))
46     out["log_clicks"] = np.log(clicks)
47     feats = day_features(out["date"]).drop(columns=["date"])
48     return pd.concat([out.reset_index(drop=True), feats], axis=1)
49
50
51 def _design(feats: pd.DataFrame, months: list[int]) -> np.ndarray:
52     cols = [np.ones(len(feats))]
53     for wd in range(7):
54         if wd != 2:
55             cols.append((feats["weekday"] == wd).to_numpy(dtype=float))
56     for m in months:
57         cols.append((feats["month"] == m).to_numpy(dtype=float))
58     cols.append(feats["is_holiday"].to_numpy(dtype=float))
59     cols.append(feats["is_adjusted_workday"].to_numpy(dtype=float))
60     return np.column_stack(cols)
61
62
63 class CalendarModel:
64     """Ridge-stabilised least squares of a target on weekday, month and holiday indicators."""
65
66     def __init__(self, ridge: float = 1e-3) -> None:
67         self.ridge = ridge
68         self.months: list[int] = []
69         self.beta = np.zeros(0)
70         self.sd = float("nan")
71         self.month_sd = 0.0
72
73     def fit(self, train: pd.DataFrame, target: str) -> CalendarModel:
74         months = sorted(int(m) for m in train["month"].unique())
75         self.months = [m for m in months if m != months[0]]
76         X = _design(train, self.months)
77         y = train[target].to_numpy(dtype=float)

```

```

78     reg = self.ridge * np.eye(X.shape[1])
79     reg[0, 0] = 0.0
80     self.beta = np.linalg.solve(X.T @ X + reg, X.T @ y)
81     resid = y - X @ self.beta
82     dof = max(len(y) - X.shape[1], 1)
83     self.sd = float(np.sqrt(np.sum(resid**2) / dof))
84     n_wd = 6
85     month_effects = self.beta[1 + n_wd : 1 + n_wd + len(self.months)]
86     self.month_sd = float(np.std(np.concatenate([[0.0], month_effects]))) if len(month_effects) else 0.0
87     return self
88
89 def predict(self, feats: pd.DataFrame, month_known: bool = True) -> np.ndarray:
90     f = feats.copy()
91     if not month_known:
92         f["month"] = -1 # reference-month behaviour when the target month never appeared in training
93     return _design(f, self.months) @ self.beta
94
95
96 def seasonal_naive(train: pd.DataFrame, target: str, future: pd.DataFrame) -> np.ndarray:
97     """Last observed value on the same weekday (falls back to the last observation)."""
98     out = np.empty(len(future))
99     last = train[target].to_numpy(dtype=float)[-1]
100    by_wd = train.groupby("weekday")[target].last()
101    for i, wd in enumerate(future["weekday"].to_numpy()):
102        out[i] = float(by_wd.get(int(wd), last))
103    return out
104
105
106 def pinball(y: np.ndarray, q: np.ndarray, tau: float) -> float:
107     diff = y - q
108     return float(np.mean(np.maximum(tau * diff, (tau - 1) * diff)))
109
110
111 def rolling_backtest(
112     series: pd.DataFrame, target: str, origins: list[pd.Timestamp], horizon: int = 7, min_train: int = 40
113 ) -> pd.DataFrame:
114     """Rolling-origin evaluation of the calendar model vs. seasonal-naive vs. 28-day mean."""
115     rows = []
116     info = TARGETS[target]
117     for origin in origins:
118         train = series[series["date"] < origin]
119         test = series[(series["date"] >= origin) & (series["date"] < origin + pd.Timedelta(days=horizon))]
120         if len(train) < min_train or len(test) == 0:
121             continue
122         y = test[target].to_numpy(dtype=float)
123         y_raw = back_transform(y, info["transform"])
124         preds: dict[str, tuple[np.ndarray, np.ndarray, np.ndarray]] = {}
125         model = CalendarModel().fit(train, target)
126         known = int(test["month"].iloc[0]) in {*model.months, sorted(train["month"].unique())[0]}
127         mu = model.predict(test, month_known=known)
128         preds["calendar"] = (mu, mu - Z80 * model.sd, mu + Z80 * model.sd)
129         # the deployed 2026 intervals widen the residual sd by the between-month dispersion; the same
130         # widened interval is backtested here so that the reported coverage refers to what is shipped
131         sd_wide = float(np.sqrt(model.sd**2 + model.month_sd**2))
132         preds["calendar_wide"] = (mu, mu - Z80 * sd_wide, mu + Z80 * sd_wide)
133         sn = seasonal_naive(train, target, test)
134         tr = train[target].to_numpy(dtype=float)
135         sn_err = tr[7:] - tr[:-7] if len(tr) > 7 else np.array([0.0])
136         preds["seasonal_naive"] = (sn, sn + np.quantile(sn_err, 0.1), sn + np.quantile(sn_err, 0.9))
137         m28 = float(tr[-28:].mean())
138         dev = tr[-28:] - m28
139         preds["mean28"] = (np.full(len(y), m28), m28 + np.quantile(dev, 0.1), m28 + np.quantile(dev, 0.9))
140         for name, (p, lo, hi) in preds.items():

```

```

141         p_raw = back_transform(p, info["transform"])
142         rows.append(
143             {
144                 "target": target,
145                 "model": name,
146                 "origin": origin,
147                 "n": len(y),
148                 "mae": float(np.mean(np.abs(y - p))),
149                 "rmse": float(np.sqrt(np.mean((y - p) ** 2))),
150                 "mape_raw": float(np.mean(np.abs(y_raw - p_raw) / np.maximum(np.abs(y_raw), 1e-9))),
151                 "pinball10": pinball(y, lo, 0.1),
152                 "pinball90": pinball(y, hi, 0.9),
153                 "coverage80": float(np.mean((y >= lo) & (y <= hi))),
154             }
155         )
156     return pd.DataFrame(rows)
157
158
159 def forecast_unit(series: pd.DataFrame, target: str, future: pd.DataFrame) -> dict[str, Any]:
160     """Point forecast, residual sd and between-month sd for the future days (calendar model on all data)."""
161     model = CalendarModel().fit(series, target)
162     known = all(int(m) in {*model.months, sorted(series["month"].unique())[0]} for m in future["month"].unique())
163     mu = model.predict(future, month_known=known)
164     return {"mean": mu, "sd": model.sd, "month_sd": model.month_sd, "month_known": known, "n": len(series)}
165
166
167 def simulate_group(
168     x: np.ndarray,
169     params: pd.DataFrame,
170     gamma: float,
171     eff_mean: float,
172     eff_sd: float,
173     kw_sd: float,
174     ctr_mean_logit: float,
175     ctr_sd: float,
176     pos_top: dict[str, Any],
177     pos_first: dict[str, Any],
178     top_sd: float,
179     rng: np.random.Generator,
180     n_scen: int = 500,
181 ) -> dict[str, np.ndarray]:
182     """Monte Carlo of clicks, CPC, impressions, position, views and registrations for one unit-day allocation.
183
184     Common day shock (log-normal efficiency), keyword idiosyncratic log-normal noise, CTR and position
185     day shocks, Poisson registrations. Returns arrays of shape (n_scen, n_keywords).
186     """
187     from pipelines.e.response import expected_position, position_shares
188
189     n = len(x)
190     c = params["c"].to_numpy(dtype=float)
191     s = params["s"].to_numpy(dtype=float)
192     rho = params["rho"].to_numpy(dtype=float)
193     depth = params["depth"].to_numpy(dtype=float)
194     base = c * np.power(np.maximum(x, 0.0) / s, gamma)
195     # eff_mean is the calendar model's conditional mean of log eff, so the day multiplier is
196     # log-normal with mean exp(eff_mean + eff_sd^2 / 2) -- the same expectation the allocation uses;
197     # the keyword noise is a mean-one multiplicative disturbance around that expectation
198     day = np.exp(eff_mean + eff_sd * rng.standard_normal((n_scen, 1)))
199     idio = np.exp(kw_sd * rng.standard_normal((n_scen, n)) - 0.5 * kw_sd**2)
200     clicks = base[None, :] * day * idio
201     with np.errstate(divide="ignore", invalid="ignore"):
202         cpc = np.where(clicks > 0, x[None, :] / clicks, np.nan)
203     ctr = 1 / (1 + np.exp(-(ctr_mean_logit + ctr_sd * rng.standard_normal((n_scen, 1)))))

```

```

204     imp = clicks / ctr
205     p_top, p_first = position_shares(np.nan_to_num(cpc, nan=1.0), pos_top, pos_first)
206     shock = top_sd * rng.standard_normal((n_scen, 1))
207     p_top = 1 / (1 + np.exp(-(np.log(p_top / (1 - p_top)) + shock)))
208     p_first = np.minimum(p_first, p_top)
209     position = expected_position(p_top, p_first)
210     views = clicks * depth[None, :]
211     regs = rng.poisson(np.maximum(rho[None, :] * clicks, 0.0)).astype(float)
212     return {
213         "clicks": clicks,
214         "cpc": cpc,
215         "imp": imp,
216         "position": position,
217         "views": views,
218         "regs": regs,
219         "p_top": p_top,
220         "p_first": p_first,
221     }
222
223
224 def summarise(samples: np.ndarray, axis: int = 0) -> dict[str, np.ndarray]:
225     return {
226         "mean": np.nanmean(samples, axis=axis),
227         "q10": np.nanquantile(samples, 0.1, axis=axis),
228         "q50": np.nanquantile(samples, 0.5, axis=axis),
229         "q90": np.nanquantile(samples, 0.9, axis=axis),
230     }

```

pipelines/e/response.py

```

1  """Keyword response model (concave power law calibrated per unit), position model and keyword parameters."""
2
3  from __future__ import annotations
4
5  from typing import Any
6
7  import numpy as np
8  import pandas as pd
9  import statsmodels.api as sm
10
11  GAMMA_BOUNDS = (0.3, 0.95)
12  MIN_DAYS_FOR_UNIT_GAMMA = 60
13  POSITION_NON_TOP = 4.0 # ranking index assigned to impressions outside the top region (positions > 3)
14  POSITION_TOP_OTHER = 2.5 # mean ranking of top-region impressions that are not in first place
15
16
17 def fit_unit_gamma(df: pd.DataFrame) -> dict[str, Any]:
18     """log clicks = const + gamma * log spend + weekday dummies, on days with positive spend and clicks."""
19     d = df[(df["消费额"] > 0) & (df["点击量"] > 0)]
20     n = len(d)
21     if n < 10:
22         return {"n": n, "gamma": np.nan, "se": np.nan, "r2": np.nan}
23     X = pd.DataFrame({"const": 1.0, "log_spend": np.log(d["消费额"].to_numpy(dtype=float))}, index=d.index)
24     for wd in range(1, 7):
25         X[f"wd{wd}"] = (d["weekday"] == wd).astype(float)
26     fit = sm.OLS(np.log(d["点击量"].to_numpy(dtype=float)), X).fit(cov_type="HC3")
27     return {
28         "n": int(n),
29         "gamma": float(fit.params["log_spend"]),
30         "se": float(fit.bse["log_spend"]),
31         "r2": float(fit.rsquared),

```

```

32     }
33
34
35 def pooled_gamma(ud: pd.DataFrame) -> dict[str, Any]:
36     """Same regression pooled over units with unit fixed effects."""
37     d = ud[(ud["消费额"] > 0) & (ud["点击量"] > 0)]
38     X = pd.DataFrame({"const": 1.0, "log_spend": np.log(d["消费额"].to_numpy(dtype=float))}, index=d.index)
39     units = sorted(d["推广单元ID"].unique())
40     for u in units[1:]:
41         X[f"u{u}"] = (d["推广单元ID"] == u).astype(float)
42     for wd in range(1, 7):
43         X[f"wd{wd}"] = (d["weekday"] == wd).astype(float)
44     fit = sm.OLS(np.log(d["点击量"].to_numpy(dtype=float)), X).fit(cov_type="HC3")
45     return {
46         "n": len(d),
47         "gamma": float(fit.params["log_spend"]),
48         "se": float(fit.bse["log_spend"]),
49         "r2": float(fit.rsquared),
50     }
51
52
53 def select_gamma(est: dict[str, Any], pooled: float) -> tuple[float, str]:
54     """Unit estimate when well identified and inside the concave range, else the pooled elasticity."""
55     g = est.get("gamma", np.nan)
56     if est.get("n", 0) >= MIN_DAYS_FOR_UNIT_GAMMA and np.isfinite(g) and GAMMA_BOUNDS[0] <= g <= GAMMA_BOUNDS[1]:
57         return float(g), "unit"
58     return float(np.clip(pooled, *GAMMA_BOUNDS)), "pooled"
59
60
61 def unit_response_table(ud: pd.DataFrame) -> pd.DataFrame:
62     """Per-unit elasticity table (estimate, SE, n, R2, selected gamma and its source)."""
63     pooled = pooled_gamma(ud)
64     rows = []
65     for (plan, unit), df in ud.groupby(["方案ID", "推广单元ID"]):
66         est = fit_unit_gamma(df)
67         gamma, source = select_gamma(est, pooled["gamma"])
68         active = df[df["消费额"] > 0]
69         rows.append(
70             {
71                 "方案ID": int(plan),
72                 "推广单元ID": int(unit),
73                 "n_days": est["n"],
74                 "gamma_hat": est["gamma"],
75                 "gamma_se": est["se"],
76                 "r2": est["r2"],
77                 "gamma": gamma,
78                 "gamma_source": source,
79                 "active_days": len(active),
80                 "mean_daily_spend": float(active["消费额"].mean()) if len(active) else 0.0,
81                 "mean_daily_clicks": float(active["点击量"].mean()) if len(active) else 0.0,
82                 "p95_spend_ratio": float(active["消费额"].quantile(0.95) / max(active["消费额"].mean(), 1e-9))
83                 if len(active)
84                 else 1.0,
85                 "pooled_gamma": pooled["gamma"],
86                 "pooled_se": pooled["se"],
87             }
88         )
89     return pd.DataFrame(rows)
90
91
92 def clicks_response(x: np.ndarray, c: np.ndarray, s: np.ndarray, gamma: float) -> np.ndarray:
93     """Expected clicks at spend `x` for keywords with mean daily spend `s` and clicks `c`:  $c (x/s)^{\gamma}$ """
94     x = np.asarray(x, dtype=float)

```

```

95     return c * np.power(np.maximum(x, 0.0) / s, gamma)
96
97
98 def cpc_response(x: np.ndarray, c: np.ndarray, s: np.ndarray, gamma: float) -> np.ndarray:
99     """Average CPC at spend ``x`` (rises with spend when gamma < 1)."""
100     clicks = clicks_response(x, c, s, gamma)
101     with np.errstate(divide="ignore", invalid="ignore"):
102         return np.where(clicks > 0, np.asarray(x, dtype=float) / clicks, np.nan)
103
104
105 def _logit(p: np.ndarray) -> np.ndarray:
106     p = np.clip(p, 0.005, 0.995)
107     return np.log(p / (1 - p))
108
109
110 def fit_position_model(df: pd.DataFrame, share_col: str, min_imp: int = 30) -> dict[str, Any]:
111     """logit(share) = a + b log CPC on unit-days (impression-weighted); slope forced non-negative."""
112     d = df[(df["展现量"] >= min_imp) & (df["点击量"] > 0) & (df["消费额"] > 0)]
113     mean_share = float((df[share_col] * df["展现量"]).sum() / max(df["展现量"].sum(), 1.0)) if len(df) else 0.0
114     if len(d) < 20:
115         return {
116             "a": float(_logit(np.array([mean_share]))[0]),
117             "b": 0.0,
118             "n": len(d),
119             "r2": np.nan,
120             "mean_share": mean_share,
121             "source": "constant",
122         }
123     y = _logit(d[share_col].to_numpy(dtype=float))
124     X = sm.add_constant(np.log(d["cpc"].to_numpy(dtype=float)))
125     fit = sm.WLS(y, X, weights=np.sqrt(d["展现量"].to_numpy(dtype=float))).fit()
126     a, b = float(fit.params[0]), float(fit.params[1])
127     if b < 0: # a negative slope has no causal reading (bid up -> lower position); use the constant model
128         return {
129             "a": float(_logit(np.array([mean_share]))[0]),
130             "b": 0.0,
131             "n": len(d),
132             "r2": float(fit.rsquared),
133             "mean_share": mean_share,
134             "source": "constant",
135         }
136     return {"a": a, "b": b, "n": len(d), "r2": float(fit.rsquared), "mean_share": mean_share, "source": "logit"}
137
138
139 def position_shares(
140     cpc: np.ndarray, model_top: dict[str, Any], model_first: dict[str, Any]
141 ) -> tuple[np.ndarray, np.ndarray]:
142     """Expected top-region and first-place impression shares at a given CPC."""
143     lc = np.log(np.maximum(np.asarray(cpc, dtype=float), 1e-6))
144     p_top = 1 / (1 + np.exp(-(model_top["a"] + model_top["b"] * lc)))
145     p_first = 1 / (1 + np.exp(-(model_first["a"] + model_first["b"] * lc)))
146     p_first = np.minimum(p_first, p_top)
147     return p_top, p_first
148
149
150 def expected_position(p_top: np.ndarray, p_first: np.ndarray) -> np.ndarray:
151     """Expected ranking index: 1 for first place, 2.5 for other top-region slots, 4 outside the top region."""
152     return 1.0 * p_first + POSITION_TOP_OTHER * (p_top - p_first) + POSITION_NON_TOP * (1.0 - p_top)
153
154
155 def keyword_parameters(
156     kw: pd.DataFrame,
157     units: pd.DataFrame,

```

```

158     rates: dict[int, float],
159     kappa_bounds: tuple[float, float] = (0.25, 2.5),
160 ) -> pd.DataFrame:
161     """Per-keyword response parameters for active keywords (spend > 0).
162
163     s_i, c_i: mean daily spend / clicks over the unit's active days; depth_i views per click (unit
164     fallback); kappa_i bounce-quality multiplier normalised to the unit's click-weighted mean bounce;
165     rho_i = r_u * kappa_i expected registrations per click.
166
167     """
168     u = units.set_index("推广单元ID")
169     active = kw[kw["spend"] > 0].copy()
170     days = active["推广单元ID"].map(u["active_days"]).astype(float)
171     active["s"] = active["spend"] / days
172     active["c"] = active["clicks"] / days
173     active["gamma"] = active["推广单元ID"].map(u["gamma"]).astype(float)
174     # keywords with clicks but no recorded page views (bounce reported as 0) are tracking failures:
175     # both engagement fields are treated as missing and fall back to the unit's click-weighted means.
176     untracked = (active["views"] <= 0) & (active["clicks"] > 0)
177     active.loc[untracked, "depth"] = np.nan
178     active.loc[untracked, "bounce"] = np.nan
179     tracked = active[~untracked]
180     unit_depth = tracked.groupby("推广单元ID").apply(
181         lambda d: d["views"].sum() / max(d["clicks"].sum(), 1), include_groups=False
182     )
183     active["depth"] = active["depth"].fillna(active["推广单元ID"].map(unit_depth)).fillna(1.0)
184     unit_bounce = tracked.groupby("推广单元ID").apply(
185         lambda d: float(np.average(d["bounce"].fillna(1.0), weights=np.maximum(d["clicks"], 1))), include_groups=False
186     )
187     b_i = active["bounce"].fillna(active["推广单元ID"].map(unit_bounce)).fillna(0.5)
188     kappa = (1.0 - b_i) / (1.0 - active["推广单元ID"].map(unit_bounce)).clip(lower=0.02)
189     active["kappa"] = kappa.clip(*kappa_bounds).fillna(1.0)
190     active["rate"] = active["推广单元ID"].map(rates).astype(float)
191     active["rho"] = active["rate"] * active["kappa"]
192     active["cpc"] = active["spend"] / active["clicks"]
193     return active

```

pipelines/e/stages.py

```

1 """Problem E stages: validate, eda (Q1), classify (Q2), allocate (Q3), forecast (Q4), results, figures, tables.
2
3 Conventions (see docs/ENGINEERING_STANDARD.md):
4 * every stage is ``@stage(name, deps=(...))`` and returns a JSON-serialisable metrics dict;
5 * outputs go only to ``ctx.out(...)``; paper numbers via ``ctx.number("Key", value)``;
6 * ``results`` writes result*.xlsx with ``forge.xlsx.write_result`` from the organisers' templates;
7 * every forecast carries a backtest and every allocation an independent optimality audit.
8
9
10 from __future__ import annotations
11
12 from typing import Any
13
14 import numpy as np
15 import pandas as pd
16
17 from forge import xlsx
18 from forge.context import StageContext
19 from forge.runner import stage
20 from pipelines.common.validation import run_validation
21 from pipelines.e import allocate as alloc
22 from pipelines.e import classify as cls
23 from pipelines.e import eda as eda_mod

```

```

24 from pipelines.e import forecast as fc
25 from pipelines.e import response as resp
26 from pipelines.e.calendar import day_features
27 from pipelines.e.contracts import INPUT_CONTRACTS
28 from pipelines.e.data import daily_totals, keyword_table, load_sheets, unit_click_matrix, unit_daily
29
30 Q3_WINDOWS: dict[str, tuple[str, str]] = {"feb": ("2025-02-01", "2025-02-08"), "aug": ("2025-08-01", "2025-08-08")}
31 Q4_DATES = ("2026-09-11", "2026-09-17")
32 Q4_REFERENCE = ("2025-09-11", "2025-09-17")
33 RESULT_HEADER = [
34     "日期",
35     "方案ID",
36     "推广单元",
37     "关键词",
38     "投入金额",
39     "预期展位",
40     "预期点击量",
41     "预期浏览量",
42     "预期注册量",
43 ]
44
45
46 @stage("validate", deps=("ingest",), description="Validate the three SEM sheets against their contracts")
47 def validate(ctx: StageContext) -> dict[str, Any]:
48     return run_validation(ctx, INPUT_CONTRACTS)
49
50
51 def _save(ctx: StageContext, df: pd.DataFrame, name: str) -> None:
52     df.to_parquet(ctx.out(f"{name}.parquet"), index=False)
53     df.to_csv(ctx.out(f"{name}.csv"), index=False)
54
55
56 # ----- Q1
57 @stage(
58     "eda",
59     deps=("validate",),
60     description="Q1: KPIs, keyword concentration, calendar/holiday effects, registration attribution",
61 )
62 def eda(ctx: StageContext) -> dict[str, Any]:
63     ctx.seed_everything("eda")
64     s1, s2, s3 = load_sheets(ctx.dep("ingest"))
65     ud = unit_daily(s1)
66     daily = daily_totals(s1, s2)
67     kw = keyword_table(s3)
68     _save(ctx, ud, "unit_daily")
69     _save(ctx, daily.reset_index(), "daily_totals")
70
71     kpis = eda_mod.unit_kpis(s1)
72     _save(ctx, kpis, "unit_kpis")
73     conc = eda_mod.keyword_concentration(kw)
74     _save(ctx, conc.pop("lorenz"), "lorenz")
75     kw_per_unit = conc.pop("per_unit")
76     _save(ctx, kw_per_unit, "keyword_per_unit")
77     ctx.write_json("concentration.json", conc)
78
79     coef_frames, summaries = [], []
80     specs: list[tuple[str, bool, tuple[str, ...]]] = [
81         ("regs", True, ()),
82         ("regs", True, ("spend",)),
83         ("spend", True, ()),
84         ("clicks", True, ()),
85         ("imp", True, ()),
86         ("cpc", False, ()),

```

```

87         ("ctr", False, ()),
88         ("top_share", False, ()),
89     ]
90     for target, log, controls in specs:
91         coef, summary = eda_mod.calendar_regression(daily, target, log, controls)
92         coef_frames.append(coef)
93         summaries.append(summary)
94     coefs = pd.concat(coef_frames, ignore_index=True)
95     _save(ctx, coefs, "calendar_regression")
96     nonparam = [eda_mod.holiday_nonparametric(daily, t) for t in ("regs", "spend", "clicks")]
97     ctx.write_json("calendar_regression_summary.json", {"models": summaries, "mann_whitney": nonparam})
98     _save(
99         ctx,
100         eda_mod.day_type_profile(daily, ("spend", "clicks", "imp", "regs", "cpc", "ctr", "top_share")),
101         "day_type_profile",
102     )
103
104     attribution = eda_mod.attribution_model(unit_click_matrix(s1), daily)
105     _save(ctx, attribution.pop("fitted"), "attribution_fit")
106     ctx.write_json("attribution.json", attribution)
107     units = resp.unit_response_table(ud)
108     _save(ctx, units, "unit_response")
109     pooled_g = float(units["pooled_gamma"].iloc[0])
110     cut = eda_mod.holiday_optimal_cut(daily, alt_elasticities=(pooled_g,), seed=ctx.seed("optimal-cut"))
111     ctx.write_json("optimal_cut.json", cut)
112     diag = eda_mod.attribution_diagnostics(unit_click_matrix(s1), daily, attribution, seed=ctx.seed("attribution-boot"))
113     ↵ )
114     _save(ctx, diag.pop("table"), "attribution_rates")
115     ctx.write_json("attribution_diagnostics.json", diag)
116
117     total_spend = float(s1["消费额"].sum())
118     total_clicks, total_imp = int(s1["点击量"].sum()), int(s1["展现量"].sum())
119     ctx.number("TotalSpend", total_spend, ".2f")
120     ctx.number("TotalSpendWan", total_spend / 1e4, ".2f")
121     ctx.number("TotalClicks", total_clicks, ",d")
122     ctx.number("TotalImpressions", total_imp, ",d")
123     ctx.number("TotalRegs", int(daily["regs"].sum()), ",d")
124     ctx.number("OverallCtrPct", 100 * total_clicks / total_imp, ".2f")
125     ctx.number("OverallCpc", total_spend / total_clicks, ".4f")
126     ctx.number("TopSharePct", 100 * s1["上方位展现量"].sum() / total_imp, ".2f")
127     ctx.number("FirstSharePct", 100 * s1["上方首位展现量"].sum() / total_imp, ".2f")
128     ctx.number("TopClickSharePct", 100 * s1["上方位点击量"].sum() / total_clicks, ".2f")
129     ctx.number("TopSpendSharePct", 100 * s1["上方位消费额"].sum() / total_spend, ".2f")
130     ctx.number("TopCpc", s1["上方位消费额"].sum() / s1["上方位点击量"].sum(), ".4f")
131     other_clicks = total_clicks - s1["上方位点击量"].sum()
132     ctx.number("OtherCpc", (total_spend - s1["上方位消费额"].sum()) / other_clicks, ".4f")
133     top_imp = s1["上方位展现量"].sum()
134     ctx.number("TopRegionCtrPct", 100 * s1["上方位点击量"].sum() / top_imp, ".2f")
135     ctx.number("OtherRegionCtrPct", 100 * other_clicks / (total_imp - top_imp), ".2f")
136     ctx.number("UnitDays", len(s1))
137     ctx.number("UnitsCount", int(s1["推广单元ID"].nunique()))
138     ctx.number("PlansCount", int(s1["方案ID"].nunique()))
139     ctx.number("ZeroSpendUnitDays", int((s1["消费额"] == 0).sum()))
140     ctx.number("KeywordRows", conc["keywords"])
141     ctx.number("UniqueKeywordIds", conc["unique_keyword_ids"])
142     ctx.number("SharedKeywordIds", conc["shared_keyword_ids"])
143     ctx.number("ActiveKeywords", conc["active_keywords"])
144     ctx.number("ZeroKeywords", conc["zero_cost_zero_benefit"])
145     ctx.number("ZeroKeywordSharePct", 100 * conc["zero_cost_zero_benefit"] / conc["keywords"], ".1f")
146     ctx.number("SharedKeywordRows", int((kw["shared_units"] > 1).sum()))
147     ctx.number("GiniSpendActive", conc["gini_spend_active"], ".4f")
148     ctx.number("TopTenSpendSharePct", 100 * conc["top10_spend_share"], ".2f")
149     ctx.number("TopHundredSpendSharePct", 100 * conc["top100_spend_share"], ".2f")

```

```

149 big = kpis.sort_values("spend", ascending=False).iloc[0]
150 ctx.number("BiggestUnitSpendSharePct", 100 * big["spend_share"], ".2f")
151 ctx.number("BiggestUnitId", int(big["推广单元ID"]))
152 ctx.number("MaxUnitCpc", float(kpis["cpc"].max()), ".2f")
153 ctx.number("MinUnitCpc", float(kpis["cpc"].min()), ".2f")
154 weak = kpis.sort_values("ctr", ascending=True).iloc[0]
155 ctx.number("MinCtrUnitId", int(weak["推广单元ID"]))
156 ctx.number("MinCtrUnitCtrPct", 100 * weak["ctr"], ".2f")
157 brand = kpis.sort_values("ctr", ascending=False).iloc[0] # navigational/brand-type unit: extreme CTR
158 ctx.number("TopCtrUnitId", int(brand["推广单元ID"]))
159 ctx.number("TopCtrUnitCtrPct", 100 * brand["ctr"], ".1f")
160 ctx.number("TopCtrUnitCpc", brand["cpc"], ".2f")
161 ctx.number("TopCtrUnitTopSharePct", 100 * brand["top_share"], ".1f")
162 ctx.number(
163     "TopCtrUnitKeywords", int(kw_per_unit.loc[kw_per_unit["推广单元ID"] == brand["推广单元ID"], "keywords"].iloc[0])
164 )
165
166 def term(target: str, name: str) -> pd.Series:
167     return coefs[(coefs["target"] == target) & (coefs["term"] == name)].iloc[0]
168
169 for target, key in (("regs", "Reg"), ("spend", "Spend"), ("clicks", "Clicks"), ("imp", "Imp")):
170     row = term(target, "holiday")
171     ctx.number(f"Holiday{key}EffectPct", row["effect_pct"], ".2f")
172     ctx.number(f"Holiday{key}CiLow", row["effect_pct_low"], ".2f")
173     ctx.number(f"Holiday{key}CiHigh", row["effect_pct_high"], ".2f")
174     ctx.number(f"Holiday{key}P", row["p"], ".4f")
175     ctx.number(f"Holiday{key}PSci", row["p"], ".1e")
176 for name, key in (
177     ("adjusted_workday", "AdjustedWorkday"),
178     ("pre_holiday", "PreHoliday"),
179     ("post_holiday", "PostHoliday"),
180     ("wd_周一", "Monday"),
181     ("wd_周六", "Saturday"),
182     ("wd_周日", "Sunday"),
183 ):
184     row = term("regs", name)
185     ctx.number(f"{key}RegEffectPct", row["effect_pct"], ".2f")
186     ctx.number(f"{key}RegP", row["p"], ".4f")
187 for name, key in (("holiday", "Holiday"), ("wd_周一", "Monday")):
188     row = term("cpc", name)
189     ctx.number(f"{key}CpcEffect", row["estimate"], ".4f")
190     ctx.number(f"{key}CpcP", row["p"], ".4f")
191 ctrl = term("regs|spend", "holiday")
192 ctx.number("HolidayRegGivenSpendEffectPct", ctrl["effect_pct"], ".2f")
193 ctx.number("HolidayRegGivenSpendCiLow", ctrl["effect_pct_low"], ".2f")
194 ctx.number("HolidayRegGivenSpendCiHigh", ctrl["effect_pct_high"], ".2f")
195 ctx.number("HolidayRegGivenSpendP", ctrl["p"], ".4f")
196 # marginal-return equalisation under the log-log response: optimal holiday/normal-day spend ratio
197 #  $\exp(\Delta_H / (1 - \theta))$ , where  $\Delta_H$  is the demand-side holiday effect and  $\theta$  the elasticity
198 theta = float(term("regs|spend", "log_spend")["estimate"])
199 holiday_ratio = float(np.exp(float(ctrl["estimate"]) / max(1.0 - theta, 1e-6)))
200 ctx.number("HolidayOptimalSpendRatioPct", 100 * holiday_ratio, ".1f")
201 ctx.number("HolidayOptimalSpendCutPct", 100 * (1 - holiday_ratio), ".1f")
202 ctx.number("MondayRegGivenSpendEffectPct", term("regs|spend", "wd_周一")["effect_pct"], ".2f")
203 ctx.number("MondayRegGivenSpendP", term("regs|spend", "wd_周一")["p"], ".4f")
204 ctx.number("SundayRegGivenSpendEffectPct", term("regs|spend", "wd_周日")["effect_pct"], ".2f")
205 ctx.number("SundayRegGivenSpendP", term("regs|spend", "wd_周日")["p"], ".4f")
206 ctx.number("RegSpendElasticity", term("regs|spend", "log_spend")["estimate"], ".4f")
207 ctx.number("RegSpendElasticitySe", term("regs|spend", "log_spend")["se"], ".4f")
208 ctx.number("HolidayTopEffectPp", 100 * term("top_share", "holiday")["estimate"], ".2f")
209 ctx.number("HolidayTopP", term("top_share", "holiday")["p"], ".4f")
210 ctx.number("HolidayCtrEffectPp", 100 * term("ctr", "holiday")["estimate"], ".3f")
211 ctx.number("HolidayCtrP", term("ctr", "holiday")["p"], ".4f")

```

```

212 reg_summary = next(s for s in summaries if s["target"] == "regs")
213 ctx.number("RegCalendarRsq", reg_summary["r2"], ".4f")
214 ctx.number("RegWeekdayWaldP", reg_summary["weekday_wald_p"], ".2e")
215 ctx.number("SpendCalendarRsq", next(s for s in summaries if s["target"] == "spend")["r2"], ".4f")
216 ctx.number("RegGivenSpendRsq", next(s for s in summaries if s["target"] == "regs|spend")["r2"], ".4f")
217 mw = next(m for m in nonparam if m["target"] == "regs")
218 ctx.number("HolidayRegMedianRatio", mw["ratio_of_medians"], ".4f")
219 ctx.number("HolidayRegMannWhitneyP", mw["p"], ".2e")
220 ctx.number("HolidayRegMedian", mw["holiday_median"], ".0f")
221 ctx.number("WorkdayRegMedian", mw["workday_median"], ".0f")
222 ctx.number("HolidayDays", mw["holiday_n"])
223 ctx.number("WorkdayDays", mw["workday_n"])
224 ctx.number("AttributionLambda", attribution["lambda"], ".1f")
225 ctx.number("AttributionRsq", attribution["r2"], ".4f")
226 ctx.number("AttributionHoldoutRsq", attribution["holdout"]["r2"], ".4f")
227 ctx.number("AttributionHoldoutMape", 100 * attribution["holdout"]["mape"], ".2f")
228 ctx.number("BaselineRegsPerDay", attribution["baseline_per_day"], ".2f")
229 ctx.number("PooledRegRatePerHundredClicks", 100 * attribution["pooled_rate"], ".4f")
230 attributed = sum(attribution["attributed_regs"].values())
231 ctx.number("AttributedRegs", attributed, ".0f")
232 ctx.number("AttributedRegsSharePct", 100 * attributed / float(daily["regs"].sum()), ".2f")
233 ctx.number("CostPerAttributedReg", total_spend / attributed, ".2f")
234 ctx.number("UnitsWithOwnRate", sum(1 for v in attribution["rate_source"].values() if v == "unit"))
235 ctx.number("PooledGamma", units["pooled_gamma"].iloc[0], ".4f")
236 ctx.number("PooledGammaSe", units["pooled_se"].iloc[0], ".4f")
237 ctx.number("MinUnitGamma", units["gamma"].min(), ".4f")
238 ctx.number("MaxUnitGamma", units["gamma"].max(), ".4f")
239 ctx.number("UnitsWithOwnGamma", int((units["gamma_source"] == "unit").sum()))
240 ctx.number("MinUnitGammaRsq", float(units["r2"].min()), ".2f")
241 ctx.number("MaxUnitGammaRsq", float(units["r2"].max()), ".2f")
242 # raw regression estimates (the adopted values are a subset; one unit estimates gamma > 1)
243 gh = units["gamma_hat"].to_numpy(dtype=float)
244 se = units["gamma_se"].to_numpy(dtype=float)
245 ctx.number("MinUnitGammaHat", float(np.nanmin(gh)), ".4f")
246 ctx.number("MaxUnitGammaHat", float(np.nanmax(gh)), ".4f")
247 below = (gh < 1) & (gh + 1.96 * se < 1)
248 ctx.number("UnitsGammaHatBelowOne", int(np.nansum(below)))
249 ctx.number("UnitsGammaHatAboveOne", int(np.nansum((gh > 1) & (gh - 1.96 * se > 1))))
250 hi_row = units.iloc[int(np.nanargmax(gh))]
251 ctx.number("GammaAboveOneUnitId", int(hi_row["推广单元ID"]))
252 ctx.number("GammaAboveOneHat", float(hi_row["gamma_hat"]), ".4f")
253 ctx.number("GammaAboveOneSe", float(hi_row["gamma_se"]), ".4f")
254 ctx.number("GammaAboveOneT", float((hi_row["gamma_hat"] - 1.0) / max(hi_row["gamma_se"], 1e-9)), ".2f")
255 ctx.number("GammaAboveOneActiveDays", int(hi_row["active_days"]))
256 short = units[(units["gamma_source"] == "pooled") & (units["推广单元ID"] != hi_row["推广单元ID"])]
257 if len(short):
258     ctx.number("GammaShortUnitId", int(short.iloc[0]["推广单元ID"]))
259     ctx.number("GammaShortActiveDays", int(short.iloc[0]["active_days"]))
260     ctx.number("GammaShortHat", float(short.iloc[0]["gamma_hat"]), ".4f")
261     ctx.number("GammaShortDays", int(short.iloc[0]["n_days"]))
262 ctx.number("GammaMinActiveDays", int(units["active_days"].min()))
263 ctx.number("MinPninefiveSpendRatio", float(units["p95_spend_ratio"].min()), ".2f")
264 ctx.number("MaxPninefiveSpendRatio", float(units["p95_spend_ratio"].max()), ".2f")
265 ctx.number("MedianPninefiveSpendRatio", float(units["p95_spend_ratio"].median()), ".2f")
266 # marginal-return equalisation: sampling uncertainty of the optimal day-type spend cut
267 for cut_term, key in (("holiday", ("wd_周一", "Monday")), ("wd_周日", "Sunday")):
268     t = cut["terms"].get(cut_term)
269     if not t:
270         continue
271     ctx.number(f"{key}OptimalCutPct", 100 * t["cut"], ".1f")
272     ctx.number(f"{key}OptimalCutCiLowPct", 100 * t["cut_ci"][0], ".1f")
273     ctx.number(f"{key}OptimalCutCiHighPct", 100 * t["cut_ci"][1], ".1f")
274     ctx.number(f"{key}ActualCutPct", 100 * t["actual_cut"], ".1f")

```

```

275     ctx.number(f"{key}ThetaStar", t["theta_star"], ".4f")
276     ctx.number(f"{key}ProbOptimalDeeperPct", 100 * t["prob_optimal_deeper_than_actual"], ".0f")
277     ctx.number(f"{key}CutAtPooledGammaPct", 100 * next(iter(t["cut_at_alt"].values())), ".1f")
278     ctx.number(f"{key}DemandDeltaCiLowPct", 100 * (np.exp(t["delta_ci"][0]) - 1), ".2f")
279     ctx.number(f"{key}DemandDeltaCiHighPct", 100 * (np.exp(t["delta_ci"][1]) - 1), ".2f")
280     ctx.number("ThetaCiLow", cut["theta_ci"][0], ".4f")
281     ctx.number("ThetaCiHigh", cut["theta_ci"][1], ".4f")
282     ctx.number("HolidayThetaStarInsideCi", int(cut["terms"]["holiday"]["theta_star_inside_ci"]))
283     # log-scale decomposition of the holiday drop (percentage points are not additive)
284     dh = float(np.log1p(term("regs", "holiday")["effect_pct"] / 100))
285     dd = float(np.log1p(float(ctrl["effect_pct"]) / 100))
286     ctx.number("HolidayDemandLogSharePct", 100 * dd / dh, ".0f")
287     ctx.number("HolidaySupplyLogSharePct", 100 * (1 - dd / dh), ".0f")
288     # attribution diagnostics
289     ctx.number("AttributionZeroBoundUnits", diag["n_at_zero_bound"])
290     ctx.number("AttributionConditionNumber", diag["condition_number"], ".3g")
291     ctx.number("AttributionMaxSwingRatio", float(np.exp(diag["max_swing_ratio"])), ".1f")
292     ctx.number("AttributionBoot", diag["n_boot"])
293     dec = diag["decomposition"]
294     ctx.number("DecompInterceptRegs", dec["intercept"], ".0f")
295     ctx.number("DecompInterceptPct", 100 * dec["intercept"] / dec["total_regs"], ".1f")
296     ctx.number("DecompCalendarRegs", dec["calendar"], ".0f")
297     ctx.number("DecompCalendarPct", 100 * dec["calendar"] / dec["total_regs"], ".1f")
298     ctx.number("DecompSemRegs", dec["sem"], ".0f")
299     ctx.number("DecompSemPct", 100 * dec["sem"] / dec["total_regs"], ".1f")
300     ctx.number("DecompNonSemPerDay", dec["implied_non_sem_per_day"], ".1f")
301     ctx.number("OtherRegionClickSharePct", 100 * other_clicks / total_clicks, ".2f")
302     ctx.number("OtherRegionImpSharePct", 100 * (total_imp - top_imp) / total_imp, ".2f")
303     ctx.number(
304         "TopOverOtherCtrRatio", (s1["上方位点点击量"].sum() / top_imp) / (other_clicks / (total_imp - top_imp)), ".1f"
305     )
306     return {
307         "unit_days": len(s1),
308         "holiday_reg_effect_pct": float(term("regs", "holiday")["effect_pct"]),
309         "holiday_reg_p": float(term("regs", "holiday")["p"]),
310         "attribution_r2": attribution["r2"],
311         "pooled_gamma": float(units["pooled_gamma"].iloc[0]),
312     }
313
314
315 def _rates(ctx: StageContext) -> dict[int, float]:
316     attribution = ctx.dep_data("eda", "attribution.json")
317     return {int(k): float(v) for k, v in attribution["rates"].items()}
318
319
320 # ----- Q2
321 @stage(
322     "classify", deps=("eda",), description="Q2: five-way cost/benefit keyword classification with threshold robustness"
323 )
324 def classify(ctx: StageContext) -> dict[str, Any]:
325     seed = ctx.seed_everything("classify")
326     _, _, s3 = load_sheets(ctx.dep("ingest"))
327     kw = keyword_table(s3)
328     methods = tuple(ctx.cfg("classify.methods", ["jenks", "median", "gmm"]))
329     main = str(ctx.cfg("classify.main_method", "jenks"))
330     result = cls.classify_keywords(kw, _rates(ctx), methods, main, seed)
331     table = result.pop("table")
332     _save(ctx, table, "classification")
333     thr = result["thresholds"][main]
334     report = cls.verify_classification(table, thr["log10_cost"], thr["benefit"])
335     ctx.write_json("classification_check.json", report)
336     per_unit = (
337         table.groupby(["方案ID", "推广单元ID", "label"])

```

```

338     .agg(n=("序号", "size"), spend=("spend", "sum"), clicks=("clicks", "sum"))
339     .reset_index()
340 )
341 _save(ctx, per_unit, "classification_per_unit")
342 by_label = (
343     table.groupby("label")
344     .agg(
345         n=("序号", "size"),
346         spend=("spend", "sum"),
347         clicks=("clicks", "sum"),
348         views=("views", "sum"),
349         reg_attr=("reg_attr", "sum"),
350     )
351     .reindex(cls.LABELS)
352     .fillna(0)
353 )
354 by_label["spend_share"] = by_label["spend"] / by_label["spend"].sum()
355 by_label["cpc"] = by_label["spend"] / by_label["clicks"].replace(0, np.nan)
356 _save(ctx, by_label.reset_index(), "classification_by_label")
357 ctx.write_json("classification_summary.json", result)
358 if not report["ok"]:
359     raise RuntimeError(f"classification checker failed: {report}")
360 keys = {"黄金词": "Gold", "重点词": "Key", "潜力词": "Potential", "问题词": "Problem"}
361 keys["无效词"] = "Invalid"
362 for label, key in keys.items():
363     ctx.number(f"{key}Count", int(by_label.loc[label, "n"]))
364     ctx.number(f"{key}SpendSharePct", 100 * float(by_label.loc[label, "spend_share"]), ".2f")
365     ctx.number(f"{key}Cpc", float(by_label.loc[label, "cpc"]) if by_label.loc[label, "clicks"] > 0 else 0.0, ".4f")
366 ctx.number("CostThresholdYuan", thr["cost_yuan"], ".2f")
367 ctx.number("CostThresholdLog", thr["log10_cost"], ".4f")
368 ctx.number("BenefitThreshold", thr["benefit"], ".4f")
369 for comp, key in (("clicks", "Clicks"), ("views", "Views"), ("engagement", "Engagement"), ("reg_attr", "Reg")):
370     ctx.number(f"Weight{key}", result["weights"][comp], ".4f")
371 ctx.number("AgreementJenksMedianPct", 100 * result["agreement"]["jenks_vs_median"], ".2f")
372 ctx.number("AgreementGmmJenksPct", 100 * result["agreement"]["gmm_vs_jenks"], ".2f")
373 ctx.number("AgreementJenksEqualWeightsPct", 100 * result["agreement"]["jenks_vs_equal_weights"], ".2f")
374 ctx.number("EntropyEqualSpearman", result["agreement"]["entropy_vs_equal_spearman"], ".4f")
375 ctx.number("MedianCostThresholdYuan", result["thresholds"]["median"]["cost_yuan"], ".2f")
376 ctx.number("GmmCostThresholdYuan", result["thresholds"]["gmm"]["cost_yuan"], ".2f")
377 # how independent are the two axes, and what does an efficiency axis give instead
378 axis = cls.axis_diagnostics(table, thr, main, seed)
379 eff_labels = axis.pop("efficiency_labels")
380 table_out = table.assign(label_efficiency=eff_labels)
381 _save(ctx, table_out[["序号", "label", "label_efficiency"]], "classification_dual_axis")
382 ctx.write_json("axis_diagnostics.json", axis)
383 ctx.number("AxisPearson", axis["pearson_logcost_benefit"], ".4f")
384 ctx.number("AxisPearsonRsqr", axis["r2_logcost_benefit"], ".3f")
385 ctx.number("AxisSpearman", axis["spearman_logcost_benefit"], ".4f")
386 ctx.number("AxisSpearmanClicks", axis["spearman_clicks_benefit"], ".4f")
387 ctx.number("AxisSpearmanEfficiency", axis["spearman_logcost_efficiency"], ".4f")
388 ctx.number("AxisEfficiencyAgreementPct", 100 * axis["efficiency_agreement"], ".2f")
389 for label, key in keys.items():
390     ctx.number(f"{key}ClickSharePct", 100 * axis["label_shares"][label]["click_share"], ".4f")
391     ctx.number(f"Eff{key}Count", int(axis["efficiency_counts"][label]))
392 ctx.number("GoldSpendSharePctFine", 100 * axis["label_shares"]["黄金词"]["spend_share"], ".4f")
393 # engagement-component robustness: total dwell time C_i tau_i instead of non-bounced dwell time
394 alt_kw = kw.assign(engagement=(kw["clicks"] * kw["duration_s"]).fillna(0.0).clip(lower=0.0))
395 alt = cls.classify_keywords(alt_kw, _rates(ctx), (main,), main, seed)
396 alt_agree = float((alt["table"]["label"].to_numpy() == table["label"].to_numpy()).mean())
397 ctx.write_json(
398     "engagement_variant.json",
399     {"agreement": alt_agree, "counts": alt["counts"][main], "weights": alt["weights"]},
400 )

```

```

401     ctx.number("EngagementVariantAgreementPct", 100 * alt_agree, ".2f")
402     return {"counts": result["counts"][main], "checker_ok": report["ok"], "thresholds": thr}
403
404
405 # ----- Q3
406 def _load_params(
407     ctx: StageContext,
408 ) -> tuple[pd.DataFrame, pd.DataFrame, pd.DataFrame, dict[int, dict[str, Any]], dict[int, float]]:
409     s1, _, s3 = load_sheets(ctx.dep("ingest"))
410     ud = unit_daily(s1)
411     units = pd.read_parquet(ctx.dep("eda") / "unit_response.parquet")
412     rates = _rates(ctx)
413     kw = keyword_table(s3)
414     labels = pd.read_parquet(ctx.dep("classify") / "classification.parquet")[["序号", "label"]]
415     params = resp.keyword_parameters(kw, units, rates).merge(labels, on="序号", how="left")
416     params["efficiency"] = params["rho"] / params["cpc"]
417     pos: dict[int, dict[str, Any]] = {}
418     for unit, df in ud.groupby("推广单元ID"):
419         pos[int(unit)] = {
420             "top": resp.fit_position_model(df, "top_share"),
421             "first": resp.fit_position_model(df, "first_share"),
422         }
423     return ud, units, params, pos, rates
424
425
426 def _eligible(params: pd.DataFrame, active_units: set[int], problem_cap_factor: float) -> pd.DataFrame:
427     """Eligibility inside a window: invalid words never enter, problem words keep half the normal cap.
428
429     Keyword IDs shared by several active units are flagged (`dup_best` marks the most efficient copy)
430     for reporting; the copies stay eligible because the data cannot show cross-unit cannibalisation."""
431     p = params[params["推广单元ID"].isin(active_units)].copy()
432     p["cap_factor"] = np.where(p["label"] == "问题词", problem_cap_factor, 1.0)
433     p["dup_best"] = True
434     for _, grp in p[p["shared_units"] > 1].groupby("关键词"):
435         if len(grp) > 1:
436             best = grp["efficiency"].idxmax()
437             p.loc[grp.index.difference([best]), "dup_best"] = False
438     p["eligible"] = p["label"].isin(["黄金词", "重点词", "潜力词", "问题词"])
439     return p
440
441
442 def _evaluate(x: np.ndarray, p: pd.DataFrame, gamma: float, eff: float, pos: dict[str, Any]) -> pd.DataFrame:
443     c, s = p["c"].to_numpy(dtype=float), p["s"].to_numpy(dtype=float)
444     clicks = eff * resp.clicks_response(x, c, s, gamma)
445     with np.errstate(divide="ignore", invalid="ignore"):
446         cpc = np.where(clicks > 0, x / clicks, np.nan)
447     p_top, p_first = resp.position_shares(np.nan_to_num(cpc, nan=1.0), pos["top"], pos["first"])
448     return pd.DataFrame(
449         {
450             "序号": p["序号"].to_numpy(),
451             "关键词": p["关键词"].to_numpy(),
452             "方案ID": p["方案ID"].to_numpy(),
453             "推广单元ID": p["推广单元ID"].to_numpy(),
454             "label": p["label"].to_numpy(),
455             "spend": x,
456             "clicks": clicks,
457             "cpc": cpc,
458             "p_top": p_top,
459             "p_first": p_first,
460             "position": resp.expected_position(p_top, p_first),
461             "views": clicks * p["depth"].to_numpy(dtype=float),
462             "regs": clicks * p["rho"].to_numpy(dtype=float),
463         }
464     )

```

```

464     )
465
466
467 def _caps(p: pd.DataFrame, budget: float, cap_mult: float) -> np.ndarray:
468     """Per-keyword daily caps: multiplier x mean daily spend x type factor, never below the historical
469     proportional share (so the proportional baseline is always feasible) and jointly attainable."""
470     s = p["s"].to_numpy(dtype=float)
471     caps = np.maximum(cap_mult * s * p["cap_factor"].to_numpy(dtype=float), alloc.proportional_allocation(s, budget))
472     if caps.sum() < 1.2 * budget: # keep the cap structure but make the budget attainable
473         caps = caps * (1.2 * budget / caps.sum())
474     return caps
475
476
477 def _solve_unit_day(
478     p: pd.DataFrame, gamma: float, budget: float, cap_mult: float, min_spend: float
479 ) -> tuple[np.ndarray, dict[str, Any], np.ndarray, np.ndarray]:
480     w = (p["rho"] * p["c"]).to_numpy(dtype=float)
481     s = p["s"].to_numpy(dtype=float)
482     caps = _caps(p, budget, cap_mult)
483     res = alloc.solve_group(w, s, gamma, caps, budget, min_spend=min_spend)
484     return res["x"], res, w * np.power(s, -gamma), caps
485
486
487 def _day_efficiency(ud: pd.DataFrame, units: pd.DataFrame, dates: pd.DatetimeIndex) -> dict[int, dict[str, Any]]:
488     """Calendar-model expectation of the day efficiency multiplier E[eff_{u,d}] for each unit and date."""
489     feats = day_features(dates)
490     out: dict[int, dict[str, Any]] = {}
491     for _, row in units.iterrows():
492         unit = int(row["推广单元ID"])
493         series = fc.unit_series(
494             ud[ud["推广单元ID"] == unit],
495             float(row["gamma"]),
496             float(row["mean_daily_spend"]),
497             float(row["mean_daily_clicks"]),
498         )
499         if len(series) < 40:
500             out[unit] = {"eff": np.ones(len(dates)), "sd": 0.0, "n": len(series), "mean_log": np.zeros(len(dates))}
501             continue
502         f = fc.forecast_unit(series, "log_eff", feats)
503         out[unit] = {"eff": np.exp(f["mean"] + 0.5 * f["sd"] ** 2), "sd": f["sd"], "n": f["n"], "mean_log": f["mean"]}
504     return out
505
506
507 def _sensitivity(
508     all_groups: dict[str, dict[tuple[int, pd.Timestamp], dict[str, Any]]],
509     elig_by_window: dict[str, pd.DataFrame],
510     unit_index: pd.DataFrame,
511     cap_mult: float,
512     min_spend: float,
513     problem_cap: float,
514 ) -> pd.DataFrame:
515     """Gain of the optimal allocation over the proportional baseline under perturbed modelling choices."""
516     scenarios: list[tuple[str, dict[str, Any]]] = [
517         ("基准", {}),
518         ("上限倍数 2", {"cap": 2.0}),
519         ("上限倍数 8", {"cap": 8.0, "relaxation": True}),
520         ("弹性 gamma x0.9", {"gamma_scale": 0.9}),
521         ("弹性 gamma x1.1", {"gamma_scale": 1.1}),
522         ("预算 -20%", {"budget_scale": 0.8}),
523         ("预算 +20%", {"budget_scale": 1.2}),
524         ("剔除问题词", {"exclude_problem": True}),
525         ("问题词不降上限", {"problem_cap": 1.0, "relaxation": True}),
526         ("最小投放 0 (上限同基准)", {"min_spend": 0.0, "caps_as_baseline": True, "relaxation": True}),

```

```

527     ("最小投放 0 (上限随之收缩)", {"min_spend": 0.0}),
528     ("跳出率因子 kappa = 1", {"kappa": "one"}),
529     ("kappa 截断 [0.5, 2]", {"kappa": (0.5, 2.0)}),
530     ("重复词只留最优副本", {"dup_best": True}),
531 ]
532 rows = []
533 for name, opt in scenarios:
534     for window, groups in all_groups.items():
535         elig = elig_by_window[window]
536         opt_total = prop_total = 0.0
537         selected = []
538         for (unit, _date), g in groups.items():
539             gamma = float(np.clip(g["gamma"] * opt.get("gamma_scale", 1.0), *resp.GAMMA_BOUNDS))
540             budget = g["budget"] * opt.get("budget_scale", 1.0)
541             p = g["p"]
542             if opt.get("exclude_problem"):
543                 p = p[p["label"] != "问题词"]
544                 if p.empty():
545                     p = g["p"]
546             if opt.get("dup_best"):
547                 p = p[p["dup_best"]]
548                 if p.empty():
549                     p = g["p"]
550             p = p.assign(cap_factor=np.where(p["label"] == "问题词", opt.get("problem_cap", problem_cap), 1.0))
551             w = _weights(p, opt.get("kappa"))
552             s = p["s"].to_numpy(dtype=float)
553             caps = _caps(p, budget, opt.get("cap", cap_mult))
554             if opt.get("caps_as_baseline"):
555                 # a nominal relaxation of the floor must not shrink the feasible set: the caps are
556                 # held at the effective caps of the baseline problem, max(cap_i, m)
557                 caps = np.maximum(caps, min_spend)
558             r = alloc.solve_group(w, s, gamma, caps, budget, min_spend=opt.get("min_spend", min_spend))
559             opt_total += g["eff"] * r["objective"]
560             selected.append(r["n_selected"])
561             p_all = elig[elig["推广单元ID"] == unit]
562             if opt.get("dup_best"): # the baseline is rebuilt under the same rule to stay comparable
563                 p_all = p_all[p_all["dup_best"]]
564             xb = alloc.proportional_allocation(p_all["s"].to_numpy(dtype=float), budget)
565             prop_total += g["eff"] * float(
566                 np.sum(_weights(p_all, opt.get("kappa")) * np.power(xb / p_all["s"].to_numpy(), gamma))
567             )
568             rows.append(
569                 {
570                     "scenario": name,
571                     "window": {"feb": "2 月", "aug": "8 月"}[window],
572                     "opt_regs": opt_total,
573                     "prop_regs": prop_total,
574                     "gain": 100 * (opt_total / max(prop_total, 1e-9) - 1),
575                     "selected": float(np.mean(selected)) if selected else 0.0,
576                     "relaxation": bool(opt.get("relaxation", False)),
577                 }
578             )
579         return pd.DataFrame(rows)
580
581
582 def _weights(p: pd.DataFrame, kappa: Any = None) -> np.ndarray:
583     """Objective coefficients rho_i c_i, optionally with the bounce-quality factor switched off or re-clipped."""
584     c = p["c"].to_numpy(dtype=float)
585     if kappa is None:
586         return (p["rho"] * p["c"]).to_numpy(dtype=float)
587     rate = p["rate"].to_numpy(dtype=float)
588     if kappa == "one":
589         return rate * c

```

```

590     lo, hi = kappa
591     return rate * np.clip(p["kappa"].to_numpy(dtype=float), lo, hi) * c
592
593
594 def _cross_unit_allocation(
595     values: dict[int, tuple[float, float, float]], budget: float, cap_mult: float, tol: float = 1e-12
596 ) -> dict[int, float]:
597     """Marginal-return equalisation across units with heterogeneous elasticities.
598
599     ``values`` maps a unit to (K_u, gamma_u, B_u) where  $V_u(X) = K_u X^{\gamma_u}$  is the unit's value
600     function calibrated at its own historical budget B_u. Every unit takes
601      $X_u(\lambda) = (\gamma_u K_u / \lambda)^{1/(1 - \gamma_u)}$  clipped to  $[0, \text{cap\_mult} * B_u]$ ; the total is
602     strictly decreasing in lambda, so the budget price is found by bisection. This is the outer
603     problem that Section 4.2 points at (moving money between units), solved with the same machinery as
604     the keyword problem but with a unit-specific exponent.
605     """
606     units = sorted(values)
607     caps = {u: max(cap_mult * values[u][2], 1e-9) for u in units}
608
609     def total(lam: float) -> dict[int, float]:
610         out = {}
611         for u in units:
612             k, g, _ = values[u]
613             if k <= 0 or lam <= 0:
614                 out[u] = 0.0
615                 continue
616             log_x = (np.log(g * k) - np.log(lam)) / (1.0 - g) # in logs: the price sweep spans 600 decades
617             x = float(np.exp(min(log_x, 700.0)))
618             out[u] = float(min(max(x, 0.0), caps[u]))
619         return out
620
621     if sum(caps.values()) <= budget:
622         return caps
623     lo, hi = 1e-300, 1.0
624     while sum(total(hi).values()) > budget:
625         hi *= 4.0
626     for _ in range(400):
627         mid = float(np.sqrt(lo * hi))
628         if sum(total(mid).values()) > budget:
629             lo = mid
630         else:
631             hi = mid
632         if hi / lo - 1.0 < tol:
633             break
634     return total(float(np.sqrt(lo * hi)))
635
636
637 def _plan_window_for_units(
638     elig: pd.DataFrame,
639     unit_index: pd.DataFrame,
640     day_eff: dict[int, dict[str, Any]],
641     dates: pd.DatetimeIndex,
642     budgets: dict[int, float],
643     pos: dict[int, dict[str, Any]],
644     cap_mult: float,
645     min_spend: float,
646 ) -> pd.DataFrame:
647     """Two-level plan (day split then keyword split) for a window under an arbitrary per-unit budget."""
648     frames = []
649     for unit in sorted(budgets):
650         B = float(budgets[unit])
651         p = elig[(elig["推广单元ID"] == unit) & elig["eligible"]]
652         if B <= 0 or p.empty or unit not in day_eff:

```

```

653         continue
654     gamma = float(unit_index.loc[unit, "gamma"])
655     eff = np.asarray(day_eff[unit]["eff"], dtype=float)
656     day_cap = float(max(2.0 * B / len(dates), min_spend))
657     X = alloc.solve_group(eff, np.ones(len(dates)), gamma, np.full(len(dates), day_cap), B, min_spend=min_spend)[
658         "x"
659     ]
660     for i, d in enumerate(dates):
661         if X[i] <= 0:
662             continue
663         w = (p["rho"] * p["c"]).to_numpy(dtype=float)
664         sv = p["s"].to_numpy(dtype=float)
665         caps = _caps(p, float(X[i]), cap_mult)
666         x = alloc.solve_group(w, sv, gamma, caps, float(X[i]), min_spend=min_spend)["x"]
667         ev = _evaluate(x, p, gamma, float(eff[i]), pos[unit])
668         ev.insert(0, "date", d.strftime("%Y-%m-%d"))
669         frames.append(ev[ev["spend"] > 0])
670     return pd.concat(frames, ignore_index=True) if frames else pd.DataFrame()
671
672
673 @stage(
674     "allocate",
675     deps=("eda", "classify"),
676     description="Q3: keyword selection and daily budget allocation for 2025-02-01..08 and 08-01..08 with audit",
677 )
678 def allocate(ctx: StageContext) -> dict[str, Any]:
679     rng = np.random.default_rng(ctx.seed_everything("allocate"))
680     ud, units, params, pos, rates = _load_params(ctx)
681     cap_mult = float(ctx.cfg("allocate.cap_multiplier", 4.0))
682     min_spend = float(ctx.cfg("allocate.min_spend", 0.5))
683     problem_cap = float(ctx.cfg("allocate.problem_cap_factor", 0.5))
684     n_boot = int(ctx.param("bootstrap", ctx.cfg("allocate.bootstrap", 100)))
685     unit_index = units.set_index("推广单元ID")
686     s1 = ud[["日期", "方案ID", "推广单元ID", "消费额", "点击量", "展现量"]]
687     ctx.write_json("position_models.json", pos)
688
689     rows, summaries, audits = [], [], []
690     boot_records: list[dict[str, Any]] = []
691     window_alt: list[dict[str, Any]] = []
692     eligible_tables = []
693     all_groups: dict[str, dict[tuple[int, pd.Timestamp], dict[str, Any]]] = {}
694     elig_by_window: dict[str, pd.DataFrame] = {}
695     day_eff_by_window: dict[str, dict[int, dict[str, Any]]] = {}
696     dates_by_window: dict[str, pd.DatetimeIndex] = {}
697     for window, (start, end) in Q3_WINDOWS.items():
698         dates = pd.date_range(start, end, freq="D")
699         day_eff = _day_efficiency(ud, units, dates)
700         day_eff_by_window[window], dates_by_window[window] = day_eff, dates
701         actual = s1[(s1["日期"] >= start) & (s1["日期"] <= end) & (s1["消费额"] > 0)]
702         active_units = {int(u) for u in actual["推广单元ID"].unique()}
703         elig = _eligible(params, active_units, problem_cap)
704         elig["window"] = window
705         eligible_tables.append(elig)
706         groups: dict[tuple[int, pd.Timestamp], dict[str, Any]] = {}
707         for _, rec in actual.iterrows():
708             unit, date, budget = int(rec["推广单元ID"]), pd.Timestamp(rec["日期"]), float(rec["消费额"])
709             p = elig[(elig["推广单元ID"] == unit) & elig["eligible"]]
710             if p.empty:
711                 continue
712             gamma = float(unit_index.loc[unit, "gamma"])
713             eff = float(day_eff[unit]["eff"][dates.get_loc(date)])
714             x, res, a, caps = _solve_unit_day(p, gamma, budget, cap_mult, min_spend)
715             ev = _evaluate(x, p, gamma, eff, pos[unit])

```

```

716     ev.insert(0, "date", date.strftime("%Y-%m-%d"))
717     ev["window"] = window
718     rows.append(ev[ev["spend"] > 0])
719     # baselines evaluated under the same response model and day multiplier
720     p_all = elig[elig["推广单元ID"] == unit]
721     base = _evaluate(
722         alloc.proportional_allocation(p_all["s"].to_numpy(dtype=float), budget), p_all, gamma, eff, pos[unit]
723     )
724     equal = _evaluate(alloc.equal_allocation(len(p), budget), p, gamma, eff, pos[unit])
725     sel = x > 0
726     audit = alloc.verify_allocation(x, a, gamma, caps, budget, rng, floor=min_spend)
727     audits.append(
728         {
729             "window": window,
730             "date": date.strftime("%Y-%m-%d"),
731             "推广单元ID": unit,
732             **{k: v for k, v in audit.items() if k != "checks"},
733             "checks": audit["checks"],
734         }
735     )
736     groups[(unit, date)] = {"p": p, "gamma": gamma, "eff": eff, "budget": budget, "x": x, "a": a, "caps": caps}
737     all_groups[window] = groups
738     elig_by_window[window] = elig
739     summaries.append(
740         {
741             "window": window,
742             "date": date.strftime("%Y-%m-%d"),
743             "方案ID": int(rec["方案ID"]),
744             "推广单元ID": unit,
745             "budget": budget,
746             "spent": float(x.sum()),
747             "eligible": len(p),
748             "selected": int(sel.sum()),
749             "capped": audit["n_capped"],
750             "floored": audit["n_floored"],
751             "day_eff": eff,
752             "actual_clicks": float(rec["点击量"]),
753             "actual_regs_expected": float(rec["点击量"]) * rates[unit],
754             "opt_clicks": float(ev["clicks"].sum()),
755             "opt_regs": float(ev["regs"].sum()),
756             "opt_views": float(ev["views"].sum()),
757             "opt_position": float(np.average(ev["position"], weights=np.maximum(ev["clicks"], 1e-9))),
758             "opt_cpc": float(x.sum() / max(ev["clicks"].sum(), 1e-9)),
759             "prop_clicks": float(base["clicks"].sum()),
760             "prop_regs": float(base["regs"].sum()),
761             "prop_cpc": float(budget / max(base["clicks"].sum(), 1e-9)),
762             "equal_clicks": float(equal["clicks"].sum()),
763             "equal_regs": float(equal["regs"].sum()),
764             "audit_ok": audit["ok"],
765             "cvx_gap": audit["cvxpy"].get("relative_gap", np.nan),
766         }
767     )
768     # bootstrap over the elasticity uncertainty: improvement ratio of optimal vs proportional
769     for b in range(n_boot):
770         opt = prop = 0.0
771         for (unit, _date), g in groups.items():
772             row = unit_index.loc[unit]
773             mu = row["gamma_hat"] if row["gamma_source"] == "unit" else row["pooled_gamma"]
774             se = row["gamma_se"] if row["gamma_source"] == "unit" else row["pooled_se"]
775             gb = float(np.clip(rng.normal(mu, se), *resp.GAMMA_BOUNDS))
776             p = g["p"]
777             w = (p["rho"] * p["c"]).to_numpy(dtype=float)
778             s = p["s"].to_numpy(dtype=float)

```

```

779     caps = g["caps"]
780     r = alloc.solve_group(w, s, gb, caps, g["budget"], min_spend=min_spend)
781     opt += g["eff"] * r["objective"]
782     p_all = elig[elig["推广单元ID"] == unit]
783     xb = alloc.proportional_allocation(p_all["s"].to_numpy(dtype=float), g["budget"])
784     prop += g["eff"] * float(
785         np.sum((p_all["rho"] * p_all["c"]).to_numpy() * np.power(xb / p_all["s"].to_numpy(), gb))
786     )
787     boot_records.append(
788         {"window": window, "draw": b, "opt_regs": opt, "prop_regs": prop, "ratio": opt / max(prop, 1e-9)}
789     )
790     # alternative budget reading: the window total per unit is also allocated across days
791     for unit in sorted(active_units):
792         unit_days = [(u, d) for (u, d) in groups if u == unit]
793         if not unit_days:
794             continue
795         gamma = float(unit_index.loc[unit, "gamma"])
796         B = float(sum(groups[k]["budget"] for k in unit_days))
797         eff_days = np.array([day_eff[unit]["eff"][dates.get_loc(d)] for _, d in unit_days])
798         day_cap = 1.5 * max(groups[k]["budget"] for k in unit_days)
799         X = alloc.water_filling(eff_days, gamma, np.full(len(unit_days), day_cap), B)
800         total = 0.0
801         for (u, d), Xd in zip(unit_days, X):
802             g = groups[(u, d)]
803             r = alloc.solve_group(
804                 (g["p"]["rho"] * g["p"]["c"]).to_numpy(dtype=float),
805                 g["p"]["s"].to_numpy(dtype=float),
806                 gamma,
807                 g["caps"],
808                 float(Xd),
809                 min_spend=min_spend,
810             )
811             total += g["eff"] * r["objective"]
812             window_alt.append(
813                 {
814                     "window": window,
815                     "推广单元ID": unit,
816                     "date": d.strftime("%Y-%m-%d"),
817                     "daily_budget": g["budget"],
818                     "window_budget_day": float(Xd),
819                     "day_eff": g["eff"],
820                     "regs_window": g["eff"] * r["objective"],
821                 }
822             )
823     sens = _sensitivity(all_groups, elig_by_window, unit_index, cap_mult, min_spend, problem_cap)
824     _save(ctx, sens, "sensitivity")
825     allocation = pd.concat(rows, ignore_index=True)
826     _save(ctx, allocation, "allocation")
827     summary = pd.DataFrame(summaries)
828     _save(ctx, summary, "allocation_summary")
829     _save(ctx, pd.concat(eligible_tables, ignore_index=True), "keyword_parameters")
830     boot = pd.DataFrame(boot_records)
831     _save(ctx, boot, "bootstrap")
832     alt = pd.DataFrame(window_alt)
833     _save(ctx, alt, "window_budget_alternative")
834
835     # --- monotonicity of the sensitivity design: a nominally looser problem cannot be worse
836     base_by_window = sens[sens["scenario"] == "基准"].set_index("window")["opt_regs"]
837     mono = [
838         {
839             "scenario": r["scenario"],
840             "window": r["window"],
841             "opt_regs": float(r["opt_regs"]),

```

```

842         "baseline": float(base_by_window[r["window"]]),
843         "ok": bool(r["opt_regs"] >= base_by_window[r["window"]] * (1 - 1e-9)),
844     }
845     for _, r in sens[sens["relaxation"]].iterrows()
846 ]
847 ctx.write_json("sensitivity_monotonicity.json", {"ok": all(m["ok"] for m in mono), "cases": mono})
848 if not all(m["ok"] for m in mono):
849     raise RuntimeError(f"relaxed sensitivity scenario below the baseline optimum: {mono}")
850
851 # --- cross-unit reallocation counterfactual (the outer problem Q1 points at)
852 cross_rows = []
853 for window, groups in all_groups.items():
854     for date in sorted({d for _, d in groups}):
855         day_groups = {u: g for (u, d), g in groups.items() if d == date}
856         if len(day_groups) < 2:
857             continue
858         budget = float(sum(g["budget"] for g in day_groups.values()))
859         vals = {}
860         for u, g in day_groups.items():
861             v = (
862                 g["eff"]
863                 * alloc.solve_group(
864                     (g["p"]["rho"] * g["p"]["c"]).to_numpy(dtype=float),
865                     g["p"]["s"].to_numpy(dtype=float),
866                     g["gamma"],
867                     g["caps"],
868                     g["budget"],
869                     min_spend=min_spend,
870                 )["objective"]
871             )
872             vals[u] = (v / max(g["budget"] ** g["gamma"], 1e-12), g["gamma"], g["budget"])
873         split = _cross_unit_allocation(vals, budget, cap_mult)
874         base_total = cross_total = 0.0
875         for u, g in day_groups.items():
876             base_total += (
877                 g["eff"]
878                 * alloc.solve_group(
879                     (g["p"]["rho"] * g["p"]["c"]).to_numpy(dtype=float),
880                     g["p"]["s"].to_numpy(dtype=float),
881                     g["gamma"],
882                     g["caps"],
883                     g["budget"],
884                     min_spend=min_spend,
885                 )["objective"]
886             )
887             Xu = float(split[u])
888             if Xu <= 0:
889                 continue
890             cross_total += (
891                 g["eff"]
892                 * alloc.solve_group(
893                     (g["p"]["rho"] * g["p"]["c"]).to_numpy(dtype=float),
894                     g["p"]["s"].to_numpy(dtype=float),
895                     g["gamma"],
896                     _caps(g["p"], Xu, cap_mult),
897                     Xu,
898                     min_spend=min_spend,
899                 )["objective"]
900             )
901         cross_rows.append(
902             {
903                 "window": window,
904                 "date": date.strftime("%Y-%m-%d"),

```

```

905         "units": len(day_groups),
906         "budget": budget,
907         "within_unit_regs": base_total,
908         "cross_unit_regs": cross_total,
909         "gain_pct": 100 * (cross_total / max(base_total, 1e-9) - 1),
910     }
911 )
912 cross = pd.DataFrame(cross_rows)
913 _save(ctx, cross, "cross_unit_counterfactual")
914
915 # --- February window under the annual-average budget reading: a plan for every unit
916 all_units = {int(u) for u in units["推广单元ID"]}
917 elig_all = _eligible(params, all_units, problem_cap)
918 annual = ud.groupby("推广单元ID")["消费额"].sum()
919 feb_dates = dates_by_window["feb"]
920 feb_budgets = {int(u): float(annual.get(u, 0.0)) / 365.0 * len(feb_dates) for u in all_units}
921 feb_all = _plan_window_for_units(
922     elig_all, unit_index, day_eff_by_window["feb"], feb_dates, feb_budgets, pos, cap_mult, min_spend
923 )
924 if len(feb_all):
925     feb_all["window"] = "feb_annual_avg"
926     _save(ctx, feb_all, "plan_feb_annual_avg")
927
928 # --- cross-unit duplication exposure of the delivered plan
929 dup_ids = set(params.loc[params["shared_units"] > 1, "关键词"].unique())
930 dup_mask = allocation["关键词"].isin(dup_ids)
931 dup_day = allocation[dup_mask].groupby(["date", "关键词"])["推广单元ID"].nunique()
932 dup_keys = {k for k, v in dup_day.items() if v > 1}
933 exposed = allocation[[d, k] in dup_keys for d, k in zip(allocation["date"], allocation["关键词"])]
934 ctx.write_json(
935     "duplication_exposure.json",
936     {
937         "keyword_days": len(dup_keys),
938         "rows": len(exposed),
939         "regs": float(exposed["regs"].sum()),
940         "regs_share": float(exposed["regs"].sum() / max(allocation["regs"].sum(), 1e-9)),
941         "spend": float(exposed["spend"].sum()),
942         "spend_share": float(exposed["spend"].sum() / max(allocation["spend"].sum(), 1e-9)),
943     },
944 )
945
946 # --- proportional baseline coordinates below the floor (the feasibility caveat of Section 6.2)
947 below = total_prop = 0
948 min_ratio = np.inf
949 for window, groups in all_groups.items():
950     elig = elig_by_window[window]
951     for (unit, _date), g in groups.items():
952         p_all = elig[elig["推广单元ID"] == unit]
953         xb = alloc.proportional_allocation(p_all["s"].to_numpy(dtype=float), g["budget"])
954         pos_xb = xb[xb > 0]
955         below += int((pos_xb < min_spend).sum())
956         total_prop += len(pos_xb)
957 ratios = summary["opt_regs"] / summary["prop_regs"].replace(0, np.nan)
958 min_ratio = float(ratios.min())
959 ctx.write_json(
960     "baseline_feasibility.json",
961     {
962         "proportional_positive_coordinates": total_prop,
963         "below_floor": below,
964         "below_floor_share": below / max(total_prop, 1),
965         "min_opt_over_prop_ratio": min_ratio,
966         "unit_days_with_opt_at_least_prop": int((ratios >= 1 - 1e-12).sum()),
967         "unit_days": len(ratios),

```

```

968     },
969 )
970 ctx.write_json(
971     "allocation_audit.json",
972     {
973         "ok": all(a["ok"] for a in audits),
974         "groups": len(audits),
975         "failed": [a for a in audits if not a["ok"]],
976         "cvx_available": sum(1 for a in audits if a["cvxpy"].get("available")),
977         "max_cvx_gap": float(np.nanmax([a["cvxpy"].get("relative_gap", np.nan) for a in audits])),
978         "aggregate_gap": float(
979             (
980                 sum(a["cvxpy"].get("relaxed_objective", a["objective"]) for a in audits)
981                 - sum(a["objective"] for a in audits)
982             )
983             / sum(a["objective"] for a in audits)
984         ),
985         "audits": audits,
986     },
987 )
988 # response-model calibration check: proportional allocation at the actual budget should reproduce actual clicks
989 calib = summary[["window", "推广单元ID", "actual_clicks", "prop_clicks"]].copy()
990 calib["ape"] = np.abs(calib["prop_clicks"] - calib["actual_clicks"]) / np.maximum(calib["actual_clicks"], 1.0)
991 calib["signed"] = (calib["prop_clicks"] - calib["actual_clicks"]) / np.maximum(calib["actual_clicks"], 1.0)
992 # level-bias invariance: rescaling every c_i inside a unit-day by lambda = actual/baseline clicks
993 # multiplies both the optimal and the proportional objective by lambda, so the gain ratio is
994 # unchanged -- multiplicative unit-day miscalibration cannot drive the reported improvement
995 rescale_rows = []
996 for window, groups in all_groups.items():
997     elig = elig_by_window[window]
998     opt_r = prop_r = opt_o = prop_o = 0.0
999     for (unit, date), g in groups.items():
1000         row = summary[
1001             (summary["window"] == window)
1002             & (summary["推广单元ID"] == unit)
1003             & (summary["date"] == date.strftime("%Y-%m-%d"))
1004         ].iloc[0]
1005         lam = float(row["actual_clicks"]) / max(float(row["prop_clicks"]), 1e-9)
1006         p_sel = g["p"]
1007         p_all = elig[elig["推广单元ID"] == unit]
1008         for scale, acc in ((1.0, "o"), (lam, "r")):
1009             w = (p_sel["rho"] * p_sel["c"]).to_numpy(dtype=float) * scale
1010             r = alloc.solve_group(
1011                 w, p_sel["s"].to_numpy(dtype=float), g["gamma"], g["caps"], g["budget"], min_spend=min_spend
1012             )
1013             xb = alloc.proportional_allocation(p_all["s"].to_numpy(dtype=float), g["budget"])
1014             pv = float(
1015                 np.sum(
1016                     (p_all["rho"] * p_all["c"]).to_numpy()
1017                     * scale
1018                     * np.power(xb / p_all["s"].to_numpy(), g["gamma"])
1019                 )
1020             )
1021             if acc == "o":
1022                 opt_o += g["eff"] * r["objective"]
1023                 prop_o += g["eff"] * pv
1024             else:
1025                 opt_r += g["eff"] * r["objective"]
1026                 prop_r += g["eff"] * pv
1027         rescale_rows.append(
1028             {
1029                 "window": window,
1030                 "gain_pct": 100 * (opt_o / max(prop_o, 1e-9) - 1),

```

```

1031         "gain_pct_rescaled": 100 * (opt_r / max(prop_r, 1e-9) - 1),
1032     }
1033 )
1034 ctx.write_json(
1035     "calibration_check.json",
1036     {
1037         "mape": float(calib["ape"].mean()),
1038         "median_ape": float(calib["ape"].median()),
1039         "n": len(calib),
1040         "spend_weighted_mape": float(np.average(calib["ape"], weights=summary["budget"])),
1041         "signed_bias_by_window": {
1042             w: float(
1043                 (calib.loc[calib["window"] == w, "prop_clicks"].sum())
1044                 / max(calib.loc[calib["window"] == w, "actual_clicks"].sum(), 1.0)
1045                 - 1
1046             )
1047             for w in calib["window"].unique()
1048         },
1049         "rescaling_invariance": rescale_rows,
1050         "max_gain_shift_pp": float(max(abs(r["gain_pct"] - r["gain_pct_rescaled"]) for r in rescale_rows)),
1051     },
1052 )
1053 if not all(a["ok"] for a in audits):
1054     raise RuntimeError("allocation audit failed for some unit-days; see allocation_audit.json")
1055
1056 win_tot = summary.groupby("window")[
1057     [
1058         "budget",
1059         "opt_clicks",
1060         "opt_regs",
1061         "prop_clicks",
1062         "prop_regs",
1063         "equal_regs",
1064         "actual_clicks",
1065         "actual_regs_expected",
1066     ]
1067 ].sum()
1068 for window, key in (("feb", "Feb"), ("aug", "Aug")):
1069     w = win_tot.loc[window]
1070     ctx.number(f"QthreeBudget{key}", w["budget"], ".2f")
1071     ctx.number(f"QthreeOptRegs{key}", w["opt_regs"], ".2f")
1072     ctx.number(f"QthreePropRegs{key}", w["prop_regs"], ".2f")
1073     ctx.number(f"QthreeOptClicks{key}", w["opt_clicks"], ".1f")
1074     ctx.number(f"QthreePropClicks{key}", w["prop_clicks"], ".1f")
1075     ctx.number(f"QthreeActualClicks{key}", w["actual_clicks"], ".0f")
1076     ctx.number(f"QthreeRegGainPct{key}", 100 * (w["opt_regs"] / w["prop_regs"] - 1), ".2f")
1077     ctx.number(f"QthreeClickGainPct{key}", 100 * (w["opt_clicks"] / w["prop_clicks"] - 1), ".2f")
1078     ctx.number(f"QthreeEqualRegGainPct{key}", 100 * (w["opt_regs"] / w["equal_regs"] - 1), ".2f")
1079     bw = boot[boot["window"] == window]["ratio"]
1080     ctx.number(f"QthreeRegGainCiLow{key}", 100 * (bw.quantile(0.025) - 1), ".2f")
1081     ctx.number(f"QthreeRegGainCiHigh{key}", 100 * (bw.quantile(0.975) - 1), ".2f")
1082     sw = summary[summary["window"] == window]
1083     ctx.number(f"QthreeUnitDays{key}", len(sw))
1084     ctx.number(f"QthreeUnits{key}", int(sw["推广单元ID"].nunique()))
1085     ctx.number(f"QthreeSelectedKeywords{key}", int(allocation[allocation["window"] == window]["序号"].nunique()))
1086     ctx.number(f"QthreeEligibleKeywords{key}", int(sw.groupby("推广单元ID")["eligible"].first().sum()))
1087     ctx.number(f"QthreeAvgCpc{key}", w["budget"] / w["opt_clicks"], ".4f")
1088     ctx.number(f"QthreePropCpc{key}", w["budget"] / w["prop_clicks"], ".4f")
1089     aw = alt[alt["window"] == window]
1090     if len(aw):
1091         ctx.number(f"QthreeWindowRegs{key}", aw["regs_window"].sum(), ".2f")
1092         ctx.number(f"QthreeWindowGainPct{key}", 100 * (aw["regs_window"].sum() / w["opt_regs"] - 1), ".2f")
1093     ctx.number(f"QthreeAuditGroups", len(audits))

```

```

1094     ctx.number("QthreeMaxCvxGap", float(np.nanmax([a["cvxpy"].get("relative_gap", np.nan) for a in audits])), ".2e")
1095
1096     def cvx_check(a: dict[str, Any]) -> dict[str, Any]:
1097         return next((c for c in a["checks"] if c["name"] == "within_convex_relaxation_bound"), {})
1098
1099     tiny_groups = [a for a in audits if cvx_check(a).get("tiny_budget")]
1100     informative = [
1101         float(cvx_check(a)["relative_gap"]) for a in audits if cvx_check(a) and not cvx_check(a).get("tiny_budget")
1102     ]
1103     ctx.number("QthreeCvxTinyGroups", len(tiny_groups))
1104     ctx.number("QthreeMaxCvxGapInformativePct", 100 * max(informative) if informative else 0.0, ".3f")
1105     ctx.number(
1106         "QthreeMaxCvxGapPct", 100 * float(np.nanmax([a["cvxpy"].get("relative_gap", np.nan) for a in audits])), ".1f"
1107     )
1108     ctx.number("QthreeCappedKeywordDays", int(sum(a["n_capped"] for a in audits)))
1109     ctx.number("QthreeSelectedKeywordDays", int(sum(a["n_selected"] for a in audits)))
1110     # long-tail words whose cap is the floor itself: how much money and value they carry (August window)
1111     aug = allocation[allocation["window"] == "aug"]
1112     at_floor = aug["spend"] <= min_spend + 1e-9
1113     ctx.number("QthreeFloorKeywordDaysAug", int(at_floor.sum()))
1114     ctx.number("QthreeFloorSpendSharePctAug", 100 * float(aug.loc[at_floor, "spend"].sum() / aug["spend"].sum()), ".2f"
1115         ↪ )
1116     ctx.number("QthreeFloorRegsSharePctAug", 100 * float(aug.loc[at_floor, "regs"].sum() / aug["regs"].sum()), ".2f")
1117     sw_aug = summary[summary["window"] == "aug"]
1118     ctx.number("QthreeMeanSelectedAug", float(sw_aug["selected"].mean()), ".1f")
1119     unit_gain = sw_aug.groupby("推广单元ID")[["opt_regs", "prop_regs"]].sum()
1120     unit_gain_pct = 100 * (unit_gain["opt_regs"] / unit_gain["prop_regs"] - 1)
1121     ctx.number("QthreeMinUnitGainPctAug", float(unit_gain_pct.min()), ".1f")
1122     ctx.number("QthreeMaxUnitGainPctAug", float(unit_gain_pct.max()), ".1f")
1123     ctx.number("QthreeMinGainUnitAug", int(unit_gain_pct.idxmin()))
1124     ctx.number("QthreeMaxGainUnitAug", int(unit_gain_pct.idxmax()))
1125     relaxed = sum(a["cvxpy"].get("relaxed_objective", a["objective"]) for a in audits)
1126     achieved = sum(a["objective"] for a in audits)
1127     ctx.number("QthreeAggregateGapPct", 100 * (relaxed - achieved) / achieved, ".3f")
1128     ctx.number("QthreeCalibrationMape", 100 * float(calib["ape"].mean()), ".2f")
1129     ctx.number("QthreeCalibrationMedianApe", 100 * float(calib["ape"].median()), ".2f")
1130     ctx.number("QthreeRows", len(allocation))
1131     ctx.number("QthreeCapMultiplier", cap_mult, ".1f")
1132     ctx.number("QthreeMinSpend", min_spend, ".2f")
1133     # empirical dominance over the baseline (the floor makes the a-priori feasibility argument invalid)
1134     ratios = summary["opt_regs"] / summary["prop_regs"].replace(0, np.nan)
1135     ctx.number("QthreeMinOptPropRatio", float(ratios.min()), ".4f")
1136     ctx.number("QthreeUnitDaysOptAtLeastProp", int((ratios >= 1 - 1e-12).sum()))
1137     prop_below = prop_pos = 0
1138     for window, groups in all_groups.items():
1139         elig_w = elig_by_window[window]
1140         for (unit, _date), g in groups.items():
1141             xb = alloc.proportional_allocation(
1142                 elig_w[elig_w["推广单元ID"] == unit]["s"].to_numpy(dtype=float), g["budget"]
1143             )
1144             xb = xb[xb > 0]
1145             prop_below += int((xb < min_spend).sum())
1146             prop_pos += len(xb)
1147     ctx.number("QthreePropBelowFloor", prop_below, ",d")
1148     ctx.number("QthreePropPositiveCoords", prop_pos, ",d")
1149     ctx.number("QthreePropBelowFloorPct", 100 * prop_below / max(prop_pos, 1), ".1f")
1150     # duplication exposure
1151     dupj = ctx.read_json(ctx.stage_dir / "duplication_exposure.json")
1152     ctx.number("QthreeDupKeywordDays", dupj["keyword_days"], ",d")
1153     ctx.number("QthreeDupRegs", dupj["regs"], ",.2f")
1154     ctx.number("QthreeDupRegsSharePct", 100 * dupj["regs_share"], ".2f")
1155     ctx.number("QthreeDupSpend", dupj["spend"], ",.2f")
1156     ctx.number("QthreeDupSpendSharePct", 100 * dupj["spend_share"], ".2f")

```

```

1156 # calibration sign and invariance
1157 calj = ctx.read_json(ctx.stage_dir / "calibration_check.json")
1158 for window, key in (("feb", "Feb"), ("aug", "Aug")):
1159     ctx.number(f"QthreeSignedBiasPct{key}", 100 * calj["signed_bias_by_window"][window], ".1f")
1160 ctx.number("QthreeGainShiftPp", calj["max_gain_shift_pp"], ".2f")
1161 for rec in calj["rescaling_invariance"]:
1162     ctx.number(
1163         "QthreeGainRescaledPct" + {"feb": "Feb", "aug": "Aug"}[rec["window"]], rec["gain_pct_rescaled"], ".2f"
1164     )
1165 ctx.number("QthreeSpendWeightedMape", 100 * calj["spend_weighted_mape"], ".1f")
1166 # cross-unit reallocation counterfactual
1167 for window, key in (("feb", "Feb"), ("aug", "Aug")):
1168     cw = cross[cross["window"] == window]
1169     if len(cw):
1170         ctx.number(
1171             f"QthreeCrossUnitGainPct{key}",
1172             100 * (cw["cross_unit_regs"].sum() / max(cw["within_unit_regs"].sum(), 1e-9) - 1),
1173             ".2f",
1174         )
1175         ctx.number(f"QthreeCrossUnitDays{key}", len(cw))
1176 # February window under the annual-average budget reading
1177 if len(feb_all):
1178     ctx.number("QthreeFebAltRows", len(feb_all))
1179     ctx.number("QthreeFebAltUnits", int(feb_all["推广单元ID"].nunique()))
1180     ctx.number("QthreeFebAltBudget", float(feb_all["spend"].sum()), ".2f")
1181     ctx.number("QthreeFebAltRegs", float(feb_all["regs"].sum()), ".2f")
1182     ctx.number("QthreeFebAltClicks", float(feb_all["clicks"].sum()), ".1f")
1183     ctx.number("QthreeFebAltKeywords", int(feb_all["序号"].nunique()))
1184
1185 # sensitivity read-outs quoted in the text
1186 def sens_val(name: str, window: str, col: str = "gain") -> float:
1187     sel = sens[(sens["scenario"] == name) & (sens["window"] == window)]
1188     return float(sel[col].iloc[0]) if len(sel) else float("nan")
1189
1190 for window, key in (("2 月", "Feb"), ("8 月", "Aug")):
1191     base_regs = sens_val("基准", window, "opt_regs")
1192     free_regs = sens_val("最小投放 0 (上限同基准)", window, "opt_regs")
1193     ctx.number(f"QthreeFloorCostPct{key}", 100 * (free_regs / max(base_regs, 1e-9) - 1), ".3f")
1194     ctx.number(f"QthreeSelectedBase{key}", sens_val("基准", window, "selected"), ".1f")
1195     ctx.number(f"QthreeSelectedNoFloor{key}", sens_val("最小投放 0 (上限同基准)", window, "selected"), ".1f")
1196     ctx.number(f"QthreeKappaOneGainPct{key}", sens_val("跳出率因子 kappa = 1", window, "selected"), ".2f")
1197     ctx.number(f"QthreeKappaClipGainPct{key}", sens_val("kappa 截断 [0.5, 2]", window, "selected"), ".2f")
1198     ctx.number(f"QthreeDupBestGainPct{key}", sens_val("重复词只留最优副本", window, "selected"), ".2f")
1199     ctx.number("QthreeSensMinGainPct", float(sens["gain"].min()), ".1f")
1200     ctx.number("QthreeSensMaxGainPct", float(sens["gain"].max()), ".1f")
1201     ctx.number("QthreeSensScenarios", int(sens["scenario"].nunique()))
1202     kap = params["kappa"].to_numpy(dtype=float)
1203     ctx.number("KappaAtBoundPct", 100 * float(np.mean((kap <= 0.2501) | (kap >= 2.4999))), ".1f")
1204     ctx.number("KappaMedian", float(np.median(kap)), ".4f")
1205     ctx.number("KappaRows", len(kap), ",d")
1206     return {"rows": len(allocation), "audit_ok": True, "windows": win_tot.to_dict(orient="index")}
1207
1208
1209 # ----- Q4
1210 @stage(
1211     "forecast",
1212     deps=("eda", "classify", "allocate"),
1213     description="Q4: 2026-09-11..17 forecasts, backtests, stochastic allocation and expected ranges",
1214 )
1215 def forecast(ctx: StageContext) -> dict[str, Any]:
1216     rng = np.random.default_rng(ctx.seed_everything("forecast"))
1217     ud, units, params, pos, _ = _load_params(ctx)
1218     cap_mult = float(ctx.cfg("allocate.cap_multiplier", 4.0))

```

```

1219 min_spend = float(ctx.cfg("allocate.min_spend", 0.5))
1220 problem_cap = float(ctx.cfg("allocate.problem_cap_factor", 0.5))
1221 n_scen = int(ctx.param("scenarios", ctx.cfg("forecast.scenarios", 500)))
1222 unit_index = units.set_index("推广单元ID")
1223 dates = pd.date_range(*Q4_DATES, freq="D")
1224 future = day_features(dates)
1225 origins = list(pd.date_range("2025-10-09", "2025-12-25", freq="7D"))
1226
1227 series_by_unit: dict[int, pd.DataFrame] = {}
1228 for _, row in units.iterrows():
1229     unit = int(row["推广单元ID"])
1230     series_by_unit[unit] = fc.unit_series(
1231         ud[ud["推广单元ID"] == unit],
1232         float(row["gamma"]),
1233         float(row["mean_daily_spend"]),
1234         float(row["mean_daily_clicks"]),
1235     )
1236 bt_frames = []
1237 for unit, series in series_by_unit.items():
1238     for target in fc.TARGETS:
1239         bt = fc.rolling_backtest(series, target, origins)
1240         if len(bt):
1241             bt.insert(0, "推广单元ID", unit)
1242             bt_frames.append(bt)
1243 backtest = pd.concat(bt_frames, ignore_index=True)
1244 _save(ctx, backtest, "backtest")
1245 bt_summary = (
1246     backtest.groupby(["target", "model"])[["mae", "rmse", "mape_raw", "pinball10", "pinball90", "coverage80"]]
1247     .mean()
1248     .reset_index()
1249 )
1250 _save(ctx, bt_summary, "backtest_summary")
1251
1252 fc_rows = []
1253 unit_fc: dict[int, dict[str, dict[str, Any]]] = {}
1254 for unit, series in series_by_unit.items():
1255     unit_fc[unit] = {}
1256     for target, info in fc.TARGETS.items():
1257         if len(series) < 40:
1258             continue
1259         f = fc.forecast_unit(series, target, future)
1260         unit_fc[unit][target] = f
1261         sd_total = float(np.sqrt(f["sd"] ** 2 + f["month_sd"] ** 2))
1262         for i, d in enumerate(dates):
1263             fc_rows.append(
1264                 {
1265                     "推广单元ID": unit,
1266                     "date": d.strftime("%Y-%m-%d"),
1267                     "target": target,
1268                     "mean_t": float(f["mean"][i]),
1269                     "sd_t": sd_total,
1270                     "point": float(fc.back_transform(np.array([f["mean"][i]]), info["transform"])[0]),
1271                     "q10": float(
1272                         fc.back_transform(np.array([f["mean"][i] - fc.Z80 * sd_total]), info["transform"])[0]
1273                     ),
1274                     "q90": float(
1275                         fc.back_transform(np.array([f["mean"][i] + fc.Z80 * sd_total]), info["transform"])[0]
1276                     ),
1277                     "month_known": f["month_known"],
1278                 }
1279             )
1280 forecasts = pd.DataFrame(fc_rows)
1281 _save(ctx, forecasts, "unit_forecasts")

```

```

1282
1283 # budgets: 2025 same-period spend per unit (main) and the annual-average alternative
1284 s1 = ud[["日期", "方案ID", "推广单元ID", "消费额"]]
1285 ref = s1[(s1["日期"] >= Q4_REFERENCE[0]) & (s1["日期"] <= Q4_REFERENCE[1])]
1286 budget_main = ref.groupby("推广单元ID")["消费额"].sum()
1287 day_cap_ref = ref.groupby("推广单元ID")["消费额"].max()
1288 annual = s1.groupby("推广单元ID")["消费额"].sum()
1289 budget_alt = annual / 365.0 * len(dates)
1290 budgets = (
1291     pd.DataFrame({"budget_same_period": budget_main, "budget_annual_avg": budget_alt}).fillna(0.0).reset_index()
1292 )
1293 _save(ctx, budgets, "budgets")
1294 active_units = {int(u) for u, b in budget_main.items() if b > 0}
1295 all_unit_ids = {int(u) for u in units["推广单元ID"]}
1296 elig = _eligible(params, active_units, problem_cap)
1297 elig_all = _eligible(params, all_unit_ids, problem_cap)
1298 _save(ctx, elig, "keyword_parameters")
1299
1300 rows, day_rows, audits, unit_rows, joint_rows = [], [], [], [], []
1301 for unit in sorted(active_units):
1302     p = elig[(elig["推广单元ID"] == unit) & elig["eligible"]]
1303     if p.empty or unit not in unit_fc or "log_eff" not in unit_fc[unit]:
1304         continue
1305     gamma = float(unit_index.loc[unit, "gamma"])
1306     f_eff = unit_fc[unit]["log_eff"]
1307     sd_eff = float(np.sqrt(f_eff["sd"] ** 2 + f_eff["month_sd"] ** 2))
1308     eff_mean = np.exp(f_eff["mean"] + 0.5 * sd_eff**2)
1309     B = float(budget_main[unit])
1310     day_cap = float(max(1.5 * day_cap_ref[unit], B / len(dates)))
1311     # day split with the same floor: a day is either skipped or receives at least the minimum amount
1312     day_caps = np.full(len(dates), day_cap)
1313     X = alloc.solve_group(eff_mean, np.ones(len(dates)), gamma, day_caps, B, min_spend=min_spend)["x"]
1314     day_audit = alloc.verify_allocation(X, eff_mean, gamma, day_caps, B, rng, floor=min_spend)
1315     audits.append({"推广单元ID": unit, "level": "days", **{k: v for k, v in day_audit.items() if k != "cvxpy"}})
1316     f_ctr = unit_fc[unit]["logit_ctr"]
1317     f_top = unit_fc[unit]["logit_top"]
1318     f_cpc = unit_fc[unit]["log_cpc"]
1319     kw_sd = float(f_cpc["sd"])
1320     totals = {k: np.zeros(n_scen) for k in ("clicks", "imp", "views", "regs", "spend")}
1321     det_objective = 0.0
1322     s = p["s"].to_numpy(dtype=float)
1323     for i, d in enumerate(dates):
1324         if X[i] <= 0:
1325             continue
1326         w = (p["rho"] * p["c"]).to_numpy(dtype=float) * float(eff_mean[i])
1327         s = p["s"].to_numpy(dtype=float)
1328         caps = _caps(p, float(X[i]), cap_mult)
1329         res = alloc.solve_group(w, s, gamma, caps, float(X[i]), min_spend=min_spend)
1330         x = res["x"]
1331         sel = x > 0
1332         a = w * np.power(s, -gamma)
1333         audit = alloc.verify_allocation(x, a, gamma, caps, float(X[i]), rng, floor=min_spend)
1334         audits.append(
1335             {
1336                 "推广单元ID": unit,
1337                 "level": "keywords",
1338                 "date": d.strftime("%Y-%m-%d"),
1339                 **{k: v for k, v in audit.items() if k != "checks"},
1340                 "checks": audit["checks"],
1341             }
1342         )
1343     sim = fc.simulate_group(
1344         x[sel],

```

```

1345         p[sel],
1346         gamma,
1347         float(f_eff["mean"][i]),
1348         sd_eff,
1349         kw_sd,
1350         float(f_ctr["mean"][i]),
1351         float(np.sqrt(f_ctr["sd"] ** 2 + f_ctr["month_sd"] ** 2)),
1352         pos[unit]["top"],
1353         pos[unit]["first"],
1354         float(np.sqrt(f_top["sd"] ** 2 + f_top["month_sd"] ** 2)),
1355         rng,
1356         n_scen,
1357     )
1358     ps = p[sel]
1359     stats = {k: fc.summarise(v) for k, v in sim.items()}
1360     for j in range(int(sel.sum())):
1361         rows.append(
1362             {
1363                 "date": d.strftime("%Y-%m-%d"),
1364                 "方案ID": int(ps["方案ID"].iloc[j]),
1365                 "推广单元ID": unit,
1366                 "关键词": int(ps["关键词"].iloc[j]),
1367                 "序号": int(ps["序号"].iloc[j]),
1368                 "label": ps["label"].iloc[j],
1369                 "spend": float(x[sel][j]),
1370                 **{
1371                     f"{k}_{q}": float(stats[k][q][j])
1372                     for k in ("clicks", "cpc", "imp", "position", "views", "regs", "p_top")
1373                     for q in ("mean", "q10", "q50", "q90")
1374                 },
1375             }
1376         )
1377     for k in ("clicks", "imp", "views", "regs"):
1378         totals[k] += np.nansum(sim[k], axis=1)
1379     totals["spend"] += float(x.sum())
1380     det_objective += float(eff_mean[i]) * float(
1381         np.sum((p[sel]["rho"] * p[sel]["c"]).to_numpy(dtype=float) * np.power(x[sel] / s[sel], gamma))
1382     )
1383     day_tot = {k: np.nansum(sim[k], axis=1) for k in ("clicks", "imp", "views", "regs")}
1384     day_cpc = float(x.sum()) / np.maximum(day_tot["clicks"], 1e-9)
1385     pos_w = np.nansum(sim["position"] * sim["clicks"], axis=1) / np.maximum(day_tot["clicks"], 1e-9)
1386     ptop_w = np.nansum(sim["p_top"] * sim["clicks"], axis=1) / np.maximum(day_tot["clicks"], 1e-9)
1387     pfirst_w = np.nansum(sim["p_first"] * sim["clicks"], axis=1) / np.maximum(day_tot["clicks"], 1e-9)
1388     day_rows.append(
1389         {
1390             "date": d.strftime("%Y-%m-%d"),
1391             "方案ID": int(ps["方案ID"].iloc[0]),
1392             "推广单元ID": unit,
1393             "budget_day": float(X[i]),
1394             "spend": float(x.sum()),
1395             "selected": int(sel.sum()),
1396             "eff_mean": float(eff_mean[i]),
1397             "p_top_mean": float(ptop_w.mean()),
1398             "p_first_mean": float(pfirst_w.mean()),
1399             "cpc_scenario_mean": float(day_cpc.mean()),
1400             **{
1401                 f"{k}_{q}": float(v)
1402                 for k, arr in day_tot.items()
1403                 for q, v in zip(
1404                     ("mean", "q10", "q90"), (arr.mean(), np.quantile(arr, 0.1), np.quantile(arr, 0.9))
1405                 )
1406             },
1407             **{

```

```

1408         f"cpc_{q}": float(v)
1409     for q, v in zip(
1410         ("mean", "q10", "q90"),
1411         (day_cpc.mean(), np.quantile(day_cpc, 0.1), np.quantile(day_cpc, 0.9)),
1412     )
1413 },
1414 **{
1415     f"position_{q}": float(v)
1416     for q, v in zip(
1417         ("mean", "q10", "q90"), (pos_w.mean(), np.quantile(pos_w, 0.1), np.quantile(pos_w, 0.9))
1418     )
1419 },
1420 }
1421 )
1422 # joint (7 days x keywords) concave relaxation: no floor and the most generous caps, so its
1423 # optimum bounds the true joint optimum from above and certifies the two-level decomposition
1424 # the effective per-day box is max(cap_i, m) because the floor lifts caps below it, so the
1425 # relaxation must use the same lift to contain every day's feasible set
1426 caps_joint = np.maximum(_caps(p, B, cap_mult), min_spend)
1427 a_joint = np.concatenate(
1428     [
1429         float(eff_mean[i]) * (p["rho"] * p["c"]).to_numpy(dtype=float) * np.power(s, -gamma)
1430         for i in range(len(dates))
1431     ]
1432 )
1433 x_joint = alloc.water_filling(a_joint, gamma, np.tile(caps_joint, len(dates)), B)
1434 joint_bound = float(np.sum(a_joint * np.power(x_joint, gamma)))
1435 joint_rows.append(
1436     {
1437         "推广单元ID": unit,
1438         "two_level": det_objective,
1439         "joint_bound": joint_bound,
1440         "gap_pct": 100 * (joint_bound - det_objective) / max(det_objective, 1e-9),
1441     }
1442 )
1443 unit_rows.append(
1444     {
1445         "推广单元ID": unit,
1446         "budget": B,
1447         "spent": float(totals["spend"][0]),
1448         "gamma": gamma,
1449         "eligible": len(p),
1450         "regs_scenario_sd": float(np.std(totals["regs"], ddof=1)),
1451         "det_regs": det_objective,
1452         "day_split": [float(v) for v in X],
1453         **{
1454             f"{k}_{q}": float(v)
1455             for k, arr in totals.items()
1456             if k != "spend"
1457             for q, v in zip(("mean", "q10", "q90"), (arr.mean(), np.quantile(arr, 0.1), np.quantile(arr, 0.9)))
1458         },
1459     }
1460 )
1461 alt_expected: dict[str, float] = {}
1462 alt_frames: list[pd.DataFrame] = []
1463 for name, budget_series in (("same_period", budget_main), ("annual_avg", budget_alt)):
1464     total_regs = 0.0
1465     for unit in sorted(int(u) for u, b in budget_series.items() if b > 0):
1466         pu = elig_all[(elig_all["推广单元ID"] == unit) & elig_all["eligible"]]
1467         if pu.empty or unit not in unit_fc or "log_eff" not in unit_fc[unit]:
1468             continue
1469         gamma = float(unit_index.loc[unit, "gamma"])
1470         f_eff = unit_fc[unit]["log_eff"]

```

```

1471     sd_eff = float(np.sqrt(f_eff["sd"] ** 2 + f_eff["month_sd"] ** 2))
1472     eff_mean = np.exp(f_eff["mean"] + 0.5 * sd_eff**2)
1473     B = float(budget_series[unit])
1474     cap_day = float(max(1.5 * day_cap_ref.get(unit, B / len(dates)), B / len(dates)))
1475     X = alloc.solve_group(
1476         eff_mean, np.ones(len(dates)), gamma, np.full(len(dates), cap_day), B, min_spend=min_spend
1477     )["x"]
1478     for i in range(len(dates)):
1479         if X[i] <= 0:
1480             continue
1481         w = (pu["rho"] * pu["c"]).to_numpy(dtype=float) * float(eff_mean[i])
1482         sv = pu["s"].to_numpy(dtype=float)
1483         res_alt = alloc.solve_group(
1484             w, sv, gamma, _caps(pu, float(X[i]), cap_mult), float(X[i]), min_spend=min_spend
1485         )
1486         total_regs += res_alt["objective"]
1487         if name == "annual_avg": # the recommended reading also gets a full day-by-day plan
1488             ev = _evaluate(res_alt["x"], pu, gamma, float(eff_mean[i]), pos[unit])
1489             ev.insert(0, "date", dates[i].strftime("%Y-%m-%d"))
1490             alt_frames.append(ev[ev["spend"] > 0])
1491     alt_expected[name] = total_regs
1492     ctx.write_json("budget_alternatives.json", alt_expected)
1493     plan_alt = pd.concat(alt_frames, ignore_index=True) if alt_frames else pd.DataFrame()
1494     if len(plan_alt):
1495         _save(ctx, plan_alt, "plan_annual_alt")
1496     joint = pd.DataFrame(joint_rows)
1497     _save(ctx, joint, "joint_relaxation")
1498     plan = pd.DataFrame(rows)
1499     _save(ctx, plan, "plan")
1500     # units the same-period budget reading leaves with no money still need a line in result4.xlsx:
1501     # one zero row per day makes "no placement" explicit instead of silently dropping the unit
1502     zero_rows = []
1503     for unit in sorted(all_unit_ids - active_units):
1504         pz = elig_all[(elig_all["推广单元ID"] == unit) & elig_all["eligible"]]
1505         if pz.empty:
1506             continue
1507         best = pz.sort_values("efficiency", ascending=False).iloc[0]
1508         for d in dates:
1509             zero_rows.append(
1510                 {
1511                     "date": d.strftime("%Y-%m-%d"),
1512                     "方案ID": int(best["方案ID"]),
1513                     "推广单元ID": unit,
1514                     "关键词": int(best["关键词"]),
1515                     "序号": int(best["序号"]),
1516                     "spend": 0.0,
1517                     "position_mean": 0.0,
1518                     "clicks_mean": 0.0,
1519                     "views_mean": 0.0,
1520                     "regs_mean": 0.0,
1521                 }
1522             )
1523     zeros = pd.DataFrame(zero_rows)
1524     if len(zeros):
1525         _save(ctx, zeros, "plan_zero_rows")
1526     days = pd.DataFrame(day_rows)
1527     _save(ctx, days, "plan_by_unit_day")
1528     per_unit = pd.DataFrame(unit_rows)
1529     per_unit.to_json(ctx.out("plan_by_unit.json"), orient="records", force_ascii=False, indent=2)
1530     audit_ok = all(a["ok"] for a in audits)
1531     ctx.write_json(
1532         "allocation_audit.json",
1533         {"ok": audit_ok, "groups": len(audits), "failed": [a for a in audits if not a["ok"]], "audits": audits},

```

```

1534 )
1535 if not audit_ok:
1536     raise RuntimeError("Q4 allocation audit failed; see allocation_audit.json")
1537
1538 cal = bt_summary[bt_summary["model"] == "calendar"].set_index("target")
1539 wide = bt_summary[bt_summary["model"] == "calendar_wide"].set_index("target")
1540 sn = bt_summary[bt_summary["model"] == "seasonal_naive"].set_index("target")
1541 m28 = bt_summary[bt_summary["model"] == "mean28"].set_index("target")
1542 for target, key in (
1543     ("log_eff", "Eff"),
1544     ("log_cpc", "Cpc"),
1545     ("logit_ctr", "Ctr"),
1546     ("logit_top", "Top"),
1547     ("logit_first", "First"),
1548     ("log_clicks", "Clicks"),
1549 ):
1550     ctx.number(f"BacktestWideCoverage{key}", 100 * wide.loc[target, "coverage80"], ".2f")
1551     ctx.number(f"BacktestWidePinball{key}", wide.loc[target, "pinball10"] + wide.loc[target, "pinball90"], ".4f")
1552     ctx.number(f"BacktestCalendarMae{key}", cal.loc[target, "mae"], ".4f")
1553     ctx.number(f"BacktestNaiveMae{key}", sn.loc[target, "mae"], ".4f")
1554     ctx.number(f"BacktestMeanMae{key}", m28.loc[target, "mae"], ".4f")
1555     ctx.number(f"BacktestCalendarCoverage{key}", 100 * cal.loc[target, "coverage80"], ".2f")
1556     ctx.number(f"BacktestNaiveCoverage{key}", 100 * sn.loc[target, "coverage80"], ".2f")
1557     ctx.number(f"BacktestMeanCoverage{key}", 100 * m28.loc[target, "coverage80"], ".2f")
1558     ctx.number(f"BacktestCalendarPinball{key}", cal.loc[target, "pinball10"] + cal.loc[target, "pinball90"], ".4f")
1559     ctx.number(f"BacktestNaivePinball{key}", sn.loc[target, "pinball10"] + sn.loc[target, "pinball90"], ".4f")
1560 tot = per_unit[
1561     [
1562         "budget",
1563         "spent",
1564         "clicks_mean",
1565         "clicks_q10",
1566         "clicks_q90",
1567         "imp_mean",
1568         "imp_q10",
1569         "imp_q90",
1570         "views_mean",
1571         "views_q10",
1572         "views_q90",
1573         "regs_mean",
1574         "regs_q10",
1575         "regs_q90",
1576     ]
1577 ].sum()
1578 ctx.number("QfourBudget", tot["budget"], ".2f")
1579 ctx.number("QfourBudgetAnnualAlt", float(budgets["budget_annual_avg"].sum()), ".2f")
1580 ctx.number("QfourRegsExpectedSamePeriod", alt_expected["same_period"], ".1f")
1581 ctx.number("QfourRegsExpectedAnnualAlt", alt_expected["annual_avg"], ".1f")
1582 ctx.number(
1583     "QfourRegsGainAnnualAltPct",
1584     100 * (alt_expected["annual_avg"] / max(alt_expected["same_period"], 1e-9) - 1),
1585     ".1f",
1586 )
1587 biggest = per_unit.sort_values("budget", ascending=False).iloc[0]
1588 ctx.number("QfourBiggestUnitId", int(biggest["推广单元ID"]))
1589 ctx.number("QfourBiggestUnitBudgetSharePct", 100 * float(biggest["budget"]) / float(tot["budget"]), ".1f")
1590 ctx.number("QfourUnits", len(per_unit))
1591 ctx.number("QfourSkippedUnits", int(len(units) - len(per_unit)))
1592 ctx.number("QfourRows", len(plan))
1593 ctx.number("QfourSelectedKeywords", int(plan["序号"].nunique()))
1594 for k, key in (("clicks", "Clicks"), ("imp", "Imp"), ("views", "Views"), ("regs", "Regs")):
1595     ctx.number(f"Qfour{key}Mean", tot[f"{k}_mean"], ".1f")
1596     ctx.number(f"Qfour{key}Low", tot[f"{k}_q10"], ".1f")

```

```

1597     ctx.number(f"Qfour{key}High", tot[f"{k}_q90"], ",.1f")
1598     ctx.number("QfourCpcMean", tot["spent"] / tot["clicks_mean"], ".4f")
1599     ctx.number("QfourCpcLow", tot["spent"] / tot["clicks_q90"], ".4f")
1600     ctx.number("QfourCpcHigh", tot["spent"] / tot["clicks_q10"], ".4f")
1601     pos_w = np.maximum(days["clicks_mean"], 1e-9)
1602     for key, col in (("Mean", "position_mean"), ("Low", "position_q10"), ("High", "position_q90")):
1603         ctx.number(f"QfourPosition{key}", float(np.average(days[col], weights=pos_w)), ".4f")
1604     ctx.number("QfourScenarios", n_scen)
1605     ctx.number("QfourAuditGroups", len(audits))
1606     # deployed interval width relative to the backtested residual-only width
1607     infl = []
1608     for targets in unit_fc.values():
1609         for f in targets.values():
1610             if f["sd"] > 0:
1611                 infl.append(float(np.sqrt(f["sd"] ** 2 + f["month_sd"] ** 2) / f["sd"]))
1612     ctx.number("QfourWidthInflationMedian", float(np.median(infl)), ".3f")
1613     ctx.number("QfourWidthInflationMax", float(np.max(infl)), ".3f")
1614     ctx.number("QfourWidthInflationMin", float(np.min(infl)), ".3f")
1615     ctx.number("BacktestWideCoverageMin", 100 * float(wide["coverage80"].min()), ".1f")
1616     ctx.number("BacktestWideCoverageMax", 100 * float(wide["coverage80"].max()), ".1f")
1617     ctx.number("BacktestCalendarCoverageMin", 100 * float(cal["coverage80"].min()), ".1f")
1618     ctx.number("BacktestCalendarCoverageMax", 100 * float(cal["coverage80"].max()), ".1f")
1619     ctx.number("BacktestMeanCoverageMin", 100 * float(m28["coverage80"].min()), ".1f")
1620     ctx.number("BacktestMeanCoverageMax", 100 * float(m28["coverage80"].max()), ".1f")
1621     ctx.number("BacktestOrigins", int(backtest["origin"].nunique()))
1622     ctx.number("BacktestUnits", int(backtest["推广单元ID"].nunique()))
1623     # joint optimality certificate for the two-level decomposition
1624     ctx.number("QfourJointGapPct", 100 * (joint["joint_bound"].sum() / joint["two_level"].sum() - 1), ".3f")
1625     ctx.number("QfourJointMaxGapPct", float(joint["gap_pct"].max()), ".2f")
1626     ctx.number("QfourJointUnits", len(joint))
1627     worst = joint.loc[joint["gap_pct"].idxmax()]
1628     ctx.number("QfourJointMaxGapUnit", int(worst["推广单元ID"]))
1629     ctx.number("QfourJointMaxGapUnitRegs", float(worst["two_level"]), ".2f")
1630     big = joint[joint["two_level"] >= 10]
1631     ctx.number("QfourJointMaxGapBigPct", float(big["gap_pct"].max()), ".2f")
1632     ctx.number("QfourJointBigUnits", len(big))
1633     ctx.number("QfourDetRegs", float(joint["two_level"].sum()), ".1f")
1634     # Monte Carlo precision of the reported expectation (independent unit draws)
1635     mc_se = float(np.sqrt((per_unit["regs_scenario_sd"] ** 2).sum() / n_scen))
1636     ctx.number("QfourRegsMcSe", mc_se, ".1f")
1637     ctx.number("QfourRegsMcZ", abs(float(tot["regs_mean"]) - float(joint["two_level"].sum())) / max(mc_se, 1e-9), ".1f")
1638     ↪ )
1639     # position: the ranking index is a three-point mixture, so report the two shares behind it
1640     ctx.number("QfourPtopPct", 100 * float(np.average(days["p_top_mean"], weights=pos_w)), ".1f")
1641     ctx.number("QfourPfirstPct", 100 * float(np.average(days["p_first_mean"], weights=pos_w)), ".1f")
1642     ctx.number("QfourPmidPct", 100 * float(np.average(days["p_top_mean"] - days["p_first_mean"], weights=pos_w)), ".1f")
1643     ↪ )
1644     ctx.number("QfourCpcScenarioMean", float(np.average(days["cpc_scenario_mean"], weights=pos_w)), ".4f")
1645     # the recommended alternative budget reading, as a full day-by-day plan
1646     if len(plan_alt):
1647         ctx.number("QfourAltRows", len(plan_alt))
1648         ctx.number("QfourAltUnits", int(plan_alt["推广单元ID"].nunique()))
1649         ctx.number("QfourAltKeywords", int(plan_alt["序号"].nunique()))
1650         ctx.number("QfourAltSpend", float(plan_alt["spend"].sum()), ".2f")
1651         ctx.number("QfourAltClicks", float(plan_alt["clicks"].sum()), ".1f")
1652         ctx.number("QfourAltRegs", float(plan_alt["regs"].sum()), ".1f")
1653     ctx.number(
1654         "QfourBudgetAltOverMainPct", 100 * (float(budgets["budget_annual_avg"].sum()) / tot["budget"] - 1), ".1f"
1655     )
1656     ref_clicks = float(ud[(ud["日期"] >= Q4_REFERENCE[0]) & (ud["日期"] <= Q4_REFERENCE[1])]["点击量"].sum())
1657     ctx.number("QfourRefClicks", ref_clicks, ".0f")
1658     ctx.number("QfourClickGainVsRefPct", 100 * (tot["clicks_mean"] / ref_clicks - 1), ".2f")
1659     return {"rows": len(plan), "units": len(per_unit), "regs_mean": float(tot["regs_mean"]), "audit_ok": audit_ok}

```

```

1658
1659
1660 # ----- results
1661 @stage(
1662     "results",
1663     deps=("classify", "allocate", "forecast"),
1664     description="Fill result2/3/4.xlsx from the organisers' templates",
1665 )
1666 def results(ctx: StageContext) -> dict[str, Any]:
1667     table = pd.read_parquet(ctx.dep("classify") / "classification.parquet").sort_values("序号")
1668     header2 = ["方案ID", "推广单元", "序号", *cls.LABELS]
1669     rows2 = [
1670         [int(r["方案ID"]), int(r["推广单元ID"]), int(r["序号"]), *[int(r["label"] == lab) for lab in cls.LABELS]]
1671         for _, r in table.iterrows()
1672     ]
1673     info2 = xlsx.write_result(ctx.templates / "result2.xlsx", ctx.out("result2.xlsx"), {"Sheet1": (header2, rows2)})
1674
1675     def plan_rows(df: pd.DataFrame, clicks: str, views: str, regs: str, position: str) -> list[list[Any]]:
1676         df = df.sort_values(["date", "方案ID", "推广单元ID", "spend"], ascending=[True, True, True, False])
1677         return [
1678             [
1679                 str(r["date"]),
1680                 int(r["方案ID"]),
1681                 int(r["推广单元ID"]),
1682                 int(r["关键词"]),
1683                 float(r["spend"]),
1684                 float(r[position]),
1685                 float(r[clicks]),
1686                 float(r[views]),
1687                 float(r[regs]),
1688             ]
1689             for _, r in df.iterrows()
1690         ]
1691
1692     allocation = pd.read_parquet(ctx.dep("allocate") / "allocation.parquet")
1693     info3 = xlsx.write_result(
1694         ctx.templates / "result3.xlsx",
1695         ctx.out("result3.xlsx"),
1696         {"Sheet1": (RESULT_HEADER, plan_rows(allocation, "clicks", "views", "regs", "position"))},
1697     )
1698     plan = pd.read_parquet(ctx.dep("forecast") / "plan.parquet")
1699     zero_path = ctx.dep("forecast") / "plan_zero_rows.parquet"
1700     if zero_path.exists(): # zero-budget units are reported explicitly so all 12 units appear
1701         plan = pd.concat([plan, pd.read_parquet(zero_path)], ignore_index=True)
1702     info4 = xlsx.write_result(
1703         ctx.templates / "result4.xlsx",
1704         ctx.out("result4.xlsx"),
1705         {"Sheet1": (RESULT_HEADER, plan_rows(plan, "clicks_mean", "views_mean", "regs_mean", "position_mean"))},
1706     )
1707     summary = {"result2": info2["sheets"], "result3": info3["sheets"], "result4": info4["sheets"]}
1708     ctx.write_json("results_summary.json", summary)
1709     return {k: v["Sheet1"]["rows"] for k, v in summary.items()}
1710
1711
1712 @stage(
1713     "figures", deps=("eda", "classify", "allocate", "forecast"), description="Paper figures (vector PDF + PNG preview)"
1714 )
1715 def figures(ctx: StageContext) -> dict[str, Any]:
1716     from pipelines.e.figures import build_figures
1717
1718     return build_figures(ctx)
1719
1720

```

```

1721 @stage("tables", deps=("eda", "classify", "allocate", "forecast"), description="Paper tables (booktabs .tex + CSV)")
1722 def tables(ctx: StageContext) -> dict[str, Any]:
1723     from pipelines.e.tables import build_tables
1724
1725     return build_tables(ctx)

```

pipelines/e/tables.py

```

1 """Paper tables for Problem E: booktabs LaTeX fragments (tabular only) plus identical CSV files."""
2
3 from __future__ import annotations
4
5 import json
6 from collections.abc import Sequence
7 from typing import Any
8
9 import numpy as np
10 import pandas as pd
11
12 from forge.context import StageContext
13 from forge.tex import tex_escape
14 from pipelines.e.classify import LABELS
15
16
17 def _fmt(value: Any, spec: str) -> str:
18     if value is None or (isinstance(value, float) and not np.isfinite(value)):
19         return "--"
20     if spec == "raw": # already valid LaTeX (math, \%); inserted verbatim
21         return str(value)
22     if spec == "s":
23         return tex_escape(str(value))
24     if spec == "d":
25         return f"{round(float(value)):,}"
26     return format(float(value), spec)
27
28
29 def write_table(
30     ctx: StageContext, name: str, df: pd.DataFrame, columns: Sequence[tuple[str, str, str]], align: str | None = None
31 ) -> str:
32     """``columns`` = (dataframe column, header, format spec). Writes tables/<name>.tex and tables/<name>.csv."""
33     keys = [c for c, _, _ in columns]
34     headers = [h for _, h, _ in columns]
35     specs = [s for _, _, s in columns]
36     if align is None:
37         align = "".join("l" if s == "s" else "r" for s in specs)
38     lines = [f"\\begin{{tabular}}{{@{{}}}{align}@{{}}}}", "\\toprule", " & ".join(headers) + " \\\\", "\\midrule"]
39     for _, row in df.iterrows():
40         lines.append(" & ".join(_fmt(row[k], s) for k, s in zip(keys, specs)) + " \\\\")
41     lines += ["\\bottomrule", "\\end{tabular}"]
42     text = "\n".join(lines) + "\n"
43     ctx.out("tables", f"{name}.tex").write_text(text, encoding="utf-8")
44     df[keys].to_csv(ctx.out("tables", f"{name}.csv"), index=False)
45     return text
46
47
48 def build_tables(ctx: StageContext) -> dict[str, Any]:
49     eda_dir, cls_dir, alloc_dir, fc_dir = ctx.dep("eda"), ctx.dep("classify"), ctx.dep("allocate"), ctx.dep("forecast")
50     names: list[str] = []
51
52     kpis = pd.read_parquet(eda_dir / "unit_kpis.parquet").sort_values("spend", ascending=False)
53     kpis["spend_share_pct"] = 100 * kpis["spend_share"]

```

```

54 kpis["ctr_pct"] = 100 * kpis["ctr"]
55 kpis["top_pct"] = 100 * kpis["top_share"]
56 kpis["first_pct"] = 100 * kpis["first_share"]
57 write_table(
58     ctx,
59     "tab_unit_kpis",
60     kpis,
61     [
62         ("方案ID", "方案ID", "s"),
63         ("推广单元ID", "推广单元ID", "s"),
64         ("days", "投放天数", "d"),
65         ("spend", "消费额/元", ".0f"),
66         ("spend_share_pct", "占比/\\%", ".1f"),
67         ("imp", "展现量", "d"),
68         ("clicks", "点击量", "d"),
69         ("ctr_pct", "CTR/\\%", ".2f"),
70         ("cpc", "CPC/元", ".2f"),
71         ("top_pct", "上方位/\\%", ".1f"),
72         ("first_pct", "首位/\\%", ".1f"),
73     ],
74 )
75 names.append("tab_unit_kpis")
76
77 coefs = pd.read_parquet(eda_dir / "calendar_regression.parquet")
78 term_names = {
79     "holiday": "法定节假日",
80     "adjusted_workday": "调休上班日",
81     "pre_holiday": "假前一日",
82     "post_holiday": "假后一日",
83     "wd_周一": "周一",
84     "wd_周二": "周二",
85     "wd_周四": "周四",
86     "wd_周五": "周五",
87     "wd_周六": "周六",
88     "wd_周日": "周日",
89 }
90 rows = []
91 for term, tname in term_names.items():
92     row: dict[str, Any] = {"term": tname}
93     for target, key in (("regs", "reg"), ("spend", "spend"), ("clicks", "clicks")):
94         r = coefs[(coefs["target"] == target) & (coefs["term"] == term)].iloc[0]
95         row[f"{key}_eff"] = r["effect_pct"]
96         row[f"{key}_ci"] = f"{r['effect_pct_low']:.1f}, {r['effect_pct_high']:.1f}"
97         row[f"{key}_p"] = r["p"]
98     rows.append(row)
99 write_table(
100     ctx,
101     "tab_calendar_effects",
102     pd.DataFrame(rows),
103     [
104         ("term", "因素", "s"),
105         ("reg_eff", "注册 效应/\\%", ".1f"),
106         ("reg_ci", "95\\% CI", "s"),
107         ("reg_p", "$p$", ".3f"),
108         ("spend_eff", "消费 效应/\\%", ".1f"),
109         ("spend_ci", "95\\% CI", "s"),
110         ("spend_p", "$p$", ".3f"),
111         ("clicks_eff", "点击 效应/\\%", ".1f"),
112         ("clicks_p", "$p$", ".3f"),
113     ],
114 )
115 names.append("tab_calendar_effects")
116

```

```

117 attribution = json.loads((eda_dir / "attribution.json").read_text(encoding="utf-8"))
118 units = pd.read_parquet(eda_dir / "unit_response.parquet")
119 att_rows = []
120 att_diag = pd.read_parquet(eda_dir / "attribution_rates.parquet")
121 for _, u in units.sort_values("推广单元ID").iterrows():
122     unit = str(int(u["推广单元ID"]))
123     spend = float(kpis.loc[kpis["推广单元ID"] == int(unit), "spend"].iloc[0])
124     attributed = attribution["attributed_regs"].get(unit, 0.0)
125     dg = att_diag[att_diag["推广单元ID"] == int(unit)]
126     raw = float(dg["rate_raw"].iloc[0]) if len(dg) else np.nan
127     boot = (
128         f"{100 * float(dg['boot_low'].iloc[0]):.2f}, {100 * float(dg['boot_high'].iloc[0]):.2f}"
129         if len(dg)
130         else ""
131     )
132     att_rows.append(
133         {
134             "unit": unit,
135             "rate": 100 * attribution["rates"][unit],
136             "source": {"unit": "单元估计", "pooled": "合并估计"}[attribution["rate_source"][unit]],
137             "raw": f"{100 * raw:.2f}" + ("${\\dagger}$" if len(dg) and bool(dg["at_zero_bound"].iloc[0]) else ""),
138             "boot": boot,
139             "attributed": attributed,
140             "cost_per_reg": spend / attributed if attributed > 0 else np.nan,
141             "ndays": int(u["active_days"]),
142             "gamma_hat": u["gamma_hat"],
143             "gamma_se": u["gamma_se"],
144             "r2": u["r2"],
145             "gamma": u["gamma"],
146             "gsrc": {"unit": "单元", "pooled": "合并"}[u["gamma_source"]],
147         }
148     )
149 write_table(
150     ctx,
151     "tab_attribution_response",
152     pd.DataFrame(att_rows),
153     [
154         ("unit", "推广单元ID", "s"),
155         ("rate", "采用注册率/(人/百次点击)", ".3f"),
156         ("source", "来源", "s"),
157         ("raw", "原始 NNLS", "raw"),
158         ("boot", "自助 95%% 区间", "s"),
159         ("attributed", "归因注册/人", ".0f"),
160         ("cost_per_reg", "注册成本/元", ".1f"),
161         ("ndays", "活跃天数 $n_u$", "d"),
162         ("gamma_hat", "$\\hat{\\gamma}_u$", ".3f"),
163         ("gamma_se", "SE", ".3f"),
164         ("r2", "$R^2$", ".2f"),
165         ("gamma", "采用 $\\gamma_u$", ".3f"),
166         ("gsrc", "$\\gamma$ 来源", "s"),
167     ],
168 )
169 names.append("tab_attribution_response")
170
171 by_label = pd.read_parquet(cls_dir / "classification_by_label.parquet")
172 table = pd.read_parquet(cls_dir / "classification.parquet")
173 by_label["spend_share_pct"] = 100 * by_label["spend_share"]
174 by_label["share_n"] = 100 * by_label["n"] / by_label["n"].sum()
175 by_label["mean_benefit"] = by_label["label"].map(table.groupby("label")["benefit"].mean())
176 by_label["median_spend"] = by_label["label"].map(table.groupby("label")["spend"].median())
177 write_table(
178     ctx,
179     "tab_class_summary",

```

```

180     by_label,
181     [
182         ("label", "类别", "s"),
183         ("n", "数量", "d"),
184         ("share_n", "占比/\\%", ".1f"),
185         ("spend", "消费额/元", ".0f"),
186         ("spend_share_pct", "消费占比/\\%", ".1f"),
187         ("median_spend", "消费中位数/元", ".1f"),
188         ("clicks", "点击量", "d"),
189         ("cpc", "CPC/元", ".2f"),
190         ("mean_benefit", "平均效益指数", ".3f"),
191         ("reg_attr", "归因注册/人", ".0f"),
192     ],
193 )
194 names.append("tab_class_summary")
195
196 summary = json.loads((cls_dir / "classification_summary.json").read_text(encoding="utf-8"))
197 rob_rows = []
198 method_names = {
199     "jenks": "自然断点（主）",
200     "median": "中位数",
201     "gmm": "高斯混合",
202     "equal_weights": "等权效益 + 自然断点",
203 }
204 for method, counts in summary["counts"].items():
205     thr = summary["thresholds"].get(method, {})
206     rob_rows.append(
207         {
208             "method": method_names.get(method, method),
209             "cost_thr": thr.get("cost_yuan", np.nan),
210             "ben_thr": thr.get("benefit", np.nan),
211             **{lab: counts.get(lab, 0) for lab in LABELS},
212         }
213     )
214 axis = json.loads((cls_dir / "axis_diagnostics.json").read_text(encoding="utf-8"))
215 rob_rows.append(
216     {
217         "method": f"效率效益轴（每元归因注册）；与主口径一致率 {100 * axis['efficiency_agreement']:.1f}\\%",
218         "cost_thr": summary["thresholds"][summary["main"]]["cost_yuan"],
219         "ben_thr": axis["efficiency_threshold"],
220         **{lab: axis["efficiency_counts"].get(lab, 0) for lab in LABELS},
221     }
222 )
223 var = json.loads((cls_dir / "engagement_variant.json").read_text(encoding="utf-8"))
224 rob_rows.append(
225     {
226         "method": f"注意力分量取总停留时间；与主口径一致率 {100 * var['agreement']:.1f}\\%",
227         "cost_thr": summary["thresholds"][summary["main"]]["cost_yuan"],
228         "ben_thr": np.nan,
229         **{lab: var["counts"].get(lab, 0) for lab in LABELS},
230     }
231 )
232 write_table(
233     ctx,
234     "tab_class_robustness",
235     pd.DataFrame(rob_rows),
236     [
237         ("method", "阈值方法 / 口径", "raw"),
238         ("cost_thr", "成本阈值/元", ".2f"),
239         ("ben_thr", "效益阈值", ".3f"),
240         *[(lab, lab, "d") for lab in LABELS],
241     ],
242 )

```

```

243 names.append("tab_class_robustness")
244
245 per_unit = (
246     table.groupby(["推广单元ID", "label"])
247     .size()
248     .unstack(fill_value=0)
249     .reindex(columns=LABELS, fill_value=0)
250     .reset_index()
251 )
252 per_unit["total"] = per_unit[list(LABELS)].sum(axis=1)
253 per_unit["推广单元ID"] = per_unit["推广单元ID"].astype(str)
254 write_table(
255     ctx,
256     "tab_class_per_unit",
257     per_unit,
258     [{"推广单元ID", "推广单元ID", "s"}, *[lab, lab, "d") for lab in LABELS], ("total", "合计", "d")],
259 )
260 names.append("tab_class_per_unit")
261
262 asum = pd.read_parquet(alloc_dir / "allocation_summary.parquet")
263 calib = json.loads((alloc_dir / "calibration_check.json").read_text(encoding="utf-8"))
264 audit = json.loads((alloc_dir / "allocation_audit.json").read_text(encoding="utf-8"))
265 boot = pd.read_parquet(alloc_dir / "bootstrap.parquet")
266 q3_rows = []
267 for window, wname in (("feb", "2025-02-01 至 02-08"), ("aug", "2025-08-01 至 08-08")):
268     w = asum[asum["window"] == window]
269     for unit, g in w.groupby("推广单元ID"):
270         q3_rows.append(
271             {
272                 "window": wname,
273                 "unit": str(int(unit)),
274                 "days": len(g),
275                 "budget": g["budget"].sum(),
276                 "eligible": int(g["eligible"].iloc[0]),
277                 "selected": g["selected"].mean(),
278                 "opt_regs": g["opt_regs"].sum(),
279                 "prop_regs": g["prop_regs"].sum(),
280                 "gain": 100 * (g["opt_regs"].sum() / g["prop_regs"].sum() - 1),
281                 "opt_cpc": g["budget"].sum() / g["opt_clicks"].sum(),
282                 "prop_cpc": g["budget"].sum() / g["prop_clicks"].sum(),
283             }
284         )
285     b = boot[boot["window"] == window]["ratio"]
286     q3_rows.append(
287         {
288             "window": wname,
289             "unit": "合计",
290             "days": len(w),
291             "budget": w["budget"].sum(),
292             "eligible": int(w.groupby("推广单元ID")["eligible"].first().sum()),
293             "selected": w["selected"].mean(),
294             "opt_regs": w["opt_regs"].sum(),
295             "prop_regs": w["prop_regs"].sum(),
296             "gain": 100 * (w["opt_regs"].sum() / w["prop_regs"].sum() - 1),
297             "opt_cpc": w["budget"].sum() / w["opt_clicks"].sum(),
298             "prop_cpc": w["budget"].sum() / w["prop_clicks"].sum(),
299             "ci": f"[{100 * (b.quantile(0.025) - 1):.1f}, {100 * (b.quantile(0.975) - 1):.1f}]",
300         }
301     )
302 q3 = pd.DataFrame(q3_rows)
303 q3["ci"] = q3["ci"].fillna("")
304 write_table(
305     ctx,

```

```

306     "tab_q3_summary",
307     q3,
308     [
309         ("window", "窗口", "s"),
310         ("unit", "推广单元", "s"),
311         ("days", "单元--日数", "d"),
312         ("budget", "预算/元", ".0f"),
313         ("eligible", "候选词", "d"),
314         ("selected", "平均入选词", ".1f"),
315         ("prop_regs", "历史比例注册/人", ".1f"),
316         ("opt_regs", "最优注册/人", ".1f"),
317         ("gain", "提升/\\%", ".1f"),
318         ("ci", "95\\% 自助区间", "s"),
319         ("prop_cpc", "历史 CPC/元", ".2f"),
320         ("opt_cpc", "最优 CPC/元", ".2f"),
321     ],
322 )
323 names.append("tab_q3_summary")
324
325 daily_rows = (
326     asum.groupby(["window", "date"])
327     .agg(
328         budget=("budget", "sum"),
329         units=("推广单元ID", "nunique"),
330         opt_clicks=("opt_clicks", "sum"),
331         prop_clicks=("prop_clicks", "sum"),
332         actual_clicks=("actual_clicks", "sum"),
333         opt_regs=("opt_regs", "sum"),
334         prop_regs=("prop_regs", "sum"),
335         equal_regs=("equal_regs", "sum"),
336     )
337     .reset_index()
338 )
339 daily_rows["gain"] = 100 * (daily_rows["opt_regs"] / daily_rows["prop_regs"] - 1)
340 write_table(
341     ctx,
342     "tab_q3_daily",
343     daily_rows,
344     [
345         ("date", "日期", "s"),
346         ("units", "单元数", "d"),
347         ("budget", "预算/元", ".1f"),
348         ("actual_clicks", "实际点击", "d"),
349         ("prop_clicks", "历史比例点击", ".1f"),
350         ("opt_clicks", "最优点击", ".1f"),
351         ("prop_regs", "历史比例注册", ".1f"),
352         ("equal_regs", "均匀注册", ".1f"),
353         ("opt_regs", "最优注册", ".1f"),
354         ("gain", "提升/\\%", ".1f"),
355     ],
356 )
357 names.append("tab_q3_daily")
358
359 alt = pd.read_parquet(alloc_dir / "window_budget_alternative.parquet")
360 alt_rows = []
361 for window, wname in (("feb", "2 月窗口"), ("aug", "8 月窗口")):
362     a = alt[alt["window"] == window]
363     opt = asum[asum["window"] == window]["opt_regs"].sum()
364     alt_rows.append(
365         {
366             "window": wname,
367             "regs_daily": opt,
368             "regs_window": a["regs_window"].sum(),

```

```

369         "gain": 100 * (a["regs_window"].sum() / opt - 1),
370         "moved": 100 * (a["window_budget_day"] - a["daily_budget"]).abs().sum() / 2 / a["daily_budget"].sum(),
371     }
372 )
373 write_table(
374     ctx,
375     "tab_q3_window_budget",
376     pd.DataFrame(alt_rows),
377     [
378         ("window", "窗口", "s"),
379         ("regs_daily", "逐日预算最优注册/人", ".1f"),
380         ("regs_window", "窗口预算最优注册/人", ".1f"),
381         ("gain", "额外提升/\%", ".1f"),
382         ("moved", "跨日调动预算比例/\%", ".1f"),
383     ],
384 )
385 names.append("tab_q3_window_budget")
386
387 sens = (
388     pd.read_parquet(alloc_dir / "sensitivity.parquet")
389     if (alloc_dir / "sensitivity.parquet").exists()
390     else pd.DataFrame()
391 )
392 if len(sens):
393     sens = sens.copy()
394     sens["relax"] = np.where(sens.get("relaxation", False), "是", "")
395     write_table(
396         ctx,
397         "tab_q3_sensitivity",
398         sens,
399         [
400             ("scenario", "情形", "s"),
401             ("window", "窗口", "s"),
402             ("opt_regs", "最优注册/人", ".1f"),
403             ("prop_regs", "历史比例注册/人", ".1f"),
404             ("gain", "提升/\%", ".1f"),
405             ("selected", "平均入选词", ".1f"),
406             ("relax", "名义松弛", "s"),
407         ],
408     )
409     names.append("tab_q3_sensitivity")
410
411 def cvx_check(a: dict[str, Any]) -> dict[str, Any]:
412     return next((c for c in a["checks"] if c["name"] == "within_convex_relaxation_bound"), {})
413
414 tiny = sum(1 for a in audit["audits"] if cvx_check(a).get("tiny_budget"))
415 informative = [
416     float(cvx_check(a)["relative_gap"])
417     for a in audit["audits"]
418     if cvx_check(a) and not cvx_check(a).get("tiny_budget")
419 ]
420 ver_rows = [
421     {"item": "Q3 单元-日分配问题数", "value": f"{audit['groups']}"},
422     {
423         "item": "Q3 独立校验 (可行性 / KKT / 配对转移与插入 / 通用凸求解器上界)",
424         "value": "全部通过" if audit["ok"] else "存在失败",
425     },
426     {
427         "item": "Q3 凸松弛总体最优性界  $(\sum \text{上界} - \sum \text{目标值}) / \sum \text{目标值}$ ",
428         "value": f"{100 * audit['aggregate_gap']:.3f}\%",
429     },
430     {
431         "item": f"Q3 单个问题的最大相对差 (不含 {tiny} 个预算低于 20 倍最小投放额的微小问题)",

```

```

432         "value": f"{100 * max(informative):.3f}\\%" if informative else "--",
433     },
434     {
435         "item": "Q3 微小问题的最大相对差（松弛界在此处不具信息量，见正文）",
436         "value": f"{100 * audit['max_cvx_gap']:.1f}\\%",
437     },
438     {
439         "item": "响应模型校准：历史比例分配预测点击 vs 实际（MAPE / 中位 APE）",
440         "value": f"{100 * calib['mape']:.1f}\\% / {100 * calib['median_ape']:.1f}\\%",
441     },
442 ]
443 mono = json.loads((alloc_dir / "sensitivity_monotonicity.json").read_text(encoding="utf-8"))
444 ver_rows.append(
445     {
446         "item": f"Q3 灵敏度单调性（{len(mono['cases'])} 个名义松弛情形的最优值不得低于基准）",
447         "value": "通过" if mono["ok"] else "失败",
448     }
449 )
450 feas = json.loads((alloc_dir / "baseline_feasibility.json").read_text(encoding="utf-8"))
451 ver_rows.append(
452     {
453         "item": "Q3 相对历史比例基线的逐问题占优（含最小投放额时无先验保证，故逐一核对）",
454         "value": f"{feas['unit_days_with_opt_at_least_prop']/feas['unit_days']}, 最小比值 "
455         f"{feas['min_opt_over_prop_ratio']:.4f}",
456     }
457 )
458 ver_rows.append(
459     {
460         "item": "Q3 单元-日水平偏差重标定不变性（按  $\lambda_{u,t} = \text{实际} / \text{基线点击重标定 } c_{i,t}$  后的提升）",
461         "value": " / ".join(
462             f"{r['window']}: {r['gain_pct']:.2f}\\%  $\rightarrow$  {r['gain_pct_rescaled']:.2f}\\%"
463             for r in calib["rescaling_invariance"]
464         ),
465     }
466 )
467 dup = json.loads((alloc_dir / "duplication_exposure.json").read_text(encoding="utf-8"))
468 ver_rows.append(
469     {
470         "item": "Q3 跨单元重复投放暴露（预期注册 / 投放金额占比，蚕食高估的上界）",
471         "value": f"{100 * dup['regs_share']:.2f}\\% / {100 * dup['spend_share']:.2f}\\%",
472     }
473 )
474 q4_audit = json.loads((fc_dir / "allocation_audit.json").read_text(encoding="utf-8"))
475 ver_rows.append({"item": "Q4 分配问题数（跨日 + 单元-日）", "value": f"{q4_audit['groups']}"})
476 ver_rows.append({"item": "Q4 独立校验", "value": "全部通过" if q4_audit["ok"] else "存在失败"})
477 joint = pd.read_parquet(fc_dir / "joint_relaxation.parquet")
478 ver_rows.append(
479     {
480         "item": "Q4 两层分解的联合最优性界（7 日  $\times$  关键词的可分离凹松弛，去下界、上限取最宽）",
481         "value": f"{100 * (joint['joint_bound'].sum() / joint['two_level'].sum() - 1):.3f}\\%"
482         f"（单个单元最大 {joint['gap_pct'].max():.1f}\\%，出现在预期注册仅 "
483         f"{joint.loc[joint['gap_pct'].idxmax(), 'two_level']:.1f} 人的最小单元）",
484     }
485 )
486 bt_all = pd.read_parquet(fc_dir / "backtest_summary.parquet")
487 wide = bt_all[bt_all["model"] == "calendar_wide"]
488 narrow = bt_all[bt_all["model"] == "calendar"]
489 ver_rows.append(
490     {
491         "item": "Q4 区间回溯覆盖率（部署区间 / 仅残差区间，名义 80\\%）",
492         "value": f"{100 * wide['coverage80'].min():.1f}--{100 * wide['coverage80'].max():.1f}\\% / "
493         f"{100 * narrow['coverage80'].min():.1f}--{100 * narrow['coverage80'].max():.1f}\\%",
494     }
495 )

```

```

495 )
496 cls_check = json.loads((cls_dir / "classification_check.json").read_text(encoding="utf-8"))
497 ver_rows.append(
498     {"item": "Q2 分类独立复核 (规则重推 / 无效词定义 / 计数)", "value": "通过" if cls_check["ok"] else "失败"},
499 )
500 write_table(
501     ctx,
502     "tab_verification",
503     pd.DataFrame(ver_rows),
504     [{"item", "检验项", "raw"}, ("value", "结果", "raw")],
505     align="p{0.72\\linewidth}l",
506 )
507 names.append("tab_verification")
508
509 bt = pd.read_parquet(fc_dir / "backtest_summary.parquet")
510 tnames = {
511     "log_eff": "效率乘子  $\\log \\var{\\epsilon}$ ",
512     "log_cpc": " $\\log$  CPC",
513     "logit_ctr": "logit CTR",
514     "logit_top": "logit 上方位占比",
515     "logit_first": "logit 首位占比",
516     "log_clicks": " $\\log$  点击量",
517 }
518 mnames = {
519     "calendar": "日历回归 (残差区间)",
520     "calendar_wide": "日历回归 (部署区间)",
521     "seasonal_naive": "季节朴素",
522     "mean28": "28 日均值",
523 }
524 bt["target_name"] = bt["target"].map(tnames)
525 bt["model_name"] = bt["model"].map(mnames)
526 bt["cov_pct"] = 100 * bt["coverage80"]
527 bt["pinball"] = bt["pinball10"] + bt["pinball90"]
528 bt = bt.sort_values(["target", "model"])
529 write_table(
530     ctx,
531     "tab_backtest",
532     bt,
533     [
534         ("target_name", "目标", "raw"),
535         ("model_name", "模型", "s"),
536         ("mae", "MAE", ".4f"),
537         ("rmse", "RMSE", ".4f"),
538         ("pinball", "Pinball(0.1+0.9)", ".3f"),
539         ("cov_pct", "80\\% 覆盖率/\\%", ".1f"),
540     ],
541 )
542 names.append("tab_backtest")
543
544 days = pd.read_parquet(fc_dir / "plan_by_unit_day.parquet")
545 d = (
546     days.groupby("date")
547     .agg(
548         units=("推广单元ID", "nunique"),
549         spend=("spend", "sum"),
550         clicks=("clicks_mean", "sum"),
551         clicks_lo=("clicks_q10", "sum"),
552         clicks_hi=("clicks_q90", "sum"),
553         imp=("imp_mean", "sum"),
554         imp_lo=("imp_q10", "sum"),
555         imp_hi=("imp_q90", "sum"),
556         views=("views_mean", "sum"),
557         views_lo=("views_q10", "sum"),

```

```

558         views_hi=("views_q90", "sum"),
559         regs=("regs_mean", "sum"),
560         regs_lo=("regs_q10", "sum"),
561         regs_hi=("regs_q90", "sum"),
562     )
563     .reset_index()
564 )
565 d["cpc"] = d["spend"] / d["clicks"]
566 d["cpc_range"] = [f"[{s / hi:.2f}, {s / lo:.2f})" for s, hi, lo in zip(d["spend"], d["clicks_hi"], d["clicks_lo"])]
567 d["clicks_range"] = [f"[{lo:.0f}, {hi:.0f})" for lo, hi in zip(d["clicks_lo"], d["clicks_hi"])]
568 d["imp_k"] = d["imp"] / 1e3
569 d["views_k"] = d["views"] / 1e3
570 d["imp_range"] = [f"[{lo / 1e3:.1f}, {hi / 1e3:.1f})" for lo, hi in zip(d["imp_lo"], d["imp_hi"])]
571 d["views_range"] = [f"[{lo / 1e3:.1f}, {hi / 1e3:.1f})" for lo, hi in zip(d["views_lo"], d["views_hi"])]
572 d["regs_range"] = [f"[{lo:.0f}, {hi:.0f})" for lo, hi in zip(d["regs_lo"], d["regs_hi"])]
573
574 def _pos(col: str) -> list[float]:
575     return [float(np.average(g[col], weights=np.maximum(g["clicks_mean"], 1e-9))) for _, g in days.groupby("date")]
576
577 d["position"] = _pos("position_mean")
578 d["position_range"] = [f"[{lo:.2f}, {hi:.2f})" for lo, hi in zip(_pos("position_q10"), _pos("position_q90"))]
579 write_table(
580     ctx,
581     "tab_q4_daily",
582     d,
583     [
584         ("date", "日期", "s"),
585         ("units", "单元数", "d"),
586         ("spend", "投入/元", ".1f"),
587         ("cpc", "CPC/元", ".2f"),
588         ("cpc_range", "CPC 范围", "s"),
589         ("imp_k", "展现量/千次", ".1f"),
590         ("imp_range", "展现范围/千次", "s"),
591         ("position", "展位", ".2f"),
592         ("position_range", "展位范围", "s"),
593         ("clicks", "点击量", "d"),
594         ("clicks_range", "点击范围", "s"),
595         ("views_k", "浏览量/千次", ".1f"),
596         ("views_range", "浏览范围/千次", "s"),
597         ("regs", "注册量", ".0f"),
598         ("regs_range", "注册范围", "s"),
599     ],
600 )
601 names.append("tab_q4_daily")
602
603 per = pd.DataFrame(json.loads((fc_dir / "plan_by_unit.json").read_text(encoding="utf-8")))
604
605 # Six quantities Problem 4 asks a range for: bid (CPC proxy), impressions, position, clicks, views, regs.
606 # Aggregated exactly as the registered \val macros are: per-unit scenario quantiles summed over units
607 # (comonotone across units, scenario-aligned across the 7 days inside a unit); CPC and the position index
608 # are not additive and are click-weighted instead.
609 plan_kw = pd.read_parquet(fc_dir / "plan.parquet")
610
611 def _unit_tot(k: str) -> tuple[float, float, float]:
612     return tuple(float(per[f"{k}_{q}"].sum()) for q in ("mean", "q10", "q90")) # type: ignore[return-value]
613
614 clicks_tot = _unit_tot("clicks")
615 spend_tot = float(per["spend"].sum())
616 w_day = np.maximum(days["clicks_mean"], 1e-9)
617 agg = {
618     "cpc": tuple(spend_tot / v for v in (clicks_tot[0], clicks_tot[2], clicks_tot[1])),
619     "imp": _unit_tot("imp"),
620     "position": tuple(

```

```

621         float(np.average(days[c], weights=w_day)) for c in ("position_mean", "position_q10", "position_q90")
622     ),
623     "clicks": clicks_tot,
624     "views": _unit_tot("views"),
625     "regs": _unit_tot("regs"),
626     "p_top": tuple(float(np.average(days["p_top_mean"], weights=w_day)) for _ in range(3)),
627     "p_first": tuple(float(np.average(days["p_first_mean"], weights=w_day)) for _ in range(3)),
628 }
629 rng_rows = []
630 for key, name, unit, agg_kind, prec in (
631     ("cpc", "竞价 (平均点击成本 CPC)", "元/次", "点击加权", 4),
632     ("imp", "展现量", "次", "合计", 1),
633     ("position", "展现位 (排位指数  $\pi$ )", "--", "点击加权", 4),
634     ("p_top", "其中: 上方位展现占比", "--", "点击加权", 4),
635     ("p_first", "其中: 首位展现占比", "--", "点击加权", 4),
636     ("clicks", "点击量", "次", "合计", 1),
637     ("views", "浏览量", "次", "合计", 1),
638     ("regs", "注册量", "人", "合计", 1),
639 ):
640     mean, lo, hi = (float(v) for v in agg[key])
641     if key in plan_kw.columns or f"{key}_mean" in plan_kw.columns:
642         kw = plan_kw[[f"{key}_mean", f"{key}_q10", f"{key}_q90"]].to_numpy(dtype=float)
643         kw_mean, kw_range = (
644             f"{float(np.median(kw[:, 0])):.4g}",
645             (f"[{np.median(kw[:, 1]):.4g}, {np.median(kw[:, 2]):.4g}]",
646              )
647         )
648     else:
649         kw_mean, kw_range = "--", "---"
650     rng_rows.append(
651         {
652             "quantity": name,
653             "unit": unit,
654             "kind": agg_kind,
655             "mean": f"{mean:.{prec}f}",
656             "range": f"[{lo:.{prec}f}, {hi:.{prec}f}]" if key not in ("p_top", "p_first") else "--",
657             "width": 100 * (hi - lo) / max(abs(mean), 1e-9),
658             "kw_mean": kw_mean,
659             "kw_range": kw_range,
660         }
661     )
662 write_table(
663     ctx,
664     "tab_q4_ranges",
665     pd.DataFrame(rng_rows),
666     [
667         ("quantity", "量", "raw"),
668         ("unit", "单位", "s"),
669         ("kind", "聚合", "s"),
670         ("mean", "7 日期望", "s"),
671         ("range", "10\\%--90\\% 范围", "s"),
672         ("width", "相对宽度/\\%", ".0f"),
673         ("kw_mean", "单关键词--日 期望中位数", "s"),
674         ("kw_range", "单关键词--日 区间中位数", "s"),
675     ],
676     align="llllrrrr",
677 )
678 names.append("tab_q4_ranges")
679
680 per["unit"] = per["推广单元ID"].astype(str)
681 per["regs_range"] = [f"[{lo:.0f}, {hi:.0f}]" for lo, hi in zip(per["regs_q10"], per["regs_q90"])]
682 per["clicks_range"] = [f"[{lo:.0f}, {hi:.0f}]" for lo, hi in zip(per["clicks_q10"], per["clicks_q90"])]
683 per["cpc"] = per["spent"] / per["clicks_mean"]
684 per = per.sort_values("budget", ascending=False)

```

```

684     write_table(
685         ctx,
686         "tab_q4_units",
687         per,
688         [
689             ("unit", "推广单元ID", "s"),
690             ("budget", "7 日预算/元", ".1f"),
691             ("gamma", "$\\gamma$", ".3f"),
692             ("eligible", "候选词", "d"),
693             ("cpc", "CPC/元", ".2f"),
694             ("clicks_mean", "点击量", ".0f"),
695             ("clicks_range", "点击范围", "s"),
696             ("regs_mean", "注册量", ".1f"),
697             ("regs_range", "注册范围", "s"),
698         ],
699     )
700     names.append("tab_q4_units")
701
702     ctx.write_json("tables_index.json", names)
703     return {"tables": len(names)}

```

pyproject.toml

```

1 [project]
2 name = "cumcm2026-e"
3 version = "0.1.0"
4 description = "SEM 广告投放策略 — cloud-only reproducible modelling study (CUMCM 2026 Problem E)"
5 requires-python = ">=3.11"
6 license = "Unlicense"
7
8 [tool.ruff]
9 line-length = 120
10 target-version = "py311"
11 extend-exclude = ["artifacts", "releases", "manuscript"]
12
13 [tool.ruff.lint]
14 select = ["E", "F", "W", "I", "B", "UP", "NPY", "RUF", "S102"]
15 ignore = ["RUF001", "RUF002", "RUF003", "E741", "B905"]
16
17 [tool.ruff.lint.pycodestyle]
18 # E501 is measured in display width (CJK characters count double); Chinese paper strings need headroom
19 max-line-length = 150
20
21 [tool.ruff.lint.per-file-ignores]
22 "tests/**" = ["S101", "B011"]
23
24 [tool.mypy]
25 python_version = "3.11"
26 ignore_missing_imports = true
27 check_untyped_defs = true
28 warn_unused_ignores = false
29 no_implicit_optional = true
30 exclude = "(artifacts|releases|manuscript)/"
31
32 [tool.pytest.ini_options]
33 testpaths = ["tests"]
34 addopts = "-p no:cacheprovider -q"
35 markers = ["integration: needs the mounted repository inputs (runs in Modal)"]
36
37 [tool.coverage.run]
38 source = ["forge", "pipelines"]

```

tests/__init__.py

tests/conftest.py

```
1 """Shared test configuration: deterministic hypothesis profile, no on-disk example database."""
2
3 from __future__ import annotations
4
5 import os
6 from pathlib import Path
7
8 import pytest
9 from hypothesis import HealthCheck, settings
10
11 settings.register_profile(
12     "forge", database=None, deadline=None, max_examples=60, suppress_health_check=[HealthCheck.too_slow]
13 )
14 settings.load_profile("forge")
15
16 REPO = Path(os.environ.get("FORGE_REPO", Path(__file__).resolve().parents[1]))
17
18
19 @pytest.fixture(scope="session")
20 def repo() -> Path:
21     return REPO
22
23
24 @pytest.fixture
25 def tmp_repo(tmp_path: Path) -> Path:
26     """A minimal repository layout (configs only) for runtime tests that must not touch real data."""
27     (tmp_path / "configs").mkdir()
28     (tmp_path / "configs" / "default.toml").write_text("[run]\nseed = 7\n[paper]\nnsources = []\n", encoding="utf-8")
29     (tmp_path / "configs" / "project.json").write_text(
30         '{"letter": "T", "package": "t", "problem_pdf": "T.pdf", "attachments_dir": "att", '
31         '"templates_dir": "att/tpl", "result_files": []}',
32         encoding="utf-8",
33     )
34     (tmp_path / "att" / "tpl").mkdir(parents=True)
35     return tmp_path
```

tests/integration/__init__.py

tests/integration/test_ingest_validate.py

```
1 """End-to-end ingest + validate against the real attachments (runs inside Modal where /repo exists)."""
2
3 from __future__ import annotations
4
5 import json
6 import os
7 from pathlib import Path
8
9 import pytest
```

```

10
11 from forge import runner
12
13 REPO = Path(os.environ.get("FORGE_REPO", "/repo"))
14 pytestmark = pytest.mark.integration
15
16
17 @pytest.mark.skipif(not (REPO / "configs" / "project.json").exists(), reason="repository inputs not mounted")
18 def test_ingest_then_validate_on_real_inputs(tmp_path: Path) -> None:
19     vol = tmp_path / "vol"
20     ingest = runner.execute("ingest", "itest", {"code_ref": {"git_sha": "test"}}, False, REPO, vol)
21     assert ingest["status"] == "completed" and ingest["metrics"]["files"] >= 1
22     inventory = json.loads((vol / "runs" / "itest" / "ingest" / "inventory.json").read_text(encoding="utf-8"))
23     assert any(not f["template"] for f in inventory["files"])
24     validate = runner.execute("validate", "itest", {}, False, REPO, vol)
25     assert validate["status"] == "completed" and validate["metrics"]["ok"]

```

tests/unit/__init__.py

tests/unit/test_config.py

```

1 from __future__ import annotations
2
3 from pathlib import Path
4
5 import pytest
6
7 from forge.config import Config, deep_merge, load_config
8
9
10 def test_deep_merge_is_recursive_and_non_destructive() -> None:
11     base = {"a": {"x": 1, "y": 2}, "b": 1}
12     merged = deep_merge(base, {"a": {"y": 3}, "c": 4})
13     assert merged == {"a": {"x": 1, "y": 3}, "b": 1, "c": 4}
14     assert base == {"a": {"x": 1, "y": 2}, "b": 1}
15
16
17 def test_config_dotted_access_and_digest() -> None:
18     cfg = Config({"paper": {"sources": ["q1"], "max_body_pages": 30}})
19     assert cfg.get("paper.max_body_pages") == 30
20     assert cfg.get("paper.missing", "d") == "d"
21     assert cfg["paper.sources"] == ["q1"]
22     with pytest.raises(KeyError):
23         cfg["nope.nope"]
24     assert cfg.digest == Config({"paper": {"max_body_pages": 30, "sources": ["q1"]}}).digest
25
26
27 def test_load_config_with_profile_and_overrides(tmp_repo: Path) -> None:
28     (tmp_repo / "configs" / "fast.toml").write_text("[run]\nseed = 99\n", encoding="utf-8")
29     cfg = load_config(tmp_repo, profile="fast", overrides={"paper": {"sources": ["x"]}})
30     assert cfg.get("run.seed") == 99
31     assert cfg.get("paper.sources") == ["x"]

```

tests/unit/test_contracts.py

```
1 from __future__ import annotations
2
3 import numpy as np
4 import pandas as pd
5 from hypothesis import given
6 from hypothesis import strategies as st
7
8 from forge.contracts import Column, FrameContract, validate_frame
9
10 CONTRACT = FrameContract(
11     name="t",
12     columns=(
13         Column("t", "int", min=0, unique=True, monotonic="increasing", step=60),
14         Column("v", "float", min=0, max=1),
15     ),
16     min_rows=2,
17 )
18
19
20 def test_valid_frame_passes() -> None:
21     df = pd.DataFrame({"t": [0, 60, 120], "v": [0.1, 0.2, 0.3]})
22     report = validate_frame(df, CONTRACT)
23     assert report["ok"], report["errors"]
24
25
26 def test_violations_are_reported_precisely() -> None:
27     df = pd.DataFrame({"t": [0, 60, 60], "v": [0.1, 1.5, np.nan], "extra": [1, 2, 3]})
28     report = validate_frame(df, CONTRACT)
29     joined = " | ".join(report["errors"])
30     assert not report["ok"]
31     assert "unexpected columns" in joined
32     assert "duplicated" in joined
33     assert "max 1.5 > 1" in joined
34     assert "null" in joined
35     assert "not increasing" in joined
36
37
38 def test_column_names_are_stripped() -> None:
39     df = pd.DataFrame({"t ": [0, 60], " v": [0.5, 0.6]})
40     assert validate_frame(df, CONTRACT)["ok"]
41
42
43 @given(st.lists(st.floats(min_value=0, max_value=1, allow_nan=False), min_size=2, max_size=40))
44 def test_property_ranges_within_bounds_always_pass(values: list[float]) -> None:
45     df = pd.DataFrame({"t": np.arange(len(values)) * 60, "v": values})
46     assert validate_frame(df, CONTRACT)["ok"]
47
48
49 def test_regex_and_custom_checks() -> None:
50     contract = FrameContract(
51         "ids", (Column("id", "str", regex=r"[ABC]\d{3}"),), checks=(lambda df: ["custom"] if len(df) > 1 else [],)
52     )
53     assert validate_frame(pd.DataFrame({"id": ["A001"]}), contract)["ok"]
54     report = validate_frame(pd.DataFrame({"id": ["A001", "Z9"]}), contract)
55     assert any("violate" in e for e in report["errors"]) and "custom" in report["errors"]
```

tests/unit/test_e_allocate.py

```
1 from __future__ import annotations
2
3 import itertools
4
5 import numpy as np
6 import pytest
7 from hypothesis import given, settings
8 from hypothesis import strategies as st
9
10 from pipelines.e.allocate import (
11     equal_allocation,
12     objective_value,
13     proportional_allocation,
14     solve_group,
15     verify_allocation,
16     water_filling,
17 )
18 from pipelines.e.response import clicks_response, cpc_response, expected_position
19
20
21 def test_water_filling_matches_grid_search_on_small_instance() -> None:
22     a = np.array([3.0, 1.0, 2.0])
23     gamma = 0.7
24     caps = np.array([4.0, 10.0, 10.0])
25     budget = 9.0
26     x = water_filling(a, gamma, caps, budget)
27     assert abs(x.sum() - budget) < 1e-8 and (x <= caps + 1e-9).all()
28     best = -np.inf
29     grid = np.linspace(0, 9, 181)
30     for x1, x2 in itertools.product(grid, grid):
31         x3 = budget - x1 - x2
32         if x3 < 0 or x1 > caps[0] or x2 > caps[1] or x3 > caps[2]:
33             continue
34         best = max(best, objective_value(np.array([x1, x2, x3]), a, gamma))
35     assert objective_value(x, a, gamma) >= best - 1e-6
36
37
38 def test_water_filling_closed_form_without_caps() -> None:
39     a = np.array([1.0, 2.0, 4.0])
40     gamma = 0.5
41     x = water_filling(a, gamma, np.full(3, 1e9), 7.0)
42     #  $x_i$  proportional to  $a_i^{1/(1-\gamma)}$  =  $a_i^2$ 
43     expected = 7.0 * a**2 / (a**2).sum()
44     assert np.allclose(x, expected, rtol=1e-6)
45
46
47 def test_caps_bind_and_budget_not_exceeded() -> None:
48     a = np.array([10.0, 1.0])
49     x = water_filling(a, 0.8, np.array([1.0, 5.0]), 3.0)
50     assert abs(x[0] - 1.0) < 1e-9 and abs(x.sum() - 3.0) < 1e-9
51     x = water_filling(a, 0.8, np.array([1.0, 1.0]), 3.0)
52     assert np.allclose(x, [1.0, 1.0])
53
54
55 @settings(max_examples=40)
56 @given(
57     st.lists(st.floats(min_value=0.05, max_value=50.0), min_size=2, max_size=25),
58     st.floats(min_value=0.35, max_value=0.95),
59     st.floats(min_value=1.0, max_value=500.0),
60 )
61 def test_property_verifier_accepts_solver_output(weights: list[float], gamma: float, budget: float) -> None:
```

```

62     rng = np.random.default_rng(0)
63     w = np.array(weights)
64     s = np.linspace(1.0, 3.0, len(w))
65     caps = 4.0 * s
66     res = solve_group(w, s, gamma, caps, budget, min_spend=0.0)
67     a = w * s ** (-gamma)
68     sel = res["x"] > 0
69     report = verify_allocation(res["x"][sel], a[sel], gamma, caps[sel], budget, rng, n_transfers=30)
70     assert report["ok"], report["checks"]
71
72
73 def test_verifier_rejects_a_suboptimal_allocation() -> None:
74     rng = np.random.default_rng(1)
75     a = np.array([5.0, 1.0, 1.0])
76     caps = np.full(3, 100.0)
77     report = verify_allocation(np.array([1.0, 4.0, 4.0]), a, 0.6, caps, 9.0, rng)
78     assert not report["ok"]
79     names = {c["name"]: c["ok"] for c in report["checks"]}
80     assert not names["kkt_equal_marginals_interior"] or not names["no_improving_transfer_or_removal"]
81
82
83 def test_min_spend_drops_tiny_keywords_and_responds_budget() -> None:
84     w = np.array([100.0, 100.0, 0.001])
85     s = np.array([10.0, 10.0, 10.0])
86     res = solve_group(w, s, 0.8, 4 * s, 20.0, min_spend=0.5)
87     assert res["x"][2] == 0.0 and abs(res["spent"] - 20.0) < 1e-6 and res["n_selected"] == 2
88     assert (res["x"][res["x"] > 0] >= 0.5).all()
89
90
91 def test_min_spend_solution_beats_enumeration_of_selections() -> None:
92     rng = np.random.default_rng(5)
93     w = rng.uniform(0.5, 5.0, 6)
94     s = rng.uniform(0.5, 3.0, 6)
95     gamma, budget, m = 0.75, 4.0, 0.6
96     caps = 4 * s
97     res = solve_group(w, s, gamma, caps, budget, min_spend=m)
98     a = w * s ** (-gamma)
99     # brute force over selections: on a fixed subset the problem is convex; solve it with an independent
100     # general-purpose NLP solver (SLSQP) under the lower bound m
101     from scipy.optimize import minimize
102
103     best = -np.inf
104     for mask in range(1, 2**6):
105         idx = [i for i in range(6) if mask >> i & 1]
106         if m * len(idx) > budget + 1e-12:
107             continue
108         sub_a, sub_caps = a[idx], caps[idx]
109         x0 = np.clip(np.full(len(idx), budget / len(idx)), m, sub_caps)
110         res_nlp = minimize(
111             lambda y, sa=sub_a: -float(np.sum(sa * np.power(np.maximum(y, 1e-12), gamma))),
112             x0,
113             method="SLSQP",
114             bounds=[(m, c) for c in sub_caps],
115             constraints=[{"type": "ineq", "fun": lambda y: budget - y.sum()}],
116             options={"ftol": 1e-12, "maxiter": 500},
117         )
118         if res_nlp.success:
119             best = max(best, -float(res_nlp.fun))
120     assert res["objective"] >= best * (1 - 1e-6)
121     report = verify_allocation(res["x"], a, gamma, caps, budget, rng, floor=m)
122     assert report["ok"], report["checks"]
123
124

```

```

125 def test_baselines_and_response_helpers() -> None:
126     s = np.array([1.0, 3.0])
127     assert np.allclose(proportional_allocation(s, 8.0), [2.0, 6.0])
128     assert np.allclose(equal_allocation(2, 8.0), [4.0, 4.0])
129     c = np.array([10.0, 30.0])
130     assert np.allclose(clicks_response(s, c, s, 0.8), c) # passes through the operating point
131     assert cpc_response(np.array([2.0, 6.0]), c, s, 0.8)[0] > cpc_response(np.array([1.0, 3.0]), c, s, 0.8)[0]
132     pos = expected_position(np.array([1.0, 0.0, 0.5]), np.array([1.0, 0.0, 0.25]))
133     assert pos[0] == pytest.approx(1.0) and pos[1] == pytest.approx(4.0) and 1.0 < pos[2] < 4.0

```

tests/unit/test_e_calendar_data.py

```

1 from __future__ import annotations
2
3 import math
4
5 import pandas as pd
6
7 from pipelines.e.calendar import ADJUSTED_WORKDAYS, HOLIDAY_BLOCKS, day_features, holiday_map
8 from pipelines.e.data import parse_bounce, parse_duration
9
10
11 def test_holiday_calendar_matches_state_council_notice() -> None:
12     hm = holiday_map()
13     assert len(hm) == 1 + 8 + 3 + 5 + 3 + 8
14     assert hm[pd.Timestamp("2025-01-28")] == "春节" and hm[pd.Timestamp("2025-10-08")] == "国庆节中秋节"
15     assert pd.Timestamp("2025-02-08") not in hm and "2025-02-08" in ADJUSTED_WORKDAYS
16     assert all(pd.Timestamp(s) <= pd.Timestamp(e) for s, e in HOLIDAY_BLOCKS.values())
17
18
19 def test_day_features_flags() -> None:
20     f = day_features(
21         ["2025-01-27", "2025-01-28", "2025-02-04", "2025-02-05", "2025-02-08", "2025-02-09", "2026-09-11"]
22     ).set_index("date")
23     assert bool(f.loc["2025-01-27", "is_pre_holiday"]) and not bool(f.loc["2025-01-27", "is_holiday"])
24     assert bool(f.loc["2025-01-28", "is_holiday"]) and f.loc["2025-01-28", "day_type"] == "holiday"
25     assert bool(f.loc["2025-02-05", "is_post_holiday"]) and f.loc["2025-02-05", "day_type"] == "workday"
26     assert f.loc["2025-02-08", "day_type"] == "adjusted_workday" and bool(f.loc["2025-02-08", "is_workday"])
27     assert f.loc["2025-02-09", "day_type"] == "weekend"
28     assert f.loc["2026-09-11", "weekday"] == 4 and f.loc["2026-09-11", "day_type"] == "workday"
29
30
31 def test_parsers_handle_every_encoding_in_sheet3() -> None:
32     assert math.isnan(parse_bounce("/")) and parse_bounce("0.6109") == 0.6109 and parse_bounce("1") == 1.0
33     assert parse_bounce(" 45 ") == 0.45
34     assert math.isnan(parse_duration("/")) and parse_duration(" 00:03:16") == 196.0 and parse_duration("0") == 0.0
35     assert parse_duration(0) == 0.0

```

tests/unit/test_e_classify.py

```

1 from __future__ import annotations
2
3 import numpy as np
4 import pandas as pd
5 from hypothesis import given
6 from hypothesis import strategies as st
7
8 from pipelines.e.classify import (

```

```

9     LABELS,
10    assign_labels,
11    benefit_components,
12    benefit_index,
13    entropy_weights,
14    jenks_break,
15    verify_classification,
16 )
17
18
19 def _frame(n: int, rng: np.random.Generator) -> pd.DataFrame:
20     spend = np.where(rng.random(n) < 0.3, 0.0, rng.lognormal(2, 1.5, n))
21     clicks = np.where(spend > 0, rng.poisson(spend / 1.2) + 1, 0)
22     views = np.where(clicks > 0, rng.poisson(clicks * 1.5), 0)
23     bounce = np.where(clicks > 0, rng.random(n), np.nan)
24     return pd.DataFrame(
25         {
26             "序号": np.arange(1, n + 1),
27             "关键词": np.arange(1, n + 1),
28             "方案ID": 1,
29             "推广单元ID": 7,
30             "spend": spend,
31             "clicks": clicks,
32             "views": views,
33             "bounce": bounce,
34             "duration_s": np.where(clicks > 0, rng.random(n) * 300, np.nan),
35             "engagement": np.where(clicks > 0, clicks * (1 - np.nan_to_num(bounce)) * 60, 0.0),
36         }
37     )
38
39
40 def test_jenks_break_matches_brute_force() -> None:
41     rng = np.random.default_rng(1)
42     x = np.concatenate([rng.normal(0, 1, 40), rng.normal(6, 1, 30)])
43     thr = jenks_break(x)
44     xs = np.sort(x)
45     best = min(range(1, len(xs)), key=lambda k: np.var(xs[:k]) * k + np.var(xs[k:]) * (len(xs) - k))
46     assert xs[best - 1] < thr < xs[best]
47     assert 1.5 < thr < 4.5
48
49
50 def test_entropy_weights_sum_to_one_and_ignore_constant_columns() -> None:
51     rng = np.random.default_rng(2)
52     X = np.column_stack([rng.random(50), np.ones(50), rng.random(50) ** 4])
53     w = entropy_weights(X)
54     assert abs(w.sum() - 1) < 1e-12 and w[1] == 0.0 and (w >= 0).all()
55
56
57 def test_labels_follow_quadrant_rule_and_checker_agrees() -> None:
58     rng = np.random.default_rng(3)
59     kw = _frame(300, rng)
60     comp = benefit_components(kw, {7: 0.02})
61     benefit, _ = benefit_index(comp)
62     active = kw["spend"] > 0
63     ct = float(np.median(np.log10(kw.loc[active, "spend"])))
64     bt = float(np.median(benefit[active]))
65     labels = assign_labels(kw, benefit, ct, bt)
66     table = kw.assign(benefit=benefit, label=labels)
67     report = verify_classification(table, ct, bt)
68     assert report["ok"], report
69     assert set(labels.unique()) <= set(LABELS)
70     assert (labels[~active] == "无效词").all()
71     gold = table[table["label"] == "黄金词"]

```

```

72     assert (gold["spend"] <= 10**ct).all() and (gold["benefit"] >= bt).all()
73
74
75 @given(st.integers(min_value=20, max_value=200), st.integers(min_value=0, max_value=1000))
76 def test_property_every_keyword_gets_exactly_one_label(n: int, seed: int) -> None:
77     rng = np.random.default_rng(seed)
78     kw = _frame(n, rng)
79     comp = benefit_components(kw, {7: 0.01})
80     benefit, w = benefit_index(comp)
81     assert abs(w.sum() - 1) < 1e-9
82     labels = assign_labels(kw, benefit, 1.0, 0.5)
83     assert len(labels) == n and labels.isin(LABELS).all()
84     counts = labels.value_counts()
85     assert counts.sum() == n

```

tests/unit/test_e_forecast.py

```

1 from __future__ import annotations
2
3 import numpy as np
4 import pandas as pd
5
6 from pipelines.e.calendar import day_features
7 from pipelines.e.forecast import (
8     CalendarModel,
9     back_transform,
10    pinball,
11    rolling_backtest,
12    seasonal_naive,
13    simulate_group,
14    summarise,
15 )
16
17
18 def _series(n: int = 200, seed: int = 0) -> pd.DataFrame:
19     rng = np.random.default_rng(seed)
20     dates = pd.date_range("2025-03-01", periods=n, freq="D")
21     f = day_features(dates)
22     y = 0.3 * (f["weekday"] >= 5).to_numpy() - 0.5 * f["is_holiday"].to_numpy() + 0.1 * rng.standard_normal(n)
23     out = pd.DataFrame({"date": dates, "log_eff": y})
24     return pd.concat([out, f.drop(columns=["date"])], axis=1)
25
26
27 def test_calendar_model_recovers_weekend_effect() -> None:
28     s = _series()
29     m = CalendarModel().fit(s, "log_eff")
30     future = day_features(pd.date_range("2026-09-11", "2026-09-17"))
31     pred = m.predict(future)
32     weekend = future["weekday"].to_numpy() >= 5
33     assert pred[weekend].mean() - pred[~weekend].mean() > 0.2
34     assert 0.05 < m.sd < 0.2
35
36
37 def test_backtest_prefers_calendar_model_on_calendar_driven_series() -> None:
38     s = _series(260)
39     origins = list(pd.date_range("2025-08-01", "2025-10-30", freq="7D"))
40     bt = rolling_backtest(s, "log_eff", origins)
41     agg = bt.groupby("model")["mae"].mean()
42     assert agg["calendar"] < agg["mean28"]
43     assert 0.5 <= bt[bt["model"] == "calendar"]["coverage80"].mean() <= 1.0
44

```

```

45
46 def test_pinball_and_transforms() -> None:
47     y = np.array([1.0, 2.0])
48     assert pinball(y, np.array([0.0, 3.0]), 0.5) == 0.5 * (1.0 + 1.0) / 2
49     assert np.allclose(back_transform(np.log([2.0, 3.0]), "exp"), [2.0, 3.0])
50     assert np.allclose(back_transform(np.array([0.0]), "expit"), [0.5])
51     s = _series(60)
52     assert len(seasonal_naive(s, "log_eff", s.tail(7))) == 7
53
54
55 def test_simulation_shapes_and_monotone_ranges() -> None:
56     rng = np.random.default_rng(3)
57     params = pd.DataFrame({"c": [10.0, 5.0], "s": [20.0, 8.0], "rho": [0.02, 0.05], "depth": [1.5, 2.0]})
58     sim = simulate_group(
59         np.array([20.0, 8.0]),
60         params,
61         0.8,
62         0.0,
63         0.2,
64         0.2,
65         0.0,
66         0.1,
67         {"a": 0.0, "b": 0.3},
68         {"a": -1.0, "b": 0.3},
69         0.2,
70         rng,
71         n_scen=400,
72     )
73     assert sim["clicks"].shape == (400, 2)
74     st = summarise(sim["clicks"])
75     assert (st["q10"] <= st["q50"]).all() and (st["q50"] <= st["q90"]).all()
76     assert abs(st["mean"][0] / 10.0 - 1) < 0.15
77     assert ((sim["position"] >= 1.0) & (sim["position"] <= 4.0)).all()

```

tests/unit/test_e_review_fixes.py

```

1  """Regression tests for the defects the v1.0.0 review surfaced.
2
3  Each test pins a property that was violated (or unverified) before the revision:
4  relaxations must not lower the optimum, the joint relaxation must bound the two-level
5  solution, cross-unit water filling must equalise marginal returns and exhaust the budget,
6  and the holiday optimal-cut interval must bracket its own point estimate.
7  """
8
9  from __future__ import annotations
10
11  import numpy as np
12  import pytest
13
14  from pipelines.e.allocate import solve_group, water_filling
15  from pipelines.e.stages import _cross_unit_allocation, _weights
16
17
18  def _instance(n: int = 40, seed: int = 7) -> tuple[np.ndarray, np.ndarray, np.ndarray, float]:
19     rng = np.random.default_rng(seed)
20     s = np.exp(rng.normal(0.0, 1.6, n))
21     w = np.exp(rng.normal(0.0, 1.0, n)) * s
22     caps = np.maximum(4.0 * s, 0.0)
23     return w, s, caps, float(3.0 * s.sum())
24
25

```

```

26 @pytest.mark.parametrize("gamma", [0.5, 0.7, 0.9])
27 def test_dropping_the_floor_with_fixed_caps_cannot_lower_the_optimum(gamma: float) -> None:
28     """The v1.0.0 sensitivity coupled the floor to the caps, so m = 0 shrank the feasible set."""
29     w, s, caps, budget = _instance()
30     m = 0.5
31     caps_eff = np.maximum(caps, m) # the effective box of the floored problem
32     base = solve_group(w, s, gamma, caps, budget, min_spend=m)
33     relaxed = solve_group(w, s, gamma, caps_eff, budget, min_spend=0.0)
34     coupled = solve_group(w, s, gamma, caps, budget, min_spend=0.0) # the buggy comparison
35     assert relaxed["objective"] >= base["objective"] * (1 - 1e-9)
36     assert relaxed["n_selected"] >= base["n_selected"]
37     # and the coupled variant is exactly the trap: a nominally weaker problem that scores lower
38     assert coupled["objective"] <= relaxed["objective"] * (1 + 1e-9)
39
40
41 def test_joint_relaxation_bounds_the_two_level_solution() -> None:
42     """Problem 4's certificate: a 7-day x keyword relaxation with the widest box and no floor."""
43     gamma, m, n_days = 0.8, 0.5, 7
44     w, s, caps, budget = _instance(seed=11)
45     eff = np.array([1.0, 0.9, 1.2, 0.7, 1.1, 0.6, 1.3])
46     day_caps = np.full(n_days, budget)
47     X = solve_group(eff, np.ones(n_days), gamma, day_caps, budget, min_spend=m)["x"]
48     two_level = 0.0
49     for i in range(n_days):
50         if X[i] <= 0:
51             continue
52         res = solve_group(w * eff[i], s, gamma, caps, float(X[i]), min_spend=m)
53         two_level += res["objective"]
54     a_joint = np.concatenate([eff[i] * w * np.power(s, -gamma) for i in range(n_days)])
55     caps_joint = np.tile(np.maximum(caps, m), n_days)
56     x_joint = water_filling(a_joint, gamma, caps_joint, budget)
57     joint_bound = float(np.sum(a_joint * np.power(x_joint, gamma)))
58     assert joint_bound >= two_level * (1 - 1e-9)
59
60
61 def test_joint_relaxation_without_the_floor_lift_is_not_a_bound() -> None:
62     """Documents why caps must be lifted to max(cap, m): tiny caps make the bound invalid."""
63     gamma, m = 0.8, 0.5
64     s = np.array([0.02, 0.03])
65     w = np.array([1.0, 1.0]) * s
66     caps = 4.0 * s # 0.08 and 0.12, both below the floor
67     budget = 1.0
68     floored = solve_group(w, s, gamma, caps, budget, min_spend=m)
69     a = w * np.power(s, -gamma)
70     unlifted = float(np.sum(a * np.power(water_filling(a, gamma, caps, budget), gamma)))
71     assert unlifted < floored["objective"] # the unlifted relaxation is below the achieved value
72     lifted = float(np.sum(a * np.power(water_filling(a, gamma, np.maximum(caps, m), budget), gamma)))
73     assert lifted >= floored["objective"] * (1 - 1e-9)
74
75
76 def test_cross_unit_allocation_equalises_marginals_and_exhausts_the_budget() -> None:
77     values = {1: (3.0, 0.7, 100.0), 2: (1.0, 0.85, 50.0), 3: (7.0, 0.6, 20.0)}
78     budget = 120.0
79     split = _cross_unit_allocation(values, budget, cap_mult=4.0)
80     total = sum(split.values())
81     assert total == pytest.approx(budget, rel=1e-6)
82     interior = {u: x for u, x in split.items() if 1e-9 < x < 4.0 * values[u][2] - 1e-9}
83     marginals = [values[u][1] * values[u][0] * x ** (values[u][1] - 1.0) for u, x in interior.items()]
84     assert max(marginals) / min(marginals) - 1.0 < 1e-6
85
86
87 def test_cross_unit_allocation_returns_caps_when_the_budget_is_ample() -> None:
88     values = {1: (3.0, 0.7, 10.0), 2: (1.0, 0.85, 5.0)}

```

```

89     split = _cross_unit_allocation(values, 1e6, cap_mult=4.0)
90     assert split[1] == pytest.approx(40.0)
91     assert split[2] == pytest.approx(20.0)
92
93
94 def test_cross_unit_allocation_survives_extreme_price_sweeps() -> None:
95     """The first implementation raised OverflowError on the 1e-300 end of the bisection."""
96     values = {u: (float(10.0**k), 0.65, 1.0) for k, u in enumerate((1, 2, 3, 4))}
97     split = _cross_unit_allocation(values, 2.0, cap_mult=4.0)
98     assert sum(split.values()) == pytest.approx(2.0, rel=1e-6)
99     assert all(np.isfinite(v) for v in split.values())
100
101
102 def test_weights_switch_off_and_narrow_the_bounce_factor() -> None:
103     import pandas as pd
104
105     p = pd.DataFrame(
106         {
107             "c": [10.0, 20.0],
108             "rate": [0.08, 0.08],
109             "kappa": [0.25, 2.5],
110             "rho": [0.08 * 0.25, 0.08 * 2.5],
111         }
112     )
113     assert _weights(p) == pytest.approx([0.08 * 0.25 * 10, 0.08 * 2.5 * 20])
114     assert _weights(p, "one") == pytest.approx([0.8, 1.6])
115     assert _weights(p, (0.5, 2.0)) == pytest.approx([0.08 * 0.5 * 10, 0.08 * 2.0 * 20])

```

tests/unit/test_hashing.py

```

1 from __future__ import annotations
2
3 from pathlib import Path
4
5 from hypothesis import given
6 from hypothesis import strategies as st
7
8 from forge.hashing import hash_tree, sha256_bytes, sha256_json, tree_digest
9
10
11 @given(st.binary())
12 def test_sha256_bytes_is_deterministic(data: bytes) -> None:
13     assert sha256_bytes(data) == sha256_bytes(data)
14     assert len(sha256_bytes(data)) == 64
15
16
17 @given(
18     st.dictionaries(
19         st.text(min_size=1, max_size=8), st.integers() | st.floats(allow_nan=False) | st.text(max_size=5), max_size=6
20     )
21 )
22 def test_sha256_json_ignores_key_order(mapping: dict) -> None:
23     reversed_mapping = dict(reversed(list(mapping.items())))
24     assert sha256_json(mapping) == sha256_json(reversed_mapping)
25
26
27 def test_hash_tree_ignores_records_and_is_sorted(tmp_path: Path) -> None:
28     (tmp_path / "b.txt").write_text("b")
29     (tmp_path / "a.txt").write_text("a")
30     (tmp_path / "manifest.json").write_text("{}")
31     (tmp_path / "__pycache__").mkdir()

```

```

32 (tmp_path / "__pycache__" / "x.pyc").write_bytes(b"\x00")
33 tree = hash_tree(tmp_path, ignore=("manifest.json", "__pycache__"))
34 assert list(tree) == ["a.txt", "b.txt"]
35 digest = tree_digest(tree)
36 (tmp_path / "manifest.json").write_text('{"changed": true}')
37 assert tree_digest(hash_tree(tmp_path, ignore=("manifest.json", "__pycache__"))) == digest

```

tests/unit/test_manifest.py

```

1 from __future__ import annotations
2
3 from pathlib import Path
4
5 from forge.manifest import Manifest
6
7
8 def test_manifest_lifecycle_and_verification(tmp_path: Path) -> None:
9     stage_dir = tmp_path / "stage"
10    stage_dir.mkdir()
11    (stage_dir / "out.json").write_text("{}")
12    (stage_dir / "events.jsonl").write_text("{}\n")
13    manifest = Manifest.start("run1", "stage", {"p": 1}, {"git_sha": "abc"}, "cfg", {"ingest": "d"}, {})
14    assert manifest.status == "running" and manifest.runtime["python"]
15    manifest.complete(stage_dir, {"m": 1.5})
16    assert manifest.status == "completed"
17    assert list(manifest.outputs) == ["out.json"]
18    manifest.write(stage_dir / "manifest.json")
19    loaded = Manifest.read(stage_dir / "manifest.json")
20    assert loaded.outputs_digest == manifest.outputs_digest
21    assert loaded.verify_outputs(stage_dir) == []
22    (stage_dir / "out.json").write_text('{"x": 1}')
23    assert loaded.verify_outputs(stage_dir) == ["sha256 mismatch: out.json"]
24
25
26 def test_manifest_failure_records_traceback() -> None:
27     manifest = Manifest.start("run1", "stage", {}, {}, "cfg", {}, {})
28     try:
29         raise ValueError("boom")
30     except ValueError as exc:
31         manifest.fail(exc)
32     assert manifest.status == "failed"
33     assert manifest.error and manifest.error["type"] == "ValueError"
34     assert manifest.duration_s is not None

```

tests/unit/test_packaging_tex.py

```

1 from __future__ import annotations
2
3 from pathlib import Path
4
5 from forge.packaging import build_zip, code_members, run_members
6 from forge.tex import aux_page, summarize_log, tex_escape
7
8
9 def test_zip_is_deterministic(tmp_path: Path) -> None:
10    src = tmp_path / "src"
11    src.mkdir()
12    (src / "b.py").write_text("print(2)")

```

```

13 (src / "a.py").write_text("print(1)")
14 (src / "__pycache__").mkdir()
15 (src / "__pycache__" / "a.pyc").write_bytes(b"x")
16 members = code_members(src, ["**/*.py"])
17 assert [m[0] for m in members] == ["a.py", "b.py"]
18 one = build_zip(members, tmp_path / "one.zip")
19 two = build_zip(list(reversed(members)), tmp_path / "two.zip")
20 assert one["sha256"] == two["sha256"] and one["members"] == 2
21
22
23 def test_run_members_prefix(tmp_path: Path) -> None:
24     run = tmp_path / "runs" / "r1"
25     (run / "q1").mkdir(parents=True)
26     (run / "q1" / "out.json").write_text("{}")
27     assert run_members(run, ["q1", "missing"]) == [{"runs/r1/q1/out.json", run / "q1" / "out.json"}]
28
29
30 def test_log_summary_and_aux_page(tmp_path: Path) -> None:
31     log = (
32         "LaTeX Warning: Reference `fig:x' on page 3 undefined on input line 10.\n"
33         "Overfull \hbox (12.5pt too wide) in paragraph\n"
34         "Missing character: There is no  in font Latin Modern!\n"
35         "! Undefined control sequence.\n"
36         "Output written on main.pdf (7 pages).\n"
37     )
38     summary = summarize_log(log)
39     assert summary["undefined_references"] == ["fig:x"]
40     assert summary["overfull_max_pt"] == 12.5 and summary["missing_characters"] == 1
41     assert summary["errors"] == ["Undefined control sequence."] and summary["pages_from_log"] == 7
42     aux = tmp_path / "main.aux"
43     aux.write_text("\newlabel{page:body-end}{{}{27}{{}{page:body-end}}}\n\newlabel{sec:a}{{2.1}{5}{{}{}}}\n")
44     assert aux_page(aux, "page:body-end") == 27 and aux_page(aux, "sec:a") == 5 and aux_page(aux, "nope") is None
45
46
47 def test_tex_escape() -> None:
48     assert tex_escape("a_b & 100% #1") == r"a_b \& 100\% \#1"

```

tests/unit/test_runner.py

```

1 from __future__ import annotations
2
3 import json
4 from pathlib import Path
5
6 import pytest
7
8 from forge import runner
9 from forge.context import StageContext
10
11
12 @pytest.fixture(autouse=True)
13 def isolated_registry(monkeypatch: pytest.MonkeyPatch) -> None:
14     monkeypatch.setattr(runner, "STAGES", {})
15     monkeypatch.setattr(runner, "discover", lambda repo: None)
16
17
18 def test_execute_records_manifest_skips_reruns_and_enforces_deps(tmp_repo: Path, tmp_path: Path) -> None:
19     vol = tmp_path / "vol"
20
21     @runner.stage("first", description="first stage")
22     def first(ctx: StageContext) -> dict:

```

```

23     ctx.out("a.txt").write_text("hello")
24     ctx.number("Answer", 42)
25     return {"n": 1}
26
27 @runner.stage("second", deps=("first",))
28 def second(ctx: StageContext) -> dict:
29     assert (ctx.dep("first") / "a.txt").read_text() == "hello"
30     return {"ok": True}
31
32 with pytest.raises(RuntimeError):
33     runner.execute("second", "r1", {}, False, tmp_repo, vol)
34 result = runner.execute("first", "r1", {"code_ref": {"git_sha": "x"}}, False, tmp_repo, vol)
35 assert result["status"] == "completed" and result["metrics"] == {"n": 1}
36 manifest = json.loads((vol / "runs" / "r1" / "first" / "manifest.json").read_text())
37 assert (
38     manifest["status"] == "completed" and "a.txt" in manifest["outputs"] and "numbers.json" in manifest["outputs"]
39 )
40 assert json.loads((vol / "runs" / "r1" / "first" / "numbers.json").read_text()) == {"Answer": "42"}
41 assert runner.execute("first", "r1", {}, False, tmp_repo, vol)["status"] == "skipped"
42 assert runner.execute("second", "r1", {}, False, tmp_repo, vol)["status"] == "completed"
43 combined = runner.execute("all", "r1", {"stages": ["first", "second"]}, False, tmp_repo, vol)
44 assert combined["status"] == "completed" and [r["status"] for r in combined["results"]] == ["skipped", "skipped"]
45
46
47 def test_failed_stage_writes_failed_manifest(tmp_repo: Path, tmp_path: Path) -> None:
48     vol = tmp_path / "vol"
49
50     @runner.stage("bad")
51     def bad(ctx: StageContext) -> dict:
52         raise ValueError("boom")
53
54     with pytest.raises(ValueError):
55         runner.execute("bad", "r1", {}, False, tmp_repo, vol)
56     manifest = json.loads((vol / "runs" / "r1" / "bad" / "manifest.json").read_text())
57     assert manifest["status"] == "failed" and manifest["error"]["message"] == "boom"
58
59
60 def test_from_run_copies_dependency_outputs(tmp_repo: Path, tmp_path: Path) -> None:
61     vol = tmp_path / "vol"
62
63     @runner.stage("base")
64     def base(ctx: StageContext) -> dict:
65         ctx.out("x.txt").write_text("x")
66         return {}
67
68     @runner.stage("child", deps=("base",))
69     def child(ctx: StageContext) -> dict:
70         return {"seen": (ctx.dep("base") / "x.txt").read_text()}
71
72     runner.execute("base", "old", {}, False, tmp_repo, vol)
73     result = runner.execute("child", "new", {"from_run": "old"}, False, tmp_repo, vol)
74     assert result["metrics"] == {"seen": "x"}

```

tests/unit/test_xlsx.py

```

1 from __future__ import annotations
2
3 from pathlib import Path
4
5 import openpyxl
6 import pytest

```

```

7
8 from forge.xlsx import SheetContract, WorkbookContract, check_workbook, read_sheets, sheet_headers, write_result
9
10
11 def _template(path: Path) -> Path:
12     wb = openpyxl.Workbook()
13     ws = wb.active
14     ws.title = "温度"
15     ws.append(["时间\\到药材中心的距离", 0, 0.1, "...", 2])
16     ws.append([1, None, None, None, None])
17     ws2 = wb.create_sheet("水分浓度")
18     ws2.append(["时间\\到药材中心的距离", 0, 0.1, "...", 2])
19     wb.save(path)
20     return path
21
22
23 def test_write_result_keeps_all_rounds_and_passes_contract(tmp_path: Path) -> None:
24     template = _template(tmp_path / "tpl.xlsx")
25     header = ["ignored", 0.0, 0.1, 0.2]
26     rows = [[t, 28.123456, 28.2, 28.3] for t in range(1, 6)]
27     info = write_result(template, tmp_path / "out.xlsx", {"温度": (header, rows), "水分浓度": (header, rows)})
28     assert info["sheets"]["温度"]["rows"] == 5
29     headers = sheet_headers(tmp_path / "out.xlsx")
30     assert headers["温度"][0] == "时间\\到药材中心的距离"
31     assert headers["温度"][1:] == [0.0, 0.1, 0.2]
32     frames = read_sheets(tmp_path / "out.xlsx")
33     assert float(frames["温度"].iloc[0, 1]) == pytest.approx(28.1235)
34     contract = WorkbookContract(
35         "out.xlsx",
36         "tpl.xlsx",
37         (
38             SheetContract("温度", min_rows=5, max_rows=5, header_len=4, numeric_from_col=0),
39             SheetContract("水分浓度", min_rows=5, header_len=4, numeric_from_col=0),
40         ),
41     )
42     report = check_workbook(tmp_path / "out.xlsx", contract, template)
43     assert report["ok"], report["errors"]
44
45
46 def test_check_workbook_flags_blank_and_text_cells(tmp_path: Path) -> None:
47     template = _template(tmp_path / "tpl.xlsx")
48     rows = [[1, 1.0, None, "x"], [2, 2.0, 2.0, 2.0]]
49     write_result(template, tmp_path / "out.xlsx", {"温度": ([ "h", 0, 0.1, 0.2], rows)})
50     contract = WorkbookContract("out.xlsx", "tpl.xlsx", (SheetContract("温度", min_rows=2, numeric_from_col=0),))
51     report = check_workbook(tmp_path / "out.xlsx", contract, template)
52     joined = " ".join(report["errors"])
53     assert not report["ok"] and "blank" in joined and "non-numeric" in joined
54
55
56 def test_write_result_rejects_unknown_sheet(tmp_path: Path) -> None:
57     template = _template(tmp_path / "tpl.xlsx")
58     with pytest.raises(KeyError):
59         write_result(template, tmp_path / "out.xlsx", {"nope": ([ "h", ], [])})
60
61
62 def test_write_only_path_for_large_sheets(tmp_path: Path, monkeypatch: pytest.MonkeyPatch) -> None:
63     import forge.xlsx as mod
64
65     monkeypatch.setattr(mod, "BIG_SHEET_CELLS", 10)
66     template = _template(tmp_path / "tpl.xlsx")
67     rows = [[t, 1.0, 2.0] for t in range(1, 8)]
68     info = write_result(template, tmp_path / "big.xlsx", {"温度": ([ "h", 0, 0.1], rows)})
69     assert info["write_only"]

```

```

70     headers = sheet_headers(tmp_path / "big.xlsx")
71     assert list(headers) == ["温度", "水分浓度"]
72     assert headers["温度"][0] == "时间\\到药材中心的距离"

```

tools/__init__.py

tools/cli.py

```

1  #!/usr/bin/env python3
2  """Forge control plane (local). Never computes: submits cloud jobs, downloads, verifies hashes.
3
4  Examples
5      python3 tools/cli.py run ingest                # new run id, small container
6      python3 tools/cli.py run validate --run-id <id> # continue the same run
7      python3 tools/cli.py run q1,q2 --size medium    # sequential stages in one container
8      python3 tools/cli.py run q3 --size large --spawn # detached; poll with `wait`/`status`
9      python3 tools/cli.py exec --code 'print(sorted(p.name for p in RUN_DIR.iterdir()))'
10     python3 tools/cli.py status                     # manifests of the last run
11     python3 tools/cli.py download --stage results   # into artifacts/, verified against manifests
12     python3 tools/cli.py release --version v1.0.0   # deliverables into releases/v1.0.0/
13 """
14
15 from __future__ import annotations
16
17 import argparse
18 import hashlib
19 import json
20 import os
21 import shutil
22 import subprocess
23 import sys
24 from datetime import datetime
25 from pathlib import Path
26
27 REPO = Path(__file__).resolve().parents[1]
28 PROJECT = json.loads((REPO / "configs" / "project.json").read_text(encoding="utf-8"))
29 APP_FILE = REPO / "forge" / "modal_app.py"
30 STATE_DIR = REPO / ".forge"
31 LAST_RUN = STATE_DIR / "last_run"
32 MODAL = shutil.which("modal") or str(Path.home() / ".local" / "bin" / "modal")
33
34
35 def _sh(cmd: list[str], **kw) -> subprocess.CompletedProcess:
36     print("$ " + " ".join(cmd), flush=True)
37     return subprocess.run(cmd, cwd=REPO, check=False, **kw)
38
39
40 def git_ref() -> dict:
41     def out(*args: str) -> str:
42         try:
43             return subprocess.run(["git", *args], cwd=REPO, capture_output=True, text=True, check=False).stdout.strip()
44         except OSError:
45             return ""
46
47     sha = out("rev-parse", "HEAD") or "nogit"
48     return {
49         "git_sha": sha,

```

```

50     "branch": out("rev-parse", "--abbrev-ref", "HEAD"),
51     "dirty": bool(out("status", "--porcelain")),
52 }
53
54
55 def new_run_id() -> str:
56     return datetime.now().strftime("%Y%m%d-%H%M%S") + "-" + git_ref()["git_sha"][:7]
57
58
59 def remember(run_id: str) -> None:
60     STATE_DIR.mkdir(exist_ok=True)
61     LAST_RUN.write_text(run_id, encoding="utf-8")
62
63
64 def resolve_run_id(explicit: str | None, create: bool) -> str:
65     if explicit:
66         remember(explicit)
67         return explicit
68     if create or not LAST_RUN.exists():
69         run_id = new_run_id()
70         remember(run_id)
71         return run_id
72     return LAST_RUN.read_text(encoding="utf-8").strip()
73
74
75 def parse_params(items: list[str] | None) -> dict:
76     params: dict = {}
77     for item in items or []:
78         key, _, raw = item.partition("=")
79         try:
80             params[key] = json.loads(raw)
81         except json.JSONDecodeError:
82             params[key] = raw
83     return params
84
85
86 def modal_run(args: list[str], detach: bool = False) -> int:
87     cmd = [MODAL, "run"] + ([ "--detach" ] if detach else []) + [str(APP_FILE)] + args
88     return _sh(cmd).returncode
89
90
91 def cmd_run(ns: argparse.Namespace) -> int:
92     stages = [s for s in ns.stage.split(",") if s]
93     run_id = resolve_run_id(ns.run_id, create=ns.new_run)
94     params = parse_params(ns.param)
95     params.update(
96         {"code_ref": git_ref(), "size": ns.size, "submitted_at": datetime.now().isoformat(timespec="seconds")}
97     )
98     if ns.from_run:
99         params["from_run"] = ns.from_run
100     if ns.profile:
101         params["profile"] = ns.profile
102     stage = stages[0] if len(stages) == 1 else "all"
103     if stage == "all":
104         params["stages"] = stages
105     args = [ "--stage", stage, "--run-id", run_id, "--params", json.dumps(params, ensure_ascii=False), "--size", ns.size
106         ↵ ]
107     if ns.force:
108         args.append("--force")
109     if ns.spawn:
110         args.append("--spawn")
111     print(f"run_id={run_id} stages={stages} size={ns.size} spawn={ns.spawn}")
112     return modal_run(args, detach=ns.spawn)

```

```

112
113
114 def cmd_exec(ns: argparse.Namespace) -> int:
115     code = Path(ns.file).read_text(encoding="utf-8") if ns.file else ns.code
116     if not code:
117         print("provide --code or --file", file=sys.stderr)
118         return 2
119     run_id = resolve_run_id(ns.run_id, create=False)
120     return modal_run(
121         ["--stage", "exec", "--run-id", run_id, "--params", json.dumps({"code": code}, ensure_ascii=False)]
122     )
123
124
125 def cmd_provision(_: argparse.Namespace) -> int:
126     return modal_run(["--stage", "provision"])
127
128
129 STATUS_SNIPPET = r"""
130 import json
131 from pathlib import Path
132 run = RUN_DIR
133 if not run.exists():
134     print("run directory missing:", run)
135 else:
136     rows = []
137     for m in sorted(run.glob("*/manifest.json")):
138         d = json.loads(m.read_text())
139         err = (d.get("error") or {}).get("message", "")[:80]
140         digest = d.get("outputs_digest", "")[:12]
141         rows.append((d["stage"], d["status"], d.get("duration_s"), digest, len(d.get("outputs", {})), err))
142     print(f'{"stage":14s} {"status":10s} {"seconds":>9s} {"digest":12s} {"files":>5s} error')
143     for r in rows:
144         print(f"{r[0]:14s} {r[1]:10s} {str(r[2]):>9s} {r[3]:12s} {r[4]:5d} {r[5]}")
145     print("run_dir:", run)
146 """
147
148
149 def cmd_status(ns: argparse.Namespace) -> int:
150     run_id = resolve_run_id(ns.run_id, create=False)
151     return modal_run(["--stage", "exec", "--run-id", run_id, "--params", json.dumps({"code": STATUS_SNIPPET})])
152
153
154 def cmd_runs(_: argparse.Namespace) -> int:
155     return _sh([MODAL, "volume", "ls", PROJECT["volume"], "runs"]).returncode
156
157
158 def cmd_logs(ns: argparse.Namespace) -> int:
159     run_id = resolve_run_id(ns.run_id, create=False)
160     code = (
161         "from pathlib import Path\n"
162         f"p = RUN_DIR / {ns.stage!r} / 'events.jsonl'\n"
163         "print(p.read_text()[-%d:] if p.exists() else 'no events for stage')\n" % ns.tail
164     )
165     return modal_run(["--stage", "exec", "--run-id", run_id, "--params", json.dumps({"code": code})])
166
167
168 def sha256(path: Path) -> str:
169     h = hashlib.sha256()
170     with path.open("rb") as fh:
171         for chunk in iter(lambda: fh.read(1 << 20), b""):
172             h.update(chunk)
173     return h.hexdigest()
174

```

```

175
176 def verify_dir(root: Path) -> int:
177     """Verify every downloaded stage directory against its manifest (transport check only)."""
178     problems = 0
179     manifests = sorted(root.rglob("manifest.json"))
180     if not manifests:
181         print(f"no manifests under {root}")
182         return 1
183     for manifest in manifests:
184         data = json.loads(manifest.read_text(encoding="utf-8"))
185         stage_dir = manifest.parent
186         bad = []
187         for rel, meta in data.get("outputs", {}).items():
188             file = stage_dir / rel
189             if not file.exists():
190                 bad.append(f"missing {rel}")
191             elif sha256(file) != meta["sha256"]:
192                 bad.append(f"sha256 mismatch {rel}")
193         status = "OK " if not bad else "BAD"
194         print(
195             f"[{status}] {data.get('stage'):14s} {data.get('status'):10s} "
196             f"files={len(data.get('outputs', {}))} {stage_dir}"
197         )
198         for b in bad:
199             print("    " + b)
200         problems += len(bad)
201     return 0 if problems == 0 else 1
202
203
204 def volume_get(remote: str, local_parent: Path) -> int:
205     """Download a remote directory into ``local_parent/<basename>`` (replacing any previous copy)."""
206     target = local_parent / Path(remote).name
207     shutil.rmtree(target, ignore_errors=True)
208     local_parent.mkdir(parents=True, exist_ok=True)
209     return _sh([MODAL, "volume", "get", "--force", PROJECT["volume"], remote, str(local_parent) + "/"]).returncode
210
211
212 def cmd_download(ns: argparse.Namespace) -> int:
213     run_id = resolve_run_id(ns.run_id, create=False)
214     if ns.stage:
215         remote, parent = f"runs/{run_id}/{ns.stage}", REPO / ns.dest / "runs" / run_id
216     else:
217         remote, parent = f"runs/{run_id}", REPO / ns.dest / "runs"
218     rc = volume_get(remote, parent)
219     if rc != 0:
220         return rc
221     return verify_dir(parent / Path(remote).name)
222
223
224 def cmd_verify(ns: argparse.Namespace) -> int:
225     return verify_dir(Path(ns.path))
226
227
228 def cmd_release(ns: argparse.Namespace) -> int:
229     run_id = resolve_run_id(ns.run_id, create=False)
230     dest = REPO / "releases" / ns.version
231     if dest.exists() and not ns.force:
232         print(f"{dest} exists; pass --force to overwrite", file=sys.stderr)
233         return 2
234     staging = REPO / "artifacts" / "release_staging" / run_id
235     rc = volume_get(f"runs/{run_id}/release", staging)
236     if rc != 0:
237         return rc

```

```

238     shutil.rmtree(dest, ignore_errors=True)
239     shutil.copytree(staging / "release", dest)
240     manifest = json.loads((dest / "release_manifest.json").read_text(encoding="utf-8"))
241     bad = 0
242     for name, meta in manifest["files"].items():
243         file = dest / name
244         ok = file.exists() and sha256(file) == meta["sha256"]
245         bad += 0 if ok else 1
246         print(f"[{'OK' if ok else 'BAD'}] {name} {meta['bytes']} bytes sha256={meta['sha256'][:16]}")
247     print(f"release {ns.version} from run {run_id}: {'verified' if not bad else f'{bad} problems'} -> {dest}")
248     return 0 if not bad else 1
249
250
251 def cmd_wait(ns: argparse.Namespace) -> int:
252     interpreter = (
253         Path(MODAL).read_text(encoding="utf-8", errors="ignore").splitlines()[0].lstrip("#!").strip()
254         if Path(MODAL).exists()
255         else sys.executable
256     )
257     code = (
258         "import json, modal, sys\n"
259         f"call = modal.FunctionCall.from_id({ns.call_id!r})\n"
260         "print('STAGE_RESULT ' + json.dumps(call.get(), ensure_ascii=False, default=str))\n"
261     )
262     return _sh([interpreter, "-c", code]).returncode
263
264
265 def cmd_fmt(ns: argparse.Namespace) -> int:
266     """Format in the cloud, then copy the exported files back into the working tree."""
267     run_id = resolve_run_id(ns.run_id, create=False)
268     params = {"code_ref": git_ref(), "size": "small"}
269     rc = modal_run(["--stage", "fmt", "--run-id", run_id, "--params", json.dumps(params), "--force"])
270     if rc != 0:
271         return rc
272     dest = REPO / "artifacts" / "runs" / run_id / "fmt"
273     rc = volume_get(f"runs/{run_id}/fmt", dest.parent)
274     if rc != 0:
275         return rc
276     files = dest / "files"
277     changed = sorted(p for p in files.rglob("*") if p.is_file()) if files.exists() else []
278     for src in changed:
279         rel = src.relative_to(files)
280         target = REPO / rel
281         target.parent.mkdir(parents=True, exist_ok=True)
282         shutil.copy2(src, target)
283         print(f"updated {rel}")
284     report = json.loads((dest / "fmt_report.json").read_text(encoding="utf-8"))
285     print(f"{len(changed)} files formatted; remaining ruff findings: {report.get('remaining')}")
286     return 0
287
288
289 def cmd_new_run(_: argparse.Namespace) -> int:
290     run_id = new_run_id()
291     remember(run_id)
292     print(run_id)
293     return 0
294
295
296 def build_parser() -> argparse.ArgumentParser:
297     p = argparse.ArgumentParser(prog="forge", description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter
298     ↪ )
299     sub = p.add_subparsers(dest="command", required=True)

```

```

300 r = sub.add_parser("run", help="run one stage or a comma-separated sequence in one container")
301 r.add_argument("stage")
302 r.add_argument("--run-id")
303 r.add_argument("--new-run", action="store_true", help="start a fresh run id")
304 r.add_argument("--size", default="small", choices=["small", "medium", "large"])
305 r.add_argument("--force", action="store_true", help="re-run even if the stage already completed")
306 r.add_argument("--spawn", action="store_true", help="detach: return immediately, poll with status/wait")
307 r.add_argument("--from-run", help="copy missing dependency outputs from this earlier run")
308 r.add_argument("--profile", help="overlay configs/<profile>.toml")
309 r.add_argument("--param", action="append", help="key=value (JSON-parsed) forwarded to the stage")
310 r.set_defaults(fn=cmd_run)
311
312 e = sub.add_parser("exec", help="run an ad-hoc Python snippet in the cloud against the run directory")
313 e.add_argument("--code")
314 e.add_argument("--file")
315 e.add_argument("--run-id")
316 e.set_defaults(fn=cmd_exec)
317
318 sub.add_parser("provision", help="verify the cloud toolchain").set_defaults(fn=cmd_provision)
319
320 s = sub.add_parser("status", help="print manifests of a run")
321 s.add_argument("--run-id")
322 s.set_defaults(fn=cmd_status)
323
324 lg = sub.add_parser("logs", help="tail the event log of a stage")
325 lg.add_argument("stage")
326 lg.add_argument("--run-id")
327 lg.add_argument("--tail", type=int, default=6000)
328 lg.set_defaults(fn=cmd_logs)
329
330 sub.add_parser("runs", help="list runs on the volume").set_defaults(fn=cmd_runs)
331
332 d = sub.add_parser("download", help="download a run (or one stage) into artifacts/ and verify hashes")
333 d.add_argument("--run-id")
334 d.add_argument("--stage")
335 d.add_argument("--dest", default="artifacts")
336 d.set_defaults(fn=cmd_download)
337
338 v = sub.add_parser("verify", help="verify a downloaded directory against its manifests")
339 v.add_argument("path")
340 v.set_defaults(fn=cmd_verify)
341
342 rel = sub.add_parser("release", help="download the release stage into releases/<version> and verify")
343 rel.add_argument("--version", required=True)
344 rel.add_argument("--run-id")
345 rel.add_argument("--force", action="store_true")
346 rel.set_defaults(fn=cmd_release)
347
348 w = sub.add_parser("wait", help="block on a spawned function call id and print its result")
349 w.add_argument("call_id")
350 w.set_defaults(fn=cmd_wait)
351
352 f = sub.add_parser("fmt", help="ruff --fix + format in the cloud and copy the results back")
353 f.add_argument("--run-id")
354 f.set_defaults(fn=cmd_fmt)
355
356 sub.add_parser("new-run", help="mint a run id").set_defaults(fn=cmd_new_run)
357 return p
358
359
360 def main(argv: list[str] | None = None) -> int:
361     os.chdir(REPO)
362     ns = build_parser().parse_args(argv)

```

```

363     return int(ns.fn(ns))
364
365
366 if __name__ == "__main__":
367     sys.exit(main())

```

tools/run_local.py

```

1  #!/usr/bin/env python3
2  """Run the Problem-E pipeline on this machine, without Modal.
3
4  The reference execution of this repository is in the cloud (`tools/cli.py`), but an evaluator has no
5  account there. This script is the local equivalent: it calls exactly the same stage functions, in the
6  same order, through the same runner, writing into a local directory instead of a cloud volume.
7
8      python3 tools/run_local.py                # ingest -> ... -> tables, into ./local_runs/<id>
9      python3 tools/run_local.py --stages ingest,validate --out /tmp/e
10     python3 tools/run_local.py --quick        # reduced budgets: minutes rather than hours
11
12  Requirements (pip install): pandas, numpy, scipy, scikit-learn, statsmodels, openpyxl, pyarrow, matplotlib, cvxpy.
13  The organisers' attachments must be present in ``附件`` exactly as delivered; nothing else is needed.
14  Typesetting stages (`paper`/`qa`/`package`/`release`) need a TeX Live installation with XeLaTeX
15  and the CJK fonts, so they are not part of the default list here — the scientific stages are.
16  """
17
18  from __future__ import annotations
19
20  import argparse
21  import json
22  import sys
23  import time
24  from datetime import UTC, datetime
25  from pathlib import Path
26
27  REPO = Path(__file__).resolve().parents[1]
28  DEFAULT_STAGES = "ingest,validate,eda,classify,allocate,forecast,results,figures,tables"
29  # --quick reduces the Monte-Carlo scenario count and the bootstrap draws through ``config_overrides``
30  # (the same mechanism as ``--profile``): minutes instead of tens of minutes. Point estimates are
31  # unchanged; interval widths and bootstrap intervals are noisier than the published ones.
32  _QUICK_CONFIG = {"allocate": {"bootstrap": 60}, "forecast": {"scenarios": 100}}
33  QUICK = {
34      s: {"config_overrides": _QUICK_CONFIG}
35      for s in ("eda", "classify", "allocate", "forecast", "results", "figures", "tables")
36  }
37
38
39  def main() -> int:
40      ap = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
41      ap.add_argument("--stages", default=DEFAULT_STAGES, help=f"comma-separated (default: {DEFAULT_STAGES})")
42      ap.add_argument("--out", default=str(REPO / "local_runs"), help="directory that plays the role of the volume")
43      ap.add_argument("--run-id", default=None, help="reuse an existing run id instead of creating one")
44      ap.add_argument("--quick", action="store_true", help="small solver budgets (minutes instead of hours)")
45      ap.add_argument("--force", action="store_true", help="re-run stages that already completed")
46      ap.add_argument("--param", action="append", default=[], help="stage param, e.g. workers=4 or all:workers=4")
47      ns = ap.parse_args()
48
49      sys.path.insert(0, str(REPO))
50      import pipelines.e.stages # noqa: F401 - registers the stages
51      from forge.runner import execute
52
53      vol = Path(ns.out).resolve()

```

```

54 run_id = ns.run_id or datetime.now(UTC).strftime("%Y%m%d-%H%M%S-local")
55 (vol / "runs" / run_id).mkdir(parents=True, exist_ok=True)
56 extra: dict[str, dict[str, object]] = {}
57 for item in ns.param:
58     scope, _, rest = item.partition(":") if ":" in item else ("all", "", item)
59     key, _, value = rest.partition("=")
60     try:
61         parsed = json.loads(value)
62     except json.JSONDecodeError:
63         parsed = value
64     extra.setdefault(scope, {})[key] = parsed
65
66 print(f"repo={REPO}\nvolume={vol}\nrun_id={run_id}")
67 for stage in [s.strip() for s in ns.stages.split(",") if s.strip()]:
68     params: dict[str, object] = {"size": "local"}
69     if ns.quick:
70         params.update(QUICK.get(stage, {}))
71     params.update(extra.get("all", {}))
72     params.update(extra.get(stage, {}))
73     t0 = time.monotonic()
74     result = execute(stage_name=stage, run_id=run_id, params=params, force=ns.force, repo=REPO, vol=vol)
75     status = result.get("status")
76     print(f"[{time.monotonic() - t0:8.1f}s] {stage:18s} {status}")
77     if status == "failed":
78         print(json.dumps(result.get("error", {}), ensure_ascii=False, indent=2))
79         return 1
80 print(f"\nresults: {vol / 'runs' / run_id / 'results'} (result1-4.xlsx)")
81 print(f"figures: {vol / 'runs' / run_id / 'figures' / 'figures'}")
82 print(f"tables: {vol / 'runs' / run_id / 'tables' / 'tables'}")
83 return 0
84
85
86 if __name__ == "__main__":
87     raise SystemExit(main())

```