

Programme 1

```
int change(int t[3], int p);

int main()
{
    int t[3] = {3, 3, 3};
    int p = 2;

    p = change(t, p);

    cout << p << "\n";
    for (int i = 0; i < 3; i++)
        cout << t[i] << " ";
}

int change(int t[3], int p)
{
    for (int i = 2; i >= 0; i--)
    {
        p += t[i];
        t[i] = p - i;
    }
    return p;
}
```

Programme 2

```
int f(int a, int b);

int c = 5;

int main()
{
    int a = 2, b = 10;
    c = 7;

    a = f(a, b);
    b = f(b, a);

    cout << a << " " << b << " " << c;
}

int f(int a, int b)
{
    c = c + a;
    a = b - c;
    return a;
}
```

Programme 3

```
void calc(int &a, int b);

int c = 100;

int main()
{
    int a = 8, b = 3;
    c = 20;

    calc(a, b);

    cout << a << " " << b << " " << c;
}

void calc(int &a, int b)
{
    a = a + c;
    c = b * 2;
    b = a - c;
}
```

Programme 4

```
void remplir(int t[3], int x);
void ajuste(double &m, int t[3]);

int main()
{
    int t[3] = {0, 0, 0};
    double m = 2.0;

    remplir(t, 4);
    ajuste(m, t);

    cout << m << "\n";
    for (int i = 0; i < 3; i++)
        cout << t[i] << " ";
}

void remplir(int t[3], int x)
{
    for (int i = 0; i < 3; i++)
        t[i] = x + i;
}

void ajuste(double &m, int t[3])
{
    for (int i = 0; i < 3; i++)
        m += t[i] / 2.0;
}
```