#8 0x40e17b in decoder_context::decode(int*) /root/src/libde265/libde265/decctx.cc:1318 #9 0x405a61 in de265_decode /root/src/libde265/libde265/de265.cc:346

#11 0x7f349865a82f in __libc_start_main (/lib/x86_64-linux-gnu/libc.so.6+0x2082f)

#10 0x404972 in main /root/src/libde265/dec265/dec265.cc:764

⟨> Code ○ Issues 110 १ Pull requests 18 Actions Projects Wiki

New issue Jump to bottom

heap-buffer-overflow in put_weighted_bipred_16_fallback when decoding file #242

⊙ Open leonzhao7 opened this issue on Dec 24, 2019 · 1 comment leonzhao7 commented on Dec 24, 2019 heap-buffer-overflow in put_weighted_bipred_16_fallback when decoding file I found some problems during fuzzing **Test Version** dev version, git clone https://github.com/strukturag/libde265 **Test Environment** root@ubuntu:~# lsb release -a No LSB modules are available Distributor ID: Ubuntu Description: Ubuntu 16.04.6 LTS Release: 16.04 Codename: xenial root@ubuntu:#+ ie #4916.04.1-Ubuntu SMP Tue Jan 29 18:03:48 UTC 2019 x86_64 x86_64 x86_64 GNU/Linux **Test Configure** ./configure configure: Building dec265 example: yes configure: Building sherlock265 example: no configure: Building encoder: yes configure: **Test Program** dec265 [infile] **Asan Output** root@ubuntu:~# ./dec265 libde265-put_weighted_bipred_16_fallback-heap_overflow.crash WARNING: end_of_sub_stream_one_bit not set to 1 when it should be WARNING: end_of_sub_stream_one_bit not set to 1 when it should be WARNING: pps header invalid WARNING: end_of_sub_stream_one_bit not set to 1 when it should be 97574==ERROR: AddressSanitizer: heap-buffer-overflow on address 0x62b00001b510 at pc 0x000000432ac8 bp 0x7ffe6664b0a0 sp 0x7ffe6664b090 WRITE of size 2 at 0x62b00001b510 thread T0 /root/src/libde265/libde265/fallback-motion.cc:223 ../libde265/acceleration.h:286 /root/src/libde265/libde265/motion.cc:2107 $\texttt{\#4 0x47995d in read_coding_unit(thread_context*, int, int, int, int) / root/src/libde 265/libde 265/slice.cc: 43106 (libde 265/libde 265/libd$ #5 0x47b6fe in read_coding_quadtree(thread_context*) int, int, int, int) /root/src/libde265/libde265/libde265/slice.cc:4647
#6 0x47338a in read_coding_tree_unit(thread_context*) /root/src/libde265/libde265/slice.cc:2861 #7 0x47beb1 in decode_substream(thread_context*, bool, bool) /root/src/libde265/libde265/slice.cc:4736 #8 0x47db9f in read_slice_segment_data(thread_context*) /root/src/libde265/libde265/slice.cc:5049
#9 0x40bf17 in decoder_context::decode_slice_unit_sequential(image_unit*, slice_unit*) /root/src/libde265/libde265/decctx.cc:843
#10 0x40c6d7 in decoder_context::decode_slice_unit_parallel(image_unit*, slice_unit*) /root/src/libde265/libde265/decctx.cc:945 #11 0x40b589 in decoder_context::decode_some(bool*) /root/src/libde265/libde265/decctx.cc:730
#12 0x40b2f2 in decoder_context::read_slice_NAL(bitreader&, NAL_unit*, nal_header&) /root/src/libde265/libde265/decctx.cc:688 #13 0x40dbb3 in decoder_context::decode_NAL(NAL_unit*) /root/src/libde265/libde265/decctx.cc:1230
#14 0x40e17b in decoder_context::decode(int*) /root/src/libde265/libde265/decctx.cc:1318 #15 0x405a61 in de265 decode /root/src/libde265/libde265/de265.cc:346 #16 0x404972 in main /root/src/libde265/dec265/dec265.cc:764 #17 0x7f349865a82f in __libc_start_main (/lib/x86_64-linux-gnu/libc.so.6+0x2082f) #18 0x402b28 in _start (/root/dec265+0x402b28) 0x62b00001b510 is located 0 bytes to the right of 25360-byte region [0x62b000015200,0x62b00001b510) allocated by thread T0 here: #0 0x7f349955b076 in __interceptor_posix_memalign (/usr/lib/x86_64-linux-gnu/libasan.so.2+0x99076) #1 0x43e00d in ALLOC_ALIGNED /root/src/libde265/libde265/image.cc:54 #2 0x43e725 in de265_image_get_buffer /root/src/libde265/libde265/limage.cc:132
#3 0x440639 in de265_image::alloc_image(int, int, de265_chroma, std::shared_ptr<seq_parameter_set const>, bool, decoder_context*, long, void*, bool) /root/src/libde265/libde265/image.cc:384 ## 0x43afa4 in decoded_picture_buffer::new_image(std::shared_ptr<seq_parameter_set const>, decoder_context*, long, void*, bool) /root/src/libde265/libde265/dpb.cc:262 #5 0x414467 in decoder_context::process_slice_segment_header(slice_segment_header*) and the process_slice_segment_header*) are process_slice_segment_header*) and the process_slice_segment_header*) and the process_slice_segment_header*) are process_slice_segment_header*) and the process_slice_segment_header*) are process_slice_segment_header*) and the process_slice_segment_header*) are process_slice_segment_head

```
Shadow byte legend (one shadow byte represents 8 application bytes): Addressable: 00
   Heap right redzone: fb
   Freed heap region:
Stack left redzone:
                         fd
f1
   Stack mid redzone:
Stack right redzone:
                         f2
f3
   Stack right redzone:
Stack partial redzone:
Stack after return:
Stack use after scope:
Global redzone:
                         f4
    Global init order:
                         f6
f7
fc
ac
    Poisoned by user:
    Container overflow:
   Array cookie:
Intra object redzone:
                         bb
  ASan internal:
==97574==ABORTING
POC file
libde265-put_weighted_bipred_16_fallback-heap_overflow.zip
password: leon.zhao.7
CREDIT
Zhao Liang, Huawei Weiran Labs
```

coldtobi commented last week

According to Debian this is CVE-2020-21602

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

Developmen

No branches or pull requests

2 participants

