


master ▾

...

security / advisories / SICK-2022-128.md

 sickcodes [CVE-2022-36123] Publish CVE-2022-36123 ✓ History

1 contributor

259 lines (177 sloc) | 13 KB

### Title

A vulnerability in Linux kernel mainline v5.18-rc1 through v5.19-rc6 does not clear statically allocated variables in the block starting symbol (.bss) due to a failed early\_xen\_iret\_patch leading to an asm\_exc\_page\_fault, or arbitrary code execution

### CVE ID

CVE-2022-36123

### CVSS Score

N/A

### Internal IDs

SICK-2022-128

### Vendor

Kernel.org

### Product

## Product Versions

Kernel v5.18-rc1 through v5.19-rc6

## Vulnerability Details

A vulnerability in Linux kernel mainline v5.18-rc1 through v5.19-rc6 may not clear the block starting symbol (.bss) where statically allocated variables in the .bss, affecting XenPV guests, leading to an `asm_exc_page_fault`, or arbitrary code execution. An unprivileged local attacker on the host, or guest, may potentially use this flaw to cause a NULL Pointer Dereference, kernel oops or denial of service as this allows virtualized devices connected to the Xen IOMMU via `xen_set_restricted_virtio_memory_access` to potentially access restricted memory. In addition, if `kexec` is used, the 2nd kernel .bss may contain uninitialized resources and may not be clear.

## Vendor Response

Fixed in kernel mainline. `clear_bss()` now clears the .brk at early boot and `xen_set_restricted_virtio_memory_access` was added via `CONFIG_XEN_VIRTIO` kernel config.

Fix: 36e2f161fb01795722f2ff1a24d95f08100333dd

Upstream: 38fa5479b41376dc9d7f57e71c83514285a25ca0

Fixed in 5.18.13 stable <https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.18.13>

Fixed in 5.15.56 longterm 5.15.x <https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.15.56>

Fixed in 5.10.132 longterm 5.10.x <https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.10.132>

Fixed in 5.4.207 longterm 5.4.x <https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.4.207>

Fixed in 4.19.253 longterm 4.19.x <https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.19.253>

Fixed in 4.14.289 longterm 4.14.x <https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.14.289>

Fixed in 4.9.324 longterm 4.9.324 <https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.9.324>

## Proof of Concept

A note was left when v5.18-rc1 was released describing the use of xen\_start\_info arch/x86/xen/mmu\_pv.c: "The xen\_start\_info has been taken care of already in xen\_setup\_kernel\_pagetable"

[https://github.com/torvalds/linux/blob/babf0bb978e3c9fce6c4eba6b744c8754fd43d8e/arch/x86/xen/mmu\\_pv.c#L1151](https://github.com/torvalds/linux/blob/babf0bb978e3c9fce6c4eba6b744c8754fd43d8e/arch/x86/xen/mmu_pv.c#L1151)

After early\_xen\_iret\_patch was added, it was later urgently removed & cleaned up in x86\_urgent\_for\_v5.19\_rc6:

```
Merge tag 'x86_urgent_for_v5.19_rc6' of git://git.kernel.org/pub/scm/...
...linux/kernel/git/tip/tip
```

Pull x86 fixes from Borislav Petkov:

- Prepare for and clear .brk early in order to address XenPV guests failures where the hypervisor verifies page tables and uninitialized data in that range leads to bogus failures in those checks
- Add any potential setup\_data entries supplied at boot to the identity pagetable mappings to prevent kexec kernel boot failures. Usually, this is not a problem for the normal kernel as those mappings are part of the initially mapped 2M pages but if kexec gets to allocate the second kernel somewhere else, those setup\_data entries need to be mapped there too.
- Fix objtool not to discard text references from the \_\_tracepoints section so that ENDBR validation still works
- Correct the setup\_data types limit as it is user-visible, before 5.19 releases

```
* tag 'x86_urgent_for_v5.19_rc6' of
```

```
git://git.kernel.org/pub/scm/linux/kernel/git/tip/tip:
```

```
x86/boot: Fix the setup data types max limit
x86/ibt, objtool: Don't discard text references from tracepoint section
x86/compressed/64: Add identity mappings for setup_data entries
x86: Fix .brk attribute in linker script
x86: Clear .brk area at early boot
x86/xen: Use clear_bss() for Xen PV guests
```

If `clear_bss()` is not added, and a user runs `kexec`, the "normal kernel... mappings are part of the initially mapped 2M pages but `kexec` gets to allocate the second kernel somewhere else, those `setup_data` entries need to be mapped there too."

```
* tag 'x86_urgent_for_v5.19_rc6' of
git://git.kernel.org/pub/scm/linux/kernel/git/tip/tip:
  x86/boot: Fix the setup data types max limit
  x86/ibt, objtool: Don't discard text references from tracepoint section
  x86/compressed/64: Add identity mappings for setup_data entries
  x86: Fix .brk attribute in linker script
  x86: Clear .brk area at early boot
  x86/xen: Use clear_bss() for Xen PV guests
```

Virtualized devices connected to the Xen IOMMU can potentially access restricted memory.

```
[12002.517482] BUG: kernel NULL pointer dereference, address: 0000000000000344
[12002.517487] #PF: supervisor write access in kernel mode
[12002.517489] #PF: error_code(0x0002) - not-present page
[12002.517490] PGD 0 P4D 0
[12002.517493] Oops: 0002 [#1] PREEMPT SMP NOPTI
[12002.517499] RIP: 0010:copy_fpstate_to_sigframe+0xad/0x330
[12002.517505] Code: 1f 44 00 00 48 8d bd 00 02 00 00 be 40 00 00 00 e8 b8 eb 58
00 48 85 c0 75 bc 65 48 8b 1c 25 c0 0b 02 00 65 81 05 9f 73 1e 5d <00> 02 00 00
48 8b 03 f6 c4 40 0f 85 ab 00 00 00 83 83 f8 1a 00 00
[12002.517506] RSP: 0000:ffffb298c2fb3df0 EFLAGS: 00050212
[12002.517508] RAX: 000000005d1e747a RBX: fffffb298c2fb3f58 RCX: 0000000000000008
[12002.517510] RDX: 0000000000000344 RSI: 0000000000000040 RDI: 00007fdb33e8ee80
[12002.517511] RBP: 00007fdb33e8ec80 R08: ffff9510262ef640 R09: 0000000000000000
[12002.517512] R10: 000000000000000b R11: 000000000000000a R12: ffff950c8fca5d40
[12002.517513] R13: ffff950c8fca4080 R14: ffff950c8fca4080 R15: 00007fdb33e8ec80
[12002.517515] FS: 00007fdb32000340(0000) GS:ffff95128f600000(0000)
knlgS:0000000000000000
[12002.517516] CS: 0010 DS: 0000 ES: 0000 CR0: 0000000080050033
[12002.517517] CR2: 0000000000000344 CR3: 0000000204082000 CR4: 000000000350ef0
[12002.517520] Call Trace:
[12002.517521] <TASK>
[12002.517522] ? copy_fpstate_to_sigframe+0x98/0x330
[12002.517525] ? get_signal+0x7f2/0x990
[12002.517528] ? arch_do_signal_or_restart+0x64d/0x760
[12002.517531] ? early_xen_iret_patch+0x5/0xc
[12002.517535] ? exit_to_user_mode_prepare+0xd3/0x140
[12002.517538] ? asm_exc_page_fault+0xc/0x30
[12002.517540] ? irqentry_exit_to_user_mode+0x9/0x20
[12002.517542] ? asm_exc_page_fault+0x22/0x30
[12002.517545] ? early_xen_iret_patch+0x5/0xc
```

```

[12002.517547] </TASK>
...
[12002.517625] CR2: 0000000000000344
[12002.517627] ---[ end trace 0000000000000000 ]---
[12002.517629] RIP: 0010:copy_fpstate_to_sigframe+0xad/0x330
[12002.517631] Code: 1f 44 00 00 48 8d bd 00 02 00 00 be 40 00 00 00 e8 b8 eb 58
00 48 85 c0 75 bc 65 48 8b 1c 25 c0 0b 02 00 65 81 05 9f 73 1e 5d <00> 02 00 00
48 8b 03 f6 c4 40 0f 85 ab 00 00 00 83 83 f8 1a 00 00
[12002.517632] RSP: 0000:ffffb298c2fb3df0 EFLAGS: 00050212
[12002.517634] RAX: 000000005d1e747a RBX: fffffb298c2fb3f58 RCX: 0000000000000008
[12002.517635] RDX: 0000000000000344 RSI: 0000000000000040 RDI: 00007fdb33e8ee80
[12002.517636] RBP: 00007fdb33e8ec80 R08: ffff9510262ef640 R09: 0000000000000000
[12002.517637] R10: 000000000000000b R11: 000000000000000a R12: ffff950c8fca5d40
[12002.517638] R13: ffff950c8fca4080 R14: ffff950c8fca4080 R15: 00007fdb33e8ec80
[12002.517639] FS: 00007fdb32000340(0000) GS:ffff95128f600000(0000)
knlgS:0000000000000000
[12002.517641] CS: 0010 DS: 0000 ES: 0000 CR0: 0000000080050033
[12002.517642] CR2: 0000000000000344 CR3: 0000000204082000 CR4: 000000000350ef0

```

## Kernel Changelog:

commit a3c7c1a726a4c6b63b85e8c183f207543fd75e1b

Author: Juergen Gross <jgross@suse.com>

Date: Thu Jun 30 09:14:40 2022 +0200

x86: Clear .brk area at early boot

[ Upstream commit 38fa5479b41376dc9d7f57e71c83514285a25ca0 ]

The .brk section has the same properties as .bss: it is an alloc-only section and should be cleared before being used.

Not doing so is especially a problem for Xen PV guests, as the hypervisor will validate page tables (check for writable page tables and hypervisor private bits) before accepting them to be used.

Make sure .brk is initially zero by letting clear\_bss() clear the brk area, too.

Signed-off-by: Juergen Gross <jgross@suse.com>

Signed-off-by: Borislav Petkov <bp@suse.de>

Link: <https://lore.kernel.org/r/20220630071441.28576-3-jgross@suse.com>

Signed-off-by: Sasha Levin <sashal@kernel.org>

And early\_xen\_iret\_patch was added

<https://github.com/torvalds/linux/commit/8b87d8cec1b31ea710568ae49ba5f5146318da0d>

Then later urgently removed:

x86/xen: Use clear\_bss() for Xen PV guests

<https://github.com/torvalds/linux/commit/96e8fc5818686d4a1591bb6907e7fdb64ef29884>

And cleaned up in x86\_urgent\_for\_v5.19\_rc6:

<https://github.com/torvalds/linux/commit/74a0032b8524ee2bd4443128c0bf9775928680b0>

CONFIG\_XEN\_VIRTIO was added:

<https://github.com/torvalds/linux/commit/fa1f57421e0b1c57843902c89728f823abc32f02>

Upstream: 38fa5479b41376dc9d7f57e71c83514285a25ca0

Fix: 36e2f161fb01795722f2ff1a24d95f08100333dd

## Disclosure Timeline

- **2022-07-10** - Borislav Petkov & Juergen Gross fixes the vulnerability in mainline 5.19.rc6
- **2022-07-14** - Researcher encounters & reports vulnerability vulnerability on stable 5.18.11.

## Links

<https://sick.codes/sick-2022-128>

<https://github.com/sickcodes/security/blob/master/advisories/SICK-2022-128.md>

[https://github.com/torvalds/linux/blob/babf0bb978e3c9fce6c4eba6b744c8754fd43d8e/arch/x86/xen/mmu\\_pv.c#L1151](https://github.com/torvalds/linux/blob/babf0bb978e3c9fce6c4eba6b744c8754fd43d8e/arch/x86/xen/mmu_pv.c#L1151)

<https://github.com/torvalds/linux/commit/8b87d8cec1b31ea710568ae49ba5f5146318da0d>

<https://lore.kernel.org/all/20220308154317.815039833@infradead.org/>

<https://github.com/torvalds/linux/commit/96e8fc5818686d4a1591bb6907e7fdb64ef29884>

<https://lore.kernel.org/all/20220630071441.28576-2-jgross@suse.com/>

<https://github.com/torvalds/linux/commit/74a0032b8524ee2bd4443128c0bf9775928680b0>

<https://github.com/torvalds/linux/commit/fa1f57421e0b1c57843902c89728f823abc32f02>

<https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.9.324>

<https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.14.289>

<https://cdn.kernel.org/pub/linux/kernel/v4.x/ChangeLog-4.19.253>

<https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.4.207>

<https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.10.132>

<https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.15.56>

<https://cdn.kernel.org/pub/linux/kernel/v5.x/ChangeLog-5.18.13>

## Researchers

- Sick Codes <https://github.com/sickcodes> || <https://twitter.com/sickcodes>
- Borislav Petkov, SUSE <https://www.suse.com/>
- Juergen Gross, SUSE <https://www.suse.com/>

## CVE Links

<https://sick.codes/sick-2022-128>

<https://github.com/sickcodes/security/blob/master/advisories/SICK-2022-128.md>

<https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2022-36123>

<https://nvd.nist.gov/view/vuln/detail?vulnId=CVE-2022-36123>