

## Command Injection

Affecting fsa package, versions \*

INTRODUCED: 31 MAR 2020 CVE-2020-7615 CWE-79 FIRST ADDED BY SNYK

Share

### How to fix?

There is no fixed version for fsa .

### Overview

fsa is a File system auditor.

Affected versions of this package are vulnerable to Command Injection. The first argument of execGitCommand() , located within lib/rep.js#63 can be controlled by users without any sanitization to inject arbitrary commands.

### PoC

```
var root = require("fsa"); var attack_code = "& touch Song"; var dir = "./"; var options= {};  
root.rep.execGitCommand(attack_code,dir,options,function({}));
```

### Details

A cross-site scripting attack occurs when the attacker tricks a legitimate web-based application or site to accept a request as originating from a trusted source.

This is done by escaping the context of the web application; the web application then delivers that data to its users along with other trusted dynamic content, without validating it. The browser unknowingly executes malicious script on the client side (through client-side languages; usually JavaScript or HTML) in order to perform actions that are otherwise typically blocked by the browser's Same Origin Policy.

Injecting malicious code is the most prevalent manner by which XSS is exploited; for this reason, escaping characters in order to prevent this manipulation is the top method for securing code against this vulnerability.

Escaping means that the application is coded to mark key characters, and particularly key characters included in user input, to prevent those characters from being interpreted in a dangerous context. For example, in HTML, < can be coded as &lt; and > can be coded as &gt; ; in order to be interpreted and displayed as themselves in text, while within the code itself, they are used for HTML tags. If malicious content is injected into an application that escapes special characters and that malicious content uses < and > as HTML tags, those characters are nonetheless not interpreted as HTML tags by the browser if they've been correctly escaped in the application code and in this way the attempted attack is diverted.

The most prominent use of XSS is to steal cookies (source: OWASP HttpOnly) and hijack user sessions, but XSS exploits have been used to expose sensitive information, enable access to privileged services and functionality and deliver malware.

### Types of attacks

There are a few methods by which XSS can be manipulated:

Type	Origin	Description
Stored	Server	The malicious code is inserted in the application (usually as a link) by the attacker. The code is activated every time a user clicks the link.
Reflected	Server	The attacker delivers a malicious link externally from the vulnerable web site application to a user. When clicked, malicious code is sent to the vulnerable web site, which reflects the attack back to the user's browser.
DOM-based	Client	The attacker forces the user's browser to render a malicious page. The data in the page itself delivers the cross-site scripting data.
Mutated		The attacker injects code that appears safe, but is then rewritten and modified by the browser, while parsing the markup. An example is rebalancing unclosed quotation marks or even adding quotation marks to unquoted parameters.

### Affected environments

The following environments are susceptible to an XSS attack:

- Web servers
- Application servers
- Web application environments

### How to prevent

This section describes the top best practices designed to specifically protect your code:

- Sanitize data input in an HTTP request before reflecting it back, ensuring all data is validated, filtered or escaped before echoing anything back to the user, such as the values of query parameters during searches.
- Convert special characters such as ?, &, /, <, > and spaces to their respective HTML or URL encoded equivalents.
- Give users the option to disable client-side scripts.

LOW

Search by package name or CVE

### Snyk CVSS

Exploit Maturity Proof of concept

Attack Complexity High

See more

> NVD

7.8 HIGH

### Do your applications use this vulnerable package?

In a few clicks we can analyze your entire application and see what components are vulnerable in your application, and suggest you quick fixes.

Test your applications

### Snyk Learn

Learn about Command Injection vulnerabilities in an interactive lesson.

Start learning

Snyk ID SNYK-JS-FSA-564118

Published 31 Mar 2020

Disclosed 31 Mar 2020

Credit JHU System Security Lab

Report a new vulnerability

Found a mistake?

- [Redirect invalid requests.](#)
- [Detect simultaneous logins, including those from two separate IP addresses, and invalidate those sessions.](#)
- [Use and enforce a Content Security Policy \(source: Wikipedia\) to disable any features that might be manipulated for an XSS attack.](#)
- [Read the documentation for any of the libraries referenced in your code to understand which elements allow for embedded HTML.](#)

## References

- [Vulnerable Code](#)

## PRODUCT

[Snyk Open Source](#)

[Snyk Code](#)

[Snyk Container](#)

[Snyk Infrastructure as Code](#)

[Test with Github](#)

[Test with CLI](#)

## RESOURCES

[Vulnerability DB](#)

[Documentation](#)

[Disclosed Vulnerabilities](#)

[Blog](#)

[FAQs](#)

## COMPANY

[About](#)

[Jobs](#)

[Contact](#)

[Policies](#)

[Do Not Sell My Personal Information](#)

## CONTACT US

[Support](#)

[Report a new vuln](#)

[Press Kit](#)

[Events](#)

## FIND US ONLINE

## TRACK OUR DEVELOPMENT



© 2022 Snyk Limited

Registered in England and Wales. Company number: 09677925

Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.