Security problem of zabbix-agent2

There is a security problem with zabbix-agent2. zabbix-agent2-openrc package.

Old zabbix_agentd works correctly under "\$user" zabbix which is set by /etc/zabbix/zabbix_agentd.conf

```
2929 zabbix 0:00 /usr/sbin/zabbix_agentd -f
2955 zabbix 31:09 /usr/sbin/zabbix_agentd: collector [idle 1 sec]
2958 zabbix 2:34 /usr/sbin/zabbix_agentd: listener #3 [waiting for connecti
```

But "\$user" in zabbix-agent2 is set not in config file(/etc/zabbix/zabbix_agent2.conf), but in systemd , which is absent in alpine (and this is good).

It should be section of setting "\$user" in /etc/init.d/zabbix-agent2 for starting zabbix-agent2, otherwise it is executed (started) under root.

```
20950 root 0:00 supervise-daemon zabbix-agent2 --start /usr/sbin/zabbix_agent2 --
20951 root 0:00 /usr/sbin/zabbix_agent2
```

It is possible to get root access in client potentially during data transfer through public networks with default settings when using zabbix-agent2.

To upload designs, you'll need to enable LFS and have an admin enable hashed storage. More information

Child items © 0

No child items are currently assigned. Use child items to prioritize tasks that your team should complete in order to accomplish your goals!



When this merge request is accepted, this issue will be closed automatically.



