
snyk Vulnerability DB

Snyk Vulnerability Database > Maven > org.webjars.bower:chart.js

Prototype Pollution

Affecting org.webjars.bower:chart.js package, versions [,2.9.4)



Overview

org.webjars.bower:chart.js is a Simple HTML5 charts using the canvas element

Affected versions of this package are vulnerable to Prototype Pollution. The options parameter is not properly sanitized when it is processed. When the options are processed, the existing options (or the defaults options) are deeply merged with provided options. However, during this operation, the keys of the object being set are not checked, leading to a prototype pollution.

Details

Prototype Pollution is a vulnerability affecting JavaScript. Prototype Pollution refers to the ability to inject properties into existing JavaScript language construct prototypes, such as objects. JavaScript allows all Object attributes to be altered, including their magical attributes such as __proto___, constructor and prototype. An attacker manipulates these attributes to overwrite, or pollute, a JavaScript application object prototype of the base object by injecting other values. Properties on the Objects.prototype are then inherited by all the JavaScript objects through the prototype chain. When that happens, this leads to either denial of service by triggering JavaScript exceptions, or it tampers with the application source code to force the code path that the attacker injects, thereby leading to remote code execution.

There are two main ways in which the pollution of prototypes occurs:

- Unsafe Object recursive merge
- · Property definition by path

Unsafe Object recursive merge

The logic of a vulnerable recursive merge function follows the following high-level model:

```
merge (target, source)
foreach property of source

if property exists and is an object on both the target and the source merge(target[property], source[property]) else
target[property] = source[property]
```

When the source object contains a property named <code>__proto__</code> defined with <code>Object.defineProperty()</code>, the condition that checks if the property exists and is an object on both the target and the source passes and the merge recurses with the target, being the prototype of <code>Object</code> and the source of <code>Object</code> as defined by the attacker. Properties are then copied on the <code>Object</code> prototype.

Clone operations are a special sub-class of unsafe recursive merges, which occur when a recursive merge is conducted on an empty object: merge({}), source).

lodash and Hoek are examples of libraries susceptible to recursive merge attacks.

Property definition by path

There are a few JavaScript libraries that use an API to define property values on an object based on a given path. The function that is generally affected contains this signature: theFunction(object, path, value)

If the attacker can control the value of "path", they can set this value to __proto__.myValue . myValue is then assigned to the prototype of the class of the object.

Types of attacks

There are a few methods by which Prototype Pollution can be manipulated:

Туре	Origin	Short description
Denial of service (DoS)	Client	This is the most likely attack. DoS occurs when Object holds generic functions that are implicitly called for various operations (for example, toString and valueof). The attacker pollutes Object.prototype.someattr and alters its state to an unexpected value such as Int or Object. In this case, the code falls and is likely to cause a denial of service. For example: if an attacker pollutes Object.prototype.toString by defining it as an integer, if the codebase at any point was reliant on someobject.toString() it would fail.
Remote Code Execution	Client	Remote code execution is generally only possible in cases where the codebase evaluates a specific attribute of an object, and then executes that evaluation.



Snyk CVSS		
Exploit Matu	ırity	Proof of concept @
Attack Comp	plexity	Low @
Availability		HIGH
See more		
> NVD		9.8 CRITICAL
In a few clicl	ks we can analyz	s vulnerable package?
In a few clicl what compo suggest you	ks we can analyz onents are vulner	
In a few clicl what compo suggest you	ks we can analyz onents are vulner I quick fixes. applications	ze your entire application and see
In a few clici what compo suggest you Test your	ks we can analyz onents are vulner I quick fixes. applications	ze your entire application and see able in your application, and
In a few clici what compo suggest you Test your Snyk ID	ks we can analyz onents are vulner I quick fixes. applications	re your entire application and see able in your application, and

Found a mistake?

Report a new vulnerability

Туре	Origin	Short description
		For example: eval(someobject.someattr). In this case, if the attacker pollutes Object.prototype.someattr they are likely to be able to leverage this in order to execute code.
Property Injection	Client	The attacker pollutes properties that the codebase relies on for their informative value, including security properties such as cookies or tokens. For example: if a codebase checks privileges for someuser.isAdmin, then when the attacker pollutes Object.prototype.isAdmin and sets it to equal true, they can then achieve admin privileges.

Affected environments

The following environments are susceptible to a Prototype Pollution attack:

- Application server
- Web server
- Web browser

How to prevent

- 1. Freeze the prototype— use Object.freeze (Object.prototype) .
- 2. Require schema validation of JSON input.
- 3. Avoid using unsafe recursive merge functions.
- $4. \ \, \text{Consider using objects without prototypes (for example, \ \texttt{Object.create(null)}), breaking the prototype chain and preventing pollution.}$
- 5. As a best practice use $\,\mbox{Map}\,$ instead of $\,\mbox{Object}\,$.

For more information on this vulnerability type:

Arteau, Oliver. "JavaScript prototype pollution attack in NodeJS application." GitHub, 26 May 2018

References

GitHub PR

PRODUCT

Snyk Open Source

Snyk Code

Snyk Container

Snyk Infrastructure as Code

Test with Github

Test with CLI

RESOURCES
Vulnerability DB

vaniorability De

Documentation

Disclosed Vulnerabilities

Blog

FAQs

COMPANY

Jobs

Contact

Policies

Do Not Sell My Personal Information

CONTACT US

Support

Report a new vuln

Press Kit

Events

FIND US ONLINE

TRACK OUR DEVELOPMENT





Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.