heap-use-after-free in radareorg/radare2

✓ Valid Reported on Apr 5th 2022

1

Description

Whilst experimenting with radare2, built from version 5.6.6, we are able to induce a vulnerability at reg.c:101 in function r_reg_get_name_idx, using radare2 as a harness.

```
99:
       R_API int r_reg_get_name_idx(const char *type) {
        r return val if fail (type, -1);
100:
//use-after-free here
101:
        if (type[0] && type[1] && !type[2])
102:
        switch (*type | (type[1] << 8)) {</pre>
103:
        /* flags */
104:
        case 'Z' + ('F' << 8): return R REG NAME ZF;</pre>
105:
        case 'S' + ('F' << 8): return R REG NAME SF;</pre>
        case 'C' + ('F' << 8): return R REG NAME CF;</pre>
106:
        case '0' + ('F' << 8): return R REG NAME OF;</pre>
107:
108:
        /* apr */
        case 'P' + ('C' << 8): return R REG NAME PC;</pre>
109:
        case 'S' + ('R' << 8): return R REG NAME SR;</pre>
110:
111:
        case 'L' + ('R' << 8): return R REG NAME LR;
112:
        case 'S' + ('P' << 8): return R_REG_NAME_SP;</pre>
113:
        case 'B' + ('P' << 8): return R REG NAME BP;</pre>
        case 'S' + ('N' << 8): return R REG NAME SN;</pre>
114:
115:
        /* args */
116:
        case 'A' + ('0' << 8): return R REG NAME A0;
        case 'A' + ('1' << 8): return R REG NAME A1;</pre>
117:
118:
        case 'A' + ('2' << 8): return R REG NAME A2;
119:
        case 'A' + ('3' << 8): return R REG NAME A3;
120:
        case 'A' + ('4' << 8): return R REG NAME A4;
121:
        case 'A' + ('5' << 8): return R REG NAME A5;
122:
        case 'A' + ('6' << 8): return R REG NAME A6;
        case 'A' + ('7' << 8): return R REG NAME A7;
123:
```

COCO INI I /101 // 0\. notunn D DEC MAME AO.

```
124:
        case A + ( & << &): return K_KEG_NAME_A&;
        case 'A' + ('9' << 8): return R_REG_NAME_A9;</pre>
125:
126:
        /* return values */
127:
        case 'R' + ('0' << 8): return R_REG_NAME_R0;</pre>
128:
        case 'R' + ('1' << 8): return R_REG_NAME_R1;</pre>
        case 'R' + ('2' << 8): return R_REG_NAME_R2;</pre>
129:
130:
        case 'R' + ('3' << 8): return R REG NAME R3;
        case 'F' + ('0' << 8): return R REG NAME F0;
131:
        case 'F' + ('1' << 8): return R_REG_NAME_F1;</pre>
132:
        case 'F' + ('2' << 8): return R_REG_NAME_F2;</pre>
133:
134:
        case 'F' + ('3' << 8): return R REG NAME F3;
135:
136:
        return -1;
137: }
```

Due to not properly handling pointers, a heap-based use-after-free will be triggered when the software encounters a malformed file, which could result in denial of service. We found that the vulnerability exists in the latest master branch as well.

Environment

Ubuntu 20.04 LTS x86_64 gcc 10.3.0

Proof of Concept

The POC is: poc
The reproducing process is:

```
# build with address sanitizer
SANITIZE=address ./sys/sanitize.sh
# disable some features of address sanitizer to avoid false positives
export ASAN_OPTIONS=detect_leaks=0:abort_on_error=1:symbolize=1:allocator_n
# trigger the crash
./radare2 -AA -qq POC_FILE
```

 \blacktriangleleft

```
==92948==ERROR: AddressSanitizer: heap-use-after-free on address 0x60200031
READ of size 1 at 0x60200031b590 thread T0
    #0 0x7ffff1d1e8f5 in r_reg_get_name_idx /work/libraries/radare2-5.6.6/]
    #1 0x7ffff1d204f9 in r reg get /work/libraries/radare2-5.6.6/libr/reg/r
    #2 0x7ffff1d203a4 in r reg getv /work/libraries/radare2-5.6.6/libr/reg/
    #3 0x7ffff4736f70 in r_core_anal_esil /work/libraries/radare2-5.6.6/lik
    #4 0x7ffff4581bea in cmd anal all /work/libraries/radare2-5.6.6/libr/cc
    #5 0x7ffff45874d8 in cmd anal /work/libraries/radare2-5.6.6/libr/core/c
    #6 0x7ffff47024c3 in r_cmd_call /work/libraries/radare2-5.6.6/libr/core
    #7 0x7ffff4638043 in r_core_cmd_subst_i /work/libraries/radare2-5.6.6/]
    #8 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/lik
    #9 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr/c
    #10 0x7ffff463f15d in r_core_cmd /work/libraries/radare2-5.6.6/libr/cor
    #11 0x7ffff463fd0b in r_core_cmd0 /work/libraries/radare2-5.6.6/libr/cc
    #12 0x7ffff458090f in cmd anal all /work/libraries/radare2-5.6.6/libr/c
    #13 0x7ffff45874d8 in cmd_anal /work/libraries/radare2-5.6.6/libr/core,
    #14 0x7ffff47024c3 in r_cmd_call /work/libraries/radare2-5.6.6/libr/cor
    #15 0x7ffff4638043 in r core cmd subst i /work/libraries/radare2-5.6.6/
    #16 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/li
    #17 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr/
    #18 0x7ffff463f15d in r core cmd /work/libraries/radare2-5.6.6/libr/cor
    #19 0x7ffff463fd0b in r core cmd0 /work/libraries/radare2-5.6.6/libr/cc
    #20 0x7fffff7185010 in r main radare2 /work/libraries/radare2-5.6.6/libr
    #21 0x555555556ff in main /work/libraries/radare2-5.6.6/binr/radare2/r
    #22 0x7ffff6f6b0b2 in libc start main (/lib/x86 64-linux-gnu/libc.so.
    #23 0x55555555528d in start (/work/libraries/radare2-5.6.6/binr/radare
```

0x60200031b590 is located 0 bytes inside of 4-byte region [0x60200031b590, 6 freed by thread TO here:

```
#0 0x7fffff769b8f7 in interceptor free ../../../src/libsanitizer/as
#1 0x7ffff1d1f125 in r reg free internal /work/libraries/radare2-5.6.6,
#2 0x7ffff1d2bd9f in r_reg_set_profile_string /work/libraries/radare2-5
#3 0x7ffff2b9ffd5 in r anal set reg profile /work/libraries/radare2-5.6
#4 0x7ffff2ba04d7 in r anal set bits /work/libraries/radare2-5.6.6/libr
#5 0x7ffff464fe19 in cb asmbits /work/libraries/radare2-5.6.6/libr/core
#6 0x7ffff6da6bce in r config set i /work/libraries/radare2-5.6.6/libr,
#7 0x7ffff4693017 in r core seek arch bits /work/libraries/radare2-5.6.
#8 0x7ffff4736884 in r core anal esil /work/libraries/rad
                                                            Chat with us
#9 0x7ffff4581bea in cmd anal all /work/libraries/radar
#10 0x7ffff45874d8 in cmd anal /work/libraries/radare2-5.6.6/iipr/core/
```

```
#12 0x7ffff4638043 in r_core_cmd_subst_i /work/libraries/radare2-5.6.6,
#13 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/li
#14 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr,
#15 0x7ffff463f15d in r core cmd /work/libraries/radare2-5.6.6/libr/cor
#16 0x7ffff463fd0b in r core cmd0 /work/libraries/radare2-5.6.6/libr/cc
#17 0x7ffff458090f in cmd anal all /work/libraries/radare2-5.6.6/libr/c
#18 0x7ffff45874d8 in cmd anal /work/libraries/radare2-5.6.6/libr/core/
#19 0x7ffff47024c3 in r_cmd_call /work/libraries/radare2-5.6.6/libr/cor
#20 0x7ffff4638043 in r_core_cmd_subst_i /work/libraries/radare2-5.6.6,
#21 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/li
#22 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr/
#23 0x7ffff463f15d in r core cmd /work/libraries/radare2-5.6.6/libr/cor
#24 0x7ffff463fd0b in r_core_cmd0 /work/libraries/radare2-5.6.6/libr/cc
#25 0x7ffff7185010 in r main radare2 /work/libraries/radare2-5.6.6/libr
#26 0x555555556ff in main /work/libraries/radare2-5.6.6/binr/radare2/r
#27 0x7ffff6f6b0b2 in __libc_start_main (/lib/x86_64-linux-gnu/libc.so.
```

#11 Ux/tttt4/U24c3 in r_cmd_call /work/libraries/radare2-5.6.6/libr/cor

previously allocated by thread TO here:

```
#0 0x7fffff76429f7 in interceptor strdup ../../../src/libsanitizer/
#1 0x7fffff72b2ed8 in r str new /work/libraries/radare2-5.6.6/libr/util,
#2 0x7fffff72b3e62 in r str dup /work/libraries/radare2-5.6.6/libr/util,
#3 0x7ffff1d1ede8 in r reg set name /work/libraries/radare2-5.6.6/libr/
#4 0x7ffff1d2ab6c in parse alias /work/libraries/radare2-5.6.6/libr/res
#5 0x7ffff1d2c556 in r reg set profile string /work/libraries/radare2-5
#6 0x7ffff2b9ffd5 in r anal set reg profile /work/libraries/radare2-5.6
#7 0x7ffff2ba04d7 in r anal set bits /work/libraries/radare2-5.6.6/libr
#8 0x7ffff464fe19 in cb asmbits /work/libraries/radare2-5.6.6/libr/core
#9 0x7ffff6da6bce in r config set i /work/libraries/radare2-5.6.6/libraries/
#10 0x7ffff4693017 in r core seek arch bits /work/libraries/radare2-5.6
#11 0x7ffff4736884 in r core anal esil /work/libraries/radare2-5.6.6/li
#12 0x7ffff4581bea in cmd anal all /work/libraries/radare2-5.6.6/libr/c
#13 0x7ffff45874d8 in cmd anal /work/libraries/radare2-5.6.6/libr/core/
#14 0x7ffff47024c3 in r cmd call /work/libraries/radare2-5.6.6/libr/cor
#15 0x7ffff4638043 in r core cmd subst i /work/libraries/radare2-5.6.6,
#16 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/li
#17 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr/
Chat with us
#19 0x7ffff463fd0b in r core cmd0 /work/libraries/radar
#20 0x7ffff458090f in cmd anal all /work/libraries/radarez-5.6.6/11pr/(
```

```
#21 0x/tttt458/4d8 in cmd anal /work/libraries/radare2-5.6.6/libr/core/
   #22 0x7ffff47024c3 in r cmd call /work/libraries/radare2-5.6.6/libr/cor
   #23 0x7ffff4638043 in r core cmd subst i /work/libraries/radare2-5.6.6/
   #24 0x7ffff462f347 in r core cmd subst /work/libraries/radare2-5.6.6/li
   #25 0x7ffff463e901 in run cmd depth /work/libraries/radare2-5.6.6/libr,
   #26 0x7ffff463f15d in r core cmd /work/libraries/radare2-5.6.6/libr/cor
   #27 0x7ffff463fd0b in r core cmd0 /work/libraries/radare2-5.6.6/libr/cc
   #28 0x7fffff7185010 in r main radare2 /work/libraries/radare2-5.6.6/libr
    #29 0x5555555556ff in main /work/libraries/radare2-5.6.6/binr/radare2/r
SUMMARY: AddressSanitizer: heap-use-after-free /work/libraries/radare2-5.6.
Shadow bytes around the buggy address:
  0x0c048005b660: fa fa fd fa fa fd fa fa fd fa fa fd fa
  0x0c048005b670: fa fa fd fa
  0x0c048005b680: fa fa fd fa
  0x0c048005b690: fa fa fd fa
  0x0c048005b6a0: fa fa fd fa
=>0x0c048005b6b0: fa fa[fd]fa fa fa fd fa fa fd fa fa fd fa
  0x0c048005b6c0: fa fa fd fa
  0x0c048005b6d0: fa fa fd fa
  0x0c048005b6e0: fa fa fd fa
  0x0c048005b6f0: fa fa fd fa fa fd fa fa fd fa fa fd fa
  0x0c048005b700: fa fa fd fa fa fd fa fa fa fd fa fa fa fa fd fa
Shadow byte legend (one shadow byte represents 8 application bytes):
  Addressable:
                         00
  Partially addressable: 01 02 03 04 05 06 07
 Heap left redzone:
                          fa
  Freed heap region:
                          fd
  Stack left redzone:
                          f1
  Stack mid redzone:
                          f2
  Stack right redzone:
                          f3
  Stack after return:
                          f5
  Stack use after scope:
                          f8
  Global redzone:
                          f9
  Global init order:
                          f6
  Poisoned by user:
                          f7
  Container overflow:
                          fc
 Array cookie:
                           ac
                                                                Chat with us
  Intra object redzone:
                          bb
  ASan internal:
                          fe
```

Lett alloca redzone: ca Right alloca redzone: cb Shadow gap: cc

==92948==ABORTING

Aborted



Impact

This vulnerability is capable of inducing denial of service.

CVE

CVE-2022-1284 (Published)

Vulnerability Type

CWE-416: Use After Free

Severity

High (7.5)

Registry

Other

Affected Version

5.6.6

Visibility

Public

Status

Fixed

Found by



hdthky @hdthky

unranked V

Fixed by



pancake

@trufae

maintainer

This report was seen 651 times.

We are processing your report and will contact the **radareorg/radare2** team within 24 hours. 8 months ago

We have contacted a member of the radareorg/radare2 team and are waiting to hear back 8 months ago

pancake 8 months ago

Maintainer

I can reproduce! working on the fix right now

pancake 8 months ago

Maintainer

Good catch! thank you for reporting! this is causing a random DoS

pancake validated this vulnerability 8 months ago

hdthky has been awarded the disclosure bounty 🗸

The fix bounty is now up for grabs

pancake marked this as fixed in 5.6.8 with commit 64a82e 8 months ago

pancake has been awarded the fix bounty 🗸

This vulnerability will not receive a CVE 🗶

hdthky 7 months ago

Researcher

This bug was found by Xingyuan Mo from 360 IceSword Lab

Sign in to join this conversation

huntr

home

hacktivity

leaderboard

FAQ

contact us

terms

privacy policy

part of 418sec

company

about

team