New issue

## Authentication Bypass in Webui #837



⊙ Open rashley-iqt opened this issue on Mar 10, 2021 · 0 comments

rashley-iqt commented on Mar 10, 2021

(Contributor)

Jump to bottom

An unauthenticated user can utilize information provided by the login page of the webui component to craft HTTP requests that will allow that user to create, read, update, and delete entries in the subscriber database. This includes the ability to add administrative users, add/modify/delete subscribers, and add/modify/delete profiles.

Properly crafted HTTP GET and DELETE requests with empty bodies will cause data to be returned or deleted on the following routes:

http://:3000/api/db/profile

http://:3000/api/db/subscriber

http://:3000/api/db/account/

http://:3000/api/db/profile/<profile\_id>

http://:3000/api/db/subscriber/<imsi\_number>

Properly crafted HTTP POST, PUT and PATCH requests with properly crafted bodies will cause data to be inserted or updated on the following routes:

http://:3000/api/db/account

http://:3000/api/db/profile

http://:3000/api/db/subscriber

http://:3000/api/db/account/

http://:3000/api/db/profile/<profile\_id>

http://:3000/api/db/subscriber/<imsi\_number>

This is caused by the configuration of express js in index.js. This should be updated to correctly validate the user making the API calls.

☐ This was referenced on Mar 10, 2021

Add API tokens #838



Authentication Bypass in Webui nextepc/nextepc#31



No one assigned

None yet

Projects

Milestone

No milestone

No branches or pull requests

1 participant

