## [FD] KSA-Dev-008: Authenticated XSRF leads to complete account takeover in all UNIBOX WiFi Hotspot Controller

## Kaustubh via Fulldisclosure Sun, 07 Feb 2021 09:34:55 -0800

```
. contents:: Table Of Content
Title:- Authenticated XSRF leads to complete account takeover in all UNIBOX WiFi Hotspot Controller.

CVE ID:- Not -Yet - Assign
Author: Kaustubh G. Padwad
Vendor: Wifi-soft (https://www.wifi-soft.com/)
Products:

1.Unibox SMB
2.UniBox - Enterprise Series
3.UniBox - Campus Series
 Tested Version: :Controller Model : U-50 \mid UniBox 2.4 (Respetive for others) Severity: High--Critical
UniBox is one of the most innovative and reliable Hotspot Controllers in the market today. You can install UniBox to manage any sized WiFi network without having to replace any existing infrastructure. With UniBox, you don't need any other solution for managing WiFi access. It comes packed with features so just one box is enough to handle all the functions of WiFi hotspots.
 An issue was discovered on Unibox U-50 with version Unibox 2.4 and potentially respected all other devices. There is CSRF via /tools/network-trace with resultant XSS due to lack of csrf token and user input validation.
   Additional Information
   The web interface of the SMB Unibox does not validate the csrftoken, and the /tools/network-trace page does not properly sanitize the user input which leads to xss, by combining this two attack we can form the XSRF request which leads to complete account takeover using XSRF.
   Cross Site Request Forgery (CSRF)
   How to Reproduce: (POC):
Curl -i -s -k - X 'FPOST' \

-H $'Host: 'IP-OF-Device' -H $'User-Agent: Mozilla/5.0 (X11; Linux x86 64; rv:68.0) Gecko/20100101 Firefox/68.0' -H $'Accept: text/html, application/xhtml+xml, application/xml;q=0.9, "';q=0.8' -H $'Accept-Encoding: qzip, deflate' -H $'Accept-Encoding: qzip, deflate' -H $'Referer: http://IP-OF-Device/tools/network-trace' -H $'Content-Type: application/x-www-form-urlencoded' -H $'Content-Length: 130' -H $'Content-Length: 130' -H $'Content-Length: 130' -H $'PHSESSID=8619fsqxxxxxxxxxxxxxxx' -H $'Upgrade-Insecure-Requests: 1' \
-b $'PHPSESSID=6619fsq22vi4vxxxxxxxxxxxxxx'
-d $'PHPSESSID=6619fsq22vi4vxxxxxxxxxxxxxxxx'
 Vulnerable Pages to XSS :- <a href="http://xxx.xxx.xx.xx/authentication/list">http://xxx.xxx.xx.xx/authentication/list</a> users
   http://xxx.xxx.xx.xx/authentication/list_byod?usertype=raduser
   CSRF POC
   <html>
          </body>
 </html>
   [Affected Component] /tools/network-trace and CSRF Vulnerabilities,
   [Attack Type]
   [Impact Code execution]
   [Attack Vectors] once victim open the crafted url the device will get compromise % \left( 1\right) =\left( 1\right) \left( 1\right) 
   Mitigation
```

[Vendor of Product]
WiF-Soft (http://https://www.wifi-soft.com/company/about.php)

## credits:

- \* Kaustubh Padwad

  \* Information Security Researcher

  \* kingkaust...@me.com

  \* https://szcurityb3ast.github.io/

  \* https://twitter.com/szcurityb3ast

  \* http://breakthesec.com

  \* https://www.linkedin.com/in/kaustubhpadwad

Sent through the Full Disclosure mailing list https://nmap.org/mailman/listinfo/fulldisclosure Web Archives & RSS: http://seclists.org/fulldiscl

- Previous message View by thread View by date Next message

## Reply via email to



Search the site Search fulldisclosure

- The Mail Archive home
- fulldisclosure all messages fulldisclosure about the list

- Expand Previous message Next message

- The Mail Archive home
  Add your mailing list
  FAQ
  Support

- Privacy 57798d9c-1fdc-9cab-ee49-03f2be256e8d@me.com