

[\[Date Prev\]](#) [\[Date Next\]](#) [\[Thread Prev\]](#) [\[Thread Next\]](#) [\[Date Index\]](#) [\[Thread Index\]](#)

Re: [PATCH] hw/net/e1000e: advance desc_offset in case of null descripto

From: Jason Wang**Subject:** Re: [PATCH] hw/net/e1000e: advance desc_offset in case of null descriptor**Date:** Thu, 12 Nov 2020 13:51:32 +0800**User-agent:** Mozilla/5.0 (X11; Linux x86_64; rv:68.0) Gecko/20100101 Thunderbird/68.10.0

On 2020/11/11 下午9:06, P J P wrote:

From: Prasad J Pandit <pjp@fedoraproject.org>

While receiving packets via e1000e write_packet_to_guest() routine, 'desc_offset' is advanced only when RX descriptor is processed. And RX descriptor is not processed if it has NULL buffer address. This may lead to an infinite loop condition. Increment 'desc_offset' to process next descriptor in the ring to avoid infinite loop.

Reported-by: Cheol-woo Myung <330cjfdn@gmail.com>

Signed-off-by: Prasad J Pandit <pjp@fedoraproject.org>

```
---
hw/net/e1000e_core.c | 8 +++++---
1 file changed, 4 insertions(+), 4 deletions(-)

diff --git a/hw/net/e1000e_core.c b/hw/net/e1000e_core.c
index bcf46696f..3b096db3a4 100644
--- a/hw/net/e1000e_core.c
+++ b/hw/net/e1000e_core.c
@@ -1596,13 +1596,13 @@ e1000e_write_packet_to_guest(E1000ECORE *core, struct
NetRxPkt *pkt,
                                (const char *) &fcs_pad, e1000x_fcs_len(core->mac));
        }
-       desc_offset += desc_size;
-       if (desc_offset >= total_size) {
-           is_last = true;
-       }
+       } else { /* as per intel docs; skip descriptors with null buf addr */
+           trace_e1000e_rx_null_descriptor();
+       }
+       desc_offset += desc_size;
+       if (desc_offset >= total_size) {
+           is_last = true;
+       }
    }
    e1000e_write_rx_descr(core, desc, is_last ? core->rx_pkt : NULL,
                        rss_info, do_ps ? ps_hdr_len : 0,
                        &state.written);
```

Applied.

Thanks

reply via email to

[Jason Wang](#)[\[Prev in Thread\]](#)**Current Thread**[\[Next in Thread\]](#)

- [\[PATCH\] hw/net/e1000e: advance desc_offset in case of null descriptor](#), *P J P*, 2020/11/11
 - Re: [PATCH] hw/net/e1000e: advance desc_offset in case of null descriptor, *Jason Wang* <=>

- Prev by Date: [Re: \[PATCH-for-5.2 v2\] hw/i386/acpi-build: Fix maybe-uninitialized error when ACPI hotplug off](#)
- Next by Date: [Re: \[PATCH\] net: do not exit on "netdev_add help" monitor command](#)
- Previous by thread: [\[PATCH\] hw/net/e1000e: advance desc_offset in case of null descriptor](#)
- Next by thread: [\[PATCH 0/2\] char: Deprecate backend aliases](#)
- Index(es):
 - [Date](#)
 - [Thread](#)