

set_cookie function in Helpers/cookie_helper.php is not using the default value \$secure i specified in app/Config/Cookie.php.

This used to work in CI3 because I think the default value of \$secure param of set_cookie function used to be null which later on fallback to default.****

Steps to Reproduce

- 1. Set public \$secure = true in /app/Config/Cookie.php'
- 2. Call the helper function set_cookie

```
helper('cookie');
set_cookie([
    'name' => 'pmw',
    'value' => 2,
    'samesite' => 'None',
]);
```

3. CookieException::forInvalidSameSiteNone() is thrown although \$secure was suppose to be true

Expected Output

No exception

Anything else?

No response



```
ddevsr commented on Sep 14 • edited ▼
```

Collaborator

You must set variable secure to true, by default function set_cookie secure = false

If you want create cookie with default config (see

https://codeigniter.com/user_guide/libraries/cookies.html#creating-cookies) or you can using set_cookie helper

```
$cookieConfig = config('cookie');
set_cookie([
           'name'
                     => 'pmw',
           'value' => 2,
           'expire'
                     => $cookieConfig->expires,
           'domain' => $cookieConfig->domain,
           'path'
                     => $cookieConfig->path,
           'prefix' => $cookieConfig->prefix,
           'secure' => $cookieConfig->secure,
          'httponly' => $cookieConfig->httponly,
          'samesite' => $cookieConfig->samesite,
]);
```

hamzawain7 commented on Sep 15

Author

set_cookie function uses new Cookie in its implementation which makes it get the default value of "domain", "samesite" and other non bool config values, but doesn't for "secure". Isn't that inconsistency? Won't it better for all of them to fallback to values in config?



kenjis added bug and removed bug labels on Sep 15

kenjis commented on Sep 15 • edited ▼

Member

When constructing the Cookie object, only the name attribute is required. All other else are optional. If the optional attributes are not modified, their values will be filled up by the default values saved in the Cookie class. To override the defaults currently stored in the class, you can pass a Config\Cookie instance or an array of defaults to the static Cookie::setDefaults() method.

https://codeigniter4.github.io/Codelgniter4/libraries/cookies.html#creating-cookies

Reading the user guide, I think the values in the Config file should be used for unspecified items.

kenjis commented on Sep 15 • edited ▼

Member

This used to work in CI3 because I think the default value of \$secure param of set_cookie function used to be null which later on fallback to default.

Exactly.

https://github.com/bcit-

ci/Codelgniter/blob/9b8f2b7a8405acd1b8ad5956ada3d84472b1e8ae/system/helpers/cookie_helper.php#L71

Ref.

Codelgniter4/system/Helpers/cookie_helper.php Lines 39 to 49 in 354b43a function set_cookie(39 40 \$name, 41 string \$value = '', string \$expire = '', 42 string \$domain = '', 43 44 string \$path = '/', string \$prefix = '', 45 bool \$secure = false, 46 bool \$httpOnly = false, 47 ?string \$sameSite = null 48 49) {

kenjis commented on Sep 15

Member

This seems the first commit: https://github.com/codeigniter4/Codelgniter4/pull/241/files#diff-1ee301297e39aa12b421d2ad72d266269f4fc8fe56c01c366fbcdf16056a942dR82

However, no reason is given for the change in behavior from CI3.



kenjis mentioned this issue on Sep 15

fix: set_cookie() does not use Config\Cookie values #6544

№ Merged

5 tasks

kenjis commented on Sep 15

Member

I sent a PR: #6544



kenjis closed this as completed in #6544 on Sep 19

Assignees

No one assigned

Labels

bug

Projects		
None yet		
Milestone		
No milestone		
Development		

Successfully merging a pull request may close this issue.

fix: set_cookie() does not use Config\Cookie values kenjis/Codelgniter4

3 participants





