

## Cross-site Scripting (XSS)

Affecting [org.webjars.bowergithub.angular:angular](#) package, versions [0,]

INTRODUCED: 14 JUL 2022 [CVE-2022-25869](#)  [CWE-79](#) 

Share 

### How to fix?

There is no fixed version for  
`org.webjars.bowergithub.angular:angular`.

### Overview

[org.webjars.bowergithub.angular:angular](#) is a package that lets you write client-side web applications as if you had a smarter browser. It also lets you use HTML as your template language and lets you extend HTML's syntax to express your application's components clearly and succinctly.

Affected versions of this package are vulnerable to Cross-site Scripting (XSS) due to insecure page caching in the Internet Explorer browser, which allows interpolation of `<textarea>` elements.

### Details

A cross-site scripting attack occurs when the attacker tricks a legitimate web-based application or site to accept a request as originating from a trusted source.


This is done by escaping the context of the web application; the web application then delivers that data to its users along with other trusted dynamic content, without validating it. The browser unknowingly executes malicious script on the client side (through client-side languages; usually JavaScript or HTML) in order to perform actions that are otherwise typically blocked by the browser's Same Origin Policy.

Injecting malicious code is the most prevalent manner by which XSS is exploited; for this reason, escaping characters in order to prevent this manipulation is the top method for securing code against this vulnerability.



### Snyk CVSS

Exploit  
Maturity

Proof of concept  


Attack Complexity High 

User Interaction Required 

[See more](#)

> NVD

6.1 MEDIUM

### Do your applications use this vulnerable package?

In a few clicks we can analyze your entire application and see what components are vulnerable in your application, and suggest you quick fixes.

[Test your applications](#)

Escaping means that the application is coded to mark key characters, and particularly key characters included in user input, to prevent those characters from being interpreted in a dangerous context. For example, in HTML, `<` can be coded as `&lt;` ; and `>` can be coded as `&gt;` ; in order to be interpreted and displayed as themselves in text, while within the code itself, they are used for HTML tags. If malicious content is injected into an application that escapes special characters and that malicious content uses `<` and `>` as HTML tags, those characters are nonetheless not interpreted as HTML tags by the browser if they've been correctly escaped in the application code and in this way the attempted attack is diverted.

The most prominent use of XSS is to steal cookies (source: OWASP HttpOnly) and hijack user sessions, but XSS exploits have been used to expose sensitive information, enable access to privileged services and functionality and deliver malware.

### Types of attacks

There are a few methods by which XSS can be manipulated:

| Type      | Origin | Description   |
|-----------|--------|---|
| Stored    | Server | The malicious code is inserted in the application (usually as a link) by the attacker. The code is activated every time a user clicks the link.   |
| Reflected | Server | The attacker delivers a malicious link externally from the vulnerable web site application to a user. When clicked, malicious code is sent to the vulnerable web site, which reflects the attack back to the user's browser.        |
| DOM-based | Client | The attacker forces the user's browser to render a malicious page. The data in the page itself delivers the cross-site scripting data.  |
| Mutated   |        | The attacker injects code that appears safe, but is then rewritten and modified by the browser, while parsing the markup. An example is rebalancing unclosed quotation marks or even adding quotation marks to unquoted parameters. |

### Affected environments

The following environments are susceptible to an XSS attack:

- Web servers
- Application servers
- Web application environments

### How to prevent

Learn about Cross-site Scripting (XSS) vulnerabilities in an interactive lesson.

Start learning

SnykSNYK-JAVA-  
ID ORGWEBJARSBOWERGITHUBAI  
2949784

Published14 Jul 2022

Disclosed14 Jul 2022

CreditMichael Prentice

Report a new vulnerability

Found a mistake?

This section describes the top best practices designed to specifically protect your code:

- Sanitize data input in an HTTP request before reflecting it back, ensuring all data is validated, filtered or escaped before echoing anything back to the user, such as the values of query parameters during searches.
- Convert special characters such as `?`, `&`, `/`, `<`, `>` and spaces to their respective HTML or URL encoded equivalents.
- Give users the option to disable client-side scripts.
- Redirect invalid requests.
- Detect simultaneous logins, including those from two separate IP addresses, and invalidate those sessions.
- Use and enforce a Content Security Policy (source: Wikipedia) to disable any features that might be manipulated for an XSS attack.
- Read the documentation for any of the libraries referenced in your code to understand which elements allow for embedded HTML.

## References

- [PoC](#)

## PRODUCT

[Snyk Open Source](#)

[Snyk Code](#)

[Snyk Container](#)

[Snyk Infrastructure as Code](#)

[Test with Github](#)

[Test with CLI](#)

## RESOURCES

[Vulnerability DB](#)

[Documentation](#)

[Disclosed Vulnerabilities](#)

[Blog](#)

[FAQs](#)

## COMPANY

[About](#)

[Jobs](#)

[Contact](#)

[Policies](#)

[Do Not Sell My Personal Information](#)

## CONTACT US

[Support](#)

[Report a new vuln](#)

[Press Kit](#)

[Events](#)

## FIND US ONLINE

## TRACK OUR DEVELOPMENT



Join the >>  
community

© 2022 Snyk Limited

Registered in England and Wales. Company number: 09677925

Registered address: Highlands House, Basingstoke Road, Spencers Wood, Reading, Berkshire, RG7 1NT.