```
☐ tensorflow / tensorflow (Public)
<> Code
            Issues 2.1k  Pull requests 283
                                                      Actions Projects 1
  ጕ 5100e359ae ▼
tensorflow / tensorflow / core / kernels / quantized_pooling_ops.cc
      jpienaar Rename to underlying type rather than alias ... X
                                                                                        ( History
 As 6 contributors 😭 🔠 🐞 🐠
  150 lines (125 sloc) | 5.92 KB
        /* Copyright 2015 The TensorFlow Authors. All Rights Reserved.
    2
        Licensed under the Apache License, Version 2.0 (the "License");
    3
        you may not use this file except in compliance with the License.
        You may obtain a copy of the License at
    5
    6
    7
            http://www.apache.org/licenses/LICENSE-2.0
    8
    9
        Unless required by applicable law or agreed to in writing, software
        distributed under the License is distributed on an "AS IS" BASIS,
   10
        WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
   11
        See the License for the specific language governing permissions and
   12
        limitations under the License.
   13
   14
        15
   16
        // See docs in ../ops/nn_ops.cc.
   17
   18
        #define EIGEN_USE_THREADS
   19
        #include "third_party/eigen3/unsupported/Eigen/CXX11/Tensor"
   20
        #include "tensorflow/core/framework/numeric_op.h"
   21
        #include "tensorflow/core/framework/op_kernel.h"
   22
        #include "tensorflow/core/framework/tensor.h"
   23
        #include "tensorflow/core/framework/tensor_shape.h"
   24
        #include "tensorflow/core/kernels/ops_util.h"
   25
        #include "tensorflow/core/kernels/pooling_ops_common.h"
        #include "tensorflow/core/lib/core/errors.h"
   27
        #include "tensorflow/core/platform/logging.h"
   28
   29
        #include "tensorflow/core/util/padding.h"
```

```
30
     #include "tensorflow/core/util/tensor format.h"
31
32
     namespace tensorflow {
33
34
     typedef Eigen::ThreadPoolDevice CPUDevice;
35
     template <typename Device, typename T>
36
     class QuantizedAvgPoolingOp : public OpKernel {
37
38
      public:
       explicit QuantizedAvgPoolingOp(OpKernelConstruction* context)
39
40
           : OpKernel(context) {
         OP REQUIRES OK(context, context->GetAttr("ksize", &ksize ));
41
         OP REQUIRES(context, ksize .size() == 4,
42
43
                     errors::InvalidArgument("Sliding window ksize field must "
44
                                              "specify 4 dimensions"));
         OP REQUIRES OK(context, context->GetAttr("strides", &stride ));
45
         OP_REQUIRES(context, stride_.size() == 4,
46
47
                     errors::InvalidArgument("Sliding window strides field must "
                                              "specify 4 dimensions"));
48
         OP REQUIRES OK(context, context->GetAttr("padding", &padding ));
49
50
         OP_REQUIRES(context, ksize_[0] == 1 && stride_[0] == 1,
51
                     errors::Unimplemented(
52
                          "Pooling is not yet supported on the batch dimension."));
53
       }
54
       void Compute(OpKernelContext* context) override {
55
56
         const Tensor& tensor_in = context->input(0);
         PoolParameters params{context,
57
58
                                ksize_,
59
                                stride_,
                                padding_,
60
61
                                /*explicit_paddings=*/{},
                                FORMAT_NHWC,
62
63
                                tensor_in.shape()};
64
         if (!context->status().ok()) {
65
           return;
         }
66
67
68
         const float min_input = context->input(1).flat<float>()(0);
         const float max_input = context->input(2).flat<float>()(0);
69
70
71
         OP_REQUIRES(context, params.depth_window == 1,
72
                     errors::Unimplemented("Non-spatial pooling is not "
73
                                            "yet supported. Volunteers? :)"));
74
75
         OP_REQUIRES(context, tensor_in.dims() == 4,
                     errors::InvalidArgument("tensor_in must be 4-dimensional"));
76
77
78
         Tensor* output = nullptr;
```

```
79
          OP REQUIRES OK(context, context->allocate output(
 80
                                       0, params.forward output shape(), &output));
 81
          const int32_t highest = static_cast<int32>(Eigen::NumTraits<T>::highest());
          const int32_t lowest = static_cast<int32>(Eigen::NumTraits<T>::lowest());
 82
 83
 84
          // TODO(vrv): Switch this to the Eigen::Tensor version of
          // SpatialAvgPooling once that version is running quickly.
 85
          Tensor int32_output(DT_INT32, params.forward_output_shape());
 86
          // Cast input to int32 tensor and call SpatialAvgPool.
 87
          Tensor int32_input(DT_INT32, tensor_in.shape());
 88
 89
          int32_input.flat<int32>() = tensor_in.flat<T>().template cast<int32>();
          SpatialAvgPool<Device, int32>(context, &int32 output, int32 input, params,
 90
 91
                                         padding );
 92
 93
          // Clamp the int32 output back into quantized space.
 94
          output->flat<T>() = int32 output.flat<int32>()
 95
                                   .cwiseMax(lowest)
 96
                                   .cwiseMin(highest)
 97
                                   .template cast<T>();
 98
 99
          Tensor* output_min = nullptr;
100
          OP_REQUIRES_OK(context, context->allocate_output(1, {}, &output_min));
101
          output min->flat<float>()(0) = min input;
          Tensor* output max = nullptr;
102
          OP_REQUIRES_OK(context, context->allocate_output(2, {}, &output_max));
103
104
          output_max->flat<float>()(0) = max_input;
105
        }
106
107
       private:
108
        std::vector<int32> ksize_;
109
        std::vector<int32> stride ;
110
        Padding padding_;
111
      };
112
113
      template <typename Device, typename T>
114
      class QuantizedMaxPoolingOp : public MaxPoolingOp<Device, T> {
115
       public:
116
        explicit QuantizedMaxPoolingOp(OpKernelConstruction* context)
117
             : MaxPoolingOp<Device, T>(context) {}
118
119
        void Compute(OpKernelContext* context) override {
120
          const float min_input = context->input(1).flat<float>()(0);
          const float max_input = context->input(2).flat<float>()(0);
121
122
          MaxPoolingOp<Device, T>::Compute(context);
123
          Tensor* output_min = nullptr;
124
          OP_REQUIRES_OK(context, context->allocate_output(1, {}, &output_min));
125
          output_min->flat<float>()(0) = min_input;
126
          Tensor* output_max = nullptr;
127
          OP_REQUIRES_OK(context, context->allocate_output(2, {}, &output_max));
```

```
128
          output_max->flat<float>()(0) = max_input;
129
        }
130
      };
131
      REGISTER_KERNEL_BUILDER(
132
          Name("QuantizedAvgPool").Device(DEVICE_CPU).TypeConstraint<quint8>("T"),
133
          QuantizedAvgPoolingOp<CPUDevice, quint8>);
134
135
      REGISTER_KERNEL_BUILDER(
136
          Name("QuantizedMaxPool").Device(DEVICE_CPU).TypeConstraint<quint8>("T"),
137
          QuantizedMaxPoolingOp<CPUDevice, quint8>);
138
139
      #ifdef INTEL MKL
140
141
      REGISTER_KERNEL_BUILDER(
          Name("QuantizedAvgPool").Device(DEVICE_CPU).TypeConstraint<qint8>("T"),
142
          QuantizedAvgPoolingOp<CPUDevice, qint8>);
143
144
145
      REGISTER_KERNEL_BUILDER(
          Name("QuantizedMaxPool").Device(DEVICE_CPU).TypeConstraint<qint8>("T"),
146
          QuantizedMaxPoolingOp<CPUDevice, qint8>);
147
148
      #endif
149
150
      } // namespace tensorflow
```