

index: kernel/git/wireless/wireless-next.git

kvalo's fork of linux.git Wireless group

about summary tree commit stats

Colin Ian King <colin.i.king@gmail.com> 2022-10-20 14:57:09 +0100 author Kalle Valo <kvalo@kernel.org> 2022-10-21 15:54:06 +0300

80e5acb6dd72b25a6e6527443b9e9c1c3a7bcef6 (patch) commit 1feec57093b02302797d8d4304b6ec39871db63a parent 55549d6a3052990e65727bfec158e1b0e7cec4e4 (diff)

wireless-next-80e5acb6dd72b25a6e6527443b9e9c1c3a7bcef6.tar.gz

Variables hw ctrl s1 and sw ctrl s1 are not being initialized and

diff options context: 3 🕶 space include mode: unified

✓ switch

search

main

log msg

~

wifi: rtl8xxxu: Fix reads of uninitialized variables hw_ctrl_s1, sw_ctrl_s1 wireless-next-2022-10-28

potentially can contain any garbage value. Currently there is an if statement that sets one or the other of these variables, followed by an if statement that checks if any of these variables have been set to a non-zero value. In the case where they may contain uninitialized non-zero values, the latter if statement may be taken as true when it was not expected to. Fix this by ensuring hw ctrl s1 and sw ctrl s1 are initialized. Cleans up clang warning: drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu 8188f.c:432:7: warning: variable 'hw_ctrl_s1' is used uninitialized whenever 'if' condition is false [-Wsometimes-uninitialized] if (hw ctrl) { drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c:440:7: note: uninitialized use occurs here if (hw_ctrl_s1 || sw_ctrl_s1) { drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c:432:3: note: remove the 'if' if its condition is always true if (hw ctrl) { Fixes: c888183b21f3 ("wifi: rtl8xxxu: Support new chip RTL8188FU") Signed-off-by: Colin Ian King <colin.i.king@gmail.com> Reviewed-by: Nathan Chancellor <nathan@kernel.org> Signed-off-by: Kalle Valo <kvalo@kernel.org> Link: https://lore.kernel.org/r/20221020135709.1549086-1-colin.i.king@gmail.com

-rw-r--r-- drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c 2

1 files changed, 1 insertions, 1 deletions

diff --git a/drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c b/drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c index 99610bb2afd57..0025bb32538d5 100644 --- a/drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu 8188f.c +++ b/drivers/net/wireless/realtek/rtl8xxxu/rtl8xxxu_8188f.c @@ -412,7 +412,7 @@ static void rtl8188f_spur_calibration(struct rtl8xxxu_priv *priv, u8 channel) const u8 threshold = 0x16; bool do_notch, hw_ctrl, sw_ctrl, hw_ctrl_s1, sw_ctrl_s1;
bool do_notch, hw_ctrl, sw_ctrl, hw_ctrl_s1 = 0, sw_ctrl_s1 = 0; u32 val32, initial_gain, reg948; val32 = rtl8xxxu_read32(priv, REG_OFDM0_RX_D_SYNC_PATH);