

New issue

Jump to bottom

Member

Session fixation vulnerability in /verify #147

⟨> Code \odot Issues 14 % Pull requests 27 \odot Actions ⊞ Projects 3 \square Wiki





Arinerron commented on Mar 29, 2020 • edited • Description

There is a session fixation vulnerability in rCTF exploitable through the #token=\$ssid hash when making a request to the /verify endpoint.

Vulnerable code

```
document.title = 'Verify' + config.ctfTitle

const prefix = '#token='
if (document.location.hash.startsWith(prefix)) {
  route('/verify', true)

const verifyToken = document.location.hash.substring(prefix.length)
  verify({ verifyToken })
   .then(errors => {
    this.setState({
        errors
    })
    })
}
```

Exploitation Scenario

An attacker team could potentially steal flags by, for example, exploiting a stored XSS payload in a CTF challenge so that victim teams who solve the challenge are unknowingly (and against their will) signed into the attacker team's account. Then, the attacker can gain points / value off the backs of the victims.

Reproduction Steps

- 1. Create two teams: an attacker, and a victim. Sign into the victim's account.
- 2. Make an HTTP request to /verify#hash=\$ssid where \$ssid is the attacker's team code.
- 3. Observe that you have been logged in as the attacker.

Extra Details

Commit that introduced the vulnerability

1f91230 #diff-95a87eb07806dffb6d81c2ffdd27f8f5R16-R32

Potential solution

Merged
 Me

Instead of having the verification email link immediately sign users in, have it be purely for confirmation purposes. After opening the verification link and verifying the email address, the original registration page--which is polling the server for updates--would receive word that the email is verified. It would then log in without requiring a session ID from user input.



