Resources

Hash Suite - Windows password security audit tool. GUI, reports in PDF. [ [rev] [next] [ [day] [month] [year] [list]

What's new

```
Date: Thu, 9 Jun 2022 10:49:22 +0800 (GMT+08:00)
From: duoming@....edu.cn
To: oss-security@...ts.openwall.com
Cc: solar@...nwall.com
Subject: Re: Linux kernel: UAF, null-ptr-deref and double-free
vulnerabilities in nfcmrvl module
Hello,
The cve-2022-1734 was assigned to this problem.
> Hello there,
> There are double-free, use-after-free(write, read), null-ptr-deref vulnerabilities
> in drivers/nfc/nfcmrvl of linux that allow attacker to crash linux kernel by simulating
> nfc device from user-space.
> =*=*=*=*=*=*=*= Bug Details =*=*=*=*=*=*=
> There are destructive operations such as nfcmrvl fw dnld abort and
> gpio free in nfcmrvl nci unregister dev. The resources such as firmware,
> gpio and so on could be destructed while the upper layer functions such as
> nfcmrvl_fw_dnld_start and nfcmrvl_nci_recv_frame is executing, which leads
> to double-free, use-after-free and null-ptr-deref bugs.
> There are three situations that could lead to double-free bugs.
> The first situation is shown below:
     (Thread 1)
                                       (Thread 2)
> nfcmrvl fw dnld start
                                  nfcmrvl_nci_unregister_dev
  release firmware()
                                   nfcmrvl_fw_dnld_abort
   kfree(fw) //(1)
                                    fw dnld over
                                      release firmware
                                      kfree(\overline{fw}) //(2)
> The second situation is shown below:
     (Thread 1)
                                       (Thread 2)
> nfcmrvl_fw_dnld_start
 mod timer
  (wait a time)
                                  nfcmrvl_nci_unregister_dev
  fw dnld timeout
                                  nfcmrvl_fw_dnld_abort
   fw dnld over
     release firmware
                                    fw dnld over
                                     release firmware
      kfree(fw) //(1)
                                      kfree(fw) //(2)
> The third situation is shown below:
        (Thread 1)
                                          (Thread 2)
> nfcmrvl nci recv frame
 if(..->fw_download_in_progress) |
   nfcmrvl_fw_dnld_recv_frame
    queue work
> fw_dnld_rx_work
                                  | nfcmrvl_nci_unregister_dev
  fw dnld over
                                  | nfcmrvl fw dnld abort
    release firmware
                                     fw dnld over
                                      release_firmware
    kfree(fw) //(1)
```

 $kfree(\overline{fw}) //(2)$ 

```
> in position (2) again.
> What's more, there are also use-after-free and null-ptr-deref bugs
> in nfcmrvl_fw_dnld_start.
> One of the use-after-free bugs about firmware is shown below:
     (Use Thread)
                                       (Free Thread )
> nfcmrvl fw dnld start
                                   nfcmrvl nci unregister dev
                                   nfcmrvl fw dnld abort
                                    fw dnld over
                                     release firmware
                                      kfree(fw) //(1)
   priv->fw dnld.fw->data;//(2) |
> One of the use-after-free bugs about gpio is shown below:
    (Use Thread)
                                       (Free Thread )
> nfcmrvl fw dnld start
                                   nfcmrvl_nci_unregister dev
                                    gpio_free //(1)
   nfcmrvl_chip_reset
    gpio set value //(2)
> One of the null-ptr-deref bugs about firmware is shown below:
     (Use Thread)
                                       (Free Thread )
> nfcmrvl fw dnld start
                                   nfcmrvl nci unregister dev
                                   nfcmrvl_fw_dnld_abort
                                    fw dnld over
                                     priv->fw dnld.fw = NULL;//(1)
   priv->fw dnld.fw->data;//(2)|
> If we deallocate firmware struct, gpio or set null to the members of priv->fw dnld
> in position(1), then, we dereference firmware, gpio or the members of priv->fw dnld
> in position(2), the UAF or NPD bugs will happen.
> =*=*=*=*=*=*=*= Bug Effects =*=*=*=*=*=*=
> We can successfully trigger the vulnerabilities to crash the linux kernel.
> (1) One of the backtraces caused by use-after-free(write) bug is shown below.
> [ 138.280382] BUG: KASAN: use-after-free in request firmware+0x52/0x690
    138.280382] Write of size 8 at addr ffff88800c114850 by task download/11174
 [ 138.280382] Call Trace:
 [ 138.280382] <TASK>
> [ 138.280382] dump stack_lvl+0x57/0x7d
> [ 138.280382] print report.cold+0x5e/0x5db
> [ 138.280382] ? _request_firmware+0x52/0x690
> [ 138.280382] kasan_report+0xbe/0x1c0
 [ 138.280382] ? request_firmware+0x52/0x690
[ 138.280382] request_firmware+0x52/0x690
                  request firmware+0x52/0x690
> [ 138.280382] request_firmware+0x2d/0x50
> [ 138.280382] nfcmrvl_fw_dnld_start+0x7a/0xb0
> [ 138.280382] nfc fw download+0x92/0xe0
> [ 138.280382] nfc_genl_fw_download+0x10b/0x170
 [ 138.280382] ? nfc_genl_enable_se+0xa0/0xa0
                 ? __kasan_slab_alloc+0x2c/0x80
    138.280382]
> [ 138.280382]
                 ? __nla_parse+0x22/0x30
> [ 138.280382] ? genl_family_rcv_msg_attrs_parse.constprop.0+0xd3/0x130
> [ 138.280382] genl family rcv msg doit+0x17a/0x200
> [ 138.280382] ? genl_family_rcv_msg_attrs_parse.constprop.0+0x130/0x130
> [ 138.280382] ? mutex_lock_io_nested+0xb63/0xbd0
                 ? security_capable+0x48/0x60
> [ 138.280382]
    138.280382]
                 genl rcv msg+0x18d/0x2c0
> [ 138.280382]
                 ? genl get cmd+0x1b0/0x1b0
> [ 138.280382] ? rcu_read_lock_sched_held+0xd/0x70
> [ 138.280382] ? nfc genl enable se+0xa0/0xa0
> [ 138.280382] ? rcu_read_lock_sched_held+0xd/0x70
```

> The firmware struct is deallocated in position (1) and deallocated

```
> [ 138.280382] ? lock_acquire+0xce/0x410
> [ 138.280382] netlink_rcv_skb+0xc4/0x1f0
     138.280382]
                     ? genl_get_cmd+0x1b0/0x1b0
> [ 138.280382] ? netlink ack+0x4d0/0x4d0
> [ 138.280382] ? netlink deliver_tap+0xf7/0x5a0
> [ 138.280382] genl rcv+0x1f/0x30
> [ 138.280382] netlink_unicast+0x2d8/0x420
> [ 138.280382] ? netlink_attachskb+0x430/0x430
> [ 138.280382] netlink_sendmsg+0x3a9/0x6e0
> [ 138.280382] ? netlink_unicast+0x420/0x420
> [ 138.280382] ? netlink_unicast+0x420/0x420
> [ 138.280382] sock_sendmsg+0x91/0xa0
                       sys sendto+0x168/0x200
> [ 138.280382]
> [ 138.280382] ? __ia32_sys_getpeername+0x40/0x40
> [ 138.280382] ? preempt_count_sub+0xf/0xb0

> [ 138.280382] ? fd_install+0xfb/0x340

> [ 138.280382] ? _sys_socket+0xf0/0x160

> [ 138.280382] ? _x64_sys_clock_nanosleep+0x195/0x220
> [ 138.280382] ? compat_sock_ioctl+0x410/0x410
> [ 138.280382]
                       x64 sys sendto+0x6f/0x80
> [ 138.280382] do_syscall_64+0x3b/0x90
> [ 138.280382] entry_SYSCALL_64_after_hwframe+0x44/0xae
> [ 138.280382] RIP: 0033:0x7ff12ac0602c
> [ 138.280382] Code: 0a f8 ff ff 44 8b 4c 24 2c 4c 8b 44 24 20 89 c5 44 8b 54 2b
> [ 138.280382] RSP: 002b:00007ff12aa1ee00 EFLAGS: 00000293 ORIG_RAX: 0000000000c
> [ 138.280382] RAX: fffffffffffffda RBX: 00000000000000 RCX: 00007ff12ac0602c
> [ 138.280382] RDX: 000000000000002c RSI: 000055eab88030b0 RDI: 000000000000000
> [ 138.280382] RBP: 000000000000000 R08: 00007ff12aa1ee7c R09: 000000000000000
> [ 138.280382] R10: 000000000000000 R11: 000000000000293 R12: 00007ffca74ba00e
> [ 138.280382] R13: 00007ffca74ba00f R14: 00007ff12aa1efc0 R15: 00007ff12aa1f700
> (2) One of the backtraces caused by use-after-free(read) bug is shown below.
> [ 65.835462] BUG: KASAN: use-after-free in nci fw download+0x26/0x60
> [
       65.840236] Read of size 8 at addr ffff88800c2f5008 by task download/160
> [
       65.845755] Call Trace:
       65.845755] <TASK>
       65.845755] dump stack lvl+0x57/0x7d
> [
     65.845755] print_report.cold+0x5e/0x5db
> [
     65.845755] ? nci fw download+0x26/0x60
> [
> [ 65.845755] kasan_report+0xbe/0x1c0
> [ 65.856061] ? nfc_driver_failure+0x90/0xa0
> [ 65.856235] ? nci_fw_download+0x26/0x60
> [ 65.856235] nci_fw_download+0x26/0x60
> [ 65.856235] nfc_fw_download+0x99/0xe0
     65.856235] nfc genl_fw_download+0x10b/0x170
> [
> [ 65.861189] ? nfc genl enable se+0xa0/0xa0
> [ 65.861189] ? __kasan_slab_alloc+0x2c/0x80

> [ 65.861189] ? __nla_parse+0x22/0x30

> [ 65.865988] ? genl_family_rcv_msg_attrs_parse.constprop.0+0xd3/0x130
                     genl family_rcv_msg_doit+0x17a/0x200
      65.865988]
     65.865988] ? genl_family_rcv_msg_attrs_parse.constprop.0+0x130/0x130
> [
     65.870892] ? asm spurious interrupt+0x3/0x30
> [
> [ 65.870892] ? security capable+0x48/0x60
> [
       65.870892] genl_rcv_msg+0x18d/0x2c0
      65.870892] ? genl_get_cmd+0x1b0/0x1b0
65.870892] ? rcu_read_lock_sched_held+0xd/0x70
65.875946] ? nfc_genl_enable_se+0xa0/0xa0
65.875946] ? rcu_read_lock_sched_held+0xd/0x70
> [
  Γ
> [
       65.875946] ? lock acquire+0xce/0x410
> [
       65.875946] netlink rcv skb+0xc4/0x1f0
> [
       65.880842] ? genl_get_cmd+0x1b0/0x1b0
      65.881778] ? netlink_ack+0x4d0/0x4d0
65.881778] ? netlink_deliver_tap+0xf7/0x5a0
65.881778] genl_rcv+0x1f/0x30
> [
> [
      65.881778] netlink_unicast+0x2d8/0x420
> [
> [
      65.885734] ? netlink attachskb+0x430/0x430
     65.887472] netlink_sendmsg+0x3a9/0x6e0
> [
       65.887472] ? netlink_unicast+0x420/0x420
       65.887472] ? netlink_unicast+0x420/0x420
65.887472] sock_sendmsg+0x91/0xa0
> [
                       _sys_sendto+0x168/0x200
> [
       65.891949]
       65.893134] ?
                         __ia32_sys_getpeername+0x40/0x40
> [
       65.893134] ? lockdep hardirgs on prepare+0xe/0x220
> [
       65.893134] ? schedule+0x5c5/0x1180
```

```
> [
     65.893134] ? io_schedule_timeout+0xb0/0xb0
      65.897936] ? clockevents_program_event+0xd3/0x130 65.897936] ? hrtimer_interrupt+0x332/0x350
                   x64 sys sendto+0x6f/0x80
      65.897936]
      65.897936] do_syscall_64+0x3b/0x90
> [
> [
      65.897936] entry SYSCALL 64 after hwframe+0x44/0xae
      65.902930] RIP: 0033:0x7f96173ec02c
> [
      65.902930] Code: 0a f8 ff ff 44 8b 4c 24 2c 4c 8b 44 24 20 89 c5 44 8b 54 24 28 48 8b 54 24 18 b8 2c
00 00 00 48 8b 74 24 10 8b 7c 24 08 0f 05 <48> 3d 00 fb
      65.908959] RSP: 002b:00007f9617204df0 EFLAGS: 00000293 ORIG RAX: 00000000000002c
      65.908959] RAX: ffffffffffffffda RBX: 0000000000000 RCX: 00007f96173ec02c
> [
> [
      65.908959] RDX: 00000000000000034 RSI: 0000556fa2a030b0 RDI: 000000000000000
      65.908959] RBP: 0000000000000000 R08: 00007f9617204e6c R09: 00000000000000c
> [
      > [
      65.916990] R13: 00007ffde78477ef R14: 00007f9617204fc0 R15: 00007f9617205700
> (3) One of the backtraces caused by double-free bug is shown below.
> [ 122.640457] BUG: KASAN: double-free or invalid-free in fw dnld over+0x28/0xf0
> [ 122.640457] Call Trace:
> [ 122.640457] <TASK>
> [ 122.640457] dump_stack_lvl+0x57/0x7d
    122.640457] print_report.cold+0x5e/0x5db
 [
    122.640457]
                 ? fw_dnld_over+0x28/0xf0
> [ 122.640457] ? fw_dnld_over+0x28/0xf0
> [ 1re22.640457] kasan report invalid free+0x90/0x180
> [ 122.640457] ? refcount warn saturate+0x40/0x110
> [ 122.640457] ? fw_dnld_over+0x28/0xf0
                   _kasan_slab_free+0x152/0x170
> [ 122.640457]
    > [ 122.640457] kfree+0xb0/0x330
> [ 122.640457] fw_dnld_over+0x28/0xf0
> [ 122.640457] nfcmrvl nci unregister dev+0x61/0x70
> [ 122.640457] nci uart tty close+0x87/0xd0
> [ 122.640457] tty_ldisc_kill+0x3e/0x80
> [ 122.640457] tty_ldisc_hangup+0x1b2/0x2c0
    122.640457]
                  tty hangup.part.0+0x316/0x520
> [ 122.640457] tty release+0x200/0x670
> [ 122.640457]
                  __fput+0x110/0x410
> [ 122.640457] ? raw spin unlock irq+0x1f/0x40
> [ 122.640457] task_work_run+0x86/0xd0
> [ 122.640457] exit_to_user_mode_prepare+0x1aa/0x1b0
> [ 122.640457] syscall_exit_to_user_mode+0x19/0x50
> [ 122.640457] do_syscall_64+0x48/0x90
> [ 122.640457] entry_SYSCALL_64_after_hwframe+0x44/0xae
> [ 122.640457] RIP: 0033:0x7f68433f6beb
> [ 122.640457] Code: 0f 05 48 3d 00 f0 ff ff 77 45 c3 0f 1f 40 00 48 83 ec 18 84
> [ 122.640457] RSP: 002b:00007f684320fee0 EFLAGS: 00000293 ORIG RAX: 00000000003
> [ 122.640457] RAX: 000000000000000 RBX: 0000000000000 RCX: 00007f68433f6beb
    122.640457] RDX: 000000000000000 RSI: 0000000000000 RDI: 0000000000000
  [
    122.640457] RBP: 00007f684320ff00 R08: 00000000000000 R09: 00007f6843210700
> [ 122.640457] R10: 000000000000000 R11: 000000000000293 R12: 00007ffd5d6f9fde
> [ 122.640457] R13: 00007ffd5d6f9fdf R14: 00007f684320ffc0 R15: 00007f6843210700
> (4) One of the backtraces caused by null-ptr-deref bug is shown below.
      80.495478] BUG: KASAN: null-ptr-deref in nfcmrvl fw dnld start.cold+0x19/0x276
      80.498745] Read of size 8 at addr 00000000000000 by task download/161
      80.502308] Call Trace:
> [
> [
      80.502308] <TASK>
      80.502308] dump stack lvl+0x57/0x7d
> [
      80.502308] kasan_report+0xbe/0x1c0
      80.502308] ? nfcmrvl_fw_dnld_start.cold+0x19/0x276
 ſ
     80.502308] nfcmrvl_fw_dnld_start.cold+0x19/0x276
80.508210] ? nfc_fw_download+0x79/0xe0
> [
      80.508210] nfc_fw_download+0x99/0xe0
> [
> [
      80.508210] nfc genl fw download+0x10b/0x170
> [
      80.508210] ? nfc genl enable se+0xa0/0xa0
> [
      80.508210]
                 ? __kasan_slab_alloc+0x2c/0x80
> [
      80.508210]
                 ? __nla_parse+0x22/0x30
                 ? genl family rcv msg attrs parse.constprop.0+0xd3/0x130
      80.5082101
                 genl family rcv msg doit+0x17a/0x200
      80.508210]
                 ? genl_family_rcv_msg_attrs_parse.constprop.0+0x130/0x130
> [
      80.5082101
> [
      80.513085] ? mutex lock io nested+0xb43/0xbd0
      80.513085] ? security capable+0x48/0x60
```

```
> [
     80.513085] genl_rcv_msg+0x18d/0x2c0
     80.513085] ? genl_get_cmd+0x1b0/0x1b0
80.513085] ? rcu_read_lock_sched_held+0xd/0x70
     80.513085] ? nfc genl enable se+0xa0/0xa0
     80.513085] ? rcu read lock sched held+0xd/0x70
> [
> [
     80.513085] ? lock acquire+0xce/0x410
     80.513085] netlink rcv skb+0xc4/0x1f0
> [
     80.513085] ? genl_get_cmd+0x1b0/0x1b0
                ? netlink_ack+0x4d0/0x4d0
? netlink_deliver_tap+0xf7/0x5a0
 ſ
     80.518420]
     80.518420]
> [
     80.518420] genl rcv + 0x1f/0x30
     80.518420] netlink unicast+0x2d8/0x420
> [
     80.518420] ? netlink attachskb+0x430/0x430
> [
> [
     80.518420] netlink sendmsg+0x3a9/0x6e0
> [
     80.518420] ? netlink\_unicast+0x420/0x420
     80.518420]
                 ? netlink_unicast+0x420/0x420
  Γ
     80.518420] sock_sendmsg+0x91/0xa0
     80.518420]
                   _sys_sendto+0x168/0x200
> [
     80.523005] ?
> [
                    __ia32_sys_getpeername+0x40/0x40
> [
     80.523005] ? preempt count sub+0xf/0xb0
> [
     80.523005] ? fd_install+0xfb/0x340
> [
     80.523005] ? __sys_socket+0xf0/0x160
                 ? compat_sock_ioctl+0x410/0x410
     80.523005]
  [
     80.523005] x64_sys_sendto+0x6f/0x80
80.523005] do_sys_call_64+0x3b/0x90
> [
> [
     80.523005] entry SYSCALL 64 after hwframe+0x44/0xae
     80.523005] RIP: 0033:0x7f30f54f402c
     80.523005] Code: 0a f8 ff ff 44 8b 4c 24 2c 4c 8b 44 24 20 89 c5 44 8b 54 24 28 48 8b 54 24 18 b8 2b
> [
     80.528021] RSP: 002b:00007f30f530cdf0 EFLAGS: 00000293 ORIG RAX: 00000000000002c
 Γ
     80.528021] RAX: ffffffffffffffda RBX: 0000000000000 RCX: 00007f30f54f402c
     80.528021] RDX: 0000000000000034 RSI: 00005571766030b0 RDI: 000000000000005
     80.533650] RBP: 0000000000000000 R08: 00007f30f530ce6c R09: 00000000000000
> [
     [
> [ 80.533650] R13: 00007ffd9c6c6cef R14: 00007f30f530cfc0 R15: 00007f30f530d700
> =*=*=*=*=*=*=*= Bug Fix =*=*=*=*=*=*=
> The patch that have been applied to mainline Linux kernel is shown below.
> https://github.com/torvalds/linux/commit/d270453a0d9ec10bb8a802a142fb1b3601a83098
> =*=*=*=*=*=*= Timeline =*=*=*=*=*=*=
> 2022-05-01: commit d270453a0d9e accepted to mainline kernel
> 2022-06-05: send an email to secalert@...hat.com in order to request CVE number
> =*=*=*=*=*=*=*= Credit =*=*=*=*=*=*=
> Duoming Zhou <duoming@....edu.cn>
Best Regards,
Duoming Zhou
```

## Powered by blists - more mailing lists

Please check out the Open Source Software Security Wiki, which is counterpart to this mailing list.

Confused about mailing lists and their use? Read about mailing lists on Wikipedia and check out these guidelines on proper formatting of your messages.

