



The default file extension configuration has been changed to add .phar and...
Ondrej.Sury authored 5 years ago

dc253886

php-cgi.conf 1.12 KiB

```
1  # This file replaces old system MIME types and sets them only in the
2  # Apache webserver
3
4  # application/x-httpd-php                                phtml php
5  <FilesMatch ".+\.ph(ar|p|tml)$">
6      SetHandler application/x-httpd-php
7  </FilesMatch>
8  # application/x-httpd-php-source                        phps
9  <FilesMatch ".+\.phps$">
10     SetHandler application/x-httpd-php-source
11     # Deny access to raw php sources by default
12     # To re-enable it's recommended to enable access to the files
13     # only in specific virtual host or directory
14     Require all denied
15 </FilesMatch>
16 # Deny access to files without filename (e.g. '.php')
17 <FilesMatch "^\.ph(ar|p|ps|tml)$">
18     Require all denied
19 </FilesMatch>
20
21 # To enable PHP CGI site-wide, just uncomment following lines, however
22 # as a security measure, it's recommended to enable PHP just in the
23 # specific virtual servers or just specific directories
24
25 #ScriptAlias /cgi-bin/ /usr/lib/cgi-bin/
26 #<Directory "/usr/lib/cgi-bin">
27 #     AllowOverride None
28 #     Options +ExecCGI -MultiViews +SymLinksIfOwnerMatch
29 #     Order allow,deny
30 #     Allow from all
31 #</Directory>
32 #Action application/x-httpd-php /cgi-bin/php@PHP_VERSION@
```