linuxppc-dev.lists.ozlabs.org archive mirror

| search | help / color / mirror / Atom feed <u>Linux kernel: powerpc: KVM guest to host memory corruption</u> 2021-07-26 9:13 Michael Ellerman 2021-07-27 0:46 Michael Ellerman 0 siblings, 1 reply; 2+ messages in thread From: Michael Ellerman @ 2021-07-26 9:13 UTC (permalink / raw) To: oss-security; +Cc: linuxppc-dev The Linux kernel for powerpc since v3.10 has a bug which allows a malicious KVM guest to corrupt host memory. In the handling of the ${\tt H_RTAS}$ hypercall, args.rets is made to point into the args.args buffer which is located on the stack: args.rets = &args.args[be32 to cpu(args.nargs)]; However args.nargs has not been range checked. That allows the guest to point args.rets anywhere up to $\pm 16GB$ from args.args. The guest does not have control of what is written to args.rets, it is always (u32)-3, because subsequent code does check nargs. Additionally the guest will be killed as a result of the nargs being out of range, so a given guest only has a single shot at corrupting memory. Only machines using Linux as the hypervisor, aka. KVM or bare metal, are affected by the The bug was introduced in: 8e591cb72047 ("KVM: PPC: Book3S: Add infrastructure to implement kernel-side RTAS calls") Which was first released in v3.10. The upstream fix is: f62f3c20647e ("KVM: PPC: Book3S: Fix H_RTAS rets buffer overflow") Which will be included in the v5.14 release. ^ permalink raw reply [flat|nested] 2+ messages in thread * Re: Linux kernel: powerpc: KVM guest to host memory corruption emory corruption Michael Ellerman 2021-07-26 9:13 Linux kernel: power @ 2021-07-27 0:46 `Michael Ellerman O siblings, O replies; 2+ messages in thread
From: Michael Ellerman @ 2021-07-27 0:46 UTC (permalink / raw)
To: oss-security; +Cc: linuxppc-dev Michael Ellerman <mpe@ellerman.id.au> writes:
> The Linux kernel for powerpc since v3.10 has a bug which allows a malicious KVM guest to
> corrupt host memory. In the handling of the \underline{H} RTAS hypercall, args.rets is made to point into the args.args buffer which is located on the stack: args.rets = &args.args[be32_to_cpu(args.nargs)]; However args.nargs has not been range checked. That allows the guest to point args.rets anywhere up to $\pm 16GB$ from args.args. The guest does not have control of what is written to args.rets, it is always (u32)-3, because subsequent code does check nargs. Additionally the guest will be killed as a result of the nargs being out of range, so a given guest only has a single shot at corrupting memory. Only machines using Linux as the hypervisor, aka. KVM or bare metal, are affected by the > The bug was introduced in: 8e591cb72047 ("KVM: PPC: Book3S: Add infrastructure to implement kernel-side RTAS calls") f62f3c20647e ("KVM: PPC: Book3S: Fix H_RTAS rets buffer overflow") https://git.kernel.org/pub/scm/linux/kernel/git/torvalds/linux.git/commit/?id=f62f3c20647ebd5fb6ecb8f0b477b928lc44c10a > Which will be included in the v5.14 release. This has been assigned CVE-2021-37576. ^ permalink raw reply [flat|nested] 2+ messages in thread

end of thread, other threads:[~2021-07-27 0:46 UTC | newest]

Thread overview: 2+ messages (download: mbox.gz / follow: Atom feed)
-- links below jump to the message on this page -2021-07-26 9:13 Linux kernel: powerpc: KVM guest to host memory corruption Michael Ellerman
2021-07-27 0:46 Michael Ellerman

This is a public inbox, see mirroring instructions for how to clone and mirror all data and code used for this inbox; as well as URLs for NNTP newsgroup(s).