

Popup Maker < 1.16.11 - Admin+ Stored Cross Site Scripting

Description

The plugin does not sanitise and escape some of its Popup options, which could allow high privilege users such as admin to perform Stored Cross-Site Scripting attacks even when the `unfiltered_html` capability is disallowed (for example in multisite setup)

Proof of Concept

Create a New popup

Insert pop-up name, title, and body text.

Add a new trigger with default settings, choose "Click Open" and under "On Popup Close" then click add.

Click add new cookie and in the cookie name add the payload as cookie name:

```
<script>alert("XSS")</script>
```

The XSS will be triggered when editing a trigger

Affects Plugins

 **popup-maker**

Fixed in version 1.16.11 

References

CVE-2022-3690

Classification

Type

XSS

OWASP top 10

A7: Cross-Site Scripting (XSS)

CWE

CWE-79

Miscellaneous

Original Researcher

c3p0d4y

Submitter

c3p0d4y

Submitter twitter

<https://twitter.com/c3p01337>

Verified

Yes

WPVDB ID

725f6ae4-7ec5-4d7c-9533-c9b61b59cc2b

Timeline



2022-10-31 (about 25 days ago)

Added

2022-10-31 (about 25 days ago)

Last Updated

2022-10-31 (about 25 days ago)

Our Other Services

[WPScan WordPress Security Plugin](#)

Vulnerabilities

[WordPress](#)

[Plugins](#)

[Themes](#)

[Our Stats](#)

[Submit vulnerabilities](#)

About

[How it works](#)

[News](#)

[Contact](#)

For Developers

[Status](#)

[API details](#)

[CLI scanner](#)

Other

[Privacy](#)

[Terms of service](#)

[Submission terms](#)

[Disclosure policy](#)

In partnership with Jetpack

An [Automattic](#) endeavor

[Work With Us](#)