ming-soft / MCMS Public

New issue Jump to bottom

Mingsoft MCMS v5.2.8 SQL注入【后台】 #97

 \bigcirc Closed \bigcirc thunder-sec opened this issue on Jul 17 \cdot 1 comment

Assignees

Labels bug

thunder-sec commented on Jul 17

漏洞分析

漏洞路由位置/\${ms.manager.path}/mdiy/page/verify,漏洞点在如下方法,if...else两个条件中的validated方法均存在问题。

调用了父类的 validated 方法,validated方法中将传入的fieldName和fieldValue复制where对象中,并调用了appBiz.queryBySQL 方法。

```
s-basic-2.1.13.4.jar > net > mingsoft > basic > action > 🕲 BaseAction > 🧰 validated
                                                🚷 📱 🕏 🗕 🔞 PageAction.java × 🔞 BaseAction.java × 🐧 IBaseBiz.java × 🐧 BaseBizimpl.java × 🤰 IBaseDao.java × 🚵 IBaseDao.java
     ■ Maven: net.mingsoft:ms-mdiy:2.1.13.1

✓ II ms-mdiy-2.1.13.1.jar library 根
                                                                                  protected boolean validated(String tableName, String fieldName, String fieldValue) {
    Map where = new HashMap<>( | initialCapacity: 1);
                                                                                         where.put(fieldName, fieldValue);
                                                                                           List list = appBiz.queryBySQL(tableName, | fields: null, where);
            Q PageAction
bean
           > biz
> constant
           > tag
         > MEB-INF
                                                                                       protected boolean validated(String tableName, String fieldName, String fieldValue, String id,String idName) {
                                                                                          where.put(fieldName, fieldValue);
   > Mayen: net.sf.ehcache:ehcache-core:2.6.11
   > Maven: org.apache.ant:ant-launcher:1.10.5
   > In Mayon: org.apache.commons:commons-compress:1.19
> In Mayon: org.apache.commons:commons-lang3:3.10
   > Maven: org.apache.commons:commons-pool2:2.8.1
```

queryBySQL的实现方法如下调用了 getDao().queryBySQL(table, fields, wheres, null,null, null,null);


getDao().queryBySQL调用的具体SQL语句如下,其中key值对应的Map类型对象where,也就是前端传进来的fieldName

```
⊕ ፲ ☆ - ② PageAction.java × ② BaseAction.java × ③ BaseBiz.java × ③ BaseBiz.java × ③ BaseBiz.java × ③ BaseDac.java × ⑤ BaseDac.java × ⑤ BaseDac.java × ⑤ BaseDac.java × ⑥ BaseDa
 > In Mayen: net.mingsoft.ms-base.2.1.13
                                                                                                                                                                                                                                                                                                     <select id="queryBySQL" resultType="Map" databaseId="mysql">
                            net.mingsoft.mdiy
                                        > web
                                                   ConfigAction
ConfigDataAction
DictAction
                                                                                                                                                                                                                                                                                                                               1=1
<foreach item="item" index="key" collection="wheres" open="AND"</pre>
                                                  FormAction
FormDataAction
                                                                                                                                                                                                                                                                                                                                       <include refid="net.mingsoft.base.dao.IBaseDao.sqlWhere"></include>
                                                                                                                                                                                                                                                                                                                      </where>
                                                 PageAction
                                 > 🖿 bean
                               > adao > entity
                               > resources
> tag
                      > static.mdiy
> WEB-INF
                                                                                                                                                                                                                                                                                                                                         <if test="order==null">desc</if>
 > In Mayen: net.mingsoft:store-client:2.1.13
> In Mayen: net.sf.ehcache:ehcache:2.10.9.2
                                                                                                                                                                                                                                                                                                                      <if test="begin != null">
  > Ni Maven: net.sf.jopt-simple:jopt-simple:5.0.2
> Ni Maven: org.apache.ant:ant:1.10.5

    Tif Maven: org.apache.ant.ant.launcher:1.10.5
    Tif Maven: org.apache.commons.commons-collections4:4.4
    Tif Maven: org.apache.commons.commons-compress:1.19
    Tif Maven: org.apache.commons.commons-lang3:3.10
```

漏洞验证

构造如下请求包,如果数据库长度大于1,即成功睡眠3秒。



🟷 🔐 killfen added the 🛮 bug 🛮 label on Sep 8

R killfen self-assigned this on Sep 8

killfen commented on Sep 8

Contributor

5.2.9 fix it

killfen closed this as completed on Sep 8

Assignees



Projects

None yet

Milestone

No milestone

Development

No branches or pull requests

2 participants



